

Getting started

Introduction

Why React-Bootstrap?

Theming

Color modes

Getting help

RTL

Layout

Breakpoints

Grid

Stacks

Forms

Components

Accordion

Alerts

Badges

Breadcrumbs

Button group

Buttons

Cards

Carousels

Close Button

Dropdowns

Getting started

Introduction

Introduction

Learn how to include React Bootstrap in your project.

Installation

The best way to consume React-Bootstrap is via the npm package which you can install with `npm` (or `yarn` if you prefer).

If you plan on customizing the Bootstrap Sass files, or don't want to use a CDN for the stylesheet, it may be helpful to install [vanilla Bootstrap](#) as well.

```
npm install react-bootstrap bootstrap
```

Importing Components

You should import individual components like: `react-bootstrap/Button` rather than the entire library. Doing so pulls in only the specific components that you use, which can significantly reduce the amount of code you end up sending to the client.

```
import Button from 'react-bootstrap/Button';

// or less ideally
import { Button } from 'react-bootstrap';
```

Browser globals

We provide `react-bootstrap.js` and `react-bootstrap.min.js` bundles with all components exported on the `window.ReactBootstrap` object. These bundles are available on [jsDelivr](#), as well as in the npm package.

```
<script src="https://cdn.jsdelivr.net/npm/react/umd/react.production.min.js" crossorigin></script>

<script
  src="https://cdn.jsdelivr.net/npm/react-dom/umd/react-dom.production.min.js"
  crossorigin></script>

<script
  src="https://cdn.jsdelivr.net/npm/react-bootstrap@next/dist/react-bootstrap.min.js"
  crossorigin></script>

<script>var Alert = ReactBootstrap.Alert;</script>
```

Examples

React-Bootstrap has started a repo with a few basic CodeSandbox examples. [Click here](#) to check them out.

Stylesheets

Because React-Bootstrap doesn't depend on a very precise version of Bootstrap, we don't ship with any included CSS. However, some stylesheet **is required** to use these components.

CSS

```
{
  /* The following line can be included in your src/index.js or App.js file */
}
import 'bootstrap/dist/css/bootstrap.min.css';
```

How and which Bootstrap styles you include is up to you, but the simplest way is to include the latest styles from the CDN. A little more information about the benefits of using a CDN can be found [here](#).

```
<link
  rel="stylesheet"
  href="https://cdn.jsdelivr.net/npm/bootstrap@5.3.8/dist/css/bootstrap.min.css"
  integrity="sha384-sR114kxILFvY4716cr92wB87VP4J8+LH7qKQnuquKUIAvNMLzeN8tESYBuj2qJLB"
  crossorigin="anonymous"
/>
```

Sass

In case you are using **Sass** the simplest way is to include the Bootstrap's source Sass files in your main Sass file and then require it on your `src/index.js` or `App.js` file. This applies to a typical `create-react-app` application in other use cases you might have to setup the bundler of your choice to compile Sass/SCSS stylesheets to CSS.

```
/* The following line can be included in a src/App.scss */
@import '~bootstrap/scss/bootstrap';
```

```
/* The following line can be included in your src/index.js or App.js file */
import './App.scss';
```

Customize Bootstrap

If you wish to customize the Bootstrap theme or any Bootstrap variables you can create a custom Sass file:

```
/* The following block can be included in a custom.scss */

/* make the customizations */
$theme-colors: (
  'info': tomato,
  'danger': teal
);

/* import bootstrap to set changes */
@import '~bootstrap/scss/bootstrap';
```

... And import it on the main Sass file.

```
/* The following line can be included in a src/App.scss */
@import 'custom';
```

Advanced usage

See [the Bootstrap docs](#) for more advanced use cases and details about customizing stylesheets.

as Prop API

With certain React-Bootstrap components, you may want to modify the component or HTML tag that is rendered.

If you want to keep all the styling of a particular React-Bootstrap component but switch the component that is finally rendered (whether it's a different React-Bootstrap component, a different custom component, or a different HTML tag) you can use the `as` prop to do so.

The example below passes an anchor to the `as` prop in a `Button` component. This ultimately causes a `a` tag to be rendered but with the same styles as a `Button` component.

RESULT

Button as link

Button as link

LIVE EDITOR

```
<Stack direction="horizontal" gap={2}>
  <Button as="a" variant="primary">
    Button as link
  </Button>
  <Button as="a" variant="success">
    Button as link
  </Button>
</Stack>;
```

Below is an illustration of passing a React Bootstrap component. It contains a `Badge` component and a `Button` component that have been supplied to the `as` prop. This finally results in the rendering of a `Button` component with the same styles as a `Badge` component.

RESULT

Example heading

New

LIVE EDITOR

```
import Badge from 'react-bootstrap/Badge';
import Button from 'react-bootstrap/Button';

function Example() {
  return (
    <div>
      <h1>
        Example heading
        <Badge bg="secondary" as={Button}>
          New
        </Badge>
      </h1>
    </div>
  );
}
```

export default Example;

Themes

React-Bootstrap is compatible with existing Bootstrap themes. Just follow the installation instructions for your theme of choice.

 Watch out!

Because React-Bootstrap completely reimplements Bootstrap's JavaScript, it's not automatically compatible with themes that extend the default JavaScript behaviors.

 Create React App

If you would like to add a custom theme on your app using Create React App, they have additional documentation for Create React App and Bootstrap [here](#)

Next

Why React-Bootstrap? »

Docs

Getting Started

Layout

Forms

Components

Utilities

Community

Stack Overflow

Discord

More

GitHub

Copyright © 2026 React Bootstrap. Built with Docusaurus.