React Bootstrap Getting Started Components
v3.0.0-beta.5 (Bootstrap 5) GitHub Search Ctrl K

Getting started
Layout
Forms
Components
Accordion
Alerts
Badges
Breadcrumbs
Button group
Buttons
Cards
Carousels
Close Button
Dropdowns
Figures
Images
List groups
Modals
Navbars
Navs and tabs
Offcanvas
Overlay
Pagination
Placeholders
Progress bars
Spinners
Tables
Tabs
Toasts
Utilities
Migrating
About

Components › Navbars

Overview
Brand
Forms
Text and Non-nav links
Color schemes
Containers
Placement
Fixed top
Fixed bottom
Sticky top
Sticky bottom
Scrolling
Responsive behaviors
Offcanvas
API
Navbar
NavbarBrand
NavbarToggle
NavbarCollapse

Navbars

A powerful, responsive navigation header, the navbar. Includes support for branding, navigation, and more.

Improve collaboration and visibility with one DevSecOps platform. Learn more from our team.
ADS VIA CARBON

Overview

Here's what you need to know before getting started with the Navbar:

- Use the `expand` prop to allow for collapsing the `Navbar` at lower breakpoints.
- `Navbar`s and their contents are fluid by default. Use optional containers to limit their horizontal width.
- Use spacing and flex utilities to size and position content

A responsive navigation header, including support for branding, navigation, and more. Here's an example of all the sub-components included in a responsive light-themed navbar that automatically collapses at the lg (large) breakpoint.

RESULT

React-Bootstrap Home Link Dropdown

LIVE EDITOR

```
import Container from 'react-bootstrap/Container';
import Nav from 'react-bootstrap/Nav';
import Navbar from 'react-bootstrap/Navbar';
import NavDropdown from 'react-bootstrap/NavDropdown';

function BasicExample() {
  return (
    <Navbar expand="lg" className="bg-body-tertiary">
      <Container>
        <Navbar.Brand href="#home">React-Bootstrap</Navbar.Brand>
        <Navbar.Toggle aria-controls="basic-navbar-nav" />
        <Navbar.Collapse id="basic-navbar-nav">
          <Nav className="me-auto">
            <Nav.Link href="#home">Home</Nav.Link>
            <Nav.Link href="#link">Link</Nav.Link>
            <NavDropdown title="Dropdown" id="basic-nav-dropdown">
              <NavDropdown.Item href="#action/3.1">Action</NavDropdown.Item>
              <NavDropdown.Item href="#action/3.2">
                Another action
              </NavDropdown.Item>
              <NavDropdown.Item href="#action/3.3">Something</NavDropdown.Item>
              <NavDropdown.Divider />
              <NavDropdown.Item href="#action/3.4">
                Separated link
              </NavDropdown.Item>
            </NavDropdown>
          </Nav>
        </Navbar.Collapse>
      </Container>
    </Navbar>
  );
}

export default BasicExample;
```

Brand

A simple flexible branding component. Images are supported but will likely require custom styling to work well.

RESULT

Brand link

Brand text

React Bootstrap

LIVE EDITOR

```
import Container from 'react-bootstrap/Container';
import Navbar from 'react-bootstrap/Navbar';

function BrandExample() {
  return (
    <>
      <Navbar className="bg-body-tertiary">
        <Container>
          <Navbar.Brand href="#home">Brand link</Navbar.Brand>
        </Container>
      </Navbar>
      <br />
      <Navbar className="bg-body-tertiary">
        <Container>
          <Navbar.Brand>Brand text</Navbar.Brand>
        </Container>
      </Navbar>
      <br />
      <Navbar className="bg-body-tertiary">
        <Container>
          <Navbar.Brand href="#home">
            <img
              src="/img/logo.svg"
              width="30"
              height="30"
              className="d-inline-block align-top"
              alt="React Bootstrap logo"
            />
          </Navbar.Brand>
        </Container>
      </Navbar>
      <br />
      <Navbar className="bg-body-tertiary">
        <Container>
          <Navbar.Brand href="#home">
            <img
              alt=""
              src="/img/logo.svg"
              width="30"
              height="30"
              className="d-inline-block align-top"
            />{' '}
            React Bootstrap
          </Navbar.Brand>
        </Container>
      </Navbar>
    </>
  );
}

export default BrandExample;
```

Forms

Use `<Form inline>` and your various form controls within the Navbar. Align the contents as needed with utility classes.

RESULT

@ Username Search Submit

LIVE EDITOR

```
import Navbar from 'react-bootstrap/Navbar';
import Form from 'react-bootstrap/Form';
import Button from 'react-bootstrap/Button';
import InputGroup from 'react-bootstrap/InputGroup';
import Row from 'react-bootstrap/Row';
import Col from 'react-bootstrap/Col';

function FormExample() {
  return (
    <Navbar className="bg-body-tertiary justify-content-between">
      <Form inline>
        <InputGroup>
          <InputGroup.Text id="basic-addon1">@</InputGroup.Text>
          <Form.Control
            placeholder="Username"
            aria-label="Username"
            aria-describedby="basic-addon1"
          />
        </InputGroup>
      </Form>
      <Form inline>
        <Row>
          <Col xs="auto">
            <Form.Control
              type="text"
              placeholder="Search"
              className=" mr-sm-2"
            />
          </Col>
          <Col xs="auto">
            <Button type="submit">Submit</Button>
          </Col>
        </Row>
      </Form>
    </Navbar>
  );
}

export default FormExample;
```

Text and Non-nav links

Loose text and links can be wrapped `Navbar.Text` in order to correctly align it vertically.

RESULT

Navbar with text Signed in as: Mark Otto

LIVE EDITOR

```
import Container from 'react-bootstrap/Container';
import Navbar from 'react-bootstrap/Navbar';

function TextLinkExample() {
  return (
    <Navbar className="bg-body-tertiary">
      <Container>
        <Navbar.Brand href="#home">Navbar with text</Navbar.Brand>
        <Navbar.Toggle />
        <Navbar.Collapse className="justify-content-end">
          <Navbar.Text>
            Signed in as: <a href="#login">Mark Otto</a>
          </Navbar.Text>
        </Navbar.Collapse>
      </Container>
    </Navbar>
  );
}

export default TextLinkExample;
```

Color schemes

Theming the navbar has never been easier thanks to the combination of theming classes and background-color utilities. Choose from `variant="light"` for use with light background colors, or `variant="dark"` for dark background colors. Then, customize with the `bg` prop or any custom css!

> ⚠ **Heads up!**
>
> Dark variants for components were deprecated in Bootstrap v5.3.0 with the introduction of color modes. Instead of adding `variant="dark"`, set `data-bs-theme="dark"` on the `Navbar`.

RESULT

Navbar Home Features Pricing

Navbar Home Features Pricing

Navbar Home Features Pricing

LIVE EDITOR

```
import Container from 'react-bootstrap/Container';
import Nav from 'react-bootstrap/Nav';
import Navbar from 'react-bootstrap/Navbar';

function ColorSchemesExample() {
  return (
    <>
      <Navbar bg="dark" data-bs-theme="dark">
        <Container>
          <Navbar.Brand href="#home">Navbar</Navbar.Brand>
          <Nav className="me-auto">
            <Nav.Link href="#home">Home</Nav.Link>
            <Nav.Link href="#features">Features</Nav.Link>
            <Nav.Link href="#pricing">Pricing</Nav.Link>
          </Nav>
        </Container>
      </Navbar>
      <br />
      <Navbar bg="primary" data-bs-theme="dark">
        <Container>
          <Navbar.Brand href="#home">Navbar</Navbar.Brand>
          <Nav className="me-auto">
            <Nav.Link href="#home">Home</Nav.Link>
            <Nav.Link href="#features">Features</Nav.Link>
            <Nav.Link href="#pricing">Pricing</Nav.Link>
          </Nav>
        </Container>
      </Navbar>

      <br />
      <Navbar bg="light" data-bs-theme="light">
        <Container>
          <Navbar.Brand href="#home">Navbar</Navbar.Brand>
          <Nav className="me-auto">
            <Nav.Link href="#home">Home</Nav.Link>
            <Nav.Link href="#features">Features</Nav.Link>
            <Nav.Link href="#pricing">Pricing</Nav.Link>
          </Nav>
        </Container>
      </Navbar>
    </>
  );
}

export default ColorSchemesExample;
```

Containers

While not required, you can wrap the Navbar in a `<Container>` component to center it on a page, or add one within to only center the contents of a fixed or static top navbar.

RESULT

Navbar

LIVE EDITOR

```
import Container from 'react-bootstrap/Container';
import Navbar from 'react-bootstrap/Navbar';

function ContainerOutsideExample() {
  return (
    <Container>
      <Navbar expand="lg" className="bg-body-tertiary">
        <Container>
          <Navbar.Brand href="#">Navbar</Navbar.Brand>
        </Container>
      </Navbar>
    </Container>
  );
}

export default ContainerOutsideExample;
```

When the container is within your navbar, its horizontal padding is removed at breakpoints lower than your specified `expand={'sm' | 'md' | 'lg' | 'xl' | 'xxl'}` prop. This ensures we're not doubling up on padding unnecessarily on lower viewports when your navbar is collapsed.

RESULT

Navbar

LIVE EDITOR

```
import Container from 'react-bootstrap/Container';
import Navbar from 'react-bootstrap/Navbar';

function ContainerInsideExample() {
  return (
    <Navbar expand="lg" className="bg-body-tertiary">
      <Container>
        <Navbar.Brand href="#">Navbar</Navbar.Brand>
      </Container>
    </Navbar>
  );
}

export default ContainerInsideExample;
```

Placement

You can use Bootstrap's position utilities to place navbars in non-static positions. Choose from fixed to the top, fixed to the bottom, or stickied to the top (scrolls with the page until it reaches the top, then stays there), or stickied to the bottom (scrolls with the page until it reaches the bottom, then stays there).

Fixed navbars use `position: fixed`, meaning they're pulled from the normal flow of the DOM and may require custom CSS (e.g., padding-top on the `<body>`) to prevent overlap with other elements.

Since these positioning needs are so common for navbars, we've added convenience props for them.

Fixed top

```
<Navbar fixed="top" />
```

Fixed bottom

```
<Navbar fixed="bottom" />
```

Sticky top

```
<Navbar sticky="top" />
```

Sticky bottom

```
<Navbar sticky="bottom" />
```

Scrolling

You can use the `navbarScroll` prop in a `<Nav>` to enable vertical scrolling within the toggleable contents of a collapsed navbar. See the Bootstrap docs for more information.

RESULT

Navbar scroll Home Link Link Link Search Search

LIVE EDITOR

```
import Button from 'react-bootstrap/Button';
import Container from 'react-bootstrap/Container';
import Form from 'react-bootstrap/Form';
import Nav from 'react-bootstrap/Nav';
import Navbar from 'react-bootstrap/Navbar';
import NavDropdown from 'react-bootstrap/NavDropdown';

function NavScrollExample() {
  return (
    <Navbar expand="lg" className="bg-body-tertiary">
      <Container fluid>
        <Navbar.Brand href="#">Navbar scroll</Navbar.Brand>
        <Navbar.Toggle aria-controls="navbarScroll" />
        <Navbar.Collapse id="navbarScroll">
          <Nav
            className="me-auto my-2 my-lg-0"
            style={{ maxHeight: '100px' }}
            navbarScroll
          >
            <Nav.Link href="#action1">Home</Nav.Link>
            <Nav.Link href="#action2">Link</Nav.Link>
            <NavDropdown title="Link" id="navbarScrollingDropdown">
              <NavDropdown.Item href="#action3">Action</NavDropdown.Item>
              <NavDropdown.Item href="#action4">
                Another action
              </NavDropdown.Item>
              <NavDropdown.Divider />
              <NavDropdown.Item href="#action5">
                Something else here
              </NavDropdown.Item>
            </NavDropdown>
            <Nav.Link href="#" disabled>
              Link
            </Nav.Link>
          </Nav>
          <Form className="d-flex">
            <Form.Control
              type="search"
              placeholder="Search"
              className="me-2"
              aria-label="Search"
            />
            <Button variant="outline-success">Search</Button>
          </Form>
        </Navbar.Collapse>
      </Container>
    </Navbar>
  );
}

export default NavScrollExample;
```

Responsive behaviors

Use the `expand` prop as well as the `Navbar.Toggle` and `Navbar.Collapse` components to control when content collapses behind a button.

Set the `defaultExpanded` prop to make the Navbar start expanded. Set `collapseOnSelect` to make the Navbar collapse automatically when the user selects an item. You can also finely control the collapsing behavior by using the `expanded` and `onToggle` props.

> ⚠ **Caution**
>
> Watch out! You **need** to provide a breakpoint value to `expand` in order for the Navbar to collapse at all.

RESULT

React-Bootstrap Features Pricing Dropdown More deets Dank memes

LIVE EDITOR

```
import Container from 'react-bootstrap/Container';
import Nav from 'react-bootstrap/Nav';
import Navbar from 'react-bootstrap/Navbar';
import NavDropdown from 'react-bootstrap/NavDropdown';

function CollapsibleExample() {
  return (
    <Navbar collapseOnSelect expand="lg" className="bg-body-tertiary">
      <Container>
        <Navbar.Brand href="#home">React-Bootstrap</Navbar.Brand>
        <Navbar.Toggle aria-controls="responsive-navbar-nav" />
        <Navbar.Collapse id="responsive-navbar-nav">
          <Nav className="me-auto">
            <Nav.Link href="#features">Features</Nav.Link>
            <Nav.Link href="#pricing">Pricing</Nav.Link>
            <NavDropdown title="Dropdown" id="collapsible-nav-dropdown">
              <NavDropdown.Item href="#action/3.1">Action</NavDropdown.Item>
              <NavDropdown.Item href="#action/3.2">
                Another action
              </NavDropdown.Item>
              <NavDropdown.Item href="#action/3.3">Something</NavDropdown.Item>
              <NavDropdown.Divider />
              <NavDropdown.Item href="#action/3.4">
                Separated link
              </NavDropdown.Item>
            </NavDropdown>
          </Nav>
          <Nav>
            <Nav.Link href="#deets">More deets</Nav.Link>
            <Nav.Link eventKey={2} href="#memes">
              Dank memes
            </Nav.Link>
          </Nav>
        </Navbar.Collapse>
      </Container>
    </Navbar>
  );
}

export default CollapsibleExample;
```

Offcanvas

Transform your expanding and collapsing navbar into an offcanvas drawer with the offcanvas component. We extend both the offcanvas default styles and use the `expand` prop to create a dynamic and flexible navigation sidebar.

In the example below, to create an offcanvas navbar that is always collapsed across all breakpoints, set the `expand` prop to `false`.

RESULT

Navbar Offcanvas

Navbar Offcanvas Home Link Dropdown Search Search

Navbar Offcanvas Home Link Dropdown Search Search

Navbar Offcanvas Home Link Dropdown Search Search

Navbar Offcanvas Home Link Dropdown Search Search

Navbar Offcanvas Home Link Dropdown Search Search

LIVE EDITOR

```
import Button from 'react-bootstrap/Button';
import Container from 'react-bootstrap/Container';
import Form from 'react-bootstrap/Form';
import Nav from 'react-bootstrap/Nav';
import Navbar from 'react-bootstrap/Navbar';
import NavDropdown from 'react-bootstrap/NavDropdown';
import Offcanvas from 'react-bootstrap/Offcanvas';

function OffcanvasExample() {
  return (
    <>
      {[false, 'sm', 'md', 'lg', 'xl', 'xxl'].map((expand) => (
        <Navbar key={expand} expand={expand} className="bg-body-tertiary mb-3">
          <Container fluid>
            <Navbar.Brand href="#">Navbar Offcanvas</Navbar.Brand>
            <Navbar.Toggle aria-controls={`offcanvasNavbar-expand-${expand}`} />
            <Navbar.Offcanvas
              id={`offcanvasNavbar-expand-${expand}`}
              aria-labelledby={`offcanvasNavbarLabel-expand-${expand}`}
              placement="end"
            >
              <Offcanvas.Header closeButton>
                <Offcanvas.Title id={`offcanvasNavbarLabel-expand-${expand}`}>
                  Offcanvas
                </Offcanvas.Title>
              </Offcanvas.Header>
              <Offcanvas.Body>
                <Nav className="justify-content-end flex-grow-1 pe-3">
                  <Nav.Link href="#action1">Home</Nav.Link>
                  <Nav.Link href="#action2">Link</Nav.Link>
                  <NavDropdown
                    title="Dropdown"
                    id={`offcanvasNavbarDropdown-expand-${expand}`}
                  >
                    <NavDropdown.Item href="#action3">Action</NavDropdown.Item>
                    <NavDropdown.Item href="#action4">
                      Another action
                    </NavDropdown.Item>
                    <NavDropdown.Divider />
                    <NavDropdown.Item href="#action5">
                      Something else here
                    </NavDropdown.Item>
                  </NavDropdown>
                </Nav>
                <Form className="d-flex">
                  <Form.Control
                    type="search"
                    placeholder="Search"
                    className="me-2"
                    aria-label="Search"
                  />
                  <Button variant="outline-success">Search</Button>
                </Form>
              </Offcanvas.Body>
            </Navbar.Offcanvas>
          </Container>
        </Navbar>
      ))}
    </>
  );
}

export default OffcanvasExample;
```

API

Navbar

```
import Navbar from 'react-bootstrap/Navbar'
```

Name	Type	Default	Description
as	`React.ElementType | undefined`		Element used to render the component.
bsPrefix	`string | undefined`	`'navbar'`	Change the underlying component CSS base class name and modifier class names prefix. **This is an escape hatch** for working with heavily customized bootstrap css.
variant	`'light' | 'dark' | string | undefined`		The general visual variant of the Navbar. Use in combination with the `bg` prop, `background-color` utilities, or your own background styles.
expand	`boolean | string | 'sm' | 'md' | 'lg' | 'xl' | 'xxl' | undefined`		The breakpoint, below which, the Navbar will collapse. When `true` the Navbar will always be expanded regardless of screen size.
defaultExpand	`boolean | string | 'sm' | 'md' | 'lg' | 'xl' | 'xxl' | undefined`		Default expanded state of the Navbar.
bg	`string | undefined`		A convenience prop for adding `bg-*` utility classes since they are so commonly used here. `light` and `dark` are common choices but any `bg-*` class is supported, including any custom ones you might define. Pairs nicely with the `variant` prop.
fixed	`'top' | 'bottom' | undefined`		Create a fixed navbar along the top or bottom of the screen, that scrolls with the page. A convenience prop for the `fixed-*` positioning classes.
sticky	`'top' | 'bottom' | undefined`		Position the navbar at the top or bottom of the viewport, but only after scrolling past it. A convenience prop for the `sticky-*` positioning classes.
onToggle	`((expanded: boolean) => void) | undefined`		*controlled by: `expanded`, initial prop: `defaultOnToggle`* A callback fired when the `<Navbar>` body collapses or expands. Fired when a `<Navbar.Toggle>` is clicked and called with the new `expanded` boolean value.
onSelect	`SelectCallback | undefined`		A callback fired when a descendant of a child `<Nav>` is selected. Should be used to execute complex closing or other miscellaneous actions desired after selecting a descendant of `<Nav>`. Does nothing if no `<Nav>` or `<Nav>` descendants exist. The callback is called with an eventKey, which is a prop from the selected `<Nav>` descendant, and an event. `function ( eventKey: mixed, event?: SyntheticEvent )` For basic closing behavior after all `<Nav>` descendant onSelect events in mobile viewports, try using collapseOnSelect. Note: If you are manually closing the navbar using this `OnSelect` prop, ensure that you are setting `expanded` to false and not *toggling* between true and false.
collapseOnSelect	`boolean | undefined`		Toggles `expanded` to `false` after the onSelect event of a descendant of a child `<Nav>` fires. Does nothing if no `<Nav>` or `<Nav>` descendants exist. `<NavLink>` descendants of `<Nav>` will not trigger the `onSelect` event unless an `eventKey` or `href` prop is defined. Manually controlling `expanded` via the onSelect callback is recommended instead, for more complex operations that need to be executed after the `select` event of `<Nav>` descendants.
expanded	`boolean | undefined`		*controlled by: `onToggle`, initial prop: `defaultExpanded`* Controls the visibility of the navbar body
role	`string | undefined`	`'navigation'`	The ARIA role for the navbar, will default to 'navigation' for Navbars whose `as` is something other than `<nav>`.

NavbarBrand

```
import NavbarBrand from 'react-bootstrap/NavbarBrand'
```

Name	Type	Default	Description
as	`React.ElementType | undefined`		Element used to render the component.
bsPrefix	`string | undefined`	`'navbar-brand'`	Change the underlying component CSS base class name and modifier class names prefix. **This is an escape hatch** for working with heavily customized bootstrap css.
href	`string | undefined`		An href, when provided the Brand will render as an `<a>` element (unless `as` is provided).

NavbarToggle

```
import NavbarToggle from 'react-bootstrap/NavbarToggle'
```

Name	Type	Default	Description
as	`React.ElementType | undefined`	`'button'`	Element used to render the component.
bsPrefix	`string | undefined`	`'navbar-toggler'`	Change the underlying component CSS base class name and modifier class names prefix. **This is an escape hatch** for working with heavily customized bootstrap css.
label	`string | undefined`	`'Toggle navigation'`	An accessible ARIA label for the toggler button.
children	`React.ReactNode | undefined`		The toggle content. When empty, the default toggle will be rendered.

NavbarCollapse

```
import NavbarCollapse from 'react-bootstrap/NavbarCollapse'
```

Name	Type	Default	Description
bsPrefix	`string | undefined`	`'navbar-collapse'`	Change the underlying component CSS base class name and modifier class names prefix. **This is an escape hatch** for working with heavily customized bootstrap css.

Previous
« Modals

Next
Navs and tabs »

Copyright © 2026 React Bootstrap. Built with Docusaurus.