

CLAUDE.md

This file provides guidance to Claude Code (claude.ai/code) when working with code in this repository.

What this is

A personal indoor-cycling training log (Christopeit AX 4000 + Kinomap), not a software project. No build system, no package manager — just a single ground-truth CSV, a static HTML dashboard that reads it, and a PDF export of that dashboard.

Architecture: one CSV, everything else derived

training_log.csv is the **only** hand-maintained data in this repo. training.html is static — it fetch()es the CSV at load time, parses it client-side, and derives every chart, table row, hero metric, weekly rollup and legend from it at render time. Adding a session means appending one row to the CSV (via the add-training skill) — training.html itself never needs to be edited.

- training_log.csv — one row per session, or per rest-day BP-only log. Columns:
 - Datum (D.M, no year), Nr (session label — plain sequential integer since ~week 9, – for rest days; not derivable, always script-assigned)
 - Dauer_sek, Kcal, Watt (estimated, see formula below), MaxHF, Rec (editorial “strong session” flag, 1 or blank)
 - RR_ruhe, RR_training, RR_abend — blood pressure readings as SYS/DIA/PULS, optionally with a trailing (HH:MM)/(Mittag) annotation. Rest-day rows carry real BP readings too — Nr: ‘-’ only means “no training that day”, not “no data”.
 - Kinomap, Strecke, Distanz_km, Kadenz_rpm, Watt_Max, Watt_Max_PR (☐ — set automatically when a session’s max watt beats every prior Watt_Max in the file), Hoehenmeter, Temperatur_C, Max_kmh — structured fields parsed out of the Kinomap on-screen summary; blank for non-Kinomap sessions.
 - Kommentar — free-text remainder (step-test/pyramid labels, warnings, subjective notes) that doesn’t fit a structured column above.
 - **Not stored — always computed by training.html at render time:** weekday, week number ($\text{Math.floor}((\text{date}-25.5)/7)+1$, fixed 7-day blocks from 25.5, not ISO weeks), cumulative kcal, week colors (cycled from a fixed palette), week date-range labels, hero metrics, and every chart’s axis bounds. There is nothing to keep in sync by hand — if a

number ever looks stale, it’s a bug in training.html’s derivation, not a missed manual edit.

- training.html — reads training_log.csv via fetch() and renders all 4 tabs (daily, weekly, table and the 200 W plan — labelled “Täglich”, “Wöchentlich”, “Tabelle”, “Plan 200W” in the German UI) with Chart.js (loaded from cdnjs.cloudflare.com, no local deps). Because it does a real fetch(), it must be served over HTTP (python3 -m http.server from the repo root, then open http://localhost:<port>/training.html) — opening the file directly (file://) fails silently because Chrome blocks local-file fetch() under file:// (CORS). The Plan tab’s phase-progress prose cards and the target-watt series (“Ziel”) are a hand-authored training plan, not logged data — those stay manually edited and are unaffected by any of this.
- training.pdf — a print export of training.html (all four tabs, light theme, landscape, pure white background), regenerated by hand after editing the CSV — see recipe below. Not needed after a normal add-training run, which regenerates it automatically.
- stufentest.html / stufentest_regression.html — standalone step-test watt/HR calibration charts, unrelated data (watts[]/bpms[] arrays), used to derive the HR-based watt estimation formula. Untouched by the CSV refactor.
- blutdruck.html — generated blood-pressure report (target-band chart as in training.html plus two histograms — before exertion (RR_ruhe) and after exertion (RR_training) — each with the 80/140 limits) for a date period, default the last 2 months. Written by the bldr skill (.claude/skills/bldr/scripts/bldr.py fills assets/blutdruck_template.html with the readings from the CSV) — a snapshot with embedded data that opens directly via file://; never edit it by hand, change the template and rerun /bldr.
- karte_<D.M>_<route>.html / karte_<D.M>_<route>_3d.html — generated map pages for one ride, built from a Kinomap export zip (export_<id>.zip) by the kinomap-karte skill (.claude/skills/kinomap-karte/scripts/kinomap-karte.py fills assets/karte_template.html and assets/karte3d_template.html): a 2D OpenStreetMap page with profile chart, and a three.js scene with terrain, buildings, cyclist avatar, playback, cockpit and pedal/chain sound — see “Map pages” below for what each page contains. Track, heightmap and buildings are embedded, but the OSM map image is loaded live, so — like training.html — they must be served over HTTP (file:// gets “Access blocked” tiles). Never edit them by hand; change the template and rerun /kinomap-karte.
- index.html — hand-edited landing page (the GitHub Pages entry point; manifest.json, sw.js and icon*.png make it installable): a plain list of links to the dashboards, PDFs and — in the 3D-ride section (“3D-Fahrt”) —

one ride's map pages, with a thumbnail image stored next to the page as `karte_<D.M>_<route>_3d.jpg`. Nothing generates it; a new ride's map only shows up there after adding the link (and thumbnail) by hand.

- `wkg_histogram.html`, `training_slideshow.html` — other standalone single-purpose dashboards with their own embedded data. Untouched.
- `PulsCharts/` — a self-contained folder: `puls_graphen_uebersicht.html` plus the watch-screenshot `.jpg` files it displays, referenced by plain relative filename (no subfolder) in the `<img src>`.

Generating training.pdf

`training.pdf` must be regenerated by hand after editing `training_log.csv` directly (the `add-training` skill does this automatically — this recipe is for a manual/bulk edit). Because `training.html` fetches the CSV, it must be rendered through a local HTTP server, not `file://`.

Recipe (headless Google Chrome + poppler's `pdftoppm`/`pdftotext` for verification):

```
SCRATCH=/path/to/scratch # any writable temp dir
```

```
python3 - <<'EOF'
p = '/Users/haraldbeker/training/training.html'
s = open(p).read()
s = s.replace(
    ".sec{display:none}", ".sec{display:block}"
) # show all 4 tabs
s = s.replace(
    "const isDark=matchMedia("
    "'(prefers-color-scheme: dark)').matches;",
    "const isDark=false;",
)
out = '/Users/haraldbeker/training/_training_print_tmp.html'
open(out, 'w').write(s) # must live in repo root, next to CSV
EOF
```

```
PORT=8756 # any free local port, not 5000 (macOS AirPlay)
(cd /Users/haraldbeker/training \
  && python3 -m http.server $PORT >/dev/null 2>&1 &)
sleep 1
```

```
CHROME="/Applications/Google Chrome.app/Contents/MacOS/Google Chrome"
URL="http://localhost:$PORT/_training_print_tmp.html"
"$CHROME" \
  --headless --disable-gpu --no-pdf-header-footer \
```

```
--virtual-time-budget=8000 \
--print-to-pdf="$SCRATCH/final.pdf" "$URL"
```

```
cp "$SCRATCH/final.pdf" /Users/haraldbeker/training/training.pdf
rm /Users/haraldbeker/training/_training_print_tmp.html
lsof -ti:$PORT | xargs -r kill
```

Before trusting the output, verify at high DPI — the low-res inline PDF preview is not reliable enough to catch either of the bugs below:

```
pdftoppm -png -r 200 -f 1 -l 1 \
/Users/haraldbeker/training/training.pdf \
"$SCRATCH/check"
# crop/zoom the daily "Ø Watt pro Tag" chart and confirm
# the tallest bar's pixel height lines up with its real
# value's gridline.
```

Pitfalls already fixed in `training.html` — don't reintroduce them:

- **Chart bars/lines can render squashed relative to their own y-axis even when Chart.js's config and data are correct** (e.g. a value of 213 only reaching the "140" gridline on a 100–230 axis). Root cause: Chart.js's default ~1000ms bar-growth animation gets captured mid-animation by the headless PDF snapshot, since `--virtual-time-budget` doesn't reliably advance `requestAnimationFrame`. Fixed by `animation:false` in `baseOpts` (in the script's `render()` function) — every chart spreads `...baseOpts`, so this covers all 9 charts. If squashing ever comes back, check this line first.
- **Chart axis bounds are auto-derived from the actual data on every render** (`scaleMin/scaleMax` helpers, ~8% headroom, rounded to a clean step) — this is no longer a hand-maintained value that can silently clip real data past an old max, unlike before this refactor.
- **Print-only CSS overrides** live in `@media print{...}` near the top of `<style>` (pure white `--bg/--surface/--surface2`, `@page{size:landscape}`, `body{max-width:none}` so the wide session table fits) and later `(.rec-row td{background:none})` — suppresses the "strong session" row highlight in print to save toner; must be declared *after* the base `.rec-row td` rule, since two rules with equal CSS specificity resolve by source order even across separate `@media print` blocks).
- `@media print{.card{break-inside:avoid;page-break-inside:avoid}}` (next to `.card{...}`) stops a chart card from being sliced across a page boundary.
- `_training_print_tmp.html` must be written **inside the repo root** (next to `training_log.csv`), not in `$SCRATCH` — its relative `fetch('training_log.csv')` resolves against whatever URL it's served from.

Map pages (2D and 3D)

Both pages are the same per-second track (lat/lon, dist, ele, watt, hf, rpm, kmh) rendered two ways. The script only swaps the `/*__DATA__*/null` placeholder in a template for the ride's JSON; every feature below lives in the template.

2D — `assets/karte_template.html` (Leaflet + Chart.js, both from a CDN):

- Hero metrics computed from the track itself: distance, duration, power/heart rate/cadence/speed (average and max), elevation (range and total climb).
- Leaflet map on live OSM tiles with the route coloured by one selectable metric (power, heart rate, cadence, speed, elevation). The colour scale runs from blue through green and yellow to red over the 5th–95th percentile, so start/stop outliers don't flatten it.
- Profile chart of the selected metric over distance, with elevation as a filled area on a second axis. Hovering it moves a cursor on the map and fills the one-line readout with all values of that second.
- Follows the system light/dark theme. Needs no network at build time (`--no-3d` writes only this page).

3D — `assets/karte3d_template.html` (three.js from a CDN):

- Terrain mesh from a heightmap the script bakes in (Mapzen terrarium elevation tiles from AWS), textured with OSM tiles fetched live; near the rider (or the orbit target when zoomed in) patches two zoom levels deeper are loaded lazily.
- Buildings within `--radius` of the route (default 800 m) from Overpass, merged into one mesh. Heights come from OSM `height/building:levels` where tagged and are otherwise guessed from type and footprint.
- Route line coloured by power, blue to red over the 5th–95th percentile, plus a faint see-through pass so it still reads behind buildings.
- Cyclist avatar with turning wheels and two-bone legs. It is moved by the `dist` column along the route polyline, not by the raw coordinates — the export repeats each GPS fix for 2–3 s. In the overview it is scaled up to stay visible; true size in follow mode.
- Playback: play/pause, 10×/30×/90×, scrub slider. Camera is a free orbit camera, or in follow mode (the “Mitfahren” checkbox) a chase camera 30 m behind and 5 m above the rider.
- Rider's-eye inset top right: a second viewport on the same WebGL canvas, rendered from the rider's eyes.
- Profile strip top left (speed, power, pulse, elevation over distance; click or drag to seek) and the cockpit at the bottom (four dials: speed, power, pulse, cadence; plus distance, time, elevation). The strip is hidden on narrow screens.
- Sound: pedal strokes, chain whirr, breathing and heartbeat synthesized with

Web Audio (filtered noise and sine thumps, no audio files). It follows the ride's real cadence rather than the playback speed-up — at 30× the true rhythm would be a 45 Hz buzz — gets louder with power and is silent at cadence 0. On top of that a breathing sound whose rate is stretched over this ride's own power range: the ride's lowest watt reading breathes at 14 breaths/min, its highest at 50 (BREATH in the template), linearly in between, with a slow glide so it lags the power like real breathing; it is mixed quietly, under the pedals. And a heartbeat (“lub-dub”, two short low sine thumps) at the pulse measured at that moment of the ride (hf), also in real time rather than sped up. The sound checkbox (“Ton”) mutes everything. It starts only on the click on the play button, because browsers block audio before a user gesture.

- URL parameters: `?t=<seconds>` start position, `?follow` start in follow mode, `?shot` for headless-Chrome screenshots, `?rec` hands the clock to `scripts/record_video.py` (frame-by-frame .mp4 capture, only run on request; the video has no audio and is never committed).

Key domain facts

- Watt is estimated from kcal/min, not measured directly: $\text{Watt} = (\text{kcal/min} \times 1000 \times 4.185) / 60 \times 0.25$, i.e. $\text{Watt} = \text{kcal/min} \times 17.4375$. Inverting it: $\text{Dauer}_{\text{min}} = \text{kcal} \times 17.4375 / \text{Watt}$. Displayed with a `~` prefix everywhere, since it's always an estimate.
- Dates are D.M with no year (implicit 2026), no leading zeros (e.g. '5.6', '14.8').
- Training weeks are fixed calendar boundaries starting Monday-ish from 25.5, 7-day blocks, not ISO weeks — computed by `getWeek()` in `training.html`'s script, not stored anywhere.
- A day can have multiple sessions (e.g. two rides logged the same date); when aggregating per day, sum kcal and average watt across that day's entries (see `dayMap` in `training.html`'s `render()` function).
- The total-duration hero/footer figure (“Total Dauer”) truncates each session's seconds before summing (not rounding the grand total) — a quirk preserved from the pre-CSV data so the displayed total didn't shift during the migration.