

Lab 2-2

Connection values:

Server Type = Database Engine

Server Name = is-swang01.ischool.uw.edu

Authentication = SQL Server Authentication

Login = INF06210

Password = NEUHusky!

Note:

Two ways to specify comments in SQL commands:

Use -- for a line of comments

or use /* */ for a block of comments.

```
-- Set the database context
USE AdventureWorks2008R2;

-- SQL JOINS are used to retrieve data from multiple tables.
-- INNER is the default when JOIN is the only keyword used.
-- INNER JOIN returns only matching rows from left and right tables.
-- c is the alias for the Sales.Customer table in the example.
-- oh is the alias for the Sales.SalesOrderHeader table.
-- ON lists the matching columns to JOIN on.
```

```
/*
    If two tables have the same column name in a query, we must
    designate where the column is from by using the format
    TableName.ColumnName.
    If a column name is unique between the JOINed tables,
    The TableName.ColumnName format is not required.
*/
```

```
SELECT c.CustomerID, c.AccountNumber, SalesOrderID, OrderDate
FROM Sales.Customer c
INNER JOIN Sales.SalesOrderHeader oh
ON c.CustomerID = oh.CustomerID;
```

```
/*
    LEFT OUTER JOIN returns all rows from the left table,
    but only the matching rows from the right table.
*/
```

```
SELECT c.CustomerID, c.AccountNumber, SalesOrderID, OrderDate
FROM Sales.Customer c
LEFT OUTER JOIN Sales.SalesOrderHeader oh
ON c.CustomerID = oh.CustomerID;
```

```
/*
    RIGHT OUTER JOIN returns all rows from the right table,
    but only the matching rows from the left table.
*/
```

```
SELECT c.CustomerID, c.AccountNumber, SalesOrderID, OrderDate
FROM Sales.Customer c
RIGHT OUTER JOIN Sales.SalesOrderHeader oh
ON c.CustomerID = oh.CustomerID;
```

```
-- Set the database context
USE AdventureWorks2008R2;

-- COUNT, GROUP BY, ORDER
-- GROUP BY aggregates on the column(s) we specify
-- ORDER BY does sorting

SELECT c.CustomerID,
       PersonID,
       COUNT(SalesOrderID) AS "Total Order"
FROM Sales.Customer c
INNER JOIN Sales.SalesOrderHeader oh
ON c.CustomerID = oh.CustomerID
GROUP BY c.CustomerID, PersonID
ORDER BY "Total Order" DESC;
```

```
--JOIN, COUNT, GROUP BY, HAVING, ORDER
```

```
--SELECT the order count for each customer
```

```
--WHERE the count > 20
```

```
--ORDER the counts in the descending order
```

```
/*
```

For regular filtering in a query, we use WHERE.

If we use GROUP BY in a query, then we use HAVING to do the filtering for groups.

```
*/
```

```
SELECT c.CustomerID,  
       PersonID,  
       COUNT(SalesOrderID) AS "Total Order"  
FROM Sales.Customer c INNER JOIN Sales.SalesOrderHeader oh  
ON c.CustomerID = oh.CustomerID  
GROUP BY c.CustomerID, PersonID  
HAVING COUNT(SalesOrderID) > 20  
ORDER BY "Total Order" DESC;
```

	CustomerID	PersonID	Total Order
1	11091	4515	28
2	11176	15994	28
3	11185	12569	27
4	11200	5409	27
5	11223	3197	27
6	11262	20532	27
7	11276	15449	27
8	11277	4855	27
9	11287	15978	27
10	11300	13098	27

```
-- Set the database context
USE AdventureWorks2008R2;
```

```
-- IN OPERATOR
```

```
-- Can be used with any data type
```

```
SELECT ProductID, Name, Color, ListPrice, SellStartDate
FROM Production.Product
WHERE Color IN ('Red', 'Blue', 'White') -- character comparison
ORDER BY Color, Name;
```

```
SELECT ProductID, Name, Color, ListPrice, SellStartDate
FROM Production.Product
WHERE ListPrice IN (337.22, 594.83, 63.50, 8.99) -- numeric comparison
ORDER BY ListPrice;
```

```
-- LIKE operator
```

```
-- Select any person whose last name begins with a
```

```
-- % is the wildcard symbol representing 0 to many characters
```

```
-- _ is the wildcard symbol representing exactly one character
```

```
SELECT FirstName, MiddleName, LastName
FROM Person.Person
WHERE LastName LIKE 'a%'
ORDER BY LastName;
```

```
-- Select any person whose last name begins with a or c or e
```

```
SELECT FirstName, MiddleName, LastName
FROM Person.Person
WHERE LastName LIKE '[ace]%'
ORDER BY LastName;
```

```
-- Set the database context
USE AdventureWorks2008R2;
```

--Subqueries are queries that are embedded in another query.

```
SELECT Name [Product],
       ListPrice,
       (SELECT MAX(ListPrice) FROM Production.Product)
       AS [Max Price],
       (ListPrice / (SELECT MAX(ListPrice) FROM Production.Product)) * 100
       AS [Percent of MAX]
FROM Production.Product
WHERE ListPrice > 0
ORDER BY ListPrice DESC;
```

-- Lab 2 Questions

Note: 1 point for each question

/* Use the content of the AdventureWorks sample database for each of the following questions. Submit the SQL queries to Blackboard in a single .sql file. */

2-1

/* Write a query to retrieve all orders made after May 1, 2008 and had an total due value greater than \$50,000. Include the customer id, sales order id, order date and total due columns in the returned data.

Use the CAST function in the SELECT clause to display the date only for the order date. Use ROUND to display only two decimal places for the total due amount. Use an alias to give a descriptive column heading if a column heading is missing. Sort the returned data first by the customer id, then order date.

Hint: (a) Use the Sales.SalesOrderHeader table.
(b) The syntax for CAST is CAST(expression AS data_type), where expression is the column name we want to format and we can use DATE as data_type for this question to display just the date.
(c) The syntax for ROUND is ROUND(expression, position_to_round), where expression is the column name we want to format and we can use 2 for position_to_round to display two decimal places. */

2-2

/* List the latest order date and total number of orders for each customer. Include only the customer ID, account number, latest order date and the total number of orders in the report. Display date only for the order date. Use column aliases to make the report more presentable. Sort the returned data by the customer id.

Hint: You need to work with the Sales.SalesOrderHeader table. */

2-3

```
/* Write a query to select the product id, name, and list price
   for the product(s) that have a list price greater than the
   the list price of the product 912. Display only two decimal
   places for the list price and make sure all columns have a descriptive
   heading. Sort the returned data by the list price in descending.
```

Hint: You'll need to use a simple subquery to get the list price
of the product 912 and use it in a WHERE clause. */

2-4

```
/* Write a query to retrieve the number of times a product has
   been sold for each product. Note it's the number of times a
   product has been contained in an order, not the sold quantity.
   Include only the products that have been sold more than 5 times.
   Use a column alias to make the report more presentable.
   Sort the returned data by the number of times a product
   has been sold in the descending order first, then the
   product id in the ascending order. Include the product ID,
   product name and number of times a product has been sold columns
   in the report.
```

Hint: Use the Sales.SalesOrderDetail and Production.Product tables. */

2-5

```
/* Write a query to generate a unique list of customer ID's and
   account numbers that have not placed an order after January 1, 2008.
   Sort the list by CustomerID in the ascending order. */
```

2-6

```
/* Write a query to create a report containing customer id,
   first name, last name and email address for all customers.
   Sort the returned data by CustomerID in ascending. */
```


Useful Links

USE SQL Server Management Studio

<http://msdn.microsoft.com/en-us/library/ms174173.aspx>

Writing SQL Queries

[http://technet.microsoft.com/en-us/library/bb264565\(v=sql.90\).aspx](http://technet.microsoft.com/en-us/library/bb264565(v=sql.90).aspx)

SQL Aggregate Functions

<http://msdn.microsoft.com/en-us/library/ms173454.aspx>

Types of JOIN in SQL Server

<http://www.codeproject.com/Tips/712941/Types-of-Join-in-SQL-Server>

GROUP BY and HAVING

<http://technet.microsoft.com/en-us/library/ms180199.aspx>

Subquery Fundamentals

[http://technet.microsoft.com/en-us/library/ms189575\(v=sql.105\).aspx](http://technet.microsoft.com/en-us/library/ms189575(v=sql.105).aspx)

CAST and CONVERT

<https://msdn.microsoft.com/en-us/library/ms187928.aspx>