

REVIEWING COMPARE

Some common points to improve

Remember:

- "working" is not the end
- You program for other coders, not the computer
- Skimmability means you shouldn't HAVE to read the code

THIS WORKS...TECHNICALLY

```
function compare( word, guess ) {  
  var count=0;  
  var obj={};  
  for(let i=0; i<word.length; i++) {  
    if(isNaN(obj[word[i].toLowerCase()])) {  
      obj[word[i].toLowerCase()]=1;  
    } else {  
      obj[word[i].toLowerCase()]++;  
    }  
  }  
  for(let i=0; i<guess.length; i++) {  
    if(obj[guess[i].toLowerCase()] > 0) {  
      obj[guess[i].toLowerCase()]--;  
      count++;  
    }  
  }  
  return count;  
}
```

NEVER USE VAR

- `var` is for old engines, not modern
- prefer `const`
- use `let` if you have to reassign the value

```
function compare( word, guess ) {  
  let count=0;  
  const obj={};  
  for(let i=0; i<word.length; i++) {  
    if(isNaN(obj[word[i].toLowerCase()])) {  
      obj[word[i].toLowerCase()]=1;  
    } else {  
      obj[word[i].toLowerCase()]+=1;  
    }  
  }  
  //...  
}
```

VISUAL SPACE MAKES IT EASIER TO SKIM

- Just like text, use space to make it easier to skim.
- Use "paragraphs" - blank lines between ideas
- There is no reward for tiny squished code

```
function compare( word, guess ) {  
  let count = 0;  
  const obj = {};  
  
  for( let i = 0; i < word.length; i++ ) {  
    if( isNaN(obj[word[i].toLowerCase()]) ) {  
      obj[word[i].toLowerCase()] = 1;  
    } else {  
      obj[word[i].toLowerCase()]++;  
    }  
  }  
  //...  
}
```

VARIABLE NAMES ARE HUGE

- Variable and function names: main source of info!
- Name for what it holds/represents, not how
- No need to take out a few letters - just hurts

```
function compare( word, guess ) {  
  let matches = 0;  
  const letterCount = {};  
  
  for( let i = 0; i < word.length; i++ ) {  
    if( isNaN(letterCount[word[i].toLowerCase()]) ) {  
      letterCount[word[i].toLowerCase()] = 1;  
    } else {  
      letterCount[word[i].toLowerCase()]++;  
    }  
  }  
  //...  
}
```

VARIABLE NAMES ARE HARD

Bad Names:

- `obj`, `ary`, `tmp`, `str`
- `map`, `dict`, `len`, `list`
- anything spleled wrong

Usually Bad Names:

- `data`, `result`, `retval`, `count`

DO YOU ACTUALLY NEED THAT INDEX VALUE?

- use `for..of` to get the value you care about (letter)

```
function compare( word, guess ) {  
  let matches = 0;  
  const letterCount = {};  
  
  for( let letter of word ) {  
    if( isNaN( letterCount[ letter.toLowerCase() ] ) ) {  
      letterCount[ letter.toLowerCase() ] = 1;  
    } else {  
      letterCount[ letter.toLowerCase() ]++;  
    }  
  }  
  //...  
}
```

PULL OUT AND NAME VALUES

- Particularly if they are repeated
- Often you can move logic out to another function
- DRY - Don't Repeat Yourself
- DRY - Don't Repeat Yourself

```
function compare( word, guess ) {  
  let matches = 0;  
  const letterCount = {};  
  
  for( let letter of word ) {  
    const lower = letter.toLowerCase();  
    if(isNaN(letterCount[lower])) {  
      letterCount[lower] = 1;  
    } else {  
      letterCount[lower]++;  
    }  
  }  
  //...  
}
```


REMOVE UNNEEDED FOCUS

- NOT about being **shorter**
- IS about **focus** of the eye

```
function compare( word, guess ) {  
  let matches = 0;  
  const letterCount = {};  
  
  for( let letter of word.toLowerCase() ) {  
    if(isNaN(letterCount[letter])) {  
      letterCount[letter] = 1;  
    } else {  
      letterCount[letter]++;  
    }  
  }  
  //...  
}
```

USE TRUTHY/FALSY

- Improve skimmability
- Draw eye to important parts
 - not `===` or `isSomething`
- Remember: 0 is **falsy** (good here, not always)

```
function compare( word, guess ) {  
  let matches = 0;  
  const letterCount = {};  
  
  for( let letter of word.toLowerCase() ) {  
    if( !letterCount[letter] ) {  
      letterCount[letter] = 1;  
    } else {  
      letterCount[letter]++;  
    }  
  }  
  //...  
}
```

CAUTIOUS USE OF TERNARY OPERATOR

- When assigning a value, can reduce "visual noise"
- ...or INCREASE visual noise
- Remember: Shorter is NOT the exact goal
- ...I'll pass this time

```
function compare( word, guess ) {  
  let matches = 0;  
  const letterCount = {};  
  
  for( let letter of word.toLowerCase() ) {  
    letterCount[letter] = letterCount[letter] ? letterCount + 1 : 1;  
  }  
  //...  
}
```

PULL OUT LOGIC INTO MORE FUNCTIONS

- creates list of instructions instead of math
- Good to make the code DRYer
- ...I'll pass this time

```
function compare( word, guess ) {  
  let matches = 0;  
  const letterCount = {};  
  
  const increment = count => count ? count + 1 : 1;  
  
  for( let letter of word.toLowerCase() ) {  
    letterCount[letter] = increment(letterCount[letter]);  
  }  
  //...  
}
```

NOT ALWAYS POST-INC/DECREMENT

- ++ and -- aren't the only way to increase/decrease
- += 1 and -= 1 work, and allow for other numbers
- draw focus to what you're actually doing

```
function compare( word, guess ) {  
  //.. some code above  
  
  for( let letter of guess.toLowerCase() ) {  
    if( letterCount[letter] ) {  
      letterCount[letter] -= 1;  
      matches += 1;  
    }  
  }  
  
  return matches;  
}
```

DEFAULTING AND SHORT-CIRCUITING

- `&&` and `||` short circuit
- `&&` and `||` return a value
 - Not just boolean: `foo = foo || 'default';`
- Often when an `if` checks for truthyness, and assign to value either way

```
function compare( word, guess ) {  
  let matches = 0;  
  const letterCount = {};  
  
  for( let letter of word.toLowerCase() ) {  
    letterCount[letter] = letterCount + 1 || 1;  
  }  
  
  //...  
}
```

BEFORE...

```
function compare( word, guess ) {  
  var count=0;  
  var obj={};  
  for(let i=0; i<word.length; i++) {  
    if(isNaN(obj[word[i].toLowerCase()])) {  
      obj[word[i].toLowerCase()]=1;  
    } else {  
      obj[word[i].toLowerCase()]++;  
    }  
  }  
  for(let i=0; i<guess.length; i++) {  
    if(obj[guess[i].toLowerCase()] > 0) {  
      obj[guess[i].toLowerCase()]--;  
      count++;  
    }  
  }  
  return count;  
}
```

...AND AFTER

```
function compare( word, guess ) {  
  let matches = 0;  
  const letterCount = {};  
  
  for( let letter of word.toLowerCase() ) {  
    letterCount[letter] = letterCount + 1 || 1;  
  }  
  
  for( let letter of guess.toLowerCase() ) {  
    if( letterCount[letter] ) {  
      letterCount[letter] -= 1;  
      matches += 1;  
    }  
  }  
  
  return matches;  
}
```


SUMMARY

- Functions should try to be 1-15 lines
- Names should be meaningful even by themselves
- Skimmability is about managing **focus**
 - Avoid visual noise
 - Avoid "squishing"
- People will argue about how best to do this
 - ...just like with human languages

SUMMARY - PART 2

Impacts your grade:

- Meaningful Names (**useful** meaning!)
 - Not `i`, `obj`, `tmp`
- Aim for skimmability
- Never use `var`; prefer `const`
- Always use strict comparison, unless using `truthy/falsyness`