STHUTHI SECURITIES

PENETRATION TEST SCOPING WORKBOOK

Define the targets, roles, test rules, evidence, and retesting before an authorized assessment.



Sthuthi Technologies, LLC

Sthuthi Securities

A product of Sthuthi Technologies, LLC

Version 1.0 - November 2026

Copyright and use

Copyright © 2026 Sthuthi Technologies, LLC. All rights reserved.

The purchaser or authorized recipient may copy and edit the worksheets in this workbook for one organization and its contracted security providers. The workbook may not be resold, republished, or distributed as a competing template product without written permission.

This workbook supports planning. It does not authorize security testing, grant rights over a system, replace a signed contract, provide legal advice, issue an audit opinion, or prove compliance. Confirm ownership, third-party permissions, cloud-provider rules, privacy obligations, and applicable law before testing. Never place passwords, API keys, customer records, or production secrets in a copy of this workbook that will be shared through ordinary email.

How to use this workbook

A useful scope tells a tester what may be tested, what behavior matters, how far testing may go, when it must stop, and what evidence the client expects at the end. A list of domain names is not enough.

Complete the workbook with the people who own the product, operate the environment, understand customer data, and can grant written authority. Engineering usually knows the system. Product knows the critical workflows. Security knows the test controls. Legal or procurement may need to confirm third-party rights and contract terms. One person can hold several of these roles in a small company, but the decisions still need named owners.

Use the chapters in order for a first assessment. For a repeat test, begin with the prior scope and mark every changed system, role, workflow, integration, environment, or rule. Do not silently carry an old scope into a materially different release.

The completed workbook should produce five outputs:

1. A decision brief explaining why the assessment exists.
2. A system boundary with named targets and owners.
3. A coverage plan tied to roles, tenants, and critical workflows.
4. Rules of engagement signed by an authorized owner.
5. Report and retest acceptance criteria.




Figure 1. Scope starts with the decision the assessment must support, then works backward into the systems, behavior, test rules, and required output.

Table of contents

- Copyright and use
- How to use this workbook

Part I Define the assessment

1 Start with the decision the test must support
- Write one primary decision
- Identify the relying audience
- Define success without promising zero findings
- Worksheet 1 Assessment decision brief
- Decision quality check

2 Name the systems and assets
- Record targets at the level the tester can identify
- Separate scope states
- Worksheet 2 Asset register
- Worksheet 3 Ownership and authority record
- Boundary review questions

3 Map users roles tenants and critical workflows
- Inventory identities before permissions
- Map tenant boundaries explicitly
- Define critical workflows as state changes
- Worksheet 4 Identity and role matrix
- Worksheet 5 Tenant test design
- Worksheet 6 Critical workflow inventory
- Minimum role coverage

Part II Describe the test surface

4 Choose coverage by application type
- Web application coverage
- API coverage
- Mobile application coverage
- Cloud coverage
- Connected SaaS and OAuth coverage
- AI-enabled workflow coverage
- Worksheet 7 Coverage module selection
- Worksheet 8 API inventory

5 Select environments data and dependencies
- Compare environments before choosing
- Minimize sensitive data
- Map dependencies and failure paths
- Worksheet 9 Environment and data plan
- Worksheet 10 Dependency boundary

6 Define reconnaissance and discovery boundaries
- Choose the discovery model
- Handle newly discovered assets
- Worksheet 11 Discovery rules

Part III Make the engagement lawful and safe

7 Write authorization and rules of engagement
- Name the authorizing parties
- Define allowed actions by class
- Write prohibited actions plainly
- Set time and traffic controls
- Establish stop conditions
- Worksheet 12 Rules of engagement
- Authorization release check

8 Prepare accounts access and monitoring
- Build the account set from the role matrix
- Separate credential delivery
- Prepare monitoring without hiding the test
- Worksheet 13 Access readiness checklist

9 State exclusions limits and unknowns
- Distinguish an exclusion from a limitation
- Avoid generic disclaimers
- Worksheet 14 Exclusion limitation and unknown register

Part IV Agree on the output

10 Set evidence and reporting requirements
- Define the evidence unit
- Agree on severity language
- Protect sensitive evidence
- Define report versions and acceptance
- Worksheet 15 Finding acceptance criteria
- Worksheet 16 Report acceptance criteria

11 Define remediation and retesting
- Keep review and remediation states separate
- Define the retest unit
- Set commercial and timing terms
- Worksheet 17 Retest agreement

12 Fix the schedule and responsibilities
- Name contacts by responsibility
- Set decision points
- Worksheet 18 Engagement operating plan

Part V Issue the scope

13 Assemble the statement of work
- One page scope brief

Scope change control
Final issue checklist
14 Worked example for a multi tenant SaaS platform
Product description
Completed decision brief
Completed asset register
Completed role and tenant plan
Completed critical workflows
Completed rules of engagement summary
Example finding acceptance criteria
Example retest
Appendix A Master pre test checklist
Decision and scope
Roles and access
Safety and authority
Evidence and delivery
Appendix B Vendor proposal comparison scorecard
Appendix C Glossary
Sources
About Sthuthi Securities
Workbook completion record

Part I Define the assessment

1 Start with the decision the test must support

Penetration tests are bought for different reasons. A customer may require an annual report. An auditor may ask how a control was tested. A product team may be preparing a release. A board may want assurance after a major acquisition. Those are different decisions and may require different targets, timing, evidence, and report language.

Write the decision before naming tools or test cases. “Test our platform” gives no way to judge whether the result is useful. “Determine whether a customer user can access or change another customer’s records before the enterprise launch” gives the assessor a system rule, a role boundary, an impact, and a deadline.

NIST SP 800-115 treats planning as part of the assessment process, not administrative work that happens after the technical plan is set. It describes rules of engagement as detailed constraints established before testing and as the basis for authority to perform the defined activities.[1] OWASP likewise describes its testing material as a set of techniques that must be adapted to the application’s architecture, threat model, data, and business context.[2]

Write one primary decision

Choose one sentence that the report must help someone answer. Examples:

- Can a customer cross the tenant boundary in the production-equivalent SaaS application?
- Can an authenticated user call administrative API functions without the required role?
- Can the mobile application expose account data through local storage, transport, or its backend API?
- Can an AI support agent read another customer’s order or issue a refund without approval?
- Does the current release provide the technical testing evidence requested for an audit or customer review?

Secondary goals can be recorded, but they should not crowd out the primary decision. If the company needs an application test, cloud-configuration review, source-code review, phishing exercise, and recovery exercise, it probably needs several workstreams rather than one vague “full security test.”

Identify the relying audience

The same technical finding is presented differently to an engineer, a customer security team, an auditor, and a board. Record the people who will rely on the output and what they expect to receive. Do not promise a certification, compliance conclusion, or audit opinion when the assessor is only performing technical testing.

An auditor may want scope dates, methodology, tester independence, findings, remediation, and retest evidence. Engineering needs exact reproduction steps, affected components, and a specific fix. Procurement may need a short executive summary and proof that the report can be shared under controlled terms. The statement of work should name these outputs before testing begins.

Define success without promising zero findings

“No vulnerabilities found” is not a sensible success condition. A test can be well executed and still identify serious weaknesses. Use conditions the engagement can control:

- Every named critical workflow received the agreed coverage.
- Each required role and tenant combination was tested.
- Confirmed findings contain reproducible evidence and a clear affected rule.
- Limitations and untested areas are stated.
- The report is delivered by the required date.
- Retesting uses the recorded scenario against the corrected release.

Worksheet 1 Assessment decision brief

Field	Response
Engagement name	

Field	Response
Primary business decision	
Trigger for the assessment	
Deadline and reason for it	
People or organizations relying on the output	
Required report or evidence format	
Primary security concern	
Critical data or action at risk	
What a successful engagement must complete	
What the engagement must not claim	
Executive owner	
Technical owner	
Scope version and date	

Decision quality check

- ☐ The decision names a system or product boundary.
- ☐ The decision names the behavior or security rule under review.
- ☐ The deadline has a real business reason.
- ☐ The relying audience is known.
- ☐ Required deliverables are stated.
- ☐ Success does not depend on finding zero vulnerabilities.
- ☐ The test is not being described as an audit or certification unless it actually is one.

2 Name the systems and assets

The assessor cannot test an unnamed system. Start with the product as the user experiences it, then trace the components that accept requests, make decisions, store data, or call another service.

For a modern SaaS application, one “website” may include a browser application, public API, internal API, identity provider, file store, background workers, administrative console, payment provider, customer-support tooling, cloud infrastructure, and an AI model or retrieval system. The scope must distinguish client-owned components from third-party services. OWASP’s architecture-mapping guidance specifically calls for understanding technologies and components and recognizing that connected third-party systems are usually outside a tester’s authority unless separately included.[3]




Figure 2. A connection does not create authority. Third-party services require their own permission or a test plan that stops at the client-controlled integration boundary.

Record targets at the level the tester can identify

Use exact identifiers where possible:

- Fully qualified domain names and base URLs
- API hostnames, base paths, versions, and specifications
- Mobile package or bundle identifier and build number
- Cloud account, subscription, tenant, project, and region
- Source repository and commit or release tag when code review is included
- Container image digest or deployed release identifier
- Administrative interfaces and non-public routes
- Webhook destinations and callback sources
- AI model, orchestration service, retrieval index, and enabled tools

Avoid “all company infrastructure” unless the company can produce a defensible inventory and truly intends to authorize that breadth. Avoid wildcard scope such as *.example.com without stating whether discovery is allowed, which host classes are included, and what happens when a third-party or abandoned service is found.

Separate scope states

Give each asset one state:

- **In scope:** the assessor may perform the allowed tests.
- **Discovery only:** the assessor may identify and record the asset but may not actively test it.
- **Conditional:** testing requires a named condition, such as a maintenance window or separate approval.
- **Out of scope:** the assessor must not test it.
- **Unknown ownership:** testing is prohibited until ownership or authority is proved.

These states prevent a common error: treating every system discovered under a company domain as client-owned. DNS, content-delivery networks, hosted support pages, payment services, and acquisition-era systems can belong to another party.

Worksheet 2 Asset register

ID	Asset or component	Exact identifier	Owner	Environment	Scope state	Allowed test class	Notes
A-01							
A-02							
A-03							
A-04							
A-05							
A-06							

Worksheet 3 Ownership and authority record

Asset ID	Legal or operational owner	Evidence of control	Third-party terms checked	Person granting authority	Status

Acceptable evidence depends on the system. It may include cloud-console ownership, a domain record, a contract, a service account controlled by the client, or a written permission chain from the actual owner. The assessor should not decide that a client owns a target merely because the target contains the client's name.

Boundary review questions

- Which components enforce identity and authorization?
- Which component makes the final business decision?
- Where are tenant identifiers introduced and checked?
- Which stores contain customer, employee, payment, health, or regulated data?
- Which administrative interfaces are not linked from the normal application?
- Which background jobs continue after the browser request ends?
- Which integrations can read data or perform actions after a user signs out?
- Which assets were added through an acquisition or vendor relationship?
- Which systems cannot tolerate active testing?
- Which systems are being retired but remain reachable?

3 Map users roles tenants and critical workflows

Authorization testing needs more than one test account. The scope should describe who can act, which records they can reach, which operations they can perform, and how those rules change across tenants, teams, subscriptions, or lifecycle states.

OWASP's authorization testing guidance separates unauthenticated access, horizontal access between equivalent users, and vertical access into higher-privilege functions.[4] A useful role matrix turns those categories into the product's actual rules.

Inventory identities before permissions

List human users, service identities, API clients, background workers, integration tokens, and emergency accounts. Record how each identity authenticates and where its permissions are enforced. A user may sign in through an identity provider but receive product permissions from a separate application database. An API key may belong to an organization rather than a person. A background worker may carry authority far beyond the user who triggered it.

Include lifecycle states. Newly invited, suspended, deleted, password-reset, trial, past-due, and former-employee accounts can behave differently from normal active users. A test that uses only the happy-path customer account misses these transitions.

Map tenant boundaries explicitly

For a multi-tenant product, create at least two test tenants with distinct users and records. If resellers, parent organizations, workspaces, projects, or regions create nested boundaries, include those relationships. Give every test record a visible synthetic owner so cross-tenant evidence can be interpreted without exposing customer data.

The matrix should support tests such as:

- Customer A requests Customer B's object by identifier.
- Customer A submits an API call captured from Customer B.
- A team administrator changes an organization-owner setting.
- A support user accesses an unassigned customer.
- A former member reuses a token after removal.
- A user changes a tenant identifier in a file, export, webhook, or background-job reference.

Define critical workflows as state changes

"Test account management" is too broad. Write each workflow as a sequence with an expected rule:

6. Starting identity and state
7. Input or action
8. System decision
9. Data read or state change
10. Expected authorization result
11. Evidence that proves what happened

For example: "A customer administrator invites a new member to its own tenant. A standard customer must not invite members. No user from another tenant may accept or alter the invitation." This description exposes role, tenant, state, and object boundaries.

Worksheet 4 Identity and role matrix

Role or identity	Authentication method	Tenant scope	May read	May change	May administer	Test account available
Anonymous	None	None				N/A

Role or identity	Authentication method	Tenant scope	May read	May change	May administer	Test account available
Standard customer						
Customer administrator						
Support user						
Platform administrator						
Service identity						

Worksheet 5 Tenant test design

Tenant	Synthetic users	Synthetic records	Subscription or state	Special relationship	Reset method
Tenant A					
Tenant B					
Parent or reseller					

Worksheet 6 Critical workflow inventory

ID	Workflow	Starting role	Sensitive object or action	Expected rule	Failure impact	Priority
W-01						
W-02						
W-03						
W-04						
W-05						

Minimum role coverage

- ☐ Anonymous or signed-out behavior
- ☐ Lowest-privilege authenticated user
- ☐ Equivalent users in different tenants
- ☐ Customer or team administrator
- ☐ Internal support or operations role
- ☐ Highest-risk administrative role, if permitted
- ☐ Service or integration identity
- ☐ Suspended, removed, expired, or otherwise changed identity

Part II Describe the test surface

4 Choose coverage by application type

The scope should name coverage modules rather than claiming that one method covers everything. A browser test, API test, mobile test, cloud review, and AI-agent assessment can overlap, but each exposes a different part of the system.

OWASP WSTG organizes web testing across information gathering, configuration, identity, authentication, authorization, session management, input handling, error handling, cryptography, business logic, client behavior, and APIs.[2] The guide also warns that no fixed checklist can cover every application. Select the relevant techniques and tie them to the system rules recorded in this workbook.

Web application coverage

Record all browser-accessible roles, routes, critical forms, upload and download functions, administrative interfaces, and client-side storage. Include authentication entry points, password recovery, invitations, federation, MFA enrollment, and session termination.

Browser coverage should address how the application behaves when requests are changed outside the user interface. A disabled button is not an authorization control. The assessor needs permission to capture, repeat, and modify relevant requests within the agreed limits.

Typical coverage areas include:

- Public and authenticated attack surface
- Authentication and account recovery
- Session cookies, tokens, logout, expiry, and concurrent sessions
- Horizontal and vertical authorization
- Input validation and injection paths
- File upload, download, preview, and processing
- Browser storage, cross-origin behavior, and client-side trust
- Business workflows, state transitions, and race conditions
- Error handling and sensitive-data exposure
- Security headers and transport configuration

API coverage

An API scope needs the specification and the observed endpoints. They may differ. Record base URLs, versions, methods, object types, authentication schemes, webhook behavior, bulk operations, GraphQL operations, and administrative functions.

The OWASP API Security Top 10 highlights object-level authorization, authentication, object-property authorization, resource consumption, function-level authorization, sensitive business flows, server-side request forgery, configuration, inventory, and unsafe consumption of third-party APIs.[5] Use it as a risk prompt, not a claim that every relevant API test fits into ten labels.

API test planning should answer:

- Can one identity address another tenant’s object?
- Do list, search, export, batch, and indirect-reference endpoints apply the same checks as single-object endpoints?
- Can a client set server-controlled properties such as role, owner, status, price, or approval state?
- Are function permissions enforced at the API, not only in the interface?
- Can resource-intensive requests exceed agreed budgets or affect other tenants?
- Do webhooks verify source, freshness, and replay resistance?
- Does the application trust unsafe data returned by a supplier API?

Mobile application coverage

Identify the exact iOS or Android build, distribution channel, supported operating-system versions, backend environment, and whether anti-tamper or certificate-pinning controls may affect testing. Mobile coverage can include local storage, logs, backups, inter-process communication, deep links, transport, authentication, runtime behavior, and backend APIs.

Do not treat the mobile binary and backend API as one unnamed target. A mobile assessment may need separate permission to analyze the application package, instrument the running app, bypass test-environment protections, and call the API outside the app.

Cloud coverage

Cloud testing needs account-level identifiers and provider-specific rules. AWS currently allows customer testing of listed services without prior approval, but prohibits testing AWS infrastructure itself and requires prior approval for command-and-control activity.[6] Microsoft Azure allows testing of resources the customer owns or is authorized to test, subject to its published rules, and prohibits denial-of-service testing and access to other tenants.[7] Google Cloud does not require notice for testing a customer project, but the activity must follow its acceptable-use terms and affect only the customer's projects.[8]

Record the current provider policy URL in the engagement file. Policies can change. The rules checked during scoping are part of the evidence for why a planned action was allowed.

Cloud coverage may include:

- Identity roles, trust policies, service accounts, and access keys
- Public endpoints and exposed storage
- Network paths, security groups, firewalls, and private connectivity
- Secrets, configuration, and workload identity
- Management-plane versus application-plane boundaries
- Logging, alerting, and response to test activity
- Container, serverless, and managed-service configuration
- Cross-account, cross-subscription, or cross-project trust

Connected SaaS and OAuth coverage

List the integration, granted scopes, installation owner, token storage, refresh behavior, revocation behavior, and actions that remain possible after a user leaves. Define whether the assessor may install a test integration, change scopes, replay callbacks, or test only the client-owned portion.

AI-enabled workflow coverage

An AI feature may connect user input to retrieved documents, memory, external tools, and real business actions. The scope should name the model or service, orchestration layer, retrieval sources, available tools, tool identities, approval requirements, and actions whose effects must be observed.

Prompt output alone does not establish impact. The evidence plan should capture the system's deterministic decision, tool request, downstream authorization response, and resulting data access or state change. An AI assessment may include direct and indirect prompt injection, retrieval-boundary tests, tool-argument manipulation, cross-tenant context, memory behavior, sensitive-output handling, and approval bypass.

Worksheet 7 Coverage module selection

Module	Included	Named targets	Required inputs	Highest-priority rule	Material limitation
Web application					
API					
Mobile application					
Cloud configuration					
Connected SaaS or OAuth					

Module	Included	Named targets	Required inputs	Highest-priority rule	Material limitation
AI-enabled workflow					
Source-code review					
Network or infrastructure					

Worksheet 8 API inventory

API or version	Base URL	Specification	Authentication	Roles	Object types	Webhooks or callbacks	Scope state

5 Select environments data and dependencies

Production provides the most faithful behavior and the highest operational risk. Staging is safer but may differ in data, integrations, identity, configuration, or release version. Record those differences instead of describing one environment as “production-like.”

Compare environments before choosing

Question	Production	Test environment
Application version		
Infrastructure and configuration match		
Identity provider and role model match		
API and integration behavior match		
Customer data present		
Monitoring and alerting active		
Destructive test risk		
Reset or recovery available		

If the test runs in production, identify safe synthetic accounts and records. If it runs in staging, state which findings may require a limited production confirmation and who can approve it. Never copy production customer data into a test environment merely to make the test realistic.

Minimize sensitive data

The tester usually needs representative object relationships, not real customer content. Build synthetic records that show tenant, owner, state, and sensitivity without reproducing personal information. Record how test data is created, marked, reset, exported, and deleted.

Define evidence sanitization before testing. Screenshots, HTTP traces, logs, database results, model context, and files can contain tokens or customer data. State where raw evidence is stored, who can access it, how client-visible evidence is redacted, and when it is deleted.

Map dependencies and failure paths

A workflow can depend on email, payment, identity, file processing, queues, analytics, model providers, or customer-managed endpoints. For each dependency, determine whether the tester may interact with the real service, a sandbox, a stub, or only the client-controlled integration code.

Do not send test emails, refunds, support messages, or webhooks to real recipients without explicit permission and controls. For a workflow that changes money or account access, define a synthetic or reversible path and a person who can stop or undo it.

Worksheet 9 Environment and data plan

Field	Response
Primary test environment	
Exact release or build	
Known differences from production	
Production confirmation allowed	
Synthetic tenants and records	
Prohibited data classes	

Field	Response
Evidence storage location	
Client-visible redaction rule	
Raw evidence retention period	
Test data deletion owner and date	
Reset or rollback method	

Worksheet 10 Dependency boundary

Dependency	Purpose	Owner	Test mode	Allowed interaction	Prohibited interaction	Contact
Identity provider						
Email or messaging						
Payment service						
File processing						
Model or AI service						
Customer webhook						

6 Define reconnaissance and discovery boundaries

Testing a known URL and discovering the broader attack surface are different tasks. State which one the engagement includes.

OWASP's attack-surface guidance explains that applications can exist on non-obvious hosts or paths and that the rules of engagement determine whether discovery should extend beyond the listed URL.[9] Discovery can find forgotten assets, but it can also reach third-party systems or targets the client is not prepared to test.

Choose the discovery model

- **Closed list:** only the exact listed targets may be contacted.
- **Passive discovery:** public records, certificates, DNS data, and archives may be reviewed without active requests to discovered targets.
- **Active discovery within a boundary:** the assessor may enumerate hosts, paths, ports, or APIs inside a defined domain, address range, cloud account, or application.
- **Discovery with approval gate:** newly identified targets are reported and tested only after written addition to the scope.

Define whether subdomains, virtual hosts, IP addresses, alternate ports, archived URLs, JavaScript-referenced APIs, mobile backend hosts, and cloud endpoints may be collected. Then state which can receive active requests.

Handle newly discovered assets

Discovery never automatically expands authority. Use one of three outcomes:

12. Record the asset as an observation and do not test it.
13. Ask the owner to prove authority and issue a written scope change.
14. Stop and escalate if the asset appears sensitive, unstable, or owned by another party.

Worksheet 11 Discovery rules

Discovery activity	Allowed	Boundary	Active requests allowed	Rate limit	New-target action
Certificate and public-record review			N/A	N/A	
DNS and subdomain enumeration					
Host and port identification					
Content and route discovery					
JavaScript and mobile endpoint review					
Cloud resource discovery					
API inventory comparison					

Part III Make the engagement lawful and safe

7 Write authorization and rules of engagement

The rules of engagement turn the scope into permission and operating constraints. NIST defines them as detailed guidelines established before testing that give the test team authority to conduct the defined activities.[10] They should be approved by someone who can speak for the owner of every target.

An assessment request, purchase order, email introduction, or access credential is not automatically sufficient authority. The signed record should connect the legal parties, target identifiers, owner, allowed techniques, test window, and limits. If a customer wants a provider to test a system owned by its client, parent company, cloud customer, or integration partner, the permission chain must reach that owner.




Figure 3. Testing stays locked until the four authorization conditions agree and a signed record is on file.

Name the authorizing parties

Record:

- The contracting client

- The legal or operational owner of each target
- The person granting permission and their authority
- The testing provider and named test lead
- Any hosting, platform, or third party whose rules apply
- Emergency contacts with authority to pause testing

If the owner is not the contracting client, attach the separate permission rather than summarizing it as “approved.”

Define allowed actions by class

Do not rely on “standard penetration testing.” Mark which activities are allowed:

- Passive observation and public-source discovery
- Account creation and normal workflow use
- Request capture, replay, and parameter modification
- Authentication and authorization testing
- Automated crawling or scanning within rate limits
- File upload and parser testing with safe samples
- Controlled injection and command-execution proof
- Privilege escalation within client-owned systems
- Cloud identity and configuration review
- Mobile instrumentation or binary analysis
- Source-code review
- AI prompt, retrieval, memory, and tool tests
- Controlled changes to synthetic records
- Limited production confirmation

For actions that could change data, send messages, move money, affect availability, trigger fraud controls, or reach another tenant, record the safe method and approval condition.

Write prohibited actions plainly

Common exclusions include:

- Denial-of-service and load testing
- Destructive data modification
- Persistence beyond what is required to prove impact
- Access to real customer records
- Social engineering or employee targeting
- Testing third-party services
- Using exposed credentials that do not belong to the client’s test identities
- Malware deployment
- Physical access attempts
- Lateral movement outside the named boundary
- Contacting real customers or suppliers

Cloud-provider rules may prohibit actions even when the client requests them. Azure’s current rules, for example, prohibit denial-of-service testing and testing another tenant. AWS requires prior approval for command-and-control activity and prohibits testing AWS services themselves.[6][7] The engagement record should preserve the policy version or access date used during planning.

Set time and traffic controls

State the time zone, start, end, maintenance windows, blackout periods, and whether passive work may continue outside the active window. Record assessor source IP addresses or other identifiers when monitoring teams need them. Define concurrency, requests per second, scanner intensity, file size, test-account limits, and budgets for paid APIs or AI model calls.

Rate limits should match the weakest in-scope dependency, not the fastest endpoint. A login, search, export, payment, or model workflow may have different safe rates.

Establish stop conditions

Testing should pause when:

- Service health crosses an agreed threshold.
- Unexpected real customer data appears.
- A test reaches an unapproved system or tenant.
- A destructive action occurs or becomes likely.
- Monitoring reports abnormal impact.
- The authorization window expires.
- A critical vulnerability requires immediate containment.
- The client or provider stop contact invokes the agreed phrase or channel.

Record who can stop the engagement, how they contact the test lead, and what evidence is preserved after a stop. A pause should not be treated as a failed test. It is a controlled response to a condition named in advance.

Worksheet 12 Rules of engagement

Field	Agreed value
Contracting client	
Target owner or owners	
Person granting authority	
Testing provider and test lead	
Scope version incorporated by reference	
Active testing start	
Active testing end	
Time zone	
Blackout periods	
Source addresses or identifiers	
Maximum request rate or concurrency	
Allowed automated tools or classes	
Allowed data-changing actions	
Prohibited actions	
Stop conditions	
Emergency client contact	
Emergency assessor contact	
Evidence and data-handling terms	
Provider policies checked	
Client approval and date	

Field	Agreed value
Assessor acceptance and date	

Authorization release check

- ☐ Every active target has a proved owner.
- ☐ The approver can grant authority for those targets.
- ☐ Third-party and cloud-provider conditions were checked.
- ☐ Allowed and prohibited actions are explicit.
- ☐ Dates, times, time zone, and source addresses are recorded.
- ☐ Rate and cost limits are recorded.
- ☐ Stop contacts and conditions are tested or confirmed.
- ☐ The signed authorization references the same scope version the assessor will use.

8 Prepare accounts access and monitoring

Access should be sufficient to test the intended roles without granting unrelated power. Create dedicated test accounts. Do not reuse employee credentials or send passwords through the workbook.

Build the account set from the role matrix

Each required role should have a test identity with known ownership and synthetic data. For tenant testing, maintain equivalent users in at least two tenants. Record any account that carries global, support, billing, or infrastructure permissions separately.

If MFA, federation, device trust, IP allowlisting, or invitation workflows apply, decide whether the test evaluates those controls or uses an approved bypass. A bypass that is necessary for access becomes a report limitation if it prevents the assessor from testing the real control.

Separate credential delivery

Record account names and required roles in the scope. Deliver passwords, recovery codes, private keys, and tokens through the agreed secret channel after authorization. Set an owner and expiry for every testing secret. Revoke or rotate them when the engagement closes.

Prepare monitoring without hiding the test

The operations team should know the test window and stop procedure. Whether defenders know the exact actions depends on the engagement goal. A normal application assessment usually favors safe coordination. A detection exercise may intentionally limit foreknowledge, but that choice belongs in the rules of engagement.

Record the logs and alerts expected during testing. If a critical action cannot be tied to an identity and timestamp, the engagement may reveal an evidence gap even when the action itself was authorized.

Worksheet 13 Access readiness checklist

Item	Owner	Ready	Secure delivery method	Expiry or reset	Notes
Tenant A standard user					
Tenant A administrator					
Tenant B standard user					
Tenant B administrator					
Internal support role					
API client or key					
Mobile test build					
Cloud read access					
Architecture and data flow					
API specification					
Logging and alert contact					
Reset and cleanup process					

9 State exclusions limits and unknowns

Every assessment has limits. Hiding them makes the report look broader than the work.

Distinguish an exclusion from a limitation

An **exclusion** is a deliberate boundary: a third-party payment service is not tested. A **limitation** reduces coverage inside the intended boundary: the client could not provide an administrator account, so administrator-only workflows were not tested. An **unknown** has not been resolved: ownership of an old subdomain remains unclear.

Record all three. State the likely effect on assurance. “Mobile application excluded” is clear. “The backend API was tested through browser-observed calls only; unreferenced endpoints may remain untested” explains residual uncertainty.

Avoid generic disclaimers

“No test can find every issue” is true but not specific enough. Useful limits name the missing access, unavailable environment, untested role, blocked technique, time constraint, or system difference.

Examples:

- Production payment settlement was excluded; sandbox behavior may differ.
- The test did not include source code, so findings based on internal code paths may remain undiscovered.
- Rate limits prevented high-volume resource-consumption testing.
- The client supplied one customer role; support and administrator workflows were not tested.
- Third-party model infrastructure was outside the client’s authority; testing stopped at the client-controlled API boundary.

Worksheet 14 Exclusion limitation and unknown register

ID	Type	Description	Reason	Coverage effect	Decision owner	Resolution or report wording
L-01						
L-02						
L-03						
L-04						

Part IV Agree on the output

10 Set evidence and reporting requirements

A report should prove what was observed, connect the observation to a broken rule, explain material impact, and give the owner a specific correction. Tool output without validation is not a finding.

OWASP's current testing introduction describes useful reporting as reproducible, actionable, severity-ranked, and understandable to technical and business readers.[2] NIST SP 800-115 also connects testing to analysis and mitigation rather than stopping at discovery.[1]

Define the evidence unit

For each confirmed finding, require:

- Finding identifier and plain-language title
- Affected target, release, endpoint, role, and tenant
- Expected security rule
- Preconditions and test identity
- Reproduction steps
- Sanitized request, action, log, or trace
- Observed result
- Business and technical impact
- Severity and rationale
- Recommended correction
- Owner and remediation state
- Retest result and evidence when performed

Evidence should prove the server-side or downstream result. A browser message may not prove a record changed. A model response may not prove a tool ran. A scanner alert may not prove exploitability. Capture the authoritative state where the system made or recorded the decision.

Agree on severity language

Decide whether the report uses qualitative ratings, CVSS, a client risk matrix, or a combination. FIRST's CVSS specification provides a standardized way to describe vulnerability severity, but business priority can still depend on asset value, exposure, data, and compensating controls.[11] Do not promise that one numeric score will settle every remediation decision.

Record who can change a severity rating and what evidence is required. Separate technical severity from remediation priority when the client's business context calls for it.

Protect sensitive evidence

Require redaction of passwords, session tokens, private keys, customer content, and unnecessary personal data. Decide whether raw evidence stays only in the assessor's restricted store, whether the client receives a sanitized version, and how long both copies remain available.

Reports should carry a classification and an authorized distribution list. If customers will receive a summary, define whether it is a separate redacted report, an executive letter, or a controlled portal copy. Do not assume a full technical report can be forwarded without restriction.

Define report versions and acceptance

Typical versions are:

15. Draft for factual review
16. Final initial report

17. Retest report or updated final report

The client may correct factual errors, target names, owners, or reproduction details. It should not remove a supported finding merely because the fix is inconvenient. Record the dispute and review process before it is needed.

Worksheet 15 Finding acceptance criteria

Requirement	Mandatory	Report location or format	Reviewer
Plain-language title			
Affected target and release			
Expected rule			
Reproduction steps			
Sanitized evidence			
Material impact			
Severity and rationale			
Recommended correction			
Owner and state			
Retest evidence			

Worksheet 16 Report acceptance criteria

Field	Agreed value
Report audiences	
Required executive summary	
Technical detail level	
Severity method	
Required compliance or framework mapping	
Evidence sanitization rule	
Report classification	
Authorized recipients	
Draft review period	
Final delivery date and format	
Customer-shareable output	
Report retention and deletion	

11 Define remediation and retesting

Client remediation and assessor verification are different events. A development team can report that a change was deployed. Only a retest shows how the corrected system behaved under the recorded scenario.




Figure 4. Ready for retest means the client believes the correction is deployed. Fixed and verified requires new assessor evidence.

Keep review and remediation states separate

Finding review states can include Draft, Needs Review, Confirmed, and Rejected. Remediation states can include Open, In Progress, Ready for Retest, Fixed and Verified, Risk Accepted, and Not Reproducible. Mixing them creates false closure. A confirmed finding can still be open. A rejected result is not a fixed vulnerability.

Define the retest unit

The retest should name:

- The original finding and evidence
- The corrected release or configuration
- The original reproduction scenario
- Any additional regression checks
- The environment and test identity
- The observed corrected result
- Residual or partial risk
- Reviewer and verification date

A narrow retest confirms the agreed correction. It is not automatically a new full assessment. If the fix changes architecture, permissions, workflows, or dependencies, the parties may need a revised scope.

Set commercial and timing terms

State how many retest rounds are included, how long they remain available, expected scheduling notice, and what counts as a new finding or new scope. Record whether the client must resolve all findings before the retest or may submit them in groups.

Worksheet 17 Retest agreement

Field	Agreed value
Included retest rounds	
Retest availability period	
Required notice	
Client evidence required before scheduling	
Corrected release identifier	
Environment	
Original scenarios to repeat	
Regression checks included	
Treatment of partial fixes	
Treatment of new findings	
Verification approver	
Updated report format	

12 Fix the schedule and responsibilities

Most engagement delays come from access, authorization, unavailable owners, unstable environments, and late factual review. The operating plan should make those dependencies visible.

Name contacts by responsibility

Use roles, names, and backup contacts for:

- Executive scope owner
- Technical product owner
- Environment or cloud owner
- Identity and access owner
- Security monitoring contact
- Privacy or data contact
- Third-party integration owner
- Assessor test lead
- Assessor reviewer
- Emergency stop contact

Set decision points

Recommended milestones include scope approval, signed authorization, access verification, test start, midpoint review, urgent-finding notification, testing end, draft report, factual review close, final report, remediation submission, and retest.

Define the channel for routine updates and a separate channel for critical issues or stop instructions. Record whether a critical finding is reported immediately and who may receive it.

Worksheet 18 Engagement operating plan

Milestone or responsibility	Owner	Backup	Date or service target	Channel	Acceptance evidence
Scope approval					
Authorization complete					
Access verification					
Testing start					
Routine status update					
Critical issue escalation					
Draft report					
Factual review close					
Final report					
Retest request					

Part V Issue the scope

13 Assemble the statement of work

The completed workbook is planning material. The statement of work and signed rules of engagement are the controlling engagement records. Transfer the final decisions without reducing them to a vague paragraph.

One page scope brief

Assessment identity

Field	Final value
Client and product	
Assessment type	
Primary decision	
Scope version	
Test window and time zone	
Assessor	

In-scope targets

Target ID	Exact identifier	Environment	Coverage module	Owner

Critical coverage

Workflow or rule	Roles and tenants	Required test outcome	Priority

Boundaries

Item	Final value
Discovery model	
Allowed active techniques	
Data-changing actions	
Prohibited actions	
Rate and concurrency limits	
Stop conditions	
Material exclusions	

Deliverables

Deliverable	Format	Due	Acceptance owner
Draft report			
Final report			
Customer-shareable summary			
Retest output			

Scope change control

Define how changes are proposed, approved, priced, and added to the authorization. A new hostname, environment, tenant, workflow, or test technique may change effort and risk. The assessor should not test it first and seek approval later.

A scope change record should contain:

- Requested change and reason
- New or removed targets
- Coverage and timing effect
- Additional access or data
- New provider rules or third-party rights
- Price or schedule change
- Updated scope version
- Named client and assessor approvals

Final issue checklist

- ☐ The scope brief matches the detailed workbook.
- ☐ Exact target identifiers are included.
- ☐ Roles, tenants, and critical workflows are named.
- ☐ The environment and release are identified.
- ☐ Discovery rules are clear.
- ☐ Allowed and prohibited actions are clear.
- ☐ Authorization covers every target and action.
- ☐ Access and test data are ready.
- ☐ Evidence, report, severity, and retest terms are agreed.
- ☐ Exclusions and limitations will appear in the report.
- ☐ The client and assessor approved the same version.

14 Worked example for a multi tenant SaaS platform

This example uses a fictional support platform. No client systems or customer data are represented.

Product description

Example Support App lets a company's customers view orders and request refunds through a browser portal. Each customer belongs to one tenant. Customer administrators can invite team members. Internal support staff can search assigned customers. An AI support agent can look up orders through the same API and can prepare, but not approve, refund requests.

The application is preparing for an enterprise launch. The buyer requested a current penetration-test report. Engineering also wants proof that the AI agent cannot cross tenant boundaries or issue a refund without approval.

Completed decision brief

Field	Example response
Primary business decision	Determine whether a customer or AI support agent can access another tenant's order or cause an unapproved refund before enterprise launch.
Trigger	Enterprise buyer requested an independent application penetration test.
Deadline	Final report due 15 December 2026 for buyer review.
Relying audiences	Engineering, product leadership, buyer security team.
Required output	Technical report, executive summary, evidence for confirmed findings, and one retest round.
Success	Agreed web, API, role, tenant, and AI tool workflows tested; limitations stated; verified retest recorded.
Non-claim	The engagement does not issue a SOC 2 opinion or certify the product.

Completed asset register

ID	Asset	Identifier	Owner	Environment	State	Coverage
A-01	Customer web portal	https://app.example.test	Example Support App	Staging	In scope	Web application
A-02	Public product API	https://api.example.test/v1	Example Support App	Staging	In scope	API
A-03	Administration console	https://admin.example.test	Example Support App	Staging	Conditional	Support role only
A-04	AI orchestration service	https://agent.example.test	Example Support App	Staging	In scope	AI workflow
A-05	Payment sandbox	Provider sandbox account	Payment provider	Sandbox	Boundary only	Client integration calls only
A-06	Production application	https://app.example.com	Example Support App	Production	Out of scope	No active testing

Completed role and tenant plan

Role	Tenant	Allowed behavior	Prohibited behavior	Test account
Customer user A	Tenant A	Read Tenant A orders	Read or change Tenant B orders	Ready
Customer admin A	Tenant A	Invite Tenant A members	Administer Tenant B	Ready
Customer user B	Tenant B	Read Tenant B orders	Read or change Tenant A orders	Ready
Support user	Assigned tenants	Search assigned customers	Search unassigned customer	Ready
AI support agent	Calling user context	Look up caller-owned order	Cross-tenant lookup or direct refund approval	Ready

Synthetic orders are named ORDER-A-101, ORDER-A-102, and ORDER-B-204. The names make ownership visible in evidence. No real addresses, names, or payment details are used.

Completed critical workflows

ID	Workflow	Expected rule	Priority
W-01	View order detail	API verifies the requesting user belongs to the order's tenant.	Critical
W-02	Export order history	Export contains only the caller's tenant records.	High
W-03	Invite member	Only a customer administrator can invite a member to its own tenant.	High
W-04	Support search	Support user reaches only explicitly assigned tenants.	High
W-05	AI order lookup	Agent carries the caller's identity and cannot substitute another tenant's order ID.	Critical
W-06	Refund request	Agent may prepare a request; server requires customer confirmation and staff approval before execution.	Critical

Completed rules of engagement summary

Field	Example agreement
Window	1–10 December 2026, 09:00–18:00 America/New_York
Source	Two assessor VPN egress addresses listed in signed authorization
Allowed	Request capture and modification, web/API authorization testing, safe injection tests, synthetic file uploads, AI prompt and tool tests
Automated traffic	Maximum five requests per second; authentication endpoints limited to one request per second
Data changes	Synthetic invitations and refund requests in staging; all records reset nightly
Prohibited	Production requests, denial of service, real customer contact, payment-provider testing, persistence, third-party credential use
Stop conditions	Real customer data, unexpected production traffic, staging error rate above agreed threshold, third-party boundary crossed
Escalation	Dedicated client and assessor channel; critical confirmed findings reported immediately

Example finding acceptance criteria

A cross-tenant order finding must show the calling identity, requested order, expected tenant rule, sanitized request, server response, and proof that another tenant's record was returned. A model statement such as "I found the order" is insufficient unless the downstream API response or state proves access.

For a refund finding, evidence must show whether a refund record was created, which identity authorized it, whether approval was required, and whether the payment sandbox received a request. The test stops at the client-controlled sandbox integration boundary.

Example retest

The initial test records HTTP 200 when Customer A requests ORDER-B-204. Engineering adds an order-ownership check and deploys release 2026.12.12-rc2. The retest repeats the same authenticated request and records HTTP 403 with no order data in the response or application logs. A reviewer signs the new evidence and changes the remediation state to Fixed and Verified. The original finding and evidence remain in report history.

Appendix A Master pre test checklist

Decision and scope

- ☐ Primary decision written
- ☐ Deadline and relying audience named
- ☐ Exact targets listed
- ☐ Owners proved
- ☐ Environment and release recorded
- ☐ Coverage modules selected
- ☐ Critical workflows prioritized

Roles and access

- ☐ Required roles inventoried
- ☐ Two test tenants prepared where applicable
- ☐ Lifecycle states included
- ☐ Accounts and synthetic records ready
- ☐ Credentials have a secure delivery path
- ☐ Secrets have expiry and cleanup owners

Safety and authority

- ☐ Written authorization signed
- ☐ Third-party permissions checked
- ☐ Cloud-provider rules checked
- ☐ Test window and source addresses recorded
- ☐ Rate limits recorded
- ☐ Prohibited actions recorded
- ☐ Stop contacts and conditions confirmed

Evidence and delivery

- ☐ Evidence fields agreed
- ☐ Redaction and retention agreed
- ☐ Severity method agreed
- ☐ Draft and final dates agreed
- ☐ Distribution list agreed
- ☐ Retest rounds and timing agreed
- ☐ Limitations will be stated in the report

Appendix B Vendor proposal comparison scorecard

Score each item from 0 to 3: 0 absent, 1 weak, 2 acceptable, 3 strong. Multiply the score by the weight. Do not select a provider from the total alone; unresolved authority, data-handling, or tester-quality concerns can disqualify a proposal.

Criterion	Weight	Vendor A	Vendor B	Vendor C	Evidence or concern
Scope reflects named systems and workflows	5				
Manual authorization and business-logic testing	5				
Qualified named test lead and reviewer	4				
Clear rules of engagement	5				
Evidence and reproduction quality	5				
Report serves engineers and executives	4				
Data handling and retention	5				
Retesting terms	4				
Schedule and access dependencies	3				
Transparent exclusions and assumptions	4				
Price and change-control terms	3				
Relevant application or industry experience	3				

Appendix C Glossary

Active testing: Requests or actions sent to a target to evaluate security behavior.

Attack surface: Reachable systems, interfaces, inputs, identities, and trust relationships that can affect security.

Authorization: Permission from an owner for named parties to perform defined testing against defined targets.

Business logic: Product rules governing state, eligibility, price, ownership, approval, sequence, or another business decision.

Coverage: The systems, roles, workflows, test classes, and techniques included in the assessment.

Evidence: A sanitized record that supports what the assessor observed, including relevant identity, request or action, response or state, time, and target version.

Exclusion: A deliberate item outside the assessment.

Finding: A reviewed security issue supported by evidence, impact, and an expected rule.

Horizontal authorization: Access between users or tenants at a similar privilege level.

Limitation: A condition that reduces the depth, breadth, or confidence of the assessment.

Passive discovery: Collection of public or already available information without active requests to the discovered target.

Penetration test: An authorized technical assessment that attempts to identify and validate exploitable security weaknesses within an agreed boundary.

Ready for retest: A client state indicating that a correction is believed to be deployed. It is not proof of resolution.

Retest: Repetition of the relevant recorded scenario against a corrected system to collect new evidence.

Rules of engagement: The detailed permissions and constraints governing how the security test will run.

Scope change: A documented addition, removal, or modification to targets, techniques, timing, access, or outputs.

Stop condition: A defined event that requires testing to pause or end.

Tenant: A customer, organization, workspace, or another logical boundary intended to isolate identities and data.

Vertical authorization: Access from a lower-privilege identity into a higher-privilege function or record.

Sources

18. National Institute of Standards and Technology. *Technical Guide to Information Security Testing and Assessment, NIST SP 800-115.* https://csrc.nist.gov/pubs/sp/800/115/final
19. OWASP Foundation. *Web Security Testing Guide.* https://wstg.owasp.org/
20. OWASP Foundation. *Map Application Architecture, WSTG-INFO-10.* https://wstg.owasp.org/latest/4-Web_Application_Security_Testing/01-Information_Gathering/10-Map_Application_Architecture/
21. OWASP Foundation. *Bypassing Authorization Schema, WSTG-ATHZ-02.* https://wstg.owasp.org/latest/4-Web_Application_Security_Testing/05-Authorization/02-Bypassing_Authorization_Schema/
22. OWASP Foundation. *OWASP API Security Top 10 2023.* https://api-security.owasp.org/
23. Amazon Web Services. *AWS Customer Support Policy for Penetration Testing.* https://aws.amazon.com/security/penetration-testing/
24. Microsoft. *Penetration testing on Azure.* https://learn.microsoft.com/en-us/azure/security/fundamentals/pen-testing
25. Google Cloud. *Cloud Security FAQ, penetration testing.* https://support.google.com/cloud/answer/6 262 505
26. OWASP Foundation. *Attack Surface Identification.* https://wstg.owasp.org/latest/4-Web_Application_Security_Testing/01-Information_Gathering/04-Attack_Surface_Identification/
27. National Institute of Standards and Technology. *Rules of Engagement glossary definition.* https://csrc.nist.gov/glossary/term/Rules_of_Engagement
28. Forum of Incident Response and Security Teams. *Common Vulnerability Scoring System version 4.0 specification.* https://www.first.org/cvss/v4.0/specification-document
29. OWASP Foundation. *Application Security Verification Standard.* https://asvs.owasp.org/
30. OWASP Foundation. *Mobile Application Security Verification Standard.* https://mas.owasp.org/MASVS/
31. PCI Security Standards Council. *Document Library.* https://www.pcisecuritystandards.org/document_library/

Sources were accessed in November 2026. Provider rules and standards can change. Recheck the current controlling document during each engagement.

About Sthuthi Securities

Sthuthi Securities is the cybersecurity testing and remediation service from Sthuthi Technologies, LLC. It provides authorized penetration testing, AI security assessments, SaaS and cloud reviews, compliance-readiness support, remediation, and verified retesting.

The team's assessment model connects scope, authorization, evidence, human review, specific corrections, and retesting. Testing begins only after ownership, targets, allowed actions, and the test window are recorded.

Website: https://sthuthi-tech.com

Security application: use the assessment request page in Sthuthi Securities

Workbook completion record

Field	Final value
Organization	
Product or system	
Scope version	
Prepared by	
Reviewed by	
Approved by	
Authorization reference	
Date issued	
Next review date	