

# Team Reference Document

Heltion

January 2, 2024

Contents

<b>1</b>	<b>Contest</b>	<b>1</b>
1.1	Makefile	1
1.2	.clang-format	1
1.3	debug.h	1
1.4	Template	1
1.5	pbds	1
<b>2</b>	<b>Graph</b>	<b>1</b>
2.1	Connected Components	1
2.1.1	Strongly Connected Components	1
2.1.2	Two-vertex-connected Components	2
2.1.3	Two-edge-connected Components	2
2.1.4	Three-edge-connected Components	2
2.2	Euler Walks	3
2.3	Dominator Tree	4
2.4	Directed Minimum Spanning Tree	4
2.5	K Shortest Paths	5
2.6	Global Minimum Cut	5
2.7	Minimum Perfect Matching on Bipartite Graph	6
2.8	Matching on General Graph	6
2.9	Maximum Flow	7
2.10	Minimum Cost Maximum Flow	8
<b>3</b>	<b>Data Structure</b>	<b>8</b>
3.1	Disjoint Set Union	8
3.2	Sparse Table	9
3.3	Treap	9
3.4	Lines Maximum	10
3.5	Segments Maximum	10
3.6	Segment Beats	11
3.7	Tree	12
3.7.1	Least Common Ancestor	12
3.7.2	Link Cut Tree	12
<b>4</b>	<b>String</b>	<b>13</b>
4.1	Z	13
4.2	Lyndon Factorization	13
4.3	Border	13
4.4	Manacher	13
4.5	Suffix Array	13
4.6	Aho-Corasick Automaton	14
4.7	Suffix Automaton	14
4.8	Palindromic Tree	15
<b>5</b>	<b>Number Theory</b>	<b>15</b>
5.1	Modular Arithmetic	15
5.1.1	Sqrt	15
5.1.2	Logarithm	15
5.2	Chinese Remainder Theorem	16
5.3	Miller Rabin	16
5.4	Pollard Rho	16
5.5	Primitive Root	16
5.6	Sum of Floor	17
5.7	Minimum of Remainder	17
5.8	Stern Brocot Tree	17
5.9	Nim Product	17
<b>6</b>	<b>Numerical</b>	<b>18</b>
6.1	Golden Search	18
6.2	Adaptive Simpson	18
6.3	Simplex	18
6.4	Green's Theorem	19
6.5	Double Integral	19
<b>7</b>	<b>Convolution</b>	<b>19</b>
7.1	Fast Fourier Transform on $\mathbb{C}$	19
7.2	Formal Power Series on $\mathbb{F}_p$	19
7.2.1	Newton's Method	19
7.2.2	Arithmetic	20
7.2.3	Interpolation	20
7.2.4	Primes with root 3	20
7.3	Circular Transform	20
7.4	Truncated Transform	20
<b>8</b>	<b>Geometry</b>	<b>20</b>
8.1	Pick's Theorem	20
8.2	2D Geometry	20

# 1 Contest

## 1.1 Makefile

```
1 %: %.cpp
2     g++ $< -o $@ -std=gnu++20 -O2 -Wall -Wextra \
3     -D_GLIBCXX_DEBUG -D_GLIBCXX_DEBUG_PEDANTIC
```

## 1.2 .clang-format

```
1 BasedOnStyle: Chromium
2 IndentWidth: 2
3 TabWidth: 2
4 AllowShortIfStatementsOnASingleLine: true
5 AllowShortLoopsOnASingleLine: true
6 AllowShortBlocksOnASingleLine: true
7 ColumnLimit: 77
```

## 1.3 debug.h

```
1 #include <bits/stdc++.h>
2 using namespace std;
3 template <class T, size_t size = tuple_size<T>::value>
4 string to_debug(T, string s = "")
5     requires(not ranges::range<T>);
6
7 string to_debug(auto x)
8     requires requires(ostream& os) { os << x; }
9 {
10     return static_cast<ostringstream>(ostringstream() << x).str();
11 }
12 string to_debug(ranges::range auto x, string s = "")
13     requires(not is_same_v<decltype(x), string>)
14 {
15     for (auto xi : x) { s += ", " + to_debug(xi); }
16     return "[" + s.substr(s.empty() ? 0 : 2) + "]";
17 }
18 template <class T, size_t size>
19 string to_debug(T x, string s)
20     requires(not ranges::range<T>)
21 {
22     [&<size_t... I>(index_sequence<I...>) {
23         ((s += ", " + to_debug(get<I>(x))), ...);
24     }(make_index_sequence<size>());
25     return "(" + s.substr(s.empty() ? 0 : 2) + ")";
26 }
27 #define debug(...) \
28     cerr << __FILE__ ":" << __LINE__ \
29     << ": " + #__VA_ARGS__ + " " << to_debug(tuple(__VA_ARGS__)) << "\n"
```

## 1.4 Template

```
1 #include <bits/stdc++.h>
2 using namespace std;
3 using i64 = int64_t;
4 #ifndef ONLINE_JUDGE
5 #include "debug.h"
6 #else
7 #define debug(...) 417
8 #endif
9 int main() {
10     cin.tie(nullptr)->sync_with_stdio(false);
11     cout << fixed << setprecision(20);
12 }
```

## 1.5 pbds

```
1 #include <bits/extc++.h>
2 using namespace std;
3 using namespace __gnu_cxx;
4 using namespace __gnu_pbds;
5 using t = tree<int,
6             null_type,
7             less<int>,
8             rb_tree_tag,
9             tree_order_statistics_node_update>;
10 using p = __gnu_pbds::priority_queue<int, less<int>, pairing_heap_tag>;
```

# 2 Graph

## 2.1 Connected Components

### 2.1.1 Strongly Connected Components

Returns strongly connected components in topologically order.

```
1 vector<vector<int>>>
2 strongly_connected_components(const vector<vector<int>>> &g) {
3     int n = g.size();
4     vector<bool> done(n);
5     vector<int> pos(n, -1), stack;
6     vector<vector<int>>> res;
7     function<int(int)> dfs = [&](int u) {
8         int low = pos[u] = stack.size();
9         stack.push_back(u);
10        for (int v : g[u]) {
11            if (not done[v]) { low = min(low, ~pos[v] ? pos[v] : dfs(v)); }
12        }
13        if (low == pos[u]) {
14            res.emplace_back(stack.begin() + low, stack.end());
15            for (int v : res.back()) { done[v] = true; }
```

```

16     stack.resize(low);
17 }
18 return low;
19 };
20 for (int i = 0; i < n; i += 1) {
21     if (not done[i]) { dfs(i); }
22 }
23 ranges::reverse(res);
24 return res;
25 }

```

## 2.1.2 Two-vertex-connected Components

```

1 vector<vector<int>>
2 two_vertex_connected_components(const vector<vector<int>> &g) {
3     int n = g.size();
4     vector<int> pos(n, -1), stack;
5     vector<vector<int>> res;
6     function<int(int, int)> dfs = [&](int u, int p) {
7         int low = pos[u] = stack.size(), son = 0;
8         stack.push_back(u);
9         for (int v : g[u]) {
10             if (v != p) {
11                 if (~pos[v]) {
12                     low = min(low, pos[v]);
13                 } else {
14                     int end = stack.size(), lowv = dfs(v, u);
15                     low = min(low, lowv);
16                     if (lowv >= pos[u] and (~p or son++)) {
17                         res.emplace_back(stack.begin() + end, stack.end());
18                         res.back().push_back(u);
19                         stack.resize(end);
20                     }
21                 }
22             }
23         }
24         return low;
25     };
26     for (int i = 0; i < n; i += 1) {
27         if (pos[i] == -1) {
28             dfs(i, -1);
29             res.emplace_back(move(stack));
30         }
31     }
32     return res;
33 }

```

## 2.1.3 Two-edge-connected Components

```

1 vector<vector<int>> bcc(const vector<vector<int>> &g) {

```

```

2     int n = g.size();
3     vector<int> pos(n, -1), stack;
4     vector<vector<int>> res;
5     function<int(int, int)> dfs = [&](int u, int p) {
6         int low = pos[u] = stack.size(), pc = 0;
7         stack.push_back(u);
8         for (int v : g[u]) {
9             if (~pos[v]) {
10                 if (v != p or pc++) { low = min(low, pos[v]); }
11             } else {
12                 low = min(low, dfs(v, u));
13             }
14         }
15         if (low == pos[u]) {
16             res.emplace_back(stack.begin() + low, stack.end());
17             stack.resize(low);
18         }
19         return low;
20     };
21     for (int i = 0; i < n; i += 1) {
22         if (pos[i] == -1) { dfs(i, -1); }
23     }
24     return res;
25 }

```

## 2.1.4 Three-edge-connected Components

```

1 vector<vector<int>>
2 three_edge_connected_components(const vector<vector<int>> &g) {
3     int n = g.size(), dft = -1;
4     vector<int> pre(n, -1), post(n), path(n, -1), low(n), deg(n);
5     DisjointSetUnion dsu(n);
6     function<void(int, int)> dfs = [&](int u, int p) {
7         int pc = 0;
8         low[u] = pre[u] = dft += 1;
9         for (int v : g[u]) {
10             if (v != u and (v != p or pc++)) {
11                 if (pre[v] != -1) {
12                     if (pre[v] < pre[u]) {
13                         deg[u] += 1;
14                         low[u] = min(low[u], pre[v]);
15                     } else {
16                         deg[u] -= 1;
17                         for (int &p = path[u];
18                             p != -1 and pre[p] <= pre[v] and pre[v] <= post[p];) {
19                             dsu.merge(u, p);
20                             deg[u] += deg[p];
21                             p = path[p];
22                         }
23                     }
24                 } else {
25                     dfs(v, u);

```

```

26     if (path[v] == -1 and deg[v] <= 1) {
27         low[u] = min(low[u], low[v]);
28         deg[u] += deg[v];
29     } else {
30         if (deg[v] == 0) { v = path[v]; }
31         if (low[u] > low[v]) {
32             low[u] = min(low[u], low[v]);
33             swap(v, path[u]);
34         }
35         for (; v != -1; v = path[v]) {
36             dsu.merge(u, v);
37             deg[u] += deg[v];
38         }
39     }
40 }
41 }
42 }
43 post[u] = dft;
44 };
45 for (int i = 0; i < n; i += 1) {
46     if (pre[i] == -1) { dfs(i, -1); }
47 }
48 vector<vector<int>> _res(n);
49 for (int i = 0; i < n; i += 1) { _res[dsu.find(i)].push_back(i); }
50 vector<vector<int>> res;
51 for (auto &res_i : _res) {
52     if (not res_i.empty()) { res.emplace_back(move(res_i)); }
53 }
54 return res;
55 }

```

## 2.2 Euler Walks

```

1 optional<vector<vector<pair<int, bool>>>>
2 undirected_walks(int n, const vector<pair<int, int>> &edges) {
3     int m = ssize(edges);
4     vector<vector<pair<int, bool>>> res;
5     if (not m) { return res; }
6     vector<vector<pair<int, bool>>> g(n);
7     for (int i = 0; i < m; i += 1) {
8         auto [u, v] = edges[i];
9         g[u].emplace_back(i, true);
10        g[v].emplace_back(i, false);
11    }
12    for (int i = 0; i < n; i += 1) {
13        if (g[i].size() % 2) { return {}; }
14    }
15    vector<pair<int, bool>> walk;
16    vector<bool> visited(m);
17    vector<int> cur(n);
18    function<void(int)> dfs = [&](int u) {
19        for (int &i = cur[u]; i < ssize(g[u]);) {

```

```

20        auto [j, d] = g[u][i];
21        if (not visited[j]) {
22            visited[j] = true;
23            dfs(d ? edges[j].second : edges[j].first);
24            walk.emplace_back(j, d);
25        } else {
26            i += 1;
27        }
28    }
29 };
30 for (int i = 0; i < n; i += 1) {
31     dfs(i);
32     if (not walk.empty()) {
33         ranges::reverse(walk);
34         res.emplace_back(move(walk));
35     }
36 }
37 return res;
38 }
39 optional<vector<vector<int>>>
40 directed_walks(int n, const vector<pair<int, int>> &edges) {
41     int m = ssize(edges);
42     vector<vector<int>> res;
43     if (not m) { return res; }
44     vector<int> d(n);
45     vector<vector<int>> g(n);
46     for (int i = 0; i < m; i += 1) {
47         auto [u, v] = edges[i];
48         g[u].push_back(i);
49         d[v] += 1;
50     }
51     for (int i = 0; i < n; i += 1) {
52         if (ssize(g[i]) != d[i]) { return {}; }
53     }
54     vector<int> walk;
55     vector<int> cur(n);
56     vector<bool> visited(m);
57     function<void(int)> dfs = [&](int u) {
58         for (int &i = cur[u]; i < ssize(g[u]);) {
59             int j = g[u][i];
60             if (not visited[j]) {
61                 visited[j] = true;
62                 dfs(edges[j].second);
63                 walk.push_back(j);
64             } else {
65                 i += 1;
66             }
67         }
68     };
69     for (int i = 0; i < n; i += 1) {
70         dfs(i);
71         if (not walk.empty()) {
72             ranges::reverse(walk);

```

```

73     res.emplace_back(move(walk));
74 }
75 }
76 return res;
77 }

```

## 2.3 Dominator Tree

```

1 vector<int> dominator(const vector<vector<int>>& g, int s) {
2     int n = g.size();
3     vector<int> pos(n, -1), p, label(n), dom(n), sdom(n), dsu(n), par(n);
4     vector<vector<int>> rg(n), bucket(n);
5     function<void(int)> dfs = [&](int u) {
6         int t = p.size();
7         p.push_back(u);
8         label[t] = sdom[t] = dsu[t] = pos[u] = t;
9         for (int v : g[u]) {
10             if (pos[v] == -1) {
11                 dfs(v);
12                 par[pos[v]] = t;
13             }
14             rg[pos[v]].push_back(t);
15         }
16     };
17     function<int(int, int)> find = [&](int u, int x) {
18         if (u == dsu[u]) { return x ? -1 : u; }
19         int v = find(dsu[u], x + 1);
20         if (v < 0) { return u; }
21         if (sdom[label[dsu[u]]] < sdom[label[u]]) { label[u] = label[dsu[u]]; }
22         dsu[u] = v;
23         return x ? v : label[u];
24     };
25     dfs(s);
26     iota(dom.begin(), dom.end(), 0);
27     for (int i = ssize(p) - 1; i >= 0; i -= 1) {
28         for (int j : rg[i]) { sdom[j] = min(sdom[j], sdom[find(j, 0)]); }
29         if (i) { bucket[sdom[i]].push_back(i); }
30         for (int k : bucket[i]) {
31             int j = find(k, 0);
32             dom[k] = sdom[j] == sdom[k] ? sdom[j] : j;
33         }
34         if (i > 1) { dsu[i] = par[i]; }
35     }
36     for (int i = 1; i < ssize(p); i += 1) {
37         if (dom[i] != sdom[i]) { dom[i] = dom[dom[i]]; }
38     }
39     vector<int> res(n, -1);
40     res[s] = s;
41     for (int i = 1; i < ssize(p); i += 1) { res[p[i]] = p[dom[i]]; }
42     return res;
43 }

```

## 2.4 Directed Minimum Spanning Tree

```

1 struct Node {
2     Edge e;
3     int d;
4     Node *l, *r;
5     Node(Edge e) : e(e), d(0) { l = r = nullptr; }
6     void add(int v) {
7         e.w += v;
8         d += v;
9     }
10    void push() {
11        if (l) { l->add(d); }
12        if (r) { r->add(d); }
13        d = 0;
14    }
15 };
16 Node *merge(Node *u, Node *v) {
17     if (not u or not v) { return u ? v; }
18     if (u->e.w > v->e.w) { swap(u, v); }
19     u->push();
20     u->r = merge(u->r, v);
21     swap(u->l, u->r);
22     return u;
23 }
24 void pop(Node *&u) {
25     u->push();
26     u = merge(u->l, u->r);
27 }
28 pair<i64, vector<int>>
29 directed_minimum_spanning_tree(int n, const vector<Edge> &edges, int s) {
30     i64 ans = 0;
31     vector<Node *> heap(n), edge(n);
32     RollbackDisjointSetUnion dsu(n), rbdsu(n);
33     vector<pair<Node *, int>> cycles;
34     for (auto e : edges) { heap[e.v] = merge(heap[e.v], new Node(e)); }
35     for (int i = 0; i < n; i += 1) {
36         if (i == s) { continue; }
37         for (int u = i;;) {
38             if (not heap[u]) { return {}; }
39             ans += (edge[u] = heap[u])->e.w;
40             edge[u]->add(-edge[u]->e.w);
41             int v = rbdsu.find(edge[u]->e.u);
42             if (dsu.merge(u, v)) { break; }
43             int t = rbdsu.time();
44             while (rbdsu.merge(u, v)) {
45                 heap[rbdsu.find(u)] = merge(heap[u], heap[v]);
46                 u = rbdsu.find(u);
47                 v = rbdsu.find(edge[v]->e.u);
48             }
49             cycles.emplace_back(edge[u], t);
50             while (heap[u] and rbdsu.find(heap[u]->e.u) == rbdsu.find(u)) {
51                 pop(heap[u]);

```

```

52     }
53 }
54 }
55 for (auto [p, t] : cycles | views::reverse) {
56     int u = rbdsu.find(p->e.v);
57     rbdsu.rollback(t);
58     int v = rbdsu.find(edge[u]->e.v);
59     edge[v] = exchange(edge[u], p);
60 }
61 vector<int> res(n, -1);
62 for (int i = 0; i < n; i += 1) { res[i] = i == s ? i : edge[i]->e.u; }
63 return {ans, res};
64 }

```

## 2.5 K Shortest Paths

```

1 struct Node {
2     int v, h;
3     i64 w;
4     Node *l, *r;
5     Node(int v, i64 w) : v(v), w(w), h(1) { l = r = nullptr; }
6 };
7 Node *merge(Node *u, Node *v) {
8     if (not u or not v) { return u ?: v; }
9     if (u->w > v->w) { swap(u, v); }
10    Node *p = new Node(*u);
11    p->r = merge(u->r, v);
12    if (p->r and (not p->l or p->l->h < p->r->h)) { swap(p->l, p->r); }
13    p->h = (p->r ? p->r->h : 0) + 1;
14    return p;
15 }
16 struct Edge {
17     int u, v, w;
18 };
19 template <typename T>
20 using minimum_heap = priority_queue<T, vector<T>, greater<T>>;
21 vector<i64> k_shortest_paths(int n, const vector<Edge> &edges, int s, int t,
22                             int k) {
23     vector<vector<int>> g(n);
24     for (int i = 0; i < ssize(edges); i += 1) { g[edges[i].u].push_back(i); }
25     vector<int> par(n, -1), p;
26     vector<i64> d(n, -1);
27     minimum_heap<pair<i64, int>> pq;
28     pq.push({d[s] = 0, s});
29     while (not pq.empty()) {
30         auto [du, u] = pq.top();
31         pq.pop();
32         if (du > d[u]) { continue; }
33         p.push_back(u);
34         for (int i : g[u]) {
35             auto [_, v, w] = edges[i];
36             if (d[v] == -1 or d[v] > d[u] + w) {

```

```

37         par[v] = i;
38         pq.push({d[v] = d[u] + w, v});
39     }
40 }
41 }
42 if (d[t] == -1) { return vector<i64>(k, -1); }
43 vector<Node *> heap(n);
44 for (int i = 0; i < ssize(edges); i += 1) {
45     auto [u, v, w] = edges[i];
46     if (~d[u] and ~d[v] and par[v] != i) {
47         heap[v] = merge(heap[v], new Node(u, d[u] + w - d[v]));
48     }
49 }
50 for (int u : p) {
51     if (u != s) { heap[u] = merge(heap[u], heap[edges[par[u]].u]); }
52 }
53 minimum_heap<pair<i64, Node *>> q;
54 if (heap[t]) { q.push({d[t] + heap[t]->w, heap[t]}); }
55 vector<i64> res = {d[t]};
56 for (int i = 1; i < k and not q.empty(); i += 1) {
57     auto [w, p] = q.top();
58     q.pop();
59     res.push_back(w);
60     if (heap[p->v]) { q.push({w + heap[p->v]->w, heap[p->v]}); }
61     for (auto c : {p->l, p->r}) {
62         if (c) { q.push({w + c->w - p->w, c}); }
63     }
64 }
65 res.resize(k, -1);
66 return res;
67 }

```

## 2.6 Global Minimum Cut

```

1 i64 global_minimum_cut(vector<vector<i64>> &w) {
2     int n = w.size();
3     if (n == 2) { return w[0][1]; }
4     vector<bool> in(n);
5     vector<int> add;
6     vector<i64> s(n);
7     i64 st = 0;
8     for (int i = 0; i < n; i += 1) {
9         int k = -1;
10        for (int j = 0; j < n; j += 1) {
11            if (not in[j]) {
12                if (k == -1 or s[j] > s[k]) { k = j; }
13            }
14        }
15        add.push_back(k);
16        st = s[k];
17        in[k] = true;
18        for (int j = 0; j < n; j += 1) { s[j] += w[j][k]; }

```

```

19 }
20 for (int i = 0; i < n; i += 1) {}
21 int x = add.rbegin()[1], y = add.back();
22 if (x == n - 1) { swap(x, y); }
23 for (int i = 0; i < n; i += 1) {
24     swap(w[y][i], w[n - 1][i]);
25     swap(w[i][y], w[i][n - 1]);
26 }
27 for (int i = 0; i + 1 < n; i += 1) {
28     w[i][x] += w[i][n - 1];
29     w[x][i] += w[n - 1][i];
30 }
31 w.pop_back();
32 return min(st, stoer_wagner(w));
33 }

```

## 2.7 Minimum Perfect Matching on Bipartite Graph

```

1 minimum_perfect_matching_on_bipartite_graph(const vector<vector<i64>>& w) {
2     i64 n = w.size();
3     vector<int> rm(n, -1), cm(n, -1);
4     vector<i64> pi(n);
5     auto resid = [&](int r, int c) { return w[r][c] - pi[c]; };
6     for (int c = 0; c < n; c += 1) {
7         int r =
8             ranges::min(views::iota(0, n), {}, [&](int r) { return w[r][c]; });
9         pi[c] = w[r][c];
10        if (rm[r] == -1) {
11            rm[r] = c;
12            cm[c] = r;
13        }
14    }
15    vector<int> cols(n);
16    iota(cols.begin(), cols.end(), 0);
17    for (int r = 0; r < n; r += 1) {
18        if (rm[r] != -1) { continue; }
19        vector<i64> d(n);
20        for (int c = 0; c < n; c += 1) { d[c] = resid(r, c); }
21        vector<int> pre(n, r);
22        int scan = 0, label = 0, last = 0, col = -1;
23        [&]() {
24            while (true) {
25                if (scan == label) {
26                    last = scan;
27                    i64 min = d[cols[scan]];
28                    for (int j = scan; j < n; j += 1) {
29                        int c = cols[j];
30                        if (d[c] <= min) {
31                            if (d[c] < min) {
32                                min = d[c];
33                                label = scan;
34                            }

```

```

35                swap(cols[j], cols[label++]);
36            }
37        }
38        for (int j = scan; j < label; j += 1) {
39            if (int c = cols[j]; cm[c] == -1) {
40                col = c;
41                return;
42            }
43        }
44    }
45    int c1 = cols[scan++], r1 = cm[c1];
46    for (int j = label; j < n; j += 1) {
47        int c2 = cols[j];
48        i64 len = resid(r1, c2) - resid(r1, c1);
49        if (d[c2] > d[c1] + len) {
50            d[c2] = d[c1] + len;
51            pre[c2] = r1;
52            if (len == 0) {
53                if (cm[c2] == -1) {
54                    col = c2;
55                    return;
56                }
57                swap(cols[j], cols[label++]);
58            }
59        }
60    }
61 }
62 }();
63 for (int i = 0; i < last; i += 1) {
64     int c = cols[i];
65     pi[c] += d[c] - d[col];
66 }
67 for (int t = col; t != -1;) {
68     col = t;
69     int r = pre[col];
70     cm[col] = r;
71     swap(rm[r], t);
72 }
73 }
74 i64 res = 0;
75 for (int i = 0; i < n; i += 1) { res += w[i][rm[i]]; }
76 return {res, rm};
77 }

```

## 2.8 Matching on General Graph

```

1 vector<int> matching(const vector<vector<int>> &g) {
2     int n = g.size();
3     int mark = 0;
4     vector<int> matched(n, -1), par(n, -1), book(n);
5     auto match = [&](int s) {
6         vector<int> c(n), type(n, -1);

```



```

7  iota(c.begin(), c.end(), 0);
8  queue<int> q;
9  q.push(s);
10 type[s] = 0;
11 while (not q.empty()) {
12     int u = q.front();
13     q.pop();
14     for (int v : g[u])
15         if (type[v] == -1) {
16             par[v] = u;
17             type[v] = 1;
18             int w = matched[v];
19             if (w == -1) {
20                 [&](int u) {
21                     while (u != -1) {
22                         int v = matched[par[u]];
23                         matched[matched[u] = par[u]] = u;
24                         u = v;
25                     }
26                 }(v);
27                 return;
28             }
29             q.push(w);
30             type[w] = 0;
31         } else if (not type[v] and c[u] != c[v]) {
32             int w = [&](int u, int v) {
33                 mark += 1;
34                 while (true) {
35                     if (u != -1) {
36                         if (book[u] == mark) { return u; }
37                         book[u] = mark;
38                         u = c[par[matched[u]]];
39                     }
40                     swap(u, v);
41                 }
42             }(u, v);
43             auto up = [&](int u, int v, int w) {
44                 while (c[u] != w) {
45                     par[u] = v;
46                     v = matched[u];
47                     if (type[v] == 1) {
48                         q.push(v);
49                         type[v] == 0;
50                     }
51                     if (c[u] == u) { c[u] = w; }
52                     if (c[v] == v) { c[v] = w; }
53                     u = par[v];
54                 }
55             };
56             up(u, v, w);
57             up(v, u, w);
58             for (int i = 0; i < n; i += 1) { c[i] = c[c[i]]; }
59         }

```

```

60     }
61 };
62 for (int i = 0; i < n; i += 1) {
63     if (matched[i] == -1) { match(i); }
64 }
65 return matched;
66 }

```

## 2.9 Maximum Flow

```

1 struct HighestLabelPreflowPush {
2     int n;
3     vector<vector<int>> g;
4     vector<Edge> edges;
5     HighestLabelPreflowPush(int n) : n(n), g(n) {}
6     int add(int u, int v, i64 f) {
7         if (u == v) { return -1; }
8         int i = ssize(edges);
9         edges.push_back({u, v, f});
10        g[u].push_back(i);
11        edges.push_back({v, u, 0});
12        g[v].push_back(i + 1);
13        return i;
14    }
15    i64 max_flow(int s, int t) {
16        vector<i64> p(n);
17        vector<int> h(n), cur(n), count(n * 2);
18        vector<vector<int>> pq(n * 2);
19        auto push = [&](int i, i64 f) {
20            auto [u, v, _] = edges[i];
21            if (not p[v] and f) { pq[h[v]].push_back(v); }
22            edges[i].f -= f;
23            edges[i ^ 1].f += f;
24            p[u] -= f;
25            p[v] += f;
26        };
27        h[s] = n;
28        count[0] = n - 1;
29        p[t] = 1;
30        for (int i : g[s]) { push(i, edges[i].f); }
31        for (int hi = 0;;) {
32            while (pq[hi].empty()) {
33                if (not hi--) { return -p[s]; }
34            }
35            int u = pq[hi].back();
36            pq[hi].pop_back();
37            while (p[u] > 0) {
38                if (cur[u] == ssize(g[u])) {
39                    h[u] = n * 2 + 1;
40                    for (int i = 0; i < ssize(g[u]); i += 1) {
41                        auto [_, v, f] = edges[g[u][i]];
42                        if (f and h[u] > h[v] + 1) {

```

```

43         h[u] = h[v] + 1;
44         cur[u] = i;
45     }
46 }
47 count[h[u]] += 1;
48 if (not(count[hi] -= 1) and hi < n) {
49     for (int i = 0; i < n; i += 1) {
50         if (h[i] > hi and h[i] < n) {
51             count[h[i]] -= 1;
52             h[i] = n + 1;
53         }
54     }
55 }
56 hi = h[u];
57 } else {
58     int i = g[u][cur[u]];
59     auto [_ , v , f] = edges[i];
60     if (f and h[u] == h[v] + 1) {
61         push(i, min(p[u], f));
62     } else {
63         cur[u] += 1;
64     }
65 }
66 }
67 }
68 return i64(0);
69 }
70 };

```

## 2.10 Minimum Cost Maximum Flow

Constraints: there is no edge with negative cost.

```

1 struct MinimumCostMaximumFlow {
2     template <typename T>
3     using minimum_heap = priority_queue<T, vector<T>, greater<T>>;
4     int n;
5     vector<Edge> edges;
6     vector<vector<int>> g;
7     MinimumCostMaximumFlow(int n) : n(n), g(n) {}
8     int add_edge(int u, int v, i64 f, i64 c) {
9         int i = edges.size();
10        edges.push_back({u, v, f, c});
11        edges.push_back({v, u, 0, -c});
12        g[u].push_back(i);
13        g[v].push_back(i + 1);
14        return i;
15    }
16    pair<i64, i64> flow(int s, int t) {
17        constexpr i64 inf = numeric_limits<i64>::max();
18        vector<i64> d, h(n);
19        vector<int> p;
20        auto dijkstra = [&]() {

```

```

21        d.assign(n, inf);
22        p.assign(n, -1);
23        minimum_heap<pair<i64, int>> q;
24        q.emplace(d[s] = 0, s);
25        while (not q.empty()) {
26            auto [du, u] = q.top();
27            q.pop();
28            if (du > d[u]) { continue; }
29            for (int i : g[u]) {
30                auto [_ , v , f , c] = edges[i];
31                if (f and d[v] > d[u] + h[u] - h[v] + c) {
32                    p[v] = i;
33                    q.emplace(d[v] = d[u] + h[u] - h[v] + c, v);
34                }
35            }
36        }
37        return ~p[t];
38    };
39    i64 f = 0, c = 0;
40    while (dijkstra()) {
41        for (int i = 0; i < n; i += 1) { h[i] += d[i]; }
42        vector<int> path;
43        for (int u = t; u != s; u = edges[p[u]].u) { path.push_back(p[u]); }
44        i64 mf =
45            edges[ranges::min(path, {}, [&](int i) { return edges[i].f; } )].f;
46        f += mf;
47        c += mf * h[t];
48        for (int i : path) {
49            edges[i].f -= mf;
50            edges[i ^ 1].f += mf;
51        }
52    }
53    return {f, c};
54 }
55 };

```

## 3 Data Structure

### 3.1 Disjoint Set Union

```

1 struct DisjointSetUnion {
2     vector<int> dsu;
3     DisjointSetUnion(int n) : dsu(n, -1) {}
4     int find(int u) { return dsu[u] < 0 ? u : dsu[u] = find(dsu[u]); }
5     void merge(int u, int v) {
6         u = find(u);
7         v = find(v);
8         if (u != v) {
9             if (dsu[u] > dsu[v]) { swap(u, v); }
10            dsu[u] += dsu[v];
11            dsu[v] = u;

```

```

12     }
13 }
14 };
15 struct RollbackDisjointSetUnion {
16     vector<pair<int, int>> stack;
17     vector<int> dsu;
18     RollbackDisjointSetUnion(int n) : dsu(n, -1) {}
19     int find(int u) { return dsu[u] < 0 ? u : find(dsu[u]); }
20     int time() { return ssize(stack); }
21     bool merge(int u, int v) {
22         if ((u = find(u)) == (v = find(v))) { return false; }
23         if (dsu[u] < dsu[v]) { swap(u, v); }
24         stack.emplace_back(u, dsu[u]);
25         dsu[v] += dsu[u];
26         dsu[u] = v;
27         return true;
28     }
29     void rollback(int t) {
30         while (ssize(stack) > t) {
31             auto [u, dsu_u] = stack.back();
32             stack.pop_back();
33             dsu[dsu[u]] -= dsu_u;
34             dsu[u] = dsu_u;
35         }
36     }
37 };

```

## 3.2 Sparse Table

```

1 struct SparseTable {
2     vector<vector<int>> table;
3     SparseTable() {}
4     SparseTable(const vector<int> &a) {
5         int n = a.size(), h = bit_width(a.size());
6         table.resize(h);
7         table[0] = a;
8         for (int i = 1; i < h; i += 1) {
9             table[i].resize(n - (1 << i) + 1);
10            for (int j = 0; j + (1 << i) <= n; j += 1) {
11                table[i][j] = min(table[i - 1][j], table[i - 1][j + (1 << (i - 1))]);
12            }
13        }
14    }
15    int query(int l, int r) {
16        int h = bit_width(unsigned(r - l)) - 1;
17        return min(table[h][l], table[h][r - (1 << h)]);
18    }
19 };
20 struct DisjointSparseTable {
21     vector<vector<int>> table;
22     DisjointSparseTable(const vector<int> &a) {
23         int h = bit_width(a.size() - 1), n = a.size();

```

```

24         table.resize(h, a);
25         for (int i = 0; i < h; i += 1) {
26             for (int j = 0; j + (1 << i) < n; j += (2 << i)) {
27                 for (int k = j + (1 << i) - 2; k >= j; k -= 1) {
28                     table[i][k] = min(table[i][k], table[i][k + 1]);
29                 }
30                 for (int k = j + (1 << i) + 1; k < j + (2 << i) and k < n; k += 1) {
31                     table[i][k] = min(table[i][k], table[i][k - 1]);
32                 }
33             }
34         }
35     }
36     int query(int l, int r) {
37         if (l + 1 == r) { return table[0][l]; }
38         int i = bit_width(unsigned(l ^ (r - 1))) - 1;
39         return min(table[i][l], table[i][r - 1]);
40     }
41 };

```

## 3.3 Treap

```

1 struct Node {
2     static constexpr bool persistent = true;
3     static mt19937_64 mt;
4     Node *l, *r;
5     u64 priority;
6     int size, v;
7     i64 sum;
8     Node(const Node &other) { memcpy(this, &other, sizeof(Node)); }
9     Node(int v) : v(v), sum(v), priority(mt()), size(1) { l = r = nullptr; }
10    Node *update(Node *l, Node *r) {
11        Node *p = persistent ? new Node(*this) : this;
12        p->l = l;
13        p->r = r;
14        p->size = (l ? l->size : 0) + 1 + (r ? r->size : 0);
15        p->sum = (l ? l->sum : 0) + v + (r ? r->sum : 0);
16        return p;
17    }
18 };
19 mt19937_64 Node::mt;
20 pair<Node *, Node *> split_by_v(Node *p, int v) {
21     if (not p) { return {}; }
22     if (p->v < v) {
23         auto [l, r] = split_by_v(p->r, v);
24         return {p->update(p->l, l), r};
25     }
26     auto [l, r] = split_by_v(p->l, v);
27     return {l, p->update(r, p->r)};
28 }
29 pair<Node *, Node *> split_by_size(Node *p, int size) {
30     if (not p) { return {}; }
31     int l_size = p->l ? p->l->size : 0;

```

```

32 if (l_size < size) {
33     auto [l, r] = split_by_size(p->r, size - l_size - 1);
34     return {p->update(p->l, l), r};
35 }
36 auto [l, r] = split_by_size(p->l, size);
37 return {l, p->update(r, p->r)};
38 }
39 Node *merge(Node *l, Node *r) {
40     if (not l or not r) { return l ? r; }
41     if (l->priority < r->priority) { return r->update(merge(l, r->l), r->r); }
42     return l->update(l->l, merge(l->r, r));
43 }

```

### 3.4 Lines Maximum

```

1 struct Line {
2     mutable i64 k, b, p;
3     bool operator<(const Line& rhs) const { return k < rhs.k; }
4     bool operator<(const i64& x) const { return p < x; }
5 };
6 struct Lines : multiset<Line, less<>> {
7     static constexpr i64 inf = numeric_limits<i64>::max();
8     static i64 div(i64 a, i64 b) { return a / b - ((a ^ b) < 0 and a % b); }
9     bool isect(iterator x, iterator y) {
10         if (y == end()) { return x->p = inf, false; }
11         if (x->k == y->k) {
12             x->p = x->b > y->b ? inf : -inf;
13         } else {
14             x->p = div(y->b - x->b, x->k - y->k);
15         }
16         return x->p >= y->p;
17     }
18     void add(i64 k, i64 b) {
19         auto z = insert({k, b, 0}), y = z++, x = y;
20         while (isect(y, z)) { z = erase(z); }
21         if (x != begin() and isect(--x, y)) { isect(x, y = erase(y)); }
22         while ((y = x) != begin() and (--x)->p >= y->p) { isect(x, erase(y)); }
23     }
24     optional<i64> get(i64 x) {
25         if (empty()) { return {}; }
26         auto it = lower_bound(x);
27         return it->k * x + it->b;
28     }
29 };

```

### 3.5 Segments Maximum

```

1 struct Segment {
2     i64 k, b;
3     i64 get(i64 x) { return k * x + b; }

```

```

4 };
5 struct Segments {
6     struct Node {
7         optional<Segment> s;
8         Node *l, *r;
9     };
10    i64 tl, tr;
11    Node *root;
12    Segments(i64 tl, i64 tr) : tl(tl), tr(tr), root(nullptr) {}
13    void add(i64 l, i64 r, i64 k, i64 b) {
14        function<void(Node *&, i64, i64, Segment)> rec = [&](Node *&p, i64 tl,
15                                                                i64 tr, Segment s) {
16
17            if (p == nullptr) { p = new Node(); }
18            i64 tm = midpoint(tl, tr);
19            if (tl >= l and tr <= r) {
20                if (not p->s) {
21                    p->s = s;
22                    return;
23                }
24                auto t = p->s.value();
25                if (t.get(tl) >= s.get(tl)) {
26                    if (t.get(tr) >= s.get(tr)) { return; }
27                    if (t.get(tm) >= s.get(tm)) { return rec(p->r, tm + 1, tr, s); }
28                    p->s = s;
29                    return rec(p->l, tl, tm, t);
30                }
31                if (t.get(tr) <= s.get(tr)) {
32                    p->s = s;
33                    return;
34                }
35                if (t.get(tm) <= s.get(tm)) {
36                    p->s = s;
37                    return rec(p->r, tm + 1, tr, t);
38                }
39                return rec(p->l, tl, tm, s);
40            }
41            if (l <= tm) { rec(p->l, tl, tm, s); }
42            if (r > tm) { rec(p->r, tm + 1, tr, s); }
43        };
44        rec(root, tl, tr, {k, b});
45    }
46    optional<i64> get(i64 x) {
47        optional<i64> res = {};
48        function<void(Node *, i64, i64)> rec = [&](Node *p, i64 tl, i64 tr) {
49
50            if (p == nullptr) { return; }
51            i64 tm = midpoint(tl, tr);
52            if (p->s) {
53                i64 y = p->s.value().get(x);
54                if (not res or res.value() < y) { res = y; }
55            }
56            if (x <= tm) {
57                rec(p->l, tl, tm);
58            } else {

```

```

57     rec(p->r, tm + 1, tr);
58 }
59 };
60 rec(root, tl, tr);
61 return res;
62 }
63 };

```

### 3.6 Segment Beats

```

1 struct Mv {
2     static constexpr i64 inf = numeric_limits<i64>::max() / 2;
3     i64 mv, smv, cmv, tmv;
4     bool less;
5     i64 def() { return less ? inf : -inf; }
6     i64 mmv(i64 x, i64 y) { return less ? min(x, y) : max(x, y); }
7     Mv(i64 x, bool less) : less(less) {
8         mv = x;
9         smv = tmv = def();
10        cmv = 1;
11    }
12    void up(const Mv& ls, const Mv& rs) {
13        mv = mmv(ls.mv, rs.mv);
14        smv = mmv(ls.mv == mv ? ls.smv : ls.mv, rs.mv == mv ? rs.smv : rs.mv);
15        cmv = (ls.mv == mv ? ls.cmv : 0) + (rs.mv == mv ? rs.cmv : 0);
16    }
17    void add(i64 x) {
18        mv += x;
19        if (smv != def()) { smv += x; }
20        if (tmv != def()) { tmv += x; }
21    }
22 };
23 struct Node {
24     Mv mn, mx;
25     i64 sum, tsum;
26     Node *ls, *rs;
27     Node(i64 x = 0) : sum(x), tsum(0), mn(x, true), mx(x, false) {
28         ls = rs = nullptr;
29     }
30     void up() {
31         sum = ls->sum + rs->sum;
32         mx.up(ls->mx, rs->mx);
33         mn.up(ls->mn, rs->mn);
34     }
35     void down(int tl, int tr) {
36         if (tsum) {
37             int tm = midpoint(tl, tr);
38             ls->add(tl, tm, tsum);
39             rs->add(tm, tr, tsum);
40             tsum = 0;
41         }
42         if (mn.tmv != mn.def()) {

```

```

43         ls->ch(mn.tmv, true);
44         rs->ch(mn.tmv, true);
45         mn.tmv = mn.def();
46     }
47     if (mx.tmv != mx.def()) {
48         ls->ch(mx.tmv, false);
49         rs->ch(mx.tmv, false);
50         mx.tmv = mx.def();
51     }
52 }
53 bool cmp(i64 x, i64 y, bool less) { return less ? x < y : x > y; }
54 void add(int tl, int tr, i64 x) {
55     sum += (tr - tl) * x;
56     tsum += x;
57     mx.add(x);
58     mn.add(x);
59 }
60 void ch(i64 x, bool less) {
61     auto &lhs = less ? mn : mx, &rhs = less ? mx : mn;
62     if (not cmp(x, rhs.mv, less)) { return; }
63     sum += (x - rhs.mv) * rhs.cmv;
64     if (lhs.smv == rhs.mv) { lhs.smv = x; }
65     if (lhs.mv == rhs.mv) { lhs.mv = x; }
66     if (cmp(x, rhs.tmv, less)) { rhs.tmv = x; }
67     rhs.mv = lhs.tmv = x;
68 }
69 void add(int tl, int tr, int l, int r, i64 x) {
70     if (tl >= l and tr <= r) { return add(tl, tr, x); }
71     down(tl, tr);
72     int tm = midpoint(tl, tr);
73     if (l < tm) { ls->add(tl, tm, l, r, x); }
74     if (r > tm) { rs->add(tm, tr, l, r, x); }
75     up();
76 }
77 void ch(int tl, int tr, int l, int r, i64 x, bool less) {
78     auto &lhs = less ? mn : mx, &rhs = less ? mx : mn;
79     if (not cmp(x, rhs.mv, less)) { return; }
80     if (tl >= l and tr <= r and cmp(rhs.smv, x, less)) {
81         return ch(x, less);
82     }
83     down(tl, tr);
84     int tm = midpoint(tl, tr);
85     if (l < tm) { ls->ch(tl, tm, l, r, x, less); }
86     if (r > tm) { rs->ch(tm, tr, l, r, x, less); }
87     up();
88 }
89 i64 get(int tl, int tr, int l, int r) {
90     if (tl >= l and tr <= r) { return sum; }
91     down(tl, tr);
92     i64 res = 0;
93     int tm = midpoint(tl, tr);
94     if (l < tm) { res += ls->get(tl, tm, l, r); }
95     if (r > tm) { res += rs->get(tm, tr, l, r); }

```

```

96     return res;
97 }
98 };

```

## 3.7 Tree

### 3.7.1 Least Common Ancestor

```

1 struct LeastCommonAncestor {
2     SparseTable st;
3     vector<int> p, time, a, par;
4     LeastCommonAncestor(int root, const vector<vector<int>> &g) {
5         int n = g.size();
6         time.resize(n, -1);
7         par.resize(n, -1);
8         function<void(int)> dfs = [&](int u) {
9             time[u] = p.size();
10            p.push_back(u);
11            for (int v : g[u]) {
12                if (time[v] == -1) {
13                    par[v] = u;
14                    dfs(v);
15                }
16            }
17        };
18        dfs(root);
19        a.resize(n);
20        for (int i = 1; i < n; i += 1) { a[i] = time[par[p[i]]]; }
21        st = SparseTable(a);
22    }
23    int query(int u, int v) {
24        if (u == v) { return u; }
25        if (time[u] > time[v]) { swap(u, v); }
26        return p[st.query(time[u] + 1, time[v] + 1)];
27    }
28 };

```

### 3.7.2 Link Cut Tree

```

1 struct Node {
2     i64 v, sum;
3     array<Node *, 2> c;
4     Node *p;
5     bool flip;
6     Node(i64 v) : v(v), sum(v), p(nullptr) { c.fill(nullptr); }
7     int side() {
8         if (not p) { return -1; }
9         if (p->c[0] == this) { return 0; }
10        if (p->c[1] == this) { return 1; }
11        return -1;

```

```

12    }
13    void up() { sum = (c[0] ? c[0]->sum : 0) + v + (c[1] ? c[1]->sum : 0); }
14    void down() {
15        if (flip) {
16            swap(c[0], c[1]);
17            if (c[0]) { c[0]->flip ^= 1; }
18            if (c[1]) { c[1]->flip ^= 1; }
19            flip ^= 1;
20        }
21    }
22    void attach(int s, Node *u) {
23        c[s] = u;
24        if (u) { u->p = this; }
25        up();
26    }
27    void rotate() {
28        auto p = this->p;
29        auto pp = p->p;
30        int s = side();
31        int ps = p->side();
32        auto b = c[s ^ 1];
33        p->attach(s, b);
34        attach(s ^ 1, p);
35        if (~ps) { pp->attach(ps, this); }
36        this->p = pp;
37    }
38    void splay() {
39        down();
40        while (side() >= 0 and p->side() >= 0) {
41            p->p->down();
42            p->down();
43            down();
44            (side() == p->side() ? p : this)->rotate();
45            rotate();
46        }
47        if (side() >= 0) {
48            p->down();
49            down();
50            rotate();
51        }
52    }
53    void access() {
54        splay();
55        attach(1, nullptr);
56        while (p != nullptr) {
57            auto w = p;
58            w->splay();
59            w->attach(1, this);
60            rotate();
61        }
62    }
63    void reroot() {
64        access();

```

```

65     flip ^= 1;
66     down();
67 }
68 void link(Node *u) {
69     u->reroot();
70     access();
71     attach(1, u);
72 }
73 void cut(Node *u) {
74     u->reroot();
75     access();
76     if (c[0] == u) {
77         c[0] = nullptr;
78         u->p = nullptr;
79         up();
80     }
81 }
82 };

```

## 4 String

### 4.1 Z

```

1 vector<int> fz(const string &s) {
2     int n = s.size();
3     vector<int> z(n);
4     for (int i = 1, j = 0; i < n; i += 1) {
5         z[i] = max(min(z[i - j], j + z[j] - i), 0);
6         while (i + z[i] < n and s[i + z[i]] == s[z[i]]) { z[i] += 1; }
7         if (i + z[i] > j + z[j]) { j = i; }
8     }
9     return z;
10 }

```

### 4.2 Lyndon Factorization

```

1 vector<int> lyndon_factorization(string const &s) {
2     vector<int> res = {0};
3     for (int i = 0, n = s.size(); i < n;) {
4         int j = i + 1, k = i;
5         for (; j < n and s[k] <= s[j]; j += 1) { k = s[k] < s[j] ? i : k + 1; }
6         while (i <= k) { res.push_back(i += j - k); }
7     }
8     return res;
9 }

```

### 4.3 Border

```

1 vector<int> fborder(const string &s) {
2     int n = s.size();
3     vector<int> res(n);
4     for (int i = 1; i < n; i += 1) {
5         int &j = res[i] = res[i - 1];
6         while (j and s[i] != s[j]) { j = res[j - 1]; }
7         j += s[i] == s[j];
8     }
9     return res;
10 }

```

### 4.4 Manacher

```

1 vector<int> manacher(const string &s) {
2     int n = s.size();
3     vector<int> p(n);
4     for (int i = 0, j = 0; i < n; i += 1) {
5         if (j + p[j] > i) { p[i] = min(p[j * 2 - i], j + p[j] - i); }
6         while (i >= p[i] and i + p[i] < n and s[i - p[i]] == s[i + p[i]]) {
7             p[i] += 1;
8         }
9         if (i + p[i] > j + p[j]) { j = i; }
10    }
11    return p;
12 }

```

### 4.5 Suffix Array

```

1 pair<vector<int>, vector<int>> binary_lifting(const string &s) {
2     int n = s.size(), k = 0;
3     vector<int> p(n), rank(n), q, count;
4     iota(p.begin(), p.end(), 0);
5     ranges::sort(p, {}, [&](int i) { return s[i]; });
6     for (int i = 0; i < n; i += 1) {
7         rank[p[i]] = i and s[p[i]] == s[p[i - 1]] ? rank[p[i - 1]] : k++;
8     }
9     for (int m = 1; m < n; m *= 2) {
10        q.resize(m);
11        iota(q.begin(), q.end(), n - m);
12        for (int i : p) {
13            if (i >= m) { q.push_back(i - m); }
14        }
15        count.assign(k, 0);
16        for (int i : rank) { count[i] += 1; }
17        partial_sum(count.begin(), count.end(), count.begin());
18        for (int i = n - 1; i >= 0; i -= 1) { p[count[rank[q[i]]] -= 1] = q[i]; }
19        auto previous = rank;
20        previous.resize(2 * n, -1);

```

```

21     k = 0;
22     for (int i = 0; i < n; i += 1) {
23         rank[p[i]] = i and previous[p[i]] == previous[p[i - 1]] and
24             previous[p[i] + m] == previous[p[i - 1] + m]
25             ? rank[p[i - 1]]
26             : k++;
27     }
28 }
29 vector<int> lcp(n);
30 k = 0;
31 for (int i = 0; i < n; i += 1) {
32     if (rank[i]) {
33         k = max(k - 1, 0);
34         int j = p[rank[i] - 1];
35         while (i + k < n and j + k < n and s[i + k] == s[j + k]) { k += 1; }
36         lcp[rank[i]] = k;
37     }
38 }
39 return {p, lcp};
40 }

```

## 4.6 Aho-Corasick Automaton

```

1 constexpr int sigma = 26;
2 struct Node {
3     int link;
4     array<int, sigma> next;
5     Node() : link(0) { next.fill(0); }
6 };
7 struct AhoCorasick : vector<Node> {
8     AhoCorasick() : vector<Node>(1) {}
9     int add(const string &s, char first = 'a') {
10         int p = 0;
11         for (char si : s) {
12             int c = si - first;
13             if (not at(p).next[c]) {
14                 at(p).next[c] = size();
15                 emplace_back();
16             }
17             p = at(p).next[c];
18         }
19         return p;
20     }
21     void init() {
22         queue<int> q;
23         for (int i = 0; i < sigma; i += 1) {
24             if (at(0).next[i]) { q.push(at(0).next[i]); }
25         }
26         while (not q.empty()) {
27             int u = q.front();
28             q.pop();
29             for (int i = 0; i < sigma; i += 1) {

```

```

30         if (at(u).next[i]) {
31             at(at(u).next[i]).link = at(at(u).link).next[i];
32             q.push(at(u).next[i]);
33         } else {
34             at(u).next[i] = at(at(u).link).next[i];
35         }
36     }
37 }
38 }
39 };

```

## 4.7 Suffix Automaton

```

1 struct Node {
2     int link, len;
3     array<int, sigma> next;
4     Node() : link(-1), len(0) { next.fill(-1); }
5 };
6 struct SuffixAutomaton : vector<Node> {
7     SuffixAutomaton() : vector<Node>(1) {}
8     int extend(int p, int c) {
9         if (~at(p).next[c]) {
10             // For online multiple strings.
11             int q = at(p).next[c];
12             if (at(p).len + 1 == at(q).len) { return q; }
13             int clone = size();
14             push_back(at(q));
15             back().len = at(p).len + 1;
16             while (~p and at(p).next[c] == q) {
17                 at(p).next[c] = clone;
18                 p = at(p).link;
19             }
20             at(q).link = clone;
21             return clone;
22         }
23         int cur = size();
24         emplace_back();
25         back().len = at(p).len + 1;
26         while (~p and at(p).next[c] == -1) {
27             at(p).next[c] = cur;
28             p = at(p).link;
29         }
30         if (~p) {
31             int q = at(p).next[c];
32             if (at(p).len + 1 == at(q).len) {
33                 back().link = q;
34             } else {
35                 int clone = size();
36                 push_back(at(q));
37                 back().len = at(p).len + 1;
38                 while (~p and at(p).next[c] == q) {
39                     at(p).next[c] = clone;

```



```

40     p = at(p).link;
41 }
42     at(q).link = at(cur).link = clone;
43 }
44 } else {
45     back().link = 0;
46 }
47 return cur;
48 }
49 };

```

## 4.8 Palindromic Tree

```

1 struct Node {
2     int sum, len, link;
3     array<int, sigma> next;
4     Node(int len) : len(len) {
5         sum = link = 0;
6         next.fill(0);
7     }
8 };
9 struct PalindromicTree : vector<Node> {
10     int last;
11     vector<int> s;
12     PalindromicTree() : last(0) {
13         emplace_back(0);
14         emplace_back(-1);
15         at(0).link = 1;
16     }
17     int get_link(int u, int i) {
18         while (i < at(u).len + 1 or s[i - at(u).len - 1] != s[i]) u = at(u).link;
19         return u;
20     }
21     void extend(int i) {
22         int cur = get_link(last, i);
23         if (not at(cur).next[s[i]]) {
24             int now = size();
25             emplace_back(at(cur).len + 2);
26             back().link = at(get_link(at(cur).link, i)).next[s[i]];
27             back().sum = at(back().link).sum + 1;
28             at(cur).next[s[i]] = now;
29         }
30         last = at(cur).next[s[i]];
31     }
32 };

```

## 5 Number Theory

### 5.1 Modular Arithmetic

#### 5.1.1 Sqrt

Find  $x$  such that  $x^2 \equiv y \pmod{p}$ .

Constraints:  $p$  is prime and  $0 \leq y < p$ .

```

1 i64 sqrt(i64 y, i64 p) {
2     static mt19937_64 mt;
3     if (y <= 1) { return y; };
4     if (power(y, (p - 1) / 2, p) != 1) { return -1; }
5     uniform_int_distribution uid(i64(0), p - 1);
6     i64 x, w;
7     do {
8         x = uid(mt);
9         w = (x * x + p - y) % p;
10    } while (power(w, (p - 1) / 2, p) == 1);
11    auto mul = [&](pair<i64, i64> a, pair<i64, i64> b) {
12        return pair((a.first * b.first + a.second * b.second % p * w) % p,
13                    (a.first * b.second + a.second * b.first) % p);
14    };
15    pair<i64, i64> a = {x, 1}, res = {1, 0};
16    for (i64 r = (p + 1) >> 1; r; r >>= 1, a = mul(a, a)) {
17        if (r & 1) { res = mul(res, a); }
18    }
19    return res.first;
20 }

```

#### 5.1.2 Logarithm

Find  $k$  such that  $x^k \equiv y \pmod{n}$ .

Constraints:  $0 \leq x, y < n$ .

```

1 i64 log(i64 x, i64 y, i64 n) {
2     if (y == 1 or n == 1) { return 0; }
3     if (not x) { return y ? -1 : 1; }
4     i64 res = 0, k = 1 % n;
5     for (i64 d; k != y and (d = gcd(x, n)) != 1; res += 1) {
6         if (y % d) { return -1; }
7         n /= d;
8         y /= d;
9         k = k * (x / d) % n;
10    }
11    if (k == y) { return res; }
12    unordered_map<i64, i64> mp;
13    i64 px = 1, m = sqrt(n) + 1;
14    for (int i = 0; i < m; i += 1, px = px * x % n) { mp[y * px % n] = i; }
15    i64 ppx = k * px % n;
16    for (int i = 1; i <= m; i += 1, ppx = ppx * px % n) {
17        if (mp.count(ppx)) { return res + i * m - mp[ppx]; }
18    }

```

```

19     return -1;
20 }

```

## 5.2 Chinese Remainder Theorem

```

1 tuple<i64, i64, i64> exgcd(i64 a, i64 b) {
2     i64 x = 1, y = 0, x1 = 0, y1 = 1;
3     while (b) {
4         i64 q = a / b;
5         tie(x, x1) = pair(x1, x - q * x1);
6         tie(y, y1) = pair(y1, y - q * y1);
7         tie(a, b) = pair(b, a - q * b);
8     }
9     return {a, x, y};
10 }
11 optional<pair<i64, i64>> linear_equations(i64 a0, i64 b0, i64 a1, i64 b1) {
12     auto [d, x, y] = exgcd(a0, a1);
13     if ((b1 - b0) % d) { return {}; }
14     i64 a = a0 / d * a1, b = (i128)(b1 - b0) / d * x % (a1 / d);
15     if (b < 0) { b += a1 / d; }
16     b = (i128)(a0 * b + b0) % a;
17     if (b < 0) { b += a; }
18     return {{a, b}};
19 }

```

## 5.3 Miller Rabin

```

1 bool miller_rabin(i64 n) {
2     static constexpr array<int, 9> p = {2, 3, 5, 7, 11, 13, 17, 19, 23};
3     if (n == 1) { return false; }
4     if (n == 2) { return true; }
5     if (not(n % 2)) { return false; }
6     int r = countr_zero(u64(n - 1));
7     i64 d = (n - 1) >> r;
8     for (int pi : p) {
9         if (pi >= n) { break; }
10        i64 x = power(pi, d, n);
11        if (x == 1 or x == n - 1) { continue; };
12        for (int j = 1; j < r; j += 1) {
13            x = (i128)x * x % n;
14            if (x == n - 1) { break; }
15        }
16        if (x != n - 1) { return false; }
17    }
18    return true;
19 };

```

## 5.4 Pollard Rho

```

1 vector<i64> pollard_rho(i64 n) {
2     static mt19937_64 mt;
3     uniform_int_distribution uid(i64(0), n);
4     if (n == 1) { return {}; }
5     vector<i64> res;
6     function<void(i64)> rho = [&](i64 n) {
7         if (miller_rabin(n)) { return res.push_back(n); }
8         i64 d = n;
9         while (d == n) {
10             d = 1;
11             for (i64 k = 1, y = 0, x = 0, s = 1, c = uid(mt); d == 1;
12                 k <= 1, y = x, s = 1) {
13                 for (int i = 1; i <= k; i += 1) {
14                     x = ((i128)x * x + c) % n;
15                     s = (i128)s * abs(x - y) % n;
16                     if (not(i % 127) or i == k) {
17                         d = gcd(s, n);
18                         if (d != 1) { break; }
19                     }
20                 }
21             }
22         }
23         rho(d);
24         rho(n / d);
25     };
26     rho(n);
27     return res;
28 }

```

## 5.5 Primitive Root

Constraints:  $n = 2, 4, p^k, 2p^k$  where  $p$  is odd prime.

```

1 i64 phi(i64 n) {
2     auto pd = pollard_rho(n);
3     ranges::sort(pd);
4     pd.erase(ranges::unique(pd).begin(), pd.end());
5     for (i64 pi : pd) { n = n / pi * (pi - 1); }
6     return n;
7 }
8 i64 minimum_primitive_root(i64 n) {
9     i64 pn = phi(n);
10    auto pd = pollard_rho(pn);
11    ranges::sort(pd);
12    pd.erase(ranges::unique(pd).begin(), pd.end());
13    auto check = [&](i64 r) {
14        if (gcd(r, n) != 1) { return false; }
15        for (i64 pi : pd) {
16            if (power(r, pn / pi, n) == 1) { return false; }
17        }
18    };

```

```

18     return true;
19 };
20 i64 r = 1;
21 while (not check(r)) { r += 1; }
22 return r;
23 }

```

```

20     b = m - 1 - b;
21 }
22 u64 d = m / a;
23 u64 res = min_of_mod(n, a, m % a, b, c += 1, (d - 1) * p + q, d * p + q);
24 return c % 2 ? m - 1 - res : a - 1 - res;
25 }

```

## 5.6 Sum of Floor

Returns  $\sum_{i=0}^{n-1} \lfloor \frac{ai+b}{m} \rfloor$ .

```

1 u64 sum_of_floor(u64 n, u64 m, u64 a, u64 b) {
2     u64 ans = 0;
3     while (n) {
4         if (a >= m) {
5             ans += a / m * n * (n - 1) / 2;
6             a %= m;
7         }
8         if (b >= m) {
9             ans += b / m * n;
10            b %= m;
11        }
12        u64 y = a * n + b;
13        if (y < m) { break; }
14        tie(n, m, a, b) = tuple(y / m, a, m, y % m);
15    }
16    return ans;
17 }

```

## 5.7 Minimum of Remainder

Returns  $\min\{(ai + b) \bmod m : 0 \leq i < n\}$ .

```

1 u64 min_of_mod(u64 n, u64 m, u64 a, u64 b, u64 c = 1, u64 p = 1, u64 q = 1) {
2     if (a == 0) { return b; }
3     if (c % 2) {
4         if (b >= a) {
5             u64 t = (m - b + a - 1) / a;
6             u64 d = (t - 1) * p + q;
7             if (n <= d) { return b; }
8             n -= d;
9             b += a * t - m;
10        }
11        b = a - 1 - b;
12    } else {
13        if (b < m - a) {
14            u64 t = (m - b - 1) / a;
15            u64 d = t * p;
16            if (n <= d) { return (n - 1) / p * a + b; }
17            n -= d;
18            b += a * t;
19        }

```

```

1 struct Node {
2     int a, b;
3     vector<pair<int, char>> p;
4     Node(int a, int b) : a(a), b(b) {
5         // gcd(a, b) == 1
6         while (a != 1 or b != 1) {
7             if (a > b) {
8                 int k = (a - 1) / b;
9                 p.emplace_back(k, 'R');
10                a -= k * b;
11            } else {
12                int k = (b - 1) / a;
13                p.emplace_back(k, 'L');
14                b -= k * a;
15            }
16        }
17    }
18    Node(vector<pair<int, char>> p, int _a = 1, int _b = 1)
19        : p(p), a(_a), b(_b) {
20        for (auto [c, d] : p | views::reverse) {
21            if (d == 'R') {
22                a += c * b;
23            } else {
24                b += c * a;
25            }
26        }
27    }
28 };

```

## 5.8 Stern Brocot Tree

## 5.9 Nim Product

```

1 struct NimProduct {
2     array<array<u64, 64>, 64> mem;
3     NimProduct() {
4         for (int i = 0; i < 64; i += 1) {
5             for (int j = 0; j < 64; j += 1) {
6                 int k = i & j;
7                 if (k == 0) {
8                     mem[i][j] = u64(1) << (i | j);
9                 } else {
10                    int x = k & -k;

```

```

11         mem[i][j] = mem[i ^ x][j] ^
12             mem[(i ^ x) | (x - 1)][(j ^ x) | (i & (x - 1))];
13     }
14 }
15 }
16 }
17 u64 nim_product(u64 x, u64 y) {
18     u64 res = 0;
19     for (int i = 0; i < 64 and x >> i; i += 1) {
20         if ((x >> i) % 2) {
21             for (int j = 0; j < 64 and y >> j; j += 1) {
22                 if ((y >> j) % 2) { res ^= mem[i][j]; }
23             }
24         }
25     }
26     return res;
27 }
28 };

```

## 6 Numerical

### 6.1 Golden Search

```

1 template <int step> f64 golden_search(function<f64(f64)> f, f64 l, f64 r) {
2     f64 ml = (numbers::phi - 1) * l + (2 - numbers::phi) * r;
3     f64 mr = l + r - ml;
4     f64 fml = f(ml), fmr = f(mr);
5     for (int i = 0; i < step; i += 1)
6         if (fml > fmr) {
7             l = ml;
8             ml = mr;
9             fml = fmr;
10            fmr = f(mr = (numbers::phi - 1) * r + (2 - numbers::phi) * l);
11        } else {
12            r = mr;
13            mr = ml;
14            fmr = fml;
15            fml = f(ml = (numbers::phi - 1) * l + (2 - numbers::phi) * r);
16        }
17     return midpoint(l, r);
18 }

```

### 6.2 Adaptive Simpson

```

1 f64 simpson(function<f64(f64)> f, f64 l, f64 r) {
2     return (r - l) * (f(l) + f(r) + 4 * f(midpoint(l, r))) / 6;
3 }
4 f64 adaptive_simpson(const function<f64(f64)> &f, f64 l, f64 r, f64 eps) {
5     f64 m = midpoint(l, r);

```

```

6     f64 s = simpson(f, l, r);
7     f64 sl = simpson(f, l, m);
8     f64 sr = simpson(f, m, r);
9     f64 d = sl + sr - s;
10    if (abs(d) < 15 * eps) { return (sl + sr) + d / 15; }
11    return adaptive_simpson(f, l, m, eps / 2) +
12        adaptive_simpson(f, m, r, eps / 2);
13 }

```

### 6.3 Simplex

Returns maximum of  $cx$  s.t.  $ax \leq b$  and  $x \geq 0$ .

```

1 struct Simplex {
2     int n, m;
3     f64 z;
4     vector<vector<f64>> a;
5     vector<f64> b, c;
6     vector<int> base;
7     Simplex(int n, int m)
8         : n(n), m(m), a(m, vector<f64>(n)), b(m), c(n), base(n + m), z(0) {
9         iota(base.begin(), base.end(), 0);
10    }
11    void pivot(int out, int in) {
12        swap(base[out + n], base[in]);
13        f64 f = 1 / a[out][in];
14        for (f64 &aij : a[out]) { aij *= f; }
15        b[out] *= f;
16        a[out][in] = f;
17        for (int i = 0; i <= m; i += 1) {
18            if (i != out) {
19                auto &ai = i == m ? c : a[i];
20                f64 &bi = i == m ? z : b[i];
21                f64 f = -ai[in];
22                if (f < -eps or f > eps) {
23                    for (int j = 0; j < n; j += 1) { ai[j] += a[out][j] * f; }
24                    ai[in] = a[out][in] * f;
25                    bi += b[out] * f;
26                }
27            }
28        }
29    }
30    bool feasible() {
31        while (true) {
32            int i = ranges::min_element(b) - b.begin();
33            if (b[i] > -eps) { break; }
34            int k = -1;
35            for (int j = 0; j < n; j += 1) {
36                if (a[i][j] < -eps and (k == -1 or base[j] > base[k])) { k = j; }
37            }
38            if (k == -1) { return false; }
39            pivot(i, k);
40        }

```

```

41     return true;
42 }
43 bool bounded() {
44     while (true) {
45         int i = ranges::max_element(c) - c.begin();
46         if (c[i] < eps) { break; }
47         int k = -1;
48         for (int j = 0; j < m; j += 1) {
49             if (a[j][i] > eps) {
50                 if (k == -1) {
51                     k = j;
52                 } else {
53                     f64 d = b[j] * a[k][i] - b[k] * a[j][i];
54                     if (d < -eps or (d < eps and base[j] > base[k])) { k = j; }
55                 }
56             }
57         }
58         if (k == -1) { return false; }
59         pivot(k, i);
60     }
61     return true;
62 }
63 vector<f64> x() const {
64     vector<f64> res(n);
65     for (int i = n; i < n + m; i += 1) {
66         if (base[i] < n) { res[base[i]] = b[i - n]; }
67     }
68     return res;
69 }
70 };

```

## 6.4 Green's Theorem

$$\oint_C (Pdx + Qdy) = \iint_D \left( \frac{\partial Q}{\partial x} - \frac{\partial P}{\partial y} \right) dxdy.$$

## 6.5 Double Integral

$$\iint_D f(x, y) dxdy = \iint_D f(x(u, v), y(u, v)) \left| \frac{\partial x}{\partial u} \frac{\partial x}{\partial v} \right| dudv.$$

# 7 Convolution

## 7.1 Fast Fourier Transform on $\mathbb{C}$

```

1 void fft(vector<complex<f64>>& a, bool inverse) {
2     int n = a.size();
3     vector<int> r(n);
4     for (int i = 0; i < n; i += 1) {
5         r[i] = r[i / 2] / 2 | (i % 2 ? n / 2 : 0);
6     }

```

```

7     for (int i = 0; i < n; i += 1) {
8         if (i < r[i]) { swap(a[i], a[r[i]]); }
9     }
10    for (int m = 1; m < n; m *= 2) {
11        complex<f64> wn(exp((inverse ? 1.i : -1.i) * numbers::pi / (f64)m));
12        for (int i = 0; i < n; i += m * 2) {
13            complex<f64> w = 1;
14            for (int j = 0; j < m; j += 1, w = w * wn) {
15                auto &x = a[i + j + m], &y = a[i + j], t = w * x;
16                tie(x, y) = pair(y - t, y + t);
17            }
18        }
19    }
20    if (inverse) {
21        for (auto& ai : a) { ai /= n; }
22    }
23 }

```

## 7.2 Formal Power Series on $\mathbb{F}_p$

```

1 void fft(vector<i64>& a, bool inverse) {
2     int n = a.size();
3     vector<int> r(n);
4     for (int i = 0; i < n; i += 1) {
5         r[i] = r[i / 2] / 2 | (i % 2 ? n / 2 : 0);
6     }
7     for (int i = 0; i < n; i += 1) {
8         if (i < r[i]) { swap(a[i], a[r[i]]); }
9     }
10    for (int m = 1; m < n; m *= 2) {
11        i64 wn = power(inverse ? power(g, mod - 2) : g, (mod - 1) / m / 2);
12        for (int i = 0; i < n; i += m * 2) {
13            i64 w = 1;
14            for (int j = 0; j < m; j += 1, w = w * wn % mod) {
15                auto &x = a[i + j + m], &y = a[i + j], t = w * x % mod;
16                tie(x, y) = pair((y + mod - t) % mod, (y + t) % mod);
17            }
18        }
19    }
20    if (inverse) {
21        i64 inv = power(n, mod - 2);
22        for (auto& ai : a) { ai = ai * inv % mod; }
23    }
24 }

```

### 7.2.1 Newton's Method

$$h = g(f) \Leftrightarrow G(h) = f - g^{-1}(h) \equiv 0.$$

$$h = h_0 - \frac{G(h_0)}{G'(h_0)}.$$

## 7.2.2 Arithmetic

- For  $f = pg + q$ ,  $p^T = f^T g^T - 1$ .
- For  $h = \frac{1}{f}$ ,  $h = h_0(2 - h_0 f)$ .
- For  $h = \sqrt{f}$ ,  $h = \frac{1}{2}(h_0 + \frac{f}{h_0})$ .
- For  $h = \log f$ ,  $h = \int \frac{df}{f}$ .
- For  $h = \exp f$ ,  $h = h_0(1 + f - \log h_0)$ .

## 7.2.3 Interpolation

$$g(x) = \prod_i (x - x_i)$$
$$f(x) = \sum_{i=0}^{n-1} y_i \left( \prod_{j \neq i} \frac{x - x_j}{x_i - x_j} \right).$$
$$f(x) = \sum_{i=0}^{n-1} \frac{y_i}{g'(x_i)} \prod_{j \neq i} (x - x_j).$$

## 7.2.4 Primes with root 3

$$469762049 = 7 \times 2^{26} + 1.$$

$$4179340454199820289 = 29 \times 2^{57} + 1.$$

## 7.3 Circular Transform

$$A_{ij} = w_k^{ij}, A_{ij}^{-1} = \frac{1}{k} w_k^{-ij}.$$

## 7.4 Truncated Transform

$$\sum_{j=0}^{n-1} \frac{i}{\prod_{k=0}^j m_k} \bmod n \quad \text{for } 0 \leq i < \prod_{j=0}^{n-1} m_k.$$

# 8 Geometry

## 8.1 Pick's Theorem

$$\text{Area} = \#\{\text{points inside}\} + \frac{1}{2} \#\{\text{points on the border}\} - 1.$$

## 8.2 2D Geometry

P: point, L: line, G: convex hull or polygon, C: Circle.

```
7   return x < -eps<T> ? -1 : x > eps<T>;
8   }
9   template <typename T>
10  struct P {
11      T x, y;
12      explicit P(T x = 0, T y = 0) : x(x), y(y) {}
13      P operator*(T k) { return P(x * k, y * k); }
14      P operator+(P p) { return P(x + p.x, y + p.y); }
15      P operator-(P p) { return P(x - p.x, y - p.y); }
16      P operator-() { return P(-x, -y); }
17      T len2() { return x * x + y * y; }
18      T cross(P p) { return x * p.y - y * p.x; }
19      T dot(P p) { return x * p.x + y * p.y; }
20      bool operator==(P p) { return sign(x - p.x) == 0 and sign(y - p.y) == 0; }
21      int arg() { return y < 0 or (y == 0 and x > 0) ? -1 : x or y; }
22      P rotate90() { return P(-y, x); }
23  };
24  template <typename T>
25  bool argument(P<T> lhs, P<T> rhs) {
26      if (lhs.arg() != rhs.arg()) { return lhs.arg() < rhs.arg(); }
27      return lhs.cross(rhs) > 0;
28  }
29  template <typename T>
30  struct L {
31      P<T> a, b;
32      explicit L(P<T> a = {}, P<T> b = {}) : a(a), b(b) {}
33      P<T> v() { return b - a; }
34      bool contains(P<T> p) {
35          return sign((p - a).cross(p - b)) == 0 and sign((p - a).dot(p - b)) <= 0;
36      }
37      int left(P<T> p) { return sign(v().cross(p - a)); }
38      optional<pair<T, T>> intersection(L l) {
39          auto y = v().cross(l.v());
40          if (sign(y) == 0) { return {}; }
41          auto x = (l.a - a).cross(l.v());
42          return y < 0 ? pair(-x, -y) : pair(x, y);
43      }
44  };
45  template <typename T>
46  struct G {
47      vector<P<T>> g;
48      explicit G(int n) : g(n) {}
49      explicit G(const vector<P<T>>& g) : g(g) {}
50      optional<int> winding(P<T> p) {
51          int n = g.size(), res = 0;
52          for (int i = 0; i < n; i += 1) {
53              auto a = g[i], b = g[(i + 1) % n];
54              L l(a, b);
55              if (l.contains(p)) { return {}; }
56              if (sign(l.v().y) < 0 and l.left(p) >= 0) { continue; }
57              if (sign(l.v().y) == 0) { continue; }
58              if (sign(l.v().y) > 0 and l.left(p) <= 0) { continue; }
59              if (sign(a.y - p.y) < 0 and sign(b.y - p.y) >= 0) { res += 1; }
```

```

60     if (sign(a.y - p.y) >= 0 and sign(b.y - p.y) < 0) { res -= 1; }
61 }
62 return res;
63 }
64 G convex() {
65     ranges::sort(g, {}, [&](P<T> p) { return pair(p.x, p.y); });
66     vector<P<T>> h;
67     for (auto p : g) {
68         while (ssize(h) >= 2 and
69             sign((h.back() - h.end()[-2]).cross(p - h.back())) <= 0) {
70             h.pop_back();
71         }
72         h.push_back(p);
73     }
74     int m = h.size();
75     for (auto p : g | views::reverse) {
76         while (ssize(h) > m and
77             sign((h.back() - h.end()[-2]).cross(p - h.back())) <= 0) {
78             h.pop_back();
79         }
80         h.push_back(p);
81     }
82     h.pop_back();
83     return G(h);
84 }
85 // Following function are valid only for convex.
86 T diameter2() {
87     int n = g.size();
88     T res = 0;
89     for (int i = 0, j = 1; i < n; i += 1) {
90         auto a = g[i], b = g[(i + 1) % n];
91         while (sign((b - a).cross(g[(j + 1) % n] - g[j])) > 0) {
92             j = (j + 1) % n;
93         }
94         res = max(res, (a - g[j]).len2());
95         res = max(res, (a - g[j]).len2());
96     }
97     return res;
98 }
99 optional<bool> contains(P<T> p) {
100     if (g[0] == p) { return true; }
101     if (g.size() == 1) { return false; }
102     if (L(g[0], g[1]).contains(p)) { return true; }
103     if (L(g[0], g[1]).left(p) <= 0) { return false; }
104     if (L(g[0], g.back()).left(p) > 0) { return false; }
105     int i = *ranges::partition_point(views::iota(2, ssize(g)), [&](int i) {
106         return sign((p - g[0]).cross(g[i] - g[0])) <= 0;
107     });
108     int s = L(g[i - 1], g[i]).left(p);
109     if (s == 0) { return true; }
110     return s > 0;
111 }
112 int most(const function<P<T>(P<T>>>& f) {

```

```

113     int n = g.size();
114     auto check = [&](int i) {
115         return sign(f(g[i]).cross(g[(i + 1) % n] - g[i])) >= 0;
116     };
117     P<T> f0 = f(g[0]);
118     bool check0 = check(0);
119     if (not check0 and check(n - 1)) { return 0; }
120     return *ranges::partition_point(views::iota(0, n), [&](int i) -> bool {
121         if (i == 0) { return true; }
122         bool checki = check(i);
123         int t = sign(f0.cross(g[i] - g[0]));
124         if (i == 1 and checki == check0 and t == 0) { return true; }
125         return checki ^ (checki == check0 and t <= 0);
126     });
127 }
128 pair<int, int> tan(P<T> p) {
129     return {most([&](P<T> x) { return x - p; }),
130         most([&](P<T> x) { return p - x; })};
131 }
132 pair<int, int> tan(L<T> l) {
133     return {most([&](P<T> _) { return l.v(); }),
134         most([&](P<T> _) { return -l.v(); })};
135 }
136 };
137
138 template <typename T>
139 vector<L<T>> half(vector<L<T>> ls, T bound) {
140     // Ranges: bound ^ 6
141     auto check = [] (L<T> a, L<T> b, L<T> c) {
142         auto [x, y] = b.intersection(c).value();
143         a = L(a.a * y, a.b * y);
144         return a.left(b.a * y + b.v() * x) < 0;
145     };
146     ls.emplace_back(P(-bound, (T)0), P(-bound, -(T)1));
147     ls.emplace_back(P((T)0, -bound), P((T)1, -bound));
148     ls.emplace_back(P(bound, (T)0), P(bound, (T)1));
149     ls.emplace_back(P((T)0, bound), P(-(T)1, bound));
150     ranges::sort(ls, [&](L<T> lhs, L<T> rhs) {
151         if (sign(lhs.v().cross(rhs.v())) == 0 and
152             sign(lhs.v().dot(rhs.v())) >= 0) {
153             return lhs.left(rhs.a) == -1;
154         }
155         return argument(lhs.v(), rhs.v());
156     });
157     deque<L<T>> q;
158     for (int i = 0; i < ssize(ls); i += 1) {
159         if (i and sign(ls[i - 1].v().cross(ls[i].v())) == 0 and
160             sign(ls[i - 1].v().dot(ls[i].v())) == 1) {
161             continue;
162         }
163         while (q.size() > 1 and check(ls[i], q.back(), q.end()[-2])) {
164             q.pop_back();
165         }

```

```

166     while (q.size() > 1 and check(ls[i], q[0], q[1])) { q.pop_front(); }
167     if (not q.empty() and sign(q.back().v().cross(ls[i].v())) <= 0) {
168         return {};
169     }
170     q.push_back(ls[i]);
171 }
172 while (q.size() > 1 and check(q[0], q.back(), q.end()[-2])) {

```

```

173     q.pop_back();
174 }
175 while (q.size() > 1 and check(q.back(), q[0], q[1])) { q.pop_front(); }
176 return vector<L<T>>(q.begin(), q.end());
177 }

```