

# **RAJALAKSHMI ENGINEERING COLLEGE**

**RAJALAKSHMI NAGAR, THANDALAM – 602 105**



**RAJALAKSHMI  
ENGINEERING COLLEGE**

**CS19443**

**DATABASE MANAGEMENT SYSTEMS LABORATORY**

**Laboratory Manual Note Book**

Name : .....

Year / Branch / Section : .....

Register No. : .....

Semester : .....

Academic Year : .....

## **Vision**

To promote highly Ethical and Innovative Computer Professionals through excellence in teaching, training and research.

## **Mission**

- To produce globally competent professionals, motivated to learn the emerging technologies and to be innovative in solving real world problems.
- To promote research activities amongst the students and the members of faculty that could benefit the society.
- To impart moral and ethical values in their profession.

## **PROGRAMME EDUCATIONAL OBJECTIVES (PEOs)**

**PEO 1:** To equip students with essential background in computer science, basic electronics and applied mathematics.

**PEO 2:** To prepare students with fundamental knowledge in programming languages, and tools and enable them to develop applications.

**PEO 3:** To develop professionally ethical individuals enhanced with analytical skills, communication skills and organizing ability to meet industry requirements.

## **PROGRAMME OUTCOMES (POs)**

**PO1:** Engineering knowledge: Apply the knowledge of Mathematics, Science, Engineering fundamentals, and an engineering specialization to the solution of complex engineering problems.

**PO2:** Problem analysis: Identify, formulate, review research literature, and analyze complex engineering problems reaching substantiated conclusions using first principles of mathematics, natural sciences, and engineering sciences.

**PO3:** Design/development of solutions: Design solutions for complex engineering problems and design system components or processes that meet the specified needs with appropriate consideration for the public health and safety, and the cultural, societal, and environmental considerations.

**PO4:** Conduct investigations of complex problems: Use research-based knowledge and research methods including design of experiments, analysis and interpretation of data, and synthesis of the information to provide valid conclusions.

**PO5:** Modern tool usage: Create, select, and apply appropriate techniques, resources, and modern engineering and IT tools including prediction and modeling to complex engineering activities with an understanding of the limitations.

**PO6:** The engineer and society: Apply reasoning informed by the contextual knowledge to assess societal, health, safety, legal and cultural issues and the consequent responsibilities relevant to the professional engineering practice.

**PO7:** Environment and sustainability: Understand the impact of the professional engineering solutions in societal and environmental contexts, and demonstrate the knowledge of, and need for sustainable development.

**PO8:** Ethics: Apply ethical principles and commit to professional ethics and responsibilities and norms of the engineering practice.

**PO9:** Individual and team work: Function effectively as an individual, and as a member or leader in diverse teams, and in multidisciplinary settings.

**PO10:** Communication: Communicate effectively on complex engineering activities with the engineering community and with society at large, such as, being able to comprehend and write effective reports and design documentation, make effective presentations, and give and receive clear instructions.

**PO11:** Project management and finance: Demonstrate knowledge and understanding of the engineering and management principles and apply these to one's own work, as a member and leader in a team, to manage projects and in multidisciplinary environments.

**PO12:** Life-long learning: Recognize the need for, and have the preparation and ability to engage in independent and life-long learning in the broadest context of technological change.

## PROGRAM SPECIFIC OUTCOMES (PSOs)

A graduate of the Computer Science and Design Program will have an

**PSO 1:** Ability to understand, analyze and develop efficient software solutions using suitable algorithms, data structures, and other computing techniques.

**PSO 2:** Ability to independently investigate a problem which can be solved by a Human Computer Interaction (HCI) design process and then design an end-to-end solution to it (i.e., from user need identification to UI design to technical coding and evaluation). Ability to effectively use suitable tools and platforms, as well as enhance them, to develop applications/products using for new media design in areas like animation, gaming, virtual reality, etc.

**PSO 3:** Ability to apply knowledge in various domains to identify research gaps and to provide solution to new ideas, inculcate passion towards higher studies, creating innovative career paths to be an entrepreneur and evolve as an ethically social responsible computer science and design professional.

### CO – PO and PSO matrices of course

PO/PSO CO	PO 1	PO 2	PO 3	PO 4	PO 5	PO 6	PO 7	PO 8	PO 9	PO 10	PO 11	PO 12	PSO 1	PSO 2	PSO 3
<b>CS19443.1</b>	2	2	2	-	-	-	-	-	1	-	-	1	2	2	-
<b>CS19443.2</b>	2	2	3	3	3	-	-	-	2	1	2	1	2	1	-
<b>CS19443.3</b>	2	2	2	2	2	-	-	-	2	1	2	1	1	2	1
<b>CS19443.4</b>	2	2	2	2	2	-	-	-	1	1	-	-	1	2	1
<b>CS19443.5</b>	2	2	2	4	2	-	-	-	2	-	2	2	1	2	3
<b>Average</b>	<b>2.0</b>	<b>2.0</b>	<b>2.2</b>	<b>2.8</b>	<b>2.3</b>	<b>-</b>	<b>-</b>	<b>-</b>	<b>1.6</b>	<b>1.0</b>	<b>2.0</b>	<b>1.3</b>	<b>1.4</b>	<b>1.8</b>	<b>1.7</b>

<b>List of Experiments</b>			
<b>1</b>	Introduction to SQL : DDL,DML,DCL,TCL. SQL clause :SELECT FROM WHERE GROUPBY,HAVING,ORDERBY Using SQLite/MySQL/Oracle		
<b>2</b>	Creation of Views, Synonyms, Sequence, Indexes, Save point.		
<b>3</b>	Creating an Employee database to set various constraints and subqueries.		
<b>4</b>	Optimize a SQL query construct considering time complexity.		
<b>5</b>	Write a PL/SQL block to specify constraints by accepting input from the user.		
<b>6</b>	Implementation of PL/SQL Procedure (IN, OUT, INOUT ) with Exception Handling.		
<b>7</b>	Implementation of PL/SQL Function.		
<b>8</b>	Implementation of PL/SQL Cursor.		
<b>9</b>	Implementation of PL/SQL Trigger, Packages.		
<b>10</b>	Implementation of NoSQL basic commands using Cassandra/Mongo DB.		
<b>11</b>	Implementation of Data Model in NoSQL.		
<b>12</b>	Implementation of Aggregation , Indexes in NoSQL.		
<b>13</b>	<b>MINI PROJECT</b> Database Connectivity with Front End Tools(Python/C/C++/JAVA)and Back End Tools(MySQL/SQLite/CASSANDRA/MONGO DB) For any problem selected, write the ER Diagram, apply ER mapping rules, normalize the relations, and follow the application development process. Make sure that the application should have five or more tables, at least one trigger and one stored procedure, using suitable frontend tool. Indicative areas include a) Inventory Control System. b) Material Requirement Processing. c) Hospital Management System. d) Railway Reservation System. e) Personal Information System. f) Web Based User Identification System. g) Timetable Management System. h) Hotel Management System i) Library Management System.		
		<b>Contact Hours</b>	: 60
		<b>Total Contact Hours</b>	: 90

## Safety Precautions

- Regular Backups: Ensure regular backups of all databases to prevent data loss.
- Secure Passwords: Use complex and unique passwords for database access and change them regularly.
- Antivirus Protection: Install and maintain updated antivirus software on all laboratory computers.
- Data Encryption: Encrypt sensitive data both in transit and at rest to protect against data breaches.
- Software Updates: Keep all database management software and operating systems up to date with the latest security patches.
- Environment Control: Ensure proper environmental controls, such as temperature and humidity, to protect hardware.
- Power Protection: Use Uninterruptible Power Supplies (UPS) to prevent data loss due to power outages.

### Dos:

- Regular Maintenance: Perform regular maintenance and updates on the database systems to ensure optimal performance.
- Documentation: Maintain comprehensive documentation of database structures, procedures, and security policies.
- Monitoring: Continuously monitor database performance and security to detect and respond to issues promptly.
- Training: Provide regular training to staff and students on database management best practices and security measures.
- Data Integrity: Implement and enforce data integrity constraints to maintain accurate and reliable data.

### Don'ts

- Sharing Passwords: Do not share passwords or leave them written down in accessible places.
- Ignoring Errors: Do not ignore system errors or warnings; investigate and resolve them promptly.
- Unauthorized Software: Do not install unauthorized software on lab computers as it may pose security risks.
- Neglecting Backups: Do not neglect regular backups; always have a backup strategy in place.
- Weak Passwords: Do not use weak or easily guessable passwords.
- Bypassing Security: Do not bypass or disable security features for convenience.
- Unverified Sources: Do not download or install software from unverified sources as they may contain malware.
- Public Wi-Fi: Avoid accessing the database from public Wi-Fi networks to prevent unauthorized interception of data.

## INDEX

Reg. No. : \_\_\_\_\_ Name : \_\_\_\_\_

Year : \_\_\_\_\_ Branch : \_\_\_\_\_ Sec : \_\_\_\_\_

S. No.	Date	Title	Page No.	Teacher's Signature / Remarks
0		Introduction to RDBMS – study		
1		Creating and Managing Tables		
2		Manipulating Data		
3		Working with Columns, Characters, and Rows		
4		Including Constraints		
5		Writing Basic SQL SELECT Statements		
6		Restricting and Sorting data		
7		Single Row Functions		
8		Displaying data from multiple tables		
9		Aggregating Data Using Group Functions		
10		Sub queries		
11		Using The Set Operators		
12		NULL Functions		
13		CREATING VIEWS		
14		Intro to Constraints; NOT NULL and UNIQUE Constraints		
15		Creating Views		
16		OTHER DATABASE OBJECTS		
17		Controlling User Access		
18		PROCEDURES AND FUNCTIONS PROCEDURES		
19		TRIGGER		
20		NoSQL-1		
		NoSQL-2		

**Ex. No: 0**

**Date:**

**Register No: 221701020**

**Name: Hemalatha R**

### **Definition of a Relational Database**

A relational database is a collection of relations or two-dimensional tables.

### **Terminologies Used in a Relational Database**

1. A single **ROW** or table representing all data required for a particular employee. Each row should be identified by a primary key which allows no duplicate rows.
2. A **COLUMN** or attribute containing the employee number which identifies a unique employee. Here Employee number is designated as a primary key ,must contain a value and must be unique.
3. A column may contain foreign key. Here Dept\_ID is a foreign key in employee table and it is a primary key in Department table.
4. A Field can be found at the intersection of a row and column. There can be only one value in it. Also it may have no value. This is called a null value.

EMP ID	FIRST NAME	LAST NAME	EMAIL
100	King	Steven	Sking
101	John	Smith	Jsmith
102	Neena	Bai	Neenba
103	Eex	De Haan	Ldehaan

### **Relational Database Properties**

#### **A relational database :**

- Can be accessed and modified by executing structured query language (SQL) statements.
- Contains a collection of tables with no physical pointers.
- Uses a set of operators

## **Relational Database Management Systems**

RDBMS refers to a relational database plus supporting software for managing users and processing SQL queries, performing backups/restores and associated tasks. (Relational Database Management System) Software for storing data using SQL (structured query language). A relational database uses SQL to store data in a series of tables that not only record existing relationships between data items, but which also permit the data to be joined in new relationships. SQL (pronounced 'sequel') is based on a system of algebra developed by E F Codd, an IBM scientist who first defined the relational model in 1970. Relational databases are optimized for storing transactional data, and the majority of modern business software applications therefore use an RDBMS as their data store. The leading RDBMS vendors are Oracle, IBM and Microsoft.

The first commercial RDBMS was the Multics Relational Data Store, first sold in 1978. INGRES, Oracle, Sybase, Inc., Microsoft Access, and Microsoft SQL Server are well-known database products and companies. Others include PostgreSQL, SQL/DS, and RDB. A relational database management system (RDBMS) is a program that lets you create, update, and administer a relational database. Most commercial RDBMS's use the Structured Query Language (SQL) to access the database, although SQL was invented after the development of the relational model and is not necessary for its use. The leading RDBMS products are Oracle, IBM's DB2 and Microsoft's SQL Server. Despite repeated challenges by competing technologies, as well as the claim by some experts that no current RDBMS has fully implemented relational principles, the majority of new corporate databases are still being created and managed with an RDBMS.

## **SQL Statements**

1. Data Retrieval(DR)
2. Data Manipulation Language(DML)
3. Data Definition Language(DDL)
4. Data Control Language(DCL)
5. Transaction Control Language(TCL)

TYPE	STATEMENT	DESCRIPTION
DR	SELECT	Retrieves the data from the database
DML	1.INSERT 2.UPDATE 3.DELETE 4.MERGE	Enter new rows, changes existing rows, removes unwanted rows from tables in the database respectively.
DDL	1.CREATE 2.ALTER 3.DROP 4.RENAME 5.TRUNCATE	Sets up, changes and removes data structures from tables.
TCL	1.COMMIT 2.ROLLBACK 3.SAVEPOINT	Manages the changes made by DML statements. Changes to the data can be grouped together into logical transactions.
DCL	1.GRANT 2.REVOKE	Gives or removes access rights to both the oracle database and the structures within it.

## DATA TYPES

### 1. Character Data types:

- Char – fixed length character string that can varies between 1-2000 bytes
- Varchar / Varchar2 – variable length character string, size ranges from 1-4000 bytes.it saves the disk space(only length of the entered value will be assigned as the size of column)
- Long - variable length character string, maximum size is 2 GB

**2. Number Data types :** Can store +ve,-ve,zero,fixed point, floating point with 38 precision.

- Number – {p=38,s=0}
- Number(p) - fixed point
- Number(p,s) –floating point (p=1 to 38,s= -84 to 127)

**3. Date Time Data type:** used to store date and time in the table.

- DB uses its own format of storing in fixed length of 7 bytes for century, date, month, year, hour, minutes, and seconds.
- Default data type is “dd-mon-yy”
- New Date time data types have been introduced. They are TIMESTAMP-Date with fractional seconds
- INTERVAL YEAR TO MONTH-stored as an interval of years and months
- INTERVAL DAY TO SECOND-stored as o interval of days to hour's minutes and seconds

**4. Raw Data type:** used to store byte oriented data like binary data and byte string.

**5. Other :**

- CLOB – stores character object with single byte character.
- BLOB – stores large binary objects such as graphics, video, sounds.
- BFILE – stores file pointers to the LOB's.

**Creating of Base Table and Managing Tables**

1. Create MY\_EMPLOYEE table with the following structure

NAME	NULL?	TYPE
ID	Not null	Number(4)
Last_name		Varchar(25)
First_name		Varchar(25)
Userid		Varchar(25)
Salary		Number(9,2)

Ans)

```
CREATE TABLE MY_EMPLOYEE (
    ID NUMBER(4) NOT NULL,
    Last_name VARCHAR2(25),
    First_name VARCHAR2(25),
    Userid VARCHAR2(25),
    Salary NUMBER(9,2)
);
```

2. Add the first and second rows data to MY\_EMPLOYEE table from the following sample data.

ID	Last_name	First_name	Userid	salary
1	Patel	Ralph	rpatel	895
2	Dancs	Betty	bdancs	860
3	Biri	Ben	bbiri	1100
4	Newman	Chad	Cnewman	750
5	Ropebur	Audrey	aropebur	1550

Ans)

```
INSERT INTO MY_EMPLOYEE (ID, Last_name, First_name, Userid, Salary)  
VALUES (1, 'Patel', 'Ralph', 'rpatel', 895);
```

```
INSERT INTO MY_EMPLOYEE (ID, Last_name, First_name, Userid, Salary)  
VALUES (2, 'Dancs', 'Betty', 'bdancs', 860);
```

3. Display the table with values.

Ans)

```
SELECT * FROM MY_EMPLOYEE;
```

4. Populate the next two rows of data from the sample data. Concatenate the first letter of the first\_name with the first seven characters of the last\_name to produce Userid.

Ans)

```
INSERT INTO MY_EMPLOYEE (ID, Last_name, First_name, Userid, Salary)  
VALUES (3, 'Johnson', 'Michael', SUBSTR('Michael', 1, 1) || SUBSTR('Johnson', 1, 7),  
60000.00);
```

```
INSERT INTO MY_EMPLOYEE (ID, Last_name, First_name, Userid, Salary)  
VALUES (4, 'Williams', 'Sarah', SUBSTR('Sarah', 1, 1) || SUBSTR('Williams', 1, 7),  
65000.00);
```

5. first\_name with the first seven characters of the last\_name to produce Userid.

Ans)

```
UPDATE MY_EMPLOYEE
```

```
SET Userid = SUBSTR(First_name, 1, 1) || SUBSTR>Last_name, 1, 7);
```

6. Delete Betty dancs from MY\_EMPLOYEE table.

Ans)

```
DELETE FROM MY_EMPLOYEE
```

```
WHERE First_name = 'Betty' AND Last_name = 'Dancs';
```

7. Empty the fourth row of the emp table.

Ans)

UPDATE MY\_EMPLOYEE

SET ID = NULL, Last\_name = NULL, First\_name = NULL, Userid = NULL, Salary =  
NULL

WHERE ID = (SELECT ID FROM (SELECT ID, ROWNUM AS RN FROM  
MY\_EMPLOYEE) WHERE RN = 4)

8. Make the data additions permanent.

Ans) COMMIT;

9. Change the last name of employee 3 to Drexler.

Ans)

UPDATE MY\_EMPLOYEE

SET Last\_name = 'Drexler'

WHERE ID = 3;

10. Change the salary to 1000 for all the employees with a salary less than 900.

Ans)

UPDATE MY\_EMPLOYEE

SET salary = 1000

WHERE salary < 900;

**Ex. No: P-1**

**Date:**

**Register No : 221701020**

**Name: Hemalatha R**

### **DATA MANIPULATIONS**

**Create the following table with the given structure**

#### **EMPLOYEES TABLE**

<b>NAME</b>	<b>NULL?</b>	<b>TYPE</b>
Employee_id	Not null	Number(6)
First_Name		Varchar(20)
Last_Name	Not null	Varchar(25)
Email	Not null	Varchar(25)
Phone_Number		Varchar(20)
Hire_date	Not null	Date
Job_id	Not null	Varchar(10)
Salary		Number(8,2)
Commission_pct		Number(2,2)
Manager_id		Number(6)
Department_id		Number(4)

Employee_ID	First_Name	Last_Name	Email	Phone_Number	Hire_Date	Job_ID	Salary	Commission_Pct	Manager_ID	Department_ID
1	John	Doe	johndoe@example.com	555-5555	1/1/2023	IT_PROG	5000	NULL	100	60
2	Jane	Austin	janeaustin@example.com	555-5556	2/1/2023	SA REP	6000	0.1	101	70
3	Mike	Smith	mikesmith@example.com	555-5557	3/1/2023	AD_VP	7000	0.15	102	80
4	Anna	Austin	anna.austin@example.com	555-5558	4/1/2023	FI_MGR	4800	0.2	103	60
5	Bob	Brown	bob.brown@example.com	555-5559	5/1/2023	MK_MAN	4500	NULL	104	70
6	Alice	Johnson	alice.johnson@example.com	555-5560	6/1/2023	HR REP	5500	0.05	100	60
7	Steve	Wilson	steve.wilson@example.com	555-5561	7/1/2023	IT_PROG	5200	NULL	100	80
8	Laura	White	laura.white@example.com	555-5562	8/1/2023	AD_ASST	4700	NULL	105	70
9	David	Harris	david.harris@example.com	555-5563	9/1/2023	MK REP	5100	0.1	101	60
10	Emma	Martinez	emma.martinez@example.com	555-5564	10/1/2023	SA_MAN	4900	NULL	104	80

- a) Find out the employee id, names, salaries of all the employees

**Ans)**

```
SELECT Employee_ID, CONCAT(First_Name, ' ', Last_Name) AS Full_Name, Salary
FROM Employees;
```

- b) List out the employees who works under manager 100

**Ans)** SELECT \*  
FROM Employees  
WHERE Manager\_ID = 100;

- c) Find the names of the employees who have a salary greater than or equal to 4800

**Ans)**  
SELECT CONCAT(First\_Name, ' ', Last\_Name) AS Full\_Name  
FROM Employees  
WHERE Salary >= 4800;

- d) List out the employees whose last name is 'AUSTIN'

**Ans)**  
SELECT \*  
FROM Employees  
WHERE Last\_Name = 'AUSTIN';

- e) Find the names of the employees who works in departments 60,70 and 80

**Ans)**  
SELECT CONCAT(First\_Name, ' ', Last\_Name) AS Full\_Name  
FROM Employees  
WHERE Department\_ID IN (60, 70, 80);

- f) Display the unique Manager\_Id.

**Ans)**  
SELECT DISTINCT Manager\_ID  
FROM Employees;

**Ex. No: 2**

**Date:**

**Register No: 221701020**

**Name: Hemalatha R**

### **Creating and Managing Tables**

#### **OBJECTIVE**

After the completion of this exercise, students should be able to do the following:

- Create tables
- Describing the data types that can be used when specifying column definition
- Alter table definitions
- Drop, rename, and truncate tables

#### **NAMING RULES**

Table names and column names:

- Must begin with a letter
- Must be 1-30 characters long
- Must contain only A-Z, a-z, 0-9, \_, \$, and #
- Must not duplicate the name of another object owned by the same user
- Must not be an oracle server reserve words
- 2 different tables should not have same name.
- Should specify a unique column name.
- Should specify proper data type along with width
- Can include “not null” condition when needed. By default it is ‘null’.

#### **The CREATE TABLE Statement**

**Table:** Basic unit of storage; composed of rows and columns

**Syntax: 1** Create table table\_name (column\_name1 data\_type (size)  
column\_name2 data\_type (size)....);

**Syntax: 2** Create table table\_name (column\_name1 data\_type (size) constraints,  
column\_name2 data\_type constraints ...);

### Example:

```
Create table employees ( employee_id number(6), first_name varchar2(20), ..job_id varchar2(10),
CONSTRAINT emp_emp_id_pk PRIMARY KEY (employee_id));
```

### Tables Used in this course

#### Creating a table by using a Sub query

##### **SYNTAX**

```
// CREATE TABLE table_name(column_name type(size)...);
```

```
Create table table_name as select column_name1,column_name2,.....column_namen from
table_name where predicate;
```

##### **AS Subquery**

Subquery is the select statement that defines the set of rows to be inserted into the new table.

### Example

```
Create table dept80 as select employee_id, last_name, salary*12 Annsal, hire_date
from employees where dept_id=80;
```

### The ALTER TABLE Statement

The ALTER statement is used to

- Add a new column
- Modify an existing column
- Define a default value to the new column
- Drop a column
- To include or drop integrity constraint.

##### **SYNTAX**

```
ALTER TABLE table_name ADD /MODIFY(Column_name type(size));
```

```
ALTER TABLE table_name DROP COLUMN (Column_nname);
```

```
ALTER TABLE ADD CONSTRAINT Constraint_name PRIMARY KEY (Colum_Name);
```

### Example:

```
Alter table dept80 add (jod_id varchar2(9));
```

```
Alter table dept80 modify (last_name varchar2(30));
```

Alter table dept80 drop column job\_id;

**NOTE:** Once the column is dropped it cannot be recovered.

### **DROPPING A TABLE**

- All data and structure in the table is deleted.
- Any pending transactions are committed.
- All indexes are dropped.
- Cannot roll back the drop table statement.

#### **Syntax:**

**Drop table *tablename*;**

#### **Example:**

Drop table dept80;

### **RENAMING A TABLE**

To rename a table or view.

#### **Syntax**

**RENAME old\_name to new\_name**

#### **Example:**

Rename dept to detail\_dept;

### **TRUNCATING A TABLE**

Removes all rows from the table.

Releases the storage space used by that table.

#### **Syntax**

**TRUNCATE TABLE *table\_name*;**

#### **Example:**

TRUNCATE TABLE copy\_emp;

### **Find the Solution for the following:**

Create the following tables with the given structure.

## **EMPLOYEES TABLE**

NAME	NULL?	TYPE
Employee_id	Not null	Number(6)
First_Name		Varchar(20)
Last_Name	Not null	Varchar(25)
Email	Not null	Varchar(25)
Phone_Number		Varchar(20)
Hire_date	Not null	Date
Job_id	Not null	Varchar(10)
Salary		Number(8,2)
Commission_pct		Number(2,2)
Manager_id		Number(6)
Department_id		Number(4)

## **DEPARTMENT TABLE**

NAME	NULL?	TYPE
Dept_id	Not null	Number(6)
Dept_name	Not null	Varchar(20)
Manager_id		Number(6)
Location_id		Number(4)

## **JOB\_GRADE TABLE**

NAME	NULL?	TYPE
Grade_level		Varchar(2)
Lowest_sal		Number
Highest_sal		Number

## **LOCATION TABLE**

NAME	NULL?	TYPE
Location_id	Not null	Number(4)
St_addr		Varchar(40)
Postal_code		Varchar(12)
City	Not null	Varchar(30)
State_province		Varchar(25)
Country_id		Char(2)

1. Create the DEPT table based on the DEPARTMENT following the table instance chart below. Confirm that the table is created.

<b>Column name</b>	ID	NAME
<b>Key Type</b>		
<b>Nulls/Unique</b>		
<b>FK table</b>		
<b>FK column</b>		
<b>Data Type</b>	Number	Varchar2
<b>Length</b>	7	25

```
CREATE TABLE DEPT (
    ID NUMBER(7) PRIMARY KEY,
    NAME VARCHAR2(25)
);
SELECT * FROM user_tables WHERE table_name = 'DEPT';
```

2. Create the EMP table based on the following instance chart. Confirm that the table is created.

<b>Column name</b>	ID	LAST_NAME	FIRST_NAME	DEPT_ID
<b>Key Type</b>				
<b>Nulls/Unique</b>				
<b>FK table</b>				
<b>FK column</b>				
<b>Data Type</b>	Number	Varchar2	Varchar2	Number
<b>Length</b>	7	25	25	7

```
CREATE TABLE EMP (
    ID NUMBER(7) PRIMARY KEY,
    LAST_NAME VARCHAR2(25),
    FIRST_NAME VARCHAR2(25),
    DEPT_ID NUMBER(7),
    CONSTRAINT fk_dept_id FOREIGN KEY (DEPT_ID) REFERENCES DEPT(ID) -- Foreign
key constraint
);
```

```
SELECT * FROM user_tables WHERE table_name = 'EMP';
```

3. Modify the EMP table to allow for longer employee last names. Confirm the modification.(Hint: Increase the size to 50)

```
ALTER TABLE EMP  
MODIFY LAST_NAME VARCHAR2(50);  
  
SELECT COLUMN_NAME, DATA_TYPE, DATA_LENGTH  
FROM USER_TAB_COLUMNS  
WHERE TABLE_NAME = 'EMP' AND COLUMN_NAME = 'LAST_NAME';
```

221701020

4. Create the EMPLOYEES2 table based on the structure of EMPLOYEES table. Include Only the Employee\_id, First\_name, Last\_name, Salary and Dept\_id coloumns. Name the columns Id, First\_name, Last\_name, salary and Dept\_id respectively.

```
CREATE TABLE EMPLOYEES2 AS  
SELECT  
    Employee_id AS Id,  
    First_name,  
    Last_name,  
    Salary,  
    Dept_id  
FROM EMPLOYEES;
```

5. Drop the EMP table.

```
SELECT * FROM user_tables WHERE table_name = 'EMP';
```

6. Rename the EMPLOYEES2 table as EMP.

```
SELECT * FROM user_tables WHERE table_name = 'EMP';
```

7. Add a comment on DEPT and EMP tables. Confirm the modification by describing the table.

```
DESCRIBE DEPT;
```

```
DESCRIBE EMP;
```

8. Drop the First\_name column from the EMP table and confirm it.

```
ALTER TABLE EMP  
DROP COLUMN FIRST_NAME;
```

**Ex. No: 2**

**Date:**

**Register No: 221701020**

**Name: Hemalatha R**

## **Manipulating Data**

### **OBJECTIVE**

After, the completion of this exercise the students will be able to do the following

- Describe each DML statement
- Insert rows into tables
- Update rows into table
- Delete rows from table
- Control Transactions

A DML statement is executed when you:

- Add new rows to a table
- Modify existing rows
- Removing existing rows

A transaction consists of a collection of DML statements that form a logical unit of work.

### **To Add a New Row**

INSERT Statement

#### **Syntax**

INSERT INTO table\_name VALUES (column1 values, column2 values, ..., column values);

#### **Example:**

INSERT INTO department (70, 'Public relations', 100,1700);

#### **Inserting rows with null values**

**Implicit Method:** (Omit the column)

INSERT INTO department VALUES (30,'purchasing');

**Explicit Method:** (Specify NULL keyword)

INSERT INTO department VALUES (100,'finance', NULL, NULL);

## Inserting Special Values

### Example:

Using SYSDATE

```
INSERT INTO employees VALUES (113,'louis', 'popp', 'lpopp','5151244567',SYSDATE,  
'ac_account', 6900, NULL, 205, 100);
```

## Inserting Specific Date Values

### Example:

```
INSERT INTO employees VALUES ( 114,'den', 'raphealy', 'drapheal','5151274561',  
TO_DATE('feb 3,1999','mon, dd ,yyyy'), 'ac_account', 11000,100,30);
```

## To Insert Multiple Rows

& is the placeholder for the variable value

### Example:

```
INSERT INTO department VALUES (&dept_id, &dept_name, &location);
```

## Copying Rows from another table

- Using Subquery

### Example:

```
INSER INTO sales_reps(id, name, salary, commission_pct)  
SELECT employee_id, Last_name, salary, commission_pct  
FROM employees WHERE jod_id LIKE '%REP');
```

## CHANGING DATA IN A TABLE

UPDATE Statement

### Syntax1: ( to update specific rows)

```
UPDATE table_name SET column=value WHERE condition;
```

### Syntax 2: (To updae all rows)

```
UPDATE table_name SET column=value;
```

### Updating columns with a subquery

```
UPDATE employees  
SET job_id= (SELECT job_id  
FROM employees  
WHERE employee_id=205)  
WHERE employee_id=114;
```

### REMOVING A ROW FROM A TABLE

#### DELETE STATEMENT

##### Syntax

```
DELETE FROM table_name WHERE conditions;
```

##### Example:

```
DELETE FROM department WHERE dept_name='finance';
```

### Find the Solution for the following:

1. Create MY\_EMPLOYEE table with the following structure

NAME	NULL?	TYPE
ID	Not null	Number(4)
Last_name		Varchar(25)
First_name		Varchar(25)
Userid		Varchar(25)
Salary		Number(9,2)

```
CREATE TABLE MY_EMPLOYEE (  
    ID NUMBER(4) NOT NULL,  
    Last_name VARCHAR2(25),  
    First_name VARCHAR2(25),  
    Userid VARCHAR2(25),  
    Salary NUMBER(9,2)  
)
```

2. Add the first and second rows data to MY\_EMPLOYEE table from the following sample data.

ID	Last_name	First_name	Userid	salary
1	Patel	Ralph	rpatel	895
2	Dancs	Betty	bdancs	860
3	Biri	Ben	bbiri	1100
4	Newman	Chad	Cnewman	750
5	Ropebur	Audrey	aropebur	1550

```
INSERT INTO MY_EMPLOYEE (ID, Last_name, First_name, Userid, Salary)
VALUES (1, 'Patel', 'Ralph', 'rpatel', 895);
```

```
INSERT INTO MY_EMPLOYEE (ID, Last_name, First_name, Userid, Salary)
VALUES (2, 'Dancs', 'Betty', 'bdancs', 860);
```

3. Display the table with values.

```
SELECT * FROM MY_EMPLOYEE;
```

4. Populate the next two rows of data from the sample data. Concatenate the first letter of the first\_name with the first seven characters of the last\_name to produce Userid.

```
INSERT INTO MY_EMPLOYEE (ID, Last_name, First_name, Userid, Salary)
VALUES (3, 'Biri', 'Ben', CONCAT(SUBSTR('Ben', 1, 1), SUBSTR('Biri', 1, 7)), 1100);
```

```
INSERT INTO MY_EMPLOYEE (ID, Last_name, First_name, Userid, Salary)
VALUES (4, 'Newman', 'Chad', CONCAT(SUBSTR('Chad', 1, 1), SUBSTR('Newman', 1, 7)), 750);
```

5. Make the data additions permanent.

```
COMMIT;
```

6. Change the last name of employee 3 to Drexler.

```
UPDATE MY_EMPLOYEE  
SET Last_name = 'Drexler'  
WHERE ID = 3;
```

7. Change the salary to 1000 for all the employees with a salary less than 900.


```
UPDATE MY_EMPLOYEE  
SET Salary = 1000  
WHERE Salary < 900;
```

8. Delete Betty dancs from MY\_EMPLOYEE table.

```
DELETE FROM MY_EMPLOYEE  
WHERE First_name = 'Betty' AND Last_name = 'Dancs';
```

9. Empty the fourth row of the emp table.

```
UPDATE EMP  
SET Last_name = NULL,  
First_name = NULL,  
Userid = NULL,  
Salary = NULL,  
Dept_id = NULL  
WHERE ID = 4;
```

**Working With Column, Characters and rows****Global Fast Foods Database Tables**

1. The manager of Global Fast Foods would like to send out coupons for the upcoming sale. He wants to send one coupon to each household. Create the SELECT statement that returns the customer last name and a mailing address.

```

SELECT Last_name, Mailing_address
FROM customers;
  
```

2. Each statement below has errors. Correct the errors and execute the query in Oracle Application Express.

a.

```
SELECT first name  
FROM f_staffs;
```

**Corrected SQL Query:**

sql

Copy code

```
SELECT first_name  
FROM f_staffs;
```

b.

```
SELECT first_name || " " || last_name AS "DJs on Demand Clients" FROM  
d_clients;
```

**Corrected SQL Query:**

sql

Copy code

```
SELECT first_name || ' ' || last_name AS "DJs on Demand Clients"  
FROM d_clients;
```

c.

```
SELECT DISTINCT f_order_lines  
FROM quantity;
```

**Corrected SQL Query:**

sql

Copy code

```
SELECT DISTINCT f_order_lines  
FROM quantity;
```

d.

```
SELECT order number  
FROM f_orders;
```

**Corrected SQL Query:**

sql

Copy code

```
SELECT "order number"  
FROM f_orders;
```

3. Sue, Bob, and Monique were the employees of the month. Using the f\_staffs table, create a SELECT statement to display the results as shown in the Super Star chart.

Super Star
*** Sue *** Sue ***
*** Bob *** Bob ***
*** Monique *** Monique ***

```
SELECT '*** ' || first_name || ' *** ' || first_name || ' ***' AS "Super Star"  
FROM f_staffs  
WHERE first_name IN ('Sue', 'Bob', 'Monique');
```

4. Which of the following is TRUE about the following query?

```
SELECT first_name, DISTINCT birthdate  
FROM f_staffs;
```

- a. Only two rows will be returned.
- b. Four rows will be returned.
- c. Only Fred 05-Jan-1988 and Lizzie 10-Nov-1987 will be returned.
- d. No rows will be returned.

No rows will be returned.

5. Global Fast Foods has decided to give all staff members a 5% raise. Prepare a report that presents the output as shown in the chart.

EMPLOYEE LAST NAME	CURRENT SALARY	SALARY WITH 5% RAISE

```
SELECT last_name AS "EMPLOYEE LAST NAME",
       salary AS "CURRENT SALARY",
       salary * 1.05 AS "SALARY WITH 5% RAISE"
  FROM f_staffs;
```

6. Create a query that will return the structure of the Oracle database EMPLOYEES table. Which columns are marked “nullable”? What does this mean?

```
SELECT column_name, data_type, nullable
  FROM user_tab_columns
 WHERE table_name = 'EMPLOYEES';
```

7. The owners of DJs on Demand would like a report of all items in their D\_CDs table with the following column headings: Inventory Item, CD Title, Music Producer, and Year Purchased. Prepare this report.

```
SELECT inventory_item AS "Inventory Item",
       cd_title AS "CD Title",
       music_producer AS "Music Producer",
       year_purchased AS "Year Purchased"
  FROM D_CDs;
```

8. True/False – The following SELECT statement executes successfully:

```
SELECT last_name, job_id, salary AS Sal FROM employees;
```

TRUE

9. True/False – The following SELECT statement executes successfully:

```
SELECT * FROM job_grades;
```

TRUE

10. There are four coding errors in this statement. Can you identify them?

```
SELECT employee_id, last_name sal x 12 ANNUAL SALARY FROM employees;
```

**Corrected SQL Query:**

sql

Copy code

```
SELECT employee_id, last_name, salary * 12 AS "ANNUAL SALARY"  
FROM employees;
```

11. In the arithmetic expression salary\*12 - 400, which operation will be evaluated first?

\* Will be evaluated first

12. Which of the following can be used in the SELECT statement to return all columns of data in the Global Fast Foods f\_staffs table?

- a. column names
  - b. \*
  - c. DISTINCT id
  - d. both a and b
- b. \*

13. Using SQL to choose the columns in a table uses which capability?

- a. selection
  - b. projection
  - c. partitioning
  - d. join
- a. selection

14. SELECT last\_name AS "Employee". The column heading in the query result will appear as:

- a. EMPLOYEE
  - b. employee
  - c. Employee
  - d. "Employee:
- c.Employee

15. Which expression below will produce the largest value?

- a. SELECT salary\*6 + 100
- b. SELECT salary\* (6 + 100)
- c. SELECT 6(salary+ 100)
- d. SELECT salary+6\*100

**b. SELECT salary \* (6 + 100)**

16. Which statement below will return a list of employees in the following format?

Mr./Ms. Steven King is an employee of our company.

- a. SELECT "Mr./Ms."||first\_name||'last\_name 'is an employee of our company.' AS "Employees"  
FROM employees;
- b. SELECT 'Mr./Ms. first\_name,last\_name ||' '||'is an employee of our company.' FROM employees;
- c. SELECT 'Mr./Ms. ||first\_name||' '||last\_name ||' '||'is an employee of our company.' AS "Employees"  
FROM employees ;
- d. SELECT Mr./Ms. ||first\_name||"||last\_name ||'"'||"is an employee of our company." AS  
"Employees" FROM employees

c. SELECT 'Mr./Ms. "'||first\_name||' '||last\_name ||' ''is an employee of our company.' AS "Employees"  
FROM employees;

17. Which is true about SQL statements?

- a. SQL statements are case-sensitive
- b. SQL clauses should not be written on separate lines.
- c. Keywords cannot be abbreviated or split across lines.
- d. SQL keywords are typically entered in lowercase; all other words in uppercase.
  
- c. keywords cannot be abbreviated or split across lines.

18. Which queries will return three columns each with UPPERCASE column headings?

- a. SELECT "Department\_id", "Last\_name", "First\_name"  
FROM employees;
- b. SELECT DEPARTMENT\_ID, LAST\_NAME,  
FIRST\_NAME FROM employees;
- c. SELECT department\_id, last\_name, first\_name AS UPPER CASE  
FROM employees
- d. SELECT department\_id, last\_name, first\_name  
FROM employees;

b. SELECT DEPARTMENT\_ID, LAST\_NAME, FIRST\_NAME FROM employees;

19. Which statement below will likely fail?

- a. SELCT \* FROM employees;
- b. Select \* FROM employees;
- c. SELECT \* FROM EMPLOYEES;
- d. SelecT\* FROM employees;
  
- a. SELCT \* FROM employees;

20. Click on the History link at the bottom of the SQL Commands window. Scroll or use the arrows at the bottom of the page to find the statement you wrote to solve problem 3 above. (The one with the column heading SuperStar). Click on the statement to load it back into the command window. Execute the command again, just to make sure it is the correct one that works. Once you know it works, click on the SAVE button in the top right corner of the SQL Commands window, and enter a name for your saved statement. Use your own initials and “\_superstar.sql”, so if your initials are CT then the filename will be CT\_superstar.sql.

Log out of OAE, and log in again immediately. Navigate back to the SQL Commands window, click the Saved SQL link at the bottom of the page and load your saved SQL statement into the Edit window. This is done by clicking on the script name. Edit the statement, to make it display + instead of \*. Run your amended statement and save it as initials\_superuser.sql.

#### **Step 1: Retrieve and Execute the Previous Statement**

1. **Click on the History link** at the bottom of the SQL Commands window.
2. **Scroll or use the arrows** at the bottom of the page to find the statement you wrote to solve problem 3 above (the one with the column heading "SuperStar").
3. **Click on the statement** to load it back into the command window.
4. **Execute the command** to ensure it's the correct one that works.

#### **Step 2: Save the Statement**

1. Once the statement executes correctly, click on the **SAVE** button in the top right corner of the SQL Commands window.
2. Enter a name for your saved statement. If your initials are **CT**, the filename will be CT\_superuser.sql.
3. **Click Save** to store the SQL statement.

#### **Step 3: Log Out and Log In Again**

1. **Log out of OAE**.
2. **Log in again immediately** with your credentials.

#### **Step 4: Load the Saved SQL Statement**

1. **Navigate back to the SQL Commands window** after logging in again.
2. **Click on the Saved SQL link** at the bottom of the page.
3. **Click the script name** (CT\_superuser.sql) to load your saved SQL statement into the Edit window.

#### **Step 5: Edit the Statement**

1. **Edit the statement** to display + instead of \*.
  - o If your original statement was something like:

sql

Copy code

```
SELECT first_name || '' || last_name AS SuperStar FROM f_staffs;
```

You would change the || concatenation to use + like this:

sql

Copy code

```
SELECT first_name + '' + last_name AS SuperStar FROM f_staffs;
```

2. **Run the amended statement** to verify it works correctly.

#### Step 6: Save the New Statement

1. **Save your amended statement** with a new name, following the same pattern as before:  
CT\_superplus.sql.
2. Click **Save** to store this new statement.

Now your query will display the concatenated values with the + sign instead of ||. You will have saved both versions (superstar.sql and superplus.sql).

**Ex. No: 4**

**Date:**

**Register No: 221701020**

**Name: Hemalatha R**

### **INCLUDING CONSTRAINTS**

#### **OBJECTIVE**

After the completion of this exercise the students should be able to do the following

- Describe the constraints
- Create and maintain the constraints

#### **What are Integrity constraints?**

- Constraints enforce rules at the table level.
- Constraints prevent the deletion of a table if there are dependencies

**The following types of integrity constraints are valid**

a) **Domain Integrity**

- ✓ NOT NULL
- ✓ CHECK

b) **Entity Integrity**

- ✓ UNIQUE
- ✓ PRIMARY KEY

c) **Referential Integrity**

- ✓ FOREIGN KEY

**Constraints can be created in either of two ways**

1. At the same time as the table is created
2. After the table has been created.

## **Defining Constraints**

Create table tablename (column\_name1 data\_type constraints, column\_name2 data\_type constraints ...);

### **Example:**

Create table employees ( employee\_id number(6), first\_name varchar2(20), ..job\_id varchar2 (10),  
CONSTRAINT emp\_emp\_id\_pk PRIMARY KEY (employee\_id));

## **Domain Integrity**

This constraint sets a range and any violations that takes place will prevent the user from performing the manipulation that caused the breach. It includes:

### **NOT NULL Constraint**

While creating tables, by default the rows can have null value. The enforcement of not null constraint in a table ensure that the table contains values.

### **Principle of null values:**

- Setting null value is appropriate when the actual value is unknown, or when a value would not be meaningful.
- A null value is not equivalent to a value of zero.
- A null value will always evaluate to null in any expression.
- When a column name is defined as not null, that column becomes a mandatory i.e., the user has to enter data into it.
- Not null Integrity constraint cannot be defined using the alter table command when the table contain rows.

### **Example**

CREATE TABLE employees (employee\_id number (6), last\_name varchar2(25) NOT NULL, salary number(8,2), commission\_pct number(2,2), hire\_date date constraint emp\_hire\_date\_nn NOT NULL'....);

## **CHECK**

Check constraint can be defined to allow only a particular range of values. When the manipulation violates this constraint, the record will be rejected. Check condition cannot contain sub queries.

```
CREATE TABLE employees (employee_id number(6), last_name varchar2(25) NOT NULL, salary number(8,2), commission_pct number(2,2), hire_date date constraint emp_hire_date_nn NOT NULL'...,CONSTRAINT emp_salary_mi CHECK(salary > 0));
```

## **Entity Integrity**

Maintains uniqueness in a record. An entity represents a table and each row of a table represents an instance of that entity. To identify each row in a table uniquely we need to use this constraint.

There are 2 entity constraints:

### **a) Unique key constraint**

It is used to ensure that information in the column for each record is unique, as with telephone or driver's license numbers. It prevents the duplication of value with rows of a specified column in a set of columns. A column defined with the constraint can allow null value.

If unique key constraint is defined in more than one column i.e., combination of columns cannot be specified. Maximum combination of columns that a composite unique key can contain is 16.

### **Example:**

```
CREATE TABLE employees (employee_id number(6), last_name varchar2(25) NOT NULL,email varchar2(25), salary number(8,2), commission_pct number(2,2), hire_date date constraint emp_hire_date_nn NOT NULL' COSTRAINT emp_email_uk UNIQUE(email));
```

## **PRIMARY KEY CONSTRAINT**

A primary key avoids duplication of rows and does not allow null values. Can be defined on one or more columns in a table and is used to uniquely identify each row in a table. These values should never be changed and should never be null.

A table should have only one primary key. If a primary key constraint is assigned to more than one column or combination of column is said to be composite primary key, which can contain 16 columns.

### **Example:**

```
CREATE TABLE employees (employee_id number(6) , last_name varchar2(25) NOT NULL,email varchar2(25), salary number(8,2), commission_pct number(2,2), hire_date date constraint emp_hire_date_nn NOT NULL, Constraint emp_id pk PRIMARY KEY (employee_id),CONSTRAINT emp_email_uk UNIQUE(email));
```

### **c) Referential Integrity**

It enforces relationship between tables. To establish parent-child relationship between 2 tables having a common column definition, we make use of this constraint. To implement this, we should define the column in the parent table as primary key and same column in the child table as foreign key referring to the corresponding parent entry.

#### **Foreign key**

A column or combination of column included in the definition of referential integrity, which would refer to a referenced key.

#### **Referenced key**

It is a unique or primary key upon which is defined on a column belonging to the parent table.

Keywords:

**FOREIGN KEY:** Defines the column in the child table at the table level constraint.

**REFERENCES:** Identifies the table and column in the parent table.

**ON DELETE CASCADE:** Deletes the dependent rows in the child table when a row in the parent table is deleted.

**ON DELETE SET NULL:** converts dependent foreign key values to null when the parent value is removed.

```
CREATE TABLE employees (employee_id number(6) , last_name varchar2(25) NOT NULL,email varchar2(25), salary number(8,2), commission_pct number(2,2), hire_date date constraint emp_hire_date_nn NOT NULL, Constraint emp_id pk PRIMARY KEY (employee_id),CONSTRAINT emp_email_uk UNIQUE(email),CONSTRAINT emp_dept_fk FOREIGN KEY (department_id) references deparments(dept_id));
```

## **ADDING A CONSTRAINT**

Use the ALTER to

- Add or Drop a constraint, but not modify the structure
- Enable or Disable the constraints
- Add a not null constraint by using the Modify clause

### **Syntax**

ALTER TABLE table name ADD CONSTRAINT Cons\_name type(column name);

### **Example:**

ALTER TABLE employees ADD CONSTRAINT emp\_manager\_fk FOREIGN KEY  
(manager\_id) REFERENCES employees (employee\_id);

## **DROPPING A CONSTRAINT**

### **Example:**

ALTER TABLE employees DROP CONSTRAINT emp\_manager\_fk;

### **CASCADE IN DROP**

- The CASCADE option of the DROP clause causes any dependent constraints also to be dropped.

### **Syntax**

ALTER TABLE departments DROP PRIMARY KEY|UNIQUE (column)| CONSTRAINT  
constraint \_name CASCADE;

## **DISABLING CONSTRAINTS**

- Execute the DISABLE clause of the ALTER TABLE statement to deactivate an integrity constraint
- Apply the CASCADE option to disable dependent integrity constraints.

### **Example**

```
ALTER TABLE employees DISABLE CONSTRAINT emp_emp_id_pk CASCADE;
```

### **ENABLING CONSTRAINTS**

- Activate an integrity constraint currently disabled in the table definition by using the ENABLE clause.

### **Example**

```
ALTER TABLE employees ENABLE CONSTRAINT emp_emp_id_pk CASCADE;
```

### **CASCADING CONSTRAINTS**

The CASCADE CONSTRAINTS clause is used along with the DROP column clause.

It drops all referential integrity constraints that refer to the primary and unique keys defined on the dropped Columns.

This clause also drops all multicolumn constraints defined on the dropped column.

### **Example:**

Assume table TEST1 with the following structure

```
CREATE TABLE test1 ( pk number PRIMARY KEY, fk number, col1 number,col2 number,  
CONSTRAINT fk_constraint FOREIGN KEY(fk) references test1, CONSTRAINT ck1 CHECK  
(pk>0 and col1>0), CONSTRAINT ck2 CHECK (col2>0));
```

An error is returned for the following statements

```
ALTER TABLE test1 DROP (pk);
```

```
ALTER TABLE test1 DROP (col1);
```

The above statement can be written with CASCADE CONSTRAINT

```
ALTER TABLE test1 DROP(pk) CASCADE CONSTRAINTS;
```

(OR)

```
ALTER TABLE test1 DROP(pk, fk, col1) CASCADE CONSTRAINTS;
```

## **VIEWING CONSTRAINTS**

Query the USER\_CONSTRAINTS table to view all the constraints definition and names.

### **Example:**

```
SELECT constraint_name, constraint_type, search_condition FROM user_constraints  
WHERE table_name='employees';
```

### **Viewing the columns associated with constraints**

```
SELECT constraint_name, constraint_type, FROM user_cons_columns  
WHERE table_name='employees';
```

### **Find the Solution for the following:**

1. Add a table-level PRIMARY KEY constraint to the EMP table on the ID column. The constraint should be named at creation. Name the constraint my\_emp\_id\_pk.

```
ALTER TABLE EMP  
ADD CONSTRAINT my_emp_id_pk PRIMARY KEY (ID);
```

2. Create a PRIMAY KEY constraint to the DEPT table using the ID colum. The constraint should be named at creation. Name the constraint my\_dept\_id\_pk.

```
ALTER TABLE DEPT  
ADD CONSTRAINT my_dept_id_pk PRIMARY KEY (ID);
```

3. Add a column DEPT\_ID to the EMP table. Add a foreign key reference on the EMP table that ensures that the employee is not assigned to nonexistent deparment. Name the constraint my\_emp\_dept\_id\_fk.

-- Step 1: Add the DEPT\_ID column to the EMP table

```
ALTER TABLE EMP  
ADD DEPT_ID NUMBER(7);
```

-- Step 2: Add the foreign key constraint

```
ALTER TABLE EMP  
ADD CONSTRAINT my_emp_dept_id_fk  
FOREIGN KEY (DEPT_ID) REFERENCES DEPT (ID);
```

4. Modify the EMP table. Add a COMMISSION column of NUMBER data type, precision 2, scale 2. Add a constraint to the commission column that ensures that a commission value is greater than zero.

-- Step 1: Add the COMMISSION column to the EMP table with data type NUMBER(2,2)

```
ALTER TABLE EMP
```

```
ADD COMMISSION NUMBER(2,2);
```

-- Step 2: Add a check constraint to ensure that the COMMISSION is greater than zero

```
ALTER TABLE EMP
```

```
ADD CONSTRAINT check_commission_positive  
CHECK (COMMISSION > 0);
```

- 5.

-- Step 1: Add the COMMISSION column to the EMP table

```
ALTER TABLE EMP
```

```
ADD COMMISSION NUMBER(2,2);
```

-- Step 2: Add a check constraint to ensure that the COMMISSION is greater than zero

```
ALTER TABLE EMP
```

```
ADD CONSTRAINT check_commission_positive  
CHECK (COMMISSION > 0);
```

**Ex. No: 5**

**Date:**

**Register No: 221701020**

**Name: Hemalatha R**

### **Writing Basic SQL SELECT Statements**

#### **OBJECTIVES**

After the completion of this exercise, the students will be able to do the following:

- List the capabilities of SQL SELECT Statement
- Execute a basic SELECT statement

#### **Capabilities of SQL SELECT statement**

A SELECT statement retrieves information from the database. Using a select statement, we can perform

- ✓ Projection: To choose the columns in a table
- ✓ Selection: To choose the rows in a table
- ✓ Joining: To bring together the data that is stored in different tables

#### **Basic SELECT Statement**

##### **Syntax**

```
SELECT *|DISTINCT Column_name| alias  
`     FROM table_name;
```

##### **NOTE:**

DISTINCT—Suppr  
ess the duplicates.

Alias—gives selected columns different headings.

##### **Example: 1**

```
SELECT * FROM departments;
```

##### **Example: 2**

```
SELECT location_id, department_id FROM departments;
```

## **Writing SQL Statements**

- SQL statements are not case sensitive
- SQL statements can be on one or more lines.
- Keywords cannot be abbreviated or split across lines
- Clauses are usually placed on separate lines
- Indents are used to enhance readability

## **Using Arithmetic Expressions**

Basic Arithmetic operators like \*, /, +, - can be used

### **Example:1**

```
SELECT last_name, salary, salary+300 FROM employees;
```

### **Example:2**

```
SELECT last_name, salary, 12*salary+100 FROM employees;
```

The statement is not same as

```
SELECT last_name, salary, 12*(salary+100) FROM employees;
```

### **Example:3**

```
SELECT last_name, job_id, salary, commission_pct FROM employees;
```

### **Example:4**

```
SELECT last_name, job_id, salary, 12*salary*commission_pct FROM employees;
```

## **Using Column Alias**

- To rename a column heading with or without AS keyword.

### **Example:1**

```
SELECT last_name AS Name  
FROM employees;
```

### **Example: 2**

```
SELECT last_name "Name" salary*12 "Annual Salary"  
FROM employees;
```

### **Concatenation Operator**

- Concatenates columns or character strings to other columns
- Represented by two vertical bars (||)
- Creates a resultant column that is a character expression

#### **Example:**

```
SELECT last_name||job_id AS "EMPLOYEES JOB" FROM employees;
```

### **Using Literal Character String**

- A literal is a character, a number, or a date included in the SELECT list.
- Date and character literal values must be enclosed within single quotation marks.

#### **Example:**

```
SELECT last_name||'is a'||job_id AS "EMPLOYEES JOB" FROM employees;
```

### **Eliminating Duplicate Rows**

- Using DISTINCT keyword.

#### **Example:**

```
SELECT DISTINCT department_id FROM employees;
```

### **Displaying Table Structure**

- Using DESC keyword.

### **Syntax**

```
DESC table_name;
```

#### **Example:**

```
DESC employees;
```

### **Find the Solution for the following:**

#### **True OR False**

1. The following statement executes successfully.

#### **Identify the Errors**

```
SELECT employee_id, last_name  
sal*12 ANNUAL SALARY  
FROM employees;
```

#### **Queries**

**Ans:** SELECT employee\_id, last\_name, sal\*12 AS "ANNUAL SALARY" FROM employees;

2. Show the structure of departments the table. Select all the data from it.

**Ans:** DESC departments;

3. Create a query to display the last name, job code, hire date, and employee number for each employee, with employee number appearing first.

**Ans:** SELECT employee\_id, last\_name, job\_id, hire\_date FROM employees;

4. Provide an alias STARTDATE for the hire date.

**Ans:** SELECT employee\_id, last\_name, job\_id, hire\_date AS STARTDATE FROM employees;

5. Create a query to display unique job codes from the employee table.

**Ans:** SELECT DISTINCT job\_id FROM employees;

6. Display the last name concatenated with the job ID , separated by a comma and space, and name the column EMPLOYEE and TITLE.

**Ans:** SELECT last\_name || ',' || job\_id AS "EMPLOYEE AND TITLE" FROM employees;

7. Create a query to display all the data from the employees table. Separate each column by a comma. Name the column THE\_OUTPUT.

**Ans:** SELECT employee\_id || ',' || last\_name || ',' || job\_id || ',' || salary || ',' || commission\_pct || ',' || hire\_date AS THE\_OUTPUT  
FROM employees;

221701020

**Ex. No: P-2**

**Date:**

**Register No: 221701020**

**Name: Hemalatha R**

---

### **COMPARISON OPERATORS**

1. Who are the partners of DJs on Demand who do not get an authorized expense amount?

**Ans:** SELECT partner\_name  
FROM partners  
WHERE company = 'DJs on Demand' AND authorized\_expense IS NULL;

2. Select all the Oracle database employees whose last names end with "s". Change the heading of the column to read Possible Candidates.

**Ans:** SELECT last\_name AS "Possible Candidates"  
FROM employees  
WHERE company = 'Oracle' AND last\_name LIKE '%s';

3. Which statement(s) are valid?
  - a. WHERE quantity <> NULL;
  - b. WHERE quantity = NULL;
  - c. WHERE quantity IS NULL;
  - d. WHERE quantity != NULL;

Ans: c

4. Write a SQL statement that lists the songs in the DJs on Demand inventory that are type code 77, 12, or 1.

**Ans:** SELECT song\_name  
FROM inventory  
WHERE type\_code IN (77, 12, 1);

## Logical Comparisons and Precedence Rules

1. Execute the two queries below. Why do these nearly identical statements produce two different results? Name the difference and explain why.

```
SELECT code, description  
FROM d_themes  
WHERE code >200 AND description IN('Tropical', 'Football', 'Carnival');  
SELECT code, description  
FROM d_themes  
WHERE code >200 OR description IN('Tropical', 'Football', 'Carnival');
```

**Ans:** SELECT code, description  
FROM d\_themes  
WHERE code > 200 AND description IN ('Tropical', 'Football', 'Carnival');

```
SELECT code, description  
FROM d_themes  
WHERE code > 200 OR description IN ('Tropical', 'Football', 'Carnival');
```

2. Display the last names of all Global Fast Foods employees who have “e” and “i” in their last names.

**Ans:** SELECT last\_name  
FROM employees  
WHERE company = 'Global Fast Foods' AND last\_name LIKE '%e%' AND last\_name LIKE '%i%';

3. "I need to know who the Global Fast Foods employees are that make more than \$6.50/hour and their position is not order taker."

**Ans:** SELECT employee\_name  
FROM employees  
WHERE company = 'Global Fast Foods' AND hourly\_wage > 6.50 AND position <> 'order taker';

4. Using the employees table, write a query to display all employees whose last names start with "D" and have "a" and "e" anywhere in their last name.

**Ans:** SELECT last\_name  
FROM employees  
WHERE last\_name LIKE 'D%' AND last\_name LIKE '%a%' AND last\_name LIKE '%e%';

5. In which venues did DJs on Demand have events that were not in private homes?

**Ans:** SELECT venue\_name  
FROM events  
WHERE company = 'DJs on Demand' AND venue\_type <> 'private home';

6. Which list of operators is in the correct order from highest precedence to lowest precedence?  
a. AND, NOT, OR  
b. NOT, OR, AND  
c. NOT, AND, OR

**Ans:** c

**For questions 7 and 8, write SQL statements that will produce the desired output.**

7. Who am I?

I was hired by Oracle after May 1998 but before June of 1999. My salary is less than \$8000 per month, and I have an “en” in my last name.

**Ans:** SELECT employee\_name  
FROM employees  
WHERE company = 'Oracle'  
AND hire\_date > '1998-05-31'  
AND hire\_date < '1999-06-01'  
AND salary < 8000  
AND last\_name LIKE '%en%';

8. What's my email address?

Because I have been working for Oracle since the beginning of 1996, I make more than \$9000 per month. Because I make so much money, I don't get a commission

**Ans:** SELECT email  
FROM employees  
WHERE company = 'Oracle'  
AND hire\_date >= '1996-01-01'  
AND salary > 9000  
AND commission\_pct IS NULL

**Ex. No: 6**

**Date:**

**Register No: 221701020**

**Name: Hemalatha R**

### **Restricting and Sorting data**

After the completion of this exercise, the students will be able to do the following:

- Limit the rows retrieved by the queries
- Sort the rows retrieved by the queries
- 

#### **Limits the Rows selected**

- Using WHERE clause
- Alias cannot be used in WHERE clause

#### **Syntax**

SELECT-----

FROM-----

WHERE condition;

#### **Example:**

```
SELECT employee_id, last_name, job_id, department_id FROM employees WHERE  
department_id=90;
```

#### **Character strings and Dates**

Character strings and date values are enclosed in single quotation marks.

Character values are case sensitive and date values are format sensitive.

### Example:

```
SELECT employee_id, last_name, job_id, department_id FROM employees  
WHERE last_name='WHALEN';
```

### Comparison Conditions

All relational operators can be used. (=, >, >=, <, <= ,<>,!=)

### Example:

```
SELECT last_name, salary  
FROM employees  
WHERE salary<=3000;
```

### **Other comparison conditions**

Operator	Meaning
BETWEEN ...AND...	Between two values
IN	Match any of a list of values
LIKE	Match a character pattern
IS NULL	Is a null values

### Example:1

```
SELECT last_name, salary  
FROM employees  
WHERE salary BETWEEN 2500 AND 3500;
```

### Example:2

```
SELECT employee_id, last_name, salary , manager_id  
FROM employees  
WHERE manager_id IN (101, 100,201);
```

**Example:3**

- Use the LIKE condition to perform wildcard searches of valid string values.
- Two symbols can be used to construct the search string
- % denotes zero or more characters
- \_ denotes one character

```
SELECT first_name, salary  
FROM employees  
WHERE first_name LIKE '%s';
```

**Example:4**

```
SELECT last_name, salary  
FROM employees  
WHERE last_name LIKE '_o%';
```

**Example:5**

**ESCAPE option**-To have an exact match for the actual % and\_ characters  
To search for the string that contain 'SA\_'

```
SELECT employee_id, first_name, salary, job_id  
FROM employees  
WHERE job_id LIKE '%sa\_%'ESCAPE'\';
```

**Test for NULL**

- Using IS NULL operator

### **Example:**

```
SELECT employee_id, last_name, salary , manager_id  
FROM employees  
WHERE manager_id IS NULL;
```

### **Logical Conditions**

All logical operators can be used.( AND,OR,NOT)

### **Example:1**

```
SELECT employee_id, last_name, salary , job_id  
FROM employees  
WHERE salary>=10000  
AND job_id LIKE '%MAN%';
```

### **Example:2**

```
SELECT employee_id, last_name, salary , job_id  
FROM employees  
WHERE salary>=10000  
OR job_id LIKE '%MAN%';
```

### **Example:3**

```
SELECT employee_id, last_name, salary , job_id  
FROM employees  
WHERE job_id NOT IN ('it_prog', st_clerk', sa_rep');
```

### **Rules of Precedence**

<b>Order Evaluated</b>	<b>Operator</b>
1	Arithmetic
2	Concatenation
3	Comparison
4	IS [NOT] NULL, LIKE, [NOT] IN
5	[NOT] BETWEEN
6	Logical NOT
7	Logical AND
8	Logical OR

### Example:1

```
SELECT employee_id, last_name, salary , job_id
FROM employees
WHERE job_id ='sa_rep'
OR job_id='ad_pres'
AND salary>15000;
```

### Example:2

```
SELECT employee_id, last_name, salary , job_id
FROM employees
WHERE (job_id ='sa_rep'
OR job_id='ad_pres')
AND salary>15000;
```

## Sorting the rows

Using ORDER BY Clause

**ASC**-Ascending Order,Default

**DESC**-Descending order

### Example:1

```
SELECT last_name, salary , job_id,department_id,hire_date  
FROM employees  
ORDER BY hire_date;
```

### Example:2

```
SELECT last_name, salary , job_id,department_id,hire_date  
FROM employees  
ORDER BY hire_date DESC;
```

### Example:3

#### Sorting by column alias

```
SELECT last_name, salary*12 annsal , job_id,department_id,hire_date  
FROM employees  
ORDER BY annsal;
```

### Example:4

#### Sorting by Multiple columns

```
SELECT last_name, salary , job_id,department_id,hire_date  
FROM employees  
ORDER BY department_id, salary DESC;
```

**Find the Solution for the following:**

1. Create a query to display the last name and salary of employees earning more than 12000.

**Ans:** SELECT last\_name, salary  
FROM employees  
WHERE salary > 12000;

2. Create a query to display the employee last name and department number for employee number 176.

**Ans:** SELECT last\_name, department\_id  
FROM employees  
WHERE employee\_id = 176;

3. Create a query to display the last name and salary of employees whose salary is not in the range of 5000 and 12000. (hints: not between )

**Ans:** SELECT last\_name, salary  
FROM employees  
WHERE salary NOT BETWEEN 5000 AND 12000;

4. Display the employee last name, job ID, and start date of employees hired between February 20,1998 and May 1,1998.order the query in ascending order by start date.(hints: between)

**Ans:** SELECT last\_name, job\_id, hire\_date  
FROM employees  
WHERE hire\_date BETWEEN '1998-02-20' AND '1998-05-01'  
ORDER BY hire\_date ASC;

5. Display the last name and department number of all employees in departments 20 and 50 in alphabetical order by name.(hints: in, orderby)

**Ans:** SELECT last\_name, department\_id  
FROM employees  
WHERE department\_id IN (20, 50)  
ORDER BY last\_name ASC;

6. Display the last name and salary of all employees who earn between 5000 and 12000 and are in departments 20 and 50 in alphabetical order by name. Label the columns EMPLOYEE, MONTHLY SALARY respectively.(hints: between, in)

**Ans:** SELECT last\_name AS "EMPLOYEE", salary AS "MONTHLY SALARY"  
FROM employees  
WHERE salary BETWEEN 5000 AND 12000  
AND department\_id IN (20, 50)  
ORDER BY last\_name ASC;

7. Display the last name and hire date of every employee who was hired in 1994.(hints: like)

**Ans:** SELECT last\_name, hire\_date  
FROM employees  
WHERE hire\_date LIKE '1994%';

8. Display the last name and job title of all employees who do not have a manager.(hints: is null)

**Ans:** SELECT last\_name, job\_id  
FROM employees  
WHERE manager\_id IS NULL;

9. Display the last name, salary, and commission for all employees who earn commissions.  
Sort data in descending order of salary and commissions.(hints: is not null, order by)

**Ans:** SELECT last\_name, salary, commission\_pct  
FROM employees  
WHERE commission\_pct IS NOT NULL  
ORDER BY salary DESC, commission\_pct DESC;

10. Display the last name of all employees where the third letter of the name is *a*.(hints: like)

**Ans:** SELECT last\_name  
FROM employees  
WHERE last\_name LIKE '\_\_a%';

11. Display the last name of all employees who have an *a* and an *e* in their last name.(hints: like)

**Ans:** SELECT last\_name  
FROM employees  
WHERE last\_name LIKE '%a%' AND last\_name LIKE '%e%';

12. Display the last name and job and salary for all employees whose job is sales representative or stock clerk and whose salary is not equal to 2500 ,3500 or 7000.(hints: in, not in)

**Ans:** SELECT last\_name, job\_id, salary  
FROM employees  
WHERE job\_id IN ('SA\_REP', 'ST\_CLERK')  
AND salary NOT IN (2500, 3500, 7000);

13. Display the last name, salary, and commission for all employees whose commission amount is 20%. (hints: use predicate logic)

**Ans:** SELECT last\_name, salary, commission\_pct  
FROM employees  
WHERE commission\_pct = 0.20;

221701020

## **Sorting Rows**

1. In the example below, assign the employee\_id column the alias of "Number." Complete the SQL statement to order the result set by the column alias.

```
SELECT employee_id, first_name, last_name FROM employees;
```

**Ans:** SELECT employee\_id, first\_name, last\_name FROM employees;  
SELECT employee\_id AS "Number", first\_name, last\_name  
FROM employees  
ORDER BY "Number";

2. Create a query that will return all the DJs on Demand CD titles ordered by year with titles in alphabetical order by year.

1. **Ans:** SELECT title, year  
FROM djs\_on\_demand  
ORDER BY year ASC, title ASC;

3. Order the DJs on Demand songs by descending title. Use the alias "Our Collection" for the song title.

**Ans:** SELECT title AS "Our Collection"  
FROM djs\_on\_demand  
ORDER BY "Our Collection" DESC;

4. Write a SQL statement using the ORDER BY clause that could retrieve the information needed.

**Ans:** SELECT employee\_id, first\_name, last\_name, salary  
FROM employees ORDER BY last\_name ASC, salary DESC;

221701020

**Ex. No:** 7

**Date:**

**Register No:** 221701020

**Name:** Hemalatha R

### **Single Row Functions**

#### **Objective**

After the completion of this exercise, the students will be able to do the following:

- Describe various types of functions available in SQL.
- Use character, number and date functions in SELECT statement.
- Describe the use of conversion functions.

#### **Single row functions:**

Manipulate data items.

Accept arguments and return one value.

Act on each row returned.

Return one result per row.

May modify the data type.

Can be nested.

Accept arguments which can be a column or an expression


#### **Syntax**

Function\_name(arg1,...argn)

An argument can be one of the following

- ✓ User-supplied constant
- ✓ Variable value
- ✓ Column name

✓ Expression



- Character Functions: Accept character input and can return both character and number values.
- Number functions: Accept numeric input and return numeric values.
- Date Functions: Operate on values of the DATE data type.
- Conversion Functions: Convert a value from one type to another.

### Character Functions

#### Character Functions

##### Case-manipulation functions

1. Lower
2. Upper
3. Initcap

##### Character-manipulation functions

1. Concat
2. Substr
3. Length
4. Instr

5. Lpad/Rpad

6. Trim

7. Repalce

Function	Purpose
lower(column(expr))	Converts alpha character values to lowercase
upper(column(expr))	Converts alpha character values to uppercase
initcap(column(expr))	Converts alpha character values the to uppercase for the first letter of each word, all other letters in lowercase
concat(column1(expr), column2(expr))	Concatenates the first character to the second character
substr(column(expr),m,n)	Returns specified characters from character value starting at character position m, n characters long
length(column(expr))	Returns the number of characters in the expression
instr(column(expr),'string',m,n)	Returns the numeric position of a named string
lpad(column(expr, n,'string'))	Pads the character value right-justified to a total width of n character positions
rpad(column(expr, 'string',m,n))	Pads the character value left-justified to a total width of n character positions
trim(leading/trailing/both, trim_character FROM trim_source)	Enables you to trim heading or string. trailing or both from a character
replace(text, search_string, replacement_string)	

**Example:**

lower('SQL Course') □ sql course

upper('SQL Course') □ SQL COURSE

initcap('SQL Course') □ Sql Course

SELECT ‘The job id for’|| upper(last\_name)||’is’||lower(job\_id) AS “EMPLOYEE DETAILS”  
FROM employees;

SELECT employee\_id, last\_name, department\_id  
FROM employees  
WHERE LOWER(last\_name)=’higgins’;

Function	Result
CONCAT(‘hello’, ‘world’)	helloworld
Substr(‘helloworld’,1,5)	Hello
Length(‘helloworld’)	10
Instr(‘helloworld’, ’w’)	6
Lpad(salary,10,’*’)	*****24000
Rpad(salary,10,’*’)	24000*****
Trim(‘h’ FROM ‘helloworld’)	elloworld

Command	Query	Output
initcap(char);	<i>select initcap(“hello”) from dual;</i>	Hello
lower (char);	<i>select lower (‘HELLO’) from dual;</i>	Hello
upper (char);	<i>select upper (‘hello’) from dual;</i>	HELLO
ltrim (char,[set]);	<i>select ltrim (‘cseit’, ‘cse’) from dual;</i>	IT

rtrim (char,[set]);	<i>select rtrim ('cseit', 'it') from dual;</i>	CSE
replace (char,search string, replace string);	<i>select replace ('jack and jue', 'j', 'bl') from dual;</i>	black and blue
substr (char,m,n);	<i>select substr ('information', 3, 4) from dual;</i>	form

### Example:

SELECT employee\_id, CONCAT(first\_name,last\_name) NAME , job\_id, LENGTH(last\_name),  
 INSTR(last\_name,'a') "contains 'a'?"  
 FROM employees WHERE SUBSTR(job\_id,4)= 'ERP';

### NUMBER FUNCTIONS

Function	Purpose
round(column/expr, n)	Rounds the value to specified decimal
trunc(column/expr,n)	Truncates value to specified decimal
mod(m,n)	Returns remainder of division

### Example

Function	Result
round(45.926,2)	45.93
trunc(45.926,2)	45.92
mod(1600,300)	100

SELECT ROUND(45.923,2), ROUND(45.923,0), ROUND(45.923,-1) FROM dual;

**NOTE:** Dual is a dummy table you can use to view results from functions and calculations.

```
SELECT TRUNC(45.923,2), TRUNC(45.923), TRUNC(45.923,-2) FROM dual;
```

```
SELECT last_name,salary,MOD(salary,5000) FROM employees WHERE job_id='sa_rep';
```

### **Working with Dates**

The Oracle database stores dates in an internal numeric format: century, year, month, day, hours, minutes, and seconds.

- The default date display format is DD-MON-RR.
  - Enables you to store 21st-century dates in the 20th century by specifying only the last two digits of the year
  - Enables you to store 20th-century dates in the 21st century in the same way

### **Example**

```
SELECT last_name, hire_date FROM employees WHERE hire_date < '01-FEB-88';
```

### **Working with Dates**

SYSDATE is a function that returns:

- Date
- Time

### **Example**

**Display the current date using the DUAL table.**

```
SELECT SYSDATE FROM DUAL;
```

### **Arithmetic with Dates**

- Add or subtract a number to or from a date for a resultant date value.
- Subtract two dates to find the number of days between those dates.
- Add hours to a date by dividing the number of hours by 24.

### **Arithmetic with Dates**

Because the database stores dates as numbers, you can perform calculations using arithmetic

Operators such as addition and subtraction. You can add and subtract number constants as well as dates.

You can perform the following operations:

Operation	Result	Description
date + number	Date	Adds a number of days to a date
date - number	Date	Subtracts a number of days from a date
date - date	Number of days	Subtracts one date from another
date + number/24	Date	Adds a number of hours to a date

### Example

```
SELECT last_name, (SYSDATE-hire_date)/7 AS WEEKS  
FROM employees  
WHERE department_id = 90;
```

### Date Functions

Function	Result
MONTHS_BETWEEN	Number of months between two dates
ADD_MONTHS	Add calendar months to date
NEXT_DAY	Next day of the date specified
LAST_DAY	Last day of the month
ROUND	Round date
TRUNC	Truncate date

### Date Functions

Date functions operate on Oracle dates. All date functions return a value of DATE data type except MONTHS\_BETWEEN, which returns a numeric value.

- MONTHS\_BETWEEN(date1, date2)::: Finds the number of months between date1 and date2. The result can be positive or negative. If date1 is later than date2, the result is positive; if date1 is earlier than date2, the result is negative. The noninteger part of the result represents a portion of the month.

- ADD\_MONTHS(date, n)::: Adds n number of calendar months to date. The value of n must be an integer and can be negative.
- NEXT\_DAY(date, 'char')::: Finds the date of the next specified day of the week ('char') following date. The value of char may be a number representing a day or a character string.
- LAST\_DAY(date)::: Finds the date of the last day of the month that contains date
- ROUND(date[,fmt'])::: Returns date rounded to the unit that is specified by the format model fmt. If the format model fmt is omitted, date is rounded to the nearest day.
- TRUNC(date[,fmt'])::: Returns date with the time portion of the day truncated to the unit that is specified by the format model fmt. If the format model fmt is omitted, date is truncated to the nearest day.

### Using Date Functions

Function	Result
MONTHS_BETWEEN ('01-SEP-95', '11-JAN-94')	19.6774194
ADD_MONTHS ('11-JAN-94', 6)	'11-JUL-94'
NEXT_DAY ('01-SEP-95', 'FRIDAY')	'08-SEP-95'
LAST_DAY ('01-FEB-95')	'28-FEB-95'

### Example

Display the employee number, hire date, number of months employed, sixmonth review date, first Friday after hire date, and last day of the hire month for all employees who have been employed for fewer than 70 months.

```


SELECT employee_id, hire_date, MONTHS_BETWEEN (SYSDATE, hire_date)
TENURE, ADD_MONTHS (hire_date, 6) REVIEW, NEXT_DAY (hire_date, 'FRIDAY'),
LAST_DAY(hire_date)
FROM employees
WHERE MONTHS_BETWEEN (SYSDATE, hire_date) < 70;

```

## Conversion Functions

This covers the following topics:

- Writing a query that displays the current date
- Creating queries that require the use of numeric, character, and date functions
- Performing calculations of years and months of service for an employee



## Implicit Data Type Conversion

For assignments, the Oracle server can automatically convert the following:


From	To
VARCHAR2 or CHAR	NUMBER
VARCHAR2 or CHAR	DATE
NUMBER	VARCHAR2
DATE	VARCHAR2

For example, the expression `hire_date > '01-JAN-90'` results in the implicit conversion from the string `'01-JAN-90'` to a date.

For expression evaluation, the Oracle Server can automatically convert the following:

From	To
VARCHAR2 or CHAR	NUMBER
VARCHAR2 or CHAR	DATE

## Explicit Data Type Conversion



SQL provides three functions to convert a value from one data type to another:

**Example:**

**Using the TO\_CHAR Function with Dates**


TO\_CHAR(date, 'format\_model')

**The format model:**

- Must be enclosed by single quotation marks
- Is case-sensitive
- Can include any valid date format element
- Has an fm element to remove padded blanks or suppress leading zeros
- Is separated from the date value by a comma

```
SELECT employee_id, TO_CHAR(hire_date, 'MM/YY') Month_Hired
FROM employees WHERE last_name = 'Higgins';
```

## Elements of the Date Format Model



## Sample Format Elements of Valid Date

Element	Description
SCC or CC	Century; server prefixes B.C. date with -
Years in dates YYYY or SYYYY	Year; server prefixes B.C. date with -
YYY or YY or Y	Last three, two, or one digits of year
Y,YYY	Year with comma in this position
IYYY, IYY, IY, I	Four-, three-, two-, or one-digit year based on the ISO standard
SYEAR or YEAR	Year spelled out; server prefixes B.C. date with -
BC or AD	Indicates B.C. or A.D. year
B.C. or A.D.	Indicates B.C. or A.D. year using periods
Q	Quarter of year
MM	Month: two-digit value
MONTH	Name of month padded with blanks to length of nine characters
MON	Name of month, three-letter abbreviation
RM	Roman numeral month
WW or W	Week of year or month
DDD or DD or D	Day of year, month, or week
DAY	Name of day padded with blanks to a length of nine characters
DY	Name of day; three-letter abbreviation
J	Julian day; the number of days since December 31, 4713 B.C.

## Date Format Elements: Time Formats

Use the formats that are listed in the following tables to display time information and literals and to change numerals to spelled numbers.

Element	Description
AM or PM	Meridian indicator
A.M. or P.M.	Meridian indicator with periods
HH or HH12 or HH24	Hour of day, or hour (1–12), or hour (0–23)
MI	Minute (0–59)
SS	Second (0–59)
SSSS	Seconds past midnight (0–86399)

#### Other Formats

Element	Description
/ . ,	Punctuation is reproduced in the result.
“of the”	Quoted string is reproduced in the result.

#### Specifying Suffixes to Influence Number Display

Element	Description
TH	Ordinal number (for example, DDTH for 4TH)
SP	Spelled-out number (for example, DDSP for FOUR)
SPTH or THSP	Spelled-out ordinal numbers (for example, DDSPTH for FOURTH)

#### Example

```
SELECT last_name,  
TO_CHAR(hire_date, 'fmDD Month YYYY') AS HIREDATE  
FROM employees;
```

Modify example to display the dates in a format that appears as “Seventeenth of June 1987 12:00:00 AM.”

```
SELECT last_name,  
TO_CHAR (hire_date, 'fmDdspth "of" Month YYYY fmHH:MI:SS AM') HIREDATE  
FROM employees;
```

#### Using the TO\_CHAR Function with Numbers

TO\_CHAR(number, 'format\_model')

These are some of the format elements that you can use with the TO\_CHAR function to display a number value as a character:

Element	Result
9	Represents a number
0	Forces a zero to be displayed
\$	Places a floating dollar sign
L	Uses the floating local currency symbol
.	Prints a decimal point
,	Prints a comma as thousands indicator

## Number Format Elements

If you are converting a number to the character data type, you can use the following format elements:

Element	Description	Example	Result
9	Numeric position (number of 9s determine display width)	999999	1234
0	Display leading zeros	099999	001234
\$	Floating dollar sign	\$999999	\$1234
L	Floating local currency symbol	L999999	FF1234
D	Returns in the specified position the decimal character. The default is a period (.).	99D99	99.99
.	Decimal point in position specified	999999.99	1234.00
G	Returns the group separator in the specified position. You can specify multiple group separators in a number format model.	9,999	9G999
,	Comma in position specified	999,999	1,234
MI	Minus signs to right (negative values)	999999MI	1234-
PR	Parenthesize negative numbers	999999PR	<1234>
EEEE	Scientific notation (format must specify four Es)	99.999EEEE	1.234E+03
U	Returns in the specified position the "Euro" (or other) dual currency	U9999	€1234
V	Multiply by 10 <i>n</i> times ( <i>n</i> = number of 9s after V)	9999V99	123400
S	Returns the negative or positive value	S9999	-1234 or +1234
B	Display zero values as blank, not 0	B9999.99	1234.00

```
SELECT TO_CHAR(salary, '$99,999.00') SALARY
```

```
FROM employees
```

```
WHERE last_name = 'Ernst';
```

## Using the TO\_NUMBER and TO\_DATE Functions

- Convert a character string to a number format using the TO\_NUMBER function:

```
TO_NUMBER(char[, 'format_model'])
```

- Convert a character string to a date format using the TO\_DATE function:

```
TO_DATE(char[, 'format_model'])
```

- These functions have an fx modifier. This modifier specifies the exact matching for the character argument and date format model of a TO\_DATE function.

The fx modifier specifies exact matching for the character argument and date format model of a TO\_DATE function:

- Punctuation and quoted text in the character argument must exactly match (except for case) the corresponding parts of the format model.

- The character argument cannot have extra blanks. Without fx, Oracle ignores extra blanks.

- Numeric data in the character argument must have the same number of digits as the corresponding element in the format model. Without fx, numbers in the character argument can omit leading zeros.

```
SELECT last_name, hire_date  
FROM employees  
WHERE hire_date = TO_DATE('May 24, 1999', 'fxMonth DD, YYYY');
```

**Find the Solution for the following:**

1. Write a query to display the current date. Label the column Date.

**Ans)**

```
SELECT CURRENT_DATE AS Date;
```

2. The HR department needs a report to display the employee number, last name, salary, and increased by 15.5% (expressed as a whole number) for each employee. Label the column New Salary.

**Ans)**

```
SELECT  
employee_number,  
last_name,  
salary,  
ROUND(salary * 1.155) AS "New Salary"  
FROM employees;
```

3. Modify your query lab\_03\_02.sql to add a column that subtracts the old salary from the new salary. Label the column Increase.

**Ans)**

```
SELECT  
employee_number,  
last_name,  
salary,  
ROUND(salary * 1.155) AS "New Salary",  
ROUND(salary * 1.155) - salary AS "Increase"  
FROM employees;
```

4. Write a query that displays the last name (with the first letter uppercase and all other letters lowercase) and the length of the last name for all employees whose name starts with the letters J, A, or M. Give each column an appropriate label. Sort the results by the employees' last names.

**Ans)**

```
SELECT  
    INITCAP(last_name) AS "Formatted Last Name",  
    LENGTH(last_name) AS "Length of Last Name"  
FROM employees  
WHERE last_name LIKE 'J%'  
    OR last_name LIKE 'A%'  
    OR last_name LIKE 'M%'  
ORDER BY last_name;
```

5. Rewrite the query so that the user is prompted to enter a letter that starts the last name. For example, if the user enters H when prompted for a letter, then the output should show all employees whose last name starts with the letter H.

**Ans)**

```
ACCEPT letter CHAR PROMPT 'Enter the starting letter for the last name: ';
```

```
SELECT  
    INITCAP(last_name) AS "Formatted Last Name",  
    LENGTH(last_name) AS "Length of Last Name"  
FROM employees  
WHERE last_name LIKE :letter || '%'  
ORDER BY last_name;
```

6. The HR department wants to find the length of employment for each employee. For each employee, display the last name and calculate the number of months between today and the date on which the employee was hired. Label the column MONTHS\_WORKED. Order your results by the number of months employed. Round the number of months up to the closest whole number.

**Ans)**

SELECT

```
last_name,  
CEIL(TIMESTAMPDIFF(MONTH, hire_date, CURDATE())) AS MONTHS_WORKED  
FROM employees  
ORDER BY MONTHS_WORKED;
```

7. Create a report that produces the following for each employee:

<employee last name> earns <salary> monthly but wants <3 times salary>. Label the column Dream Salaries.

**Ans)**

SELECT

```
last_name,  
salary,  
salary * 3 AS "Dream Salary"  
FROM employees;
```

8. Create a query to display the last name and salary for all employees. Format the salary to be 15 characters long, left-padded with the \$ symbol. Label the column SALARY.

**Ans)**

SELECT

```
last_name,  
LPAD('$' || salary, 15, '$') AS SALARY  
FROM employees;
```

9. Display each employee's last name, hire date, and salary review date, which is the first Monday after six months of service. Label the column REVIEW. Format the dates to appear in the format similar to "Monday, the Thirty-First of July, 2000."

**Ans)**

SELECT

```
last_name,  
hire_date,  
TO_CHAR(  
    NEXT_DAY(ADD_MONTHS(hire_date, 6), 'MONDAY'),  
    'FMDay, the FMDDth of FMMM, YYYY'  
) AS REVIEW  
FROM employees;
```

10. Display the last name, hire date, and day of the week on which the employee started. Label the column DAY. Order the results by the day of the week, starting with Monday.

**Ans)**

SELECT

```
last_name,  
hire_date,  
TO_CHAR(hire_date, 'Day') AS DAY  
FROM employees  
ORDER BY  
CASE TO_CHAR(hire_date, 'D')  
WHEN '1' THEN 1 -- Sunday  
WHEN '2' THEN 2 -- Monday  
WHEN '3' THEN 3 -- Tuesday  
WHEN '4' THEN 4 -- Wednesday  
WHEN '5' THEN 5 -- Thursday  
WHEN '6' THEN 6 -- Friday  
WHEN '7' THEN 7 -- Saturday  
END;
```

## **Introduction to Functions**

1. For each task, choose whether a single-row or multiple row function would be most appropriate:

- a. Showing all of the email addresses in upper case letters

**Ans)**

**sql**

**Copy code**

**SELECT UPPER(email) AS upper\_email FROM employees;**

- b. Determining the average salary for the employees in the sales department

**Ans)**

**sql**

**Copy code**

**SELECT AVG(salary) AS avg\_salary\_sales FROM employees WHERE department = 'Sales';**

- c. Showing hire dates with the month spelled out (*September 1, 2004*)

**Ans)**

**sql**

**Copy code**

**SELECT TO\_CHAR(hire\_date, 'Month DD, YYYY') AS formatted\_hire\_date FROM employees;**

- d. Finding out the employees in each department that had the most seniority (the earliest hire date)

**Ans)**

**sql**

**Copy code**

**SELECT department, MIN(hire\_date) AS most\_senior\_hire\_date**

**FROM employees**

**GROUP BY department;**

- e. Displaying the employees' salaries rounded to the hundreds place

**Ans)**

**sql**

**Copy code**

```
SELECT last_name, ROUND(salary, -2) AS rounded_salary FROM employees;
```

- f. Substituting zeros for null values when displaying employee commissions.

**Ans)**

**sql**

**Copy code**

```
SELECT last_name, NVL(commission, 0) AS commission FROM employees;
```

2. The most common multiple-row functions are: AVG, COUNT, MAX, MIN, and SUM. Give your own definition for each of these functions.

**Ans)**

Here are queries using **AVG**, **COUNT**, **MAX**, **MIN**, and **SUM** on the salary column:

- AVG (Average)** Calculates the average salary:

**sql**

**Copy code**

```
SELECT AVG(salary) AS average_salary FROM employees;
```

- COUNT** Counts the total number of employees:

**sql**

**Copy code**

```
SELECT COUNT(*) AS total_employees FROM employees;
```

- MAX (Maximum)** Finds the highest salary:

**sql**

**Copy code**

```
SELECT MAX(salary) AS max_salary FROM employees;
```

- MIN (Minimum)** Finds the lowest salary:

sql

Copy code

```
SELECT MIN(salary) AS min_salary FROM employees;
```

**SUM (Total)** Calculates the total of all salaries:

sql

Copy code

```
SELECT SUM(salary) AS total_salary FROM employees;
```

3. Test your definitions by substituting each of the multiple-row functions in this query.

```
SELECT FUNCTION(salary)
```

```
FROM employees
```

Write out each query and its results.

## Case and Character Manipulation

1. Using the three separate words “Oracle,” “Internet,” and “Academy,” use one command to produce the following output:

The Best Class Oracle Internet Academy

sql

Copy code

```
SELECT 'The Best Class ' || 'Oracle' || '' || 'Internet' || '' || 'Academy' AS result FROM DUAL;
```

2. Use the string “Oracle Internet Academy” to produce the following output:

The Net net

sql

Copy code

```
SELECT 'The ' ||  
SUBSTR('Oracle  
Internet Academy',  
8, 3) || ' ' ||  
LOWER(SUBSTR('  
Oracle Internet  
Academy', 8, 3))  
AS result FROM  
DUAL;
```

3. What is the length of the string “Oracle Internet Academy”?

```
SELECT LENGTH('Oracle Internet Academy') AS string_length FROM dual;
```

4. What's the position of “I” in “Oracle Internet Academy”?

```
SELECT INSTR('Oracle Internet Academy', 'I') AS position FROM dual;
```

5. Starting with the string “Oracle Internet Academy”, pad the string to create  
\*\*\*\*Oracle\*\*\*\*Internet\*\*\*\*Academy\*\*\*\*

```
SELECT CONCAT('****', 'Oracle', '****', 'Internet', '****', 'Academy', '****') AS padded_string FROM  
dual;
```

## Number Functions

1. Display Oracle database employee last\_name and salary for employee\_ids between 100 and 102.
2. Include a third column that divides each salary by 1.55 and rounds the result to two decimal places.

```
SELECT
    last_name,
    salary,
    ROUND(salary / 1.55, 2) AS adjusted_salary
FROM employees
WHERE employee_id BETWEEN 100 AND 102;
```

2. Display employee last\_name and salary for those employees who work in department 80. Give each of them a raise of 5.333% and truncate the result to two decimal places.

```
SELECT
    last_name,
    salary,
    TRUNC(salary * 1.05333, 2) AS new_salary
FROM employees
WHERE department_id = 80;
```

3. Use a MOD number function to determine whether 38873 is an even number or an odd number.

```
SELECT
    CASE
        WHEN MOD(38873, 2) = 0 THEN 'Even'
        ELSE 'Odd'
    END AS number_type;
```

4. Use the DUAL table to process the following numbers:

845.553 - round to one decimal place

30695.348 - round to two decimal places

30695.348 - round to -2 decimal Places 2.3454

- truncate the 454 from the decimal place

SELECT

```
ROUND(845.553, 1) AS  
rounded_1_decimal,  
ROUND(30695.348, 2) AS  
rounded_2_decimal,  
ROUND(30695.348, -2) AS  
rounded_minus_2_decimal,  
TRUNC(2.3454, 3) AS  
truncated_3_decimal  
FROM dual;
```

5. Divide each employee's salary by 3. Display only those employees' last names and salaries who earn a salary that is a multiple of 3.

SELECT

```
last_name,  
salary / 3 AS salary_divided_by_3  
FROM employees  
WHERE MOD(salary, 3) = 0;
```

6. Divide 34 by 8. Show only the remainder of the division. Name the output as EXAMPLE.

SELECT MOD(34, 8) AS EXAMPLE;

7. How would you like your paycheck – rounded or truncated? What if your paycheck was calculated to be \$565.784 for the week, but you noticed that it was issued for \$565.78. The loss of .004 cent would probably make very little difference to you. However, what if this was done to a thousand people, a 100,000 people, or a million people! Would it make a difference then? How much difference?

While the difference of **0.004 cents** may seem negligible for one individual, when applied to a large number of people, the total difference becomes much more significant. **In large-scale systems**, such as payroll for many employees, even small rounding or truncating discrepancies can accumulate into substantial amounts of money.

**Ex. No: 8**

**Date:**

**Register No: 221701020**

**Name: Hemalatha R**

---

### **Displaying data from multiple tables**

#### **Objective**

After the completion of this exercise, the students will be able to do the following:

- Write SELECT statements to access data from more than one table using equality and nonequality joins
- View data that generally does not meet a join condition by using outer joins
- Join a table to itself by using a self join

Sometimes you need to use data from more than one table.

#### **Cartesian Products**

- A Cartesian product is formed when:
  - A join condition is omitted
  - A join condition is invalid
  - All rows in the first table are joined to all rows in the second table
- To avoid a Cartesian product, always include a valid join condition in a WHERE clause.

A Cartesian product tends to generate a large number of rows, and the result is rarely useful. You should always include a valid join condition in a WHERE clause, unless you have a specific need to combine all rows from all tables.

Cartesian products are useful for some tests when you need to generate a large number of rows to simulate a reasonable amount of data.

#### **Example:**

To displays employee last name and department name from the EMPLOYEES and DEPARTMENTS tables.

SELECT last\_name, department\_name dept\_name

```
FROM employees, departments;
```

### **Types of Joins**

- Equijoin
- Non-equijoin
- Outer join
- Self join
- Cross joins
- Natural joins
- Using clause
- Full or two sided outer joins
- Arbitrary join conditions for outer joins

### **Joining Tables Using Oracle Syntax**

```
SELECT table1.column, table2.column  
FROM table1, table2  
WHERE table1.column1 = table2.column2;
```

Write the join condition in the WHERE clause.

- Prefix the column name with the table name when the same column name appears in more than one table.

### **Guidelines**

- When writing a SELECT statement that joins tables, precede the column name with the table name for clarity and to enhance database access.
- If the same column name appears in more than one table, the column name must be prefixed with the table name.
- To join n tables together, you need a minimum of n-1 join conditions. For example, to join four tables, a minimum of three joins is required. This rule may not apply if your table has a concatenated primary key, in which case more than one column is required to uniquely identify each row

## **What is an Equijoin?**

To determine an employee's department name, you compare the value in the DEPARTMENT\_ID column in the EMPLOYEES table with the DEPARTMENT\_ID values in the DEPARTMENTS table.

The relationship between the EMPLOYEES and DEPARTMENTS tables is an equijoin—that is, values in the DEPARTMENT\_ID column on both tables must be equal. Frequently, this type of join involves primary and foreign key complements.

Note: Equijoins are also called simple joins or inner joins

```
SELECT employees.employee_id, employees.last_name, employees.department_id,  
departments.department_id, departments.location_id  
FROM employees, departments  
WHERE employees.department_id = departments.department_id;
```

## **Additional Search Conditions**

### **Using the AND Operator**

#### **Example:**

To display employee Matos' department number and department name, you need an additional condition in the WHERE clause.

```
SELECT last_name, employees.department_id,  
department_name  
FROM employees, departments  
WHERE employees.department_id = departments.department_id AND last_name = 'Matos';
```

### **Qualifying Ambiguous**

#### **Column Names**

- Use table prefixes to qualify column names that are in multiple tables.
- Improve performance by using table prefixes.
- Distinguish columns that have identical names but reside in different tables by using column aliases.

## **Using Table Aliases**

- Simplify queries by using table aliases.
- Improve performance by using table prefixes

### **Example:**

```
SELECT e.employee_id, e.last_name, e.department_id,  
d.department_id, d.location_id  
FROM employees e , departments d  
WHERE e.department_id = d.department_id;
```

## **Joining More than Two Tables**

To join n tables together, you need a minimum of n-1 join conditions. For example, to join three tables, a minimum of two joins is required.

### **Example:**

To display the last name, the department name, and the city for each employee, you have to join the EMPLOYEES, DEPARTMENTS, and LOCATIONS tables.

```
SELECT e.last_name, d.department_name, l.city  
FROM employees e, departments d, locations l  
WHERE e.department_id = d.department_id  
AND d.location_id = l.location_id;
```

## **Non-Equijoins**

A non-equijoin is a join condition containing something other than an equality operator. The relationship between the EMPLOYEES table and the JOB\_GRADES table has an example of a non-equijoin. A relationship between the two tables is that the SALARY column in the EMPLOYEES table must be between the values in the LOWEST\_SALARY and HIGHEST\_SALARY columns of the JOB\_GRADES table. The relationship is obtained using an operator other than equals (=).

### **Example:**

```
SELECT e.last_name, e.salary, j.grade_level  
FROM employees e, job_grades j  
WHERE e.salary  
BETWEEN j.lowest_sal AND j.highest_sal;
```

## **Outer Joins**

### **Syntax**

- You use an outer join to also see rows that do not meet the join condition.
- The Outer join operator is the plus sign (+).

```
SELECT table1.column, table2.column  
FROM table1, table2  
WHERE table1.column(+) = table2.column;  
SELECT table1.column, table2.column  
FROM table1, table2  
WHERE table1.column = table2.column(+);
```

The missing rows can be returned if an outer join operator is used in the join condition. The operator is a plus sign enclosed in parentheses (+), and it is placed on the “side” of the join that is deficient in information. This operator has the effect of creating one or more null rows, to which one or more rows from the nondeficient table can be joined.

### **Example:**

```
SELECT e.last_name, e.department_id, d.department_name  
FROM employees e, departments d  
WHERE e.department_id(+) = d.department_id ;
```

## **Outer Join Restrictions**

- The outer join operator can appear on only one side of the expression—the side that has information missing. It returns those rows from one table that have no direct match in the other table.
- A condition involving an outer join cannot use the IN operator or be linked to another condition by the OR operator

### **Self Join**

Sometimes you need to join a table to itself.

#### **Example:**

To find the name of each employee's manager, you need to join the EMPLOYEES table to itself, or perform a self join.

```
SELECT worker.last_name || ' works for '
|| manager.last_name
FROM employees worker, employees manager
WHERE worker.manager_id = manager.employee_id ;
```

#### **Use a join to query data from more than one table.**

```
SELECT table1.column, table2.column
FROM table1
[CROSS JOIN table2] |
[NATURAL JOIN table2] |
[JOIN table2 USING (column_name)] |
[JOIN table2
ON(table1.column_name = table2.column_name)] |
[LEFT|RIGHT|FULL OUTER JOIN table2
ON (table1.column_name = table2.column_name)];
```

In the syntax:

table1.column Denotes the table and column from which data is retrieved

CROSS JOIN Returns a Cartesian product from the two tables

NATURAL JOIN Joins two tables based on the same column name

JOIN table USING column\_name Performs an equijoin based on the column name

JOIN table ON table1.column\_name Performs an equijoin based on the condition in the ON clause

= table2.column\_name

## **LEFT/RIGHT/FULL OUTER**

### **Creating Cross Joins**

- The CROSS JOIN clause produces the crossproduct of two tables.
- This is the same as a Cartesian product between the two tables.

#### **Example:**

```
SELECT last_name, department_name  
FROM employees  
CROSS JOIN departments ;  
  
SELECT last_name, department_name  
FROM employees, departments;
```

### **Creating Natural Joins**

- The NATURAL JOIN clause is based on all columns in the two tables that have the same name.
- It selects rows from the two tables that have equal values in all matched columns.
- If the columns having the same names have different data types, an error is returned.

#### **Example:**

```
SELECT department_id, department_name,  
location_id, city  
FROM departments  
NATURAL JOIN locations ;
```

LOCATIONS table is joined to the DEPARTMENT table by the LOCATION\_ID column, which is the only column of the same name in both tables. If other common columns were present, the join would have used them all.

**Example:**

```
SELECT department_id, department_name,  
location_id, city  
FROM departments  
NATURAL JOIN locations  
WHERE department_id IN (20, 50);
```

**Creating Joins with the USING Clause**

- If several columns have the same names but the data types do not match, the NATURAL JOIN clause can be modified with the USING clause to specify the columns that should be used for an equijoin.
- Use the USING clause to match only one column when more than one column matches.
- Do not use a table name or alias in the referenced columns.
- The NATURAL JOIN and USING clauses are mutually exclusive.

**Example:**

```
SELECT l.city, d.department_name  
FROM locations l JOIN departments d USING (location_id)  
WHERE location_id = 1400;
```

EXAMPLE:

```
SELECT e.employee_id, e.last_name, d.location_id  
FROM employees e JOIN departments d  
USING (department_id) ;
```

**Creating Joins with the ON Clause**

- The join condition for the natural join is basically an equijoin of all columns with the same name.
- To specify arbitrary conditions or specify columns to join, the ON clause is used.

- The join condition is separated from other searchconditions.
- The ON clause makes code easy to understand.

**Example:**

```
SELECT e.employee_id, e.last_name, e.department_id,  
d.department_id, d.location_id  
FROM employees e JOIN departments d  
ON (e.department_id = d.department_id);
```

EXAMPLE:

```
SELECT e.last_name emp, m.last_name mgr  
FROM employees e JOIN employees m  
ON (e.manager_id = m.employee_id);  
INNER Versus OUTER Joins
```

- A join between two tables that returns the results of the inner join as well as unmatched rows left (or right) tables is a left (or right) outer join.
- A join between two tables that returns the results of an inner join as well as the results of a left and right join is a full outer join.

**LEFT OUTER JOIN**

**Example:**

```
SELECT e.last_name, e.department_id, d.department_name  
FROM employees e  
LEFT OUTER JOIN departments d  
ON (e.department_id = d.department_id);
```

### Example of LEFT OUTER JOIN

This query retrieves all rows in the EMPLOYEES table, which is the left table even if there is no match in the DEPARTMENTS table.

This query was completed in earlier releases as follows:

```
SELECT e.last_name, e.department_id, d.department_name  
FROM employees e, departments d  
WHERE d.department_id (+) = e.department_id;
```

### RIGHT OUTER JOIN

#### Example:

```
SELECT e.last_name, e.department_id, d.department_name  
FROM employees e  
RIGHT OUTER JOIN departments d  
ON (e.department_id = d.department_id);
```

This query retrieves all rows in the DEPARTMENTS table, which is the right table even if there is no match in the EMPLOYEES table.

This query was completed in earlier releases as follows:

```
SELECT e.last_name, e.department_id, d.department_name  
FROM employees e, departments d  
WHERE d.department_id = e.department_id (+);
```

## **FULL OUTER JOIN**

### **Example:**

```
SELECT e.last_name, e.department_id, d.department_name  
FROM employees e  
FULL OUTER JOIN departments d  
ON (e.department_id = d.department_id);
```

This query retrieves all rows in the EMPLOYEES table, even if there is no match in the DEPARTMENTS table. It also retrieves all rows in the DEPARTMENTS table, even if there is no match in the EMPLOYEES table.

### **Find the Solution for the following:**

1. Write a query to display the last name, department number, and department name for all employees.

```
SELECT e.last_name, e.department_id, d.department_name FROM employees e JOIN  
departments d ON e.department_id = d.department_id;
```

2. Create a unique listing of all jobs that are in department 80. Include the location of the department in the output.

```
SELECT DISTINCT e.job_id, l.location_id, l.city FROM employees e JOIN departments d ON  
e.department_id = d.department_id JOIN locations l ON d.location_id = l.location_id WHERE  
e.department_id = 80;
```

3. Write a query to display the employee last name, department name, location ID, and city of all employees who earn a commission

```
SELECT e.last_name, d.department_name, d.location_id, l.city FROM employees e JOIN departments d ON e.department_id = d.department_id JOIN locations l ON d.location_id = l.location_id WHERE e.commission_pct IS NOT NULL;
```

4. Display the employee last name and department name for all employees who have an a(lowercase) in their last names.

```
SELECT e.last_name, d.department_name FROM employees e JOIN departments d ON e.department_id = d.department_id WHERE e.last_name LIKE '%a%';
```

5. Write a query to display the last name, job, department number, and department name for all employees who work in Toronto.

```
SELECT e.last_name, e.job_id, e.department_id, d.department_name FROM employees e JOIN departments d ON e.department_id = d.department_id JOIN locations l ON d.location_id = l.location_id WHERE l.city = 'Toronto';
```

6. Display the employee last name and employee number along with their manager's last name and manager number. Label the columns Employee, Emp#, Manager, and Mgr#, Respectively

```
SELECT e.last_name AS Employee, e.employee_id AS Emp#, m.last_name AS Manager, m.employee_id AS Mgr# FROM employees e LEFT JOIN employees m ON e.manager_id = m.employee_id;
```

7. Modify lab4\_6.sql to display all employees including King, who has no manager. Order the results by the employee number.

```
SELECT e.last_name AS Employee, e.employee_id AS Emp#, m.last_name AS Manager, m.employee_id AS Mgr# FROM employees e LEFT JOIN employees m ON e.manager_id = m.employee_id ORDER BY e.employee_id;
```

8. Create a query that displays employee last names, department numbers, and all the employees who work in the same department as a given employee. Give each column an appropriate label

```
SELECT e1.last_name AS Employee, e1.department_id AS Department, e2.last_name AS Colleague FROM employees e1 JOIN employees e2 ON e1.department_id = e2.department_id AND e1.employee_id != e2.employee_id;
```

9. Show the structure of the JOB\_GRADES table. Create a query that displays the name, job, department name, salary, and grade for all employees

```
DESC JOB_GRADES;  
SELECT e.last_name, e.job_id, d.department_name, e.salary, j.grade_level FROM employees e  
JOIN departments d ON e.department_id = d.department_id JOIN job_grades j ON e.salary  
BETWEEN j.lowest_sal AND j.highest_sal;
```

10. Create a query to display the name and hire date of any employee hired after employee Davies.

```
SELECT e.last_name, e.hire_date FROM employees e WHERE e.hire_date > (SELECT  
hire_date FROM employees WHERE last_name = 'Davies');
```

11. Display the names and hire dates for all employees who were hired before their managers, along with their manager's names and hire dates. Label the columns Employee, Emp Hired, Manager, and Mgr Hired, respectively.

```
SELECT e.last_name AS Employee, e.hire_date AS "Emp Hired", m.last_name AS Manager,  
m.hire_date AS "Mgr Hired" FROM employees e JOIN employees m ON e.manager_id =  
m.employee_id WHERE e.hire_date < m.hire_date;
```

**Ex. No: 9**

**Date:**

**Register No: 221701020**

**Name: Hemalatha R**

### **Aggregating Data Using Group Functions**

#### **Objectives**

After the completion of this exercise, the students will be able to do the following:

- Identify the available group functions
- Describe the use of group functions
- Group data by using the GROUP BY clause
- Include or exclude grouped rows by using the HAVING clause

#### **What Are Group Functions?**

Group functions operate on sets of rows to give one result per group

#### **Types of Group Functions**

- AVG
- COUNT
- MAX
- MIN
- STDDEV
- SUM
- VARIANCE

Each of the functions accepts an argument. The following table identifies the options that you can use in the syntax:

Function	Description
AVG ( [DISTINCT   ALL] <i>n</i> )	Average value of <i>n</i> , ignoring null values
COUNT ( { *   [DISTINCT   ALL] <i>expr</i> } )	Number of rows, where <i>expr</i> evaluates to something other than null (count all selected rows using *, including duplicates and rows with nulls)
MAX ( [DISTINCT   ALL] <i>expr</i> )	Maximum value of <i>expr</i> , ignoring null values
MIN ( [DISTINCT   ALL] <i>expr</i> )	Minimum value of <i>expr</i> , ignoring null values
STDDEV ( [DISTINCT   ALL] <i>x</i> )	Standard deviation of <i>n</i> , ignoring null values
SUM ( [DISTINCT   ALL] <i>n</i> )	Sum values of <i>n</i> , ignoring null values
VARIANCE ( [DISTINCT   ALL] <i>x</i> )	Variance of <i>n</i> , ignoring null values

### Group Functions: Syntax

SELECT [*column*,] *group\_function(column)*, ...

FROM *table*

[WHERE *condition*]

[GROUP BY *column*]

[ORDER BY *column*];

### Guidelines for Using Group Functions

- DISTINCT makes the function consider only nonduplicate values; ALL makes it consider every value, including duplicates. The default is ALL and therefore does not need to be specified.
- The data types for the functions with an *expr* argument may be CHAR, VARCHAR2, NUMBER, or DATE.
- All group functions ignore null values.

### Using the AVG and SUM Functions

You can use AVG and SUM for numeric data.

SELECT AVG(salary), MAX(salary),

```
MIN(salary), SUM(salary)
FROM employees
WHERE job_id LIKE '%REP%';
```

### **Using the MIN and MAX Functions**

You can use MIN and MAX for numeric, character, and date data types.

```
SELECT MIN(hire_date), MAX(hire_date)
FROM employees;
```

You can use the MAX and MIN functions for numeric, character, and date data types. example displays the most junior and most senior employees.

The following example displays the employee last name that is first and the employee last name that is last in an alphabetized list of all employees:

```
SELECT MIN(last_name), MAX(last_name)
FROM employees;
```

**Note:** The AVG, SUM, VARIANCE, and STDDEV functions can be used only with numeric data types. MAX and MIN cannot be used with LOB or LONG data types.

### **Using the COUNT Function**

COUNT(\*) returns the number of rows in a table:

```
SELECT COUNT(*)
FROM employees
WHERE department_id = 50;
```

COUNT(*expr*) returns the number of rows with nonnull values for the *expr*:

```
SELECT COUNT(commission_pct)
```

```
FROM employees  
WHERE department_id = 80;
```

### **Using the DISTINCT Keyword**

- COUNT(DISTINCT expr) returns the number of distinct non-null values of the *expr*.
- To display the number of distinct department values in the EMPLOYEES table:

```
SELECT COUNT(DISTINCT department_id) FROM employees;
```

Use the DISTINCT keyword to suppress the counting of any duplicate values in a column.

### **Group Functions and Null Values**

Group functions ignore null values in the column:

```
SELECT AVG(commission_pct)  
FROM employees;
```

The NVL function forces group functions to include null values:

```
SELECT AVG(NVL(commission_pct, 0))  
FROM employees;
```

### **Creating Groups of Data**

To divide the table of information into smaller groups. This can be done by using the GROUP BY clause.

### **GROUP BY Clause Syntax**

```
SELECT column, group_function(column)  
FROM table  
[WHERE condition]  
[GROUP BY group_by_expression]  
[ORDER BY column];
```

### In the syntax:

*group\_by\_expression* specifies columns whose values determine the basis for grouping rows

### Guidelines

- If you include a group function in a SELECT clause, you cannot select individual results as well, *unless* the individual column appears in the GROUP BY clause. You receive an error message if you fail to include the column list in the GROUP BY clause.
- Using a WHERE clause, you can exclude rows before dividing them into groups.
- You must include the *columns* in the GROUP BY clause.
- You cannot use a column alias in the GROUP BY clause.

### Using the GROUP BY Clause

All columns in the SELECT list that are not in group functions must be in the GROUP BY clause.

```
SELECT department_id, AVG(salary)  
FROM employees  
GROUP BY department_id ;
```

The GROUP BY column does not have to be in the SELECT list.

```
SELECT AVG(salary) FROM employees GROUP BY department_id ;
```

You can use the group function in the ORDER BY clause:

```
SELECT department_id, AVG(salary) FROM employees GROUP BY department_id ORDER BY AVG(salary);
```

### **Grouping by More Than One Column**

```
SELECT department_id dept_id, job_id, SUM(salary) FROM employees  
GROUP BY department_id, job_id ;
```

### **Illegal Queries Using Group Functions**

Any column or expression in the SELECT list that is not an aggregate function must be in the GROUP

#### **BY clause:**

```
SELECT department_id, COUNT(last_name) FROM employees;
```

You can correct the error by adding the GROUP BY clause:

```
SELECT department_id, count(last_name) FROM employees GROUP BY department_id;
```

You cannot use the WHERE clause to restrict groups.

- You use the HAVING clause to restrict groups.
- You cannot use group functions in the WHERE clause.

```
SELECT department_id, AVG(salary) FROM employees WHERE AVG(salary) > 8000  
GROUP BY department_id;
```

You can correct the error in the example by using the HAVING clause to restrict groups:

```
SELECT department_id, AVG(salary) FROM employees  
HAVING AVG(salary) > 8000 GROUP BY department_id;
```

### **Restricting Group Results**

With the HAVING Clause .When you use the HAVING clause, the Oracle server restricts groups as follows:

1. Rows are grouped.
2. The group function is applied.
3. Groups matching the HAVING clause are displayed.

### **Using the HAVING Clause**

```
SELECT department_id, MAX(salary) FROM employees  
GROUP BY department_id HAVING MAX(salary)>10000 ;
```

The following example displays the department numbers and average salaries for those departments with a maximum salary that is greater than \$10,000:

```
SELECT department_id, AVG(salary) FROM employees GROUP BY department_id  
HAVING max(salary)>10000;
```

Example displays the job ID and total monthly salary for each job that has a total payroll exceeding \$13,000. The example excludes sales representatives and sorts the list by the total monthly salary.

```
SELECT job_id, SUM(salary) PAYROLL FROM employees WHERE job_id NOT LIKE  
'%REP%'  
GROUP BY job_id HAVING SUM(salary) > 13000 ORDER BY SUM(salary);
```

## Nesting Group Functions

**Display the maximum average salary:**

Group functions can be nested to a depth of two. The slide example displays the maximum average salary.

```
SELECT MAX(AVG(salary)) FROM employees GROUP BY department_id;
```

### **Summary**

In this exercise, students should have learned how to:

- Use the group functions COUNT, MAX, MIN, and AVG
- Write queries that use the GROUP BY clause
- Write queries that use the HAVING clause

```
SELECT column, group_function
```

```
FROM table
```

```
[WHERE condition]
```

```
[GROUP BY group_by_expression]
```

```
[HAVING group_condition]
```

```
[ORDER BY column];
```

### **Find the Solution for the following:**

Determine the validity of the following three statements. Circle either True or False.

1. Group functions work across many rows to produce one result per group.

True/False

TRUE

2. Group functions include nulls in calculations.

True/False

FALSE

3. The WHERE clause restricts rows prior to inclusion in a group calculation.

True/False

TRUE

**The HR department needs the following reports:**

4. Find the highest, lowest, sum, and average salary of all employees. Label the columns Maximum, Minimum, Sum, and Average, respectively. Round your results to the nearest whole number

```
SELECT ROUND(MAX(salary)) AS Maximum, ROUND(MIN(salary)) AS Minimum,  
ROUND(SUM(salary)) AS Sum, ROUND(AVG(salary)) AS Average FROM employees;
```

5. Modify the above query to display the minimum, maximum, sum, and average salary for each job type.

```
SELECT job_id, ROUND(MIN(salary)) AS Minimum, ROUND(MAX(salary)) AS Maximum,  
ROUND(SUM(salary)) AS Sum, ROUND(AVG(salary)) AS Average FROM employees  
GROUP BY job_id;
```

6. Write a query to display the number of people with the same job. Generalize the query so that the user in the HR department is prompted for a job title.

```
SELECT job_id, COUNT(*) AS number_of_people FROM employees WHERE job_id =  
:job_title GROUP BY job_id;
```

7. Determine the number of managers without listing them. Label the column Number of Managers. *Hint: Use the MANAGER\_ID column to determine the number of managers.*

```
SELECT COUNT(DISTINCT manager_id) AS "Number of Managers" FROM employees  
WHERE manager_id IS NOT NULL;
```

8. Find the difference between the highest and lowest salaries. Label the column DIFFERENCE.

```
SELECT ROUND(MAX(salary) - MIN(salary)) AS DIFFERENCE FROM employees;
```

9. Create a report to display the manager number and the salary of the lowest-paid employee for that manager. Exclude anyone whose manager is not known. Exclude any groups where the minimum salary is \$6,000 or less. Sort the output in descending order of salary.

```
SELECT manager_id, MIN(salary) AS lowest_salary FROM employees WHERE manager_id IS  
NOT NULL GROUP BY manager_id HAVING MIN(salary) > 6000 ORDER BY lowest_salary  
DESC;
```

10. Create a query to display the total number of employees and, of that total, the number of employees hired in 1995, 1996, 1997, and 1998. Create appropriate column headings.

```
SELECT COUNT(*) AS total_employees, SUM(CASE WHEN EXTRACT(YEAR FROM  
hire_date) = 1995 THEN 1 ELSE 0 END) AS hired_1995, SUM(CASE WHEN  
EXTRACT(YEAR FROM hire_date) = 1996 THEN 1 ELSE 0 END) AS hired_1996,  
SUM(CASE WHEN EXTRACT(YEAR FROM hire_date) = 1997 THEN 1 ELSE 0 END)  
AS hired_1997, SUM(CASE WHEN EXTRACT(YEAR FROM hire_date) = 1998 THEN 1  
ELSE 0 END) AS hired_1998 FROM employees;
```

11. Create a matrix query to display the job, the salary for that job based on department number, and the total salary for that job, for departments 20, 50, 80, and 90, giving each column an appropriate heading.

```
SELECT job_id AS Job, SUM(CASE WHEN department_id = 20 THEN salary ELSE 0  
END) AS "Salary in Dept 20", SUM(CASE WHEN department_id = 50 THEN salary ELSE 0  
END) AS "Salary in Dept 50", SUM(CASE WHEN department_id = 80 THEN salary ELSE 0  
END) AS "Salary in Dept 80", SUM(CASE WHEN department_id = 90 THEN salary ELSE 0  
END) AS "Salary in Dept 90", SUM(salary) AS "Total Salary"  
FROM employees WHERE department_id IN (20, 50, 80, 90) GROUP BY job_id;
```

12. Write a query to display each department's name, location, number of employees, and the average salary for all the employees in that department. Label the column name-Location, Number of people, and salary respectively. Round the average salary to two decimal places.

```
SELECT d.department_name AS name, l.city AS Location, COUNT(e.employee_id) AS  
"Number of people", ROUND(AVG(e.salary), 2) AS salary FROM departments d JOIN  
employees e ON d.department_id = e.department_id JOIN locations l ON d.location_id =  
l.location_id GROUP BY d.department_name, l.city;
```

## **Date Functions**

1. For DJs on Demand, display the number of months between the event\_date of the Vigil wedding and today's date. Round to the nearest month.

- `SELECT ROUND(MONTHS_BETWEEN(SYSDATE, (SELECT event_date FROM events WHERE event_name = 'Vigil wedding'))) AS months_between FROM dual;`

2. Display the days between the start of last summer's school vacation break and the day school started this year. Assume 30.5 days per month. Name the output "Days."

- `SELECT ROUND((TO_DATE('2024-06-01', 'YYYY-MM-DD') - TO_DATE('2023-08-01', 'YYYY-MM-DD')), 0) AS Days FROM dual;`

3. Display the days between January 1 and December 31.

- `SELECT TO_DATE('2024-12-31', 'YYYY-MM-DD') - TO_DATE('2024-01-01', 'YYYY-MMDD') AS Days FROM dual;`

4. Using one statement, round today's date to the nearest month and nearest year and truncate it to the nearest month and nearest year. Use an alias for each column.

- `SELECT ROUND(SYSDATE, 'MONTH') AS rounded_month, ROUND(SYSDATE, 'YYYY') AS rounded_year, TRUNC(SYSDATE, 'MONTH') AS truncated_month, TRUNC(SYSDATE, 'YYYY') AS truncated_year FROM dual;`

5. What is the last day of the month for June 2005? Use an alias for the output.

- ```
SELECT LAST_DAY(TO_DATE('2005-06-01', 'YYYY-MM-DD')) AS  
Last_Day_Of_June_2005 FROM dual;
```

6. Display the number of years between the Global Fast Foods employee Bob Miller's birthday and today. Round to the nearest year.

- ```
SELECT ROUND(MONTHS_BETWEEN(SYSDATE, (SELECT birth_date FROM  
employees  
WHERE last_name = 'Miller' AND first_name = 'Bob')) / 12) AS Years_Between FROM  
dual;
```

7. Your next appointment with the dentist is six months from today. On what day will you go to the dentist? Name the output, "Appointment."

- ```
SELECT ADD_MONTHS(SYSDATE, 6) AS Appointment FROM dual;
```

8. The teacher said you have until the last day of this month to turn in your research paper. What day will this be? Name the output, "Deadline."

- ```
SELECT LAST_DAY(SYSDATE) AS Deadline FROM dual;
```

9. How many months between your birthday this year and January 1 next year?

- ```
SELECT MONTHS_BETWEEN(TO_DATE('2025-01-01', 'YYYY-MM-DD'),  
TO_DATE('2024-08-01', 'YYYY-MM-DD')) AS Months_Between FROM dual;
```

10. What's the date of the next Friday after your birthday this year? Name the output, "First Friday."

- ```
SELECT NEXT_DAY(TO_DATE('2024-08-01', 'YYYY-MM-DD'), 'FRIDAY') AS  
"First Friday" FROM dual;
```

11. Name a date function that will return a number.

- MONTHS\_BETWEEN (returns the number of months between two dates).

12. Name a date function that will return a date.

- SYSDATE (returns the current system date and time).

13. Give one example of why it is important for businesses to be able to manipulate date data?

- One example of why it is important for businesses to manipulate date data is to calculate employee payroll accurately. For example, a company might need to determine how many days an employee worked in a specific month or track the time between project start and end dates to assess efficiency

## Conversion Functions

In each of the following exercises, feel free to use labels for the converted column to make the output more readable.

1. List the last names and birthdays of Global Fast Food Employees. Convert the birth dates to character data in the Month DD, YYYY format. Suppress any leading zeros.
  - `SELECT last_name, TO_CHAR(birth_date, 'FMMonth DD, YYYY') AS birth_date FROM employees;`
2. Convert January 3, 04, to the default date format 03-Jan-2004.
  - `SELECT TO_DATE('03-JAN-04', 'DD-MON-YY') AS formatted_date FROM dual;`
3. Format a query from the Global Fast Foods f\_promotional\_menus table to print out the start\_date of promotional code 110 as: The promotion began on the tenth of February 2004.
  - `SELECT 'The promotion began on the ' || TO_CHAR(start_date, 'DDth "of" Month YYYY') AS promotion_start FROM f_promotional_menus WHERE promo_code = 110;`
4. Convert today's date to a format such as: "Today is the Twentieth of March, Two Thousand Four"
  - `SELECT 'Today is the ' || TO_CHAR(SYSDATE, 'FMDDth "of" Month, YYYY') AS today_date FROM dual;`
5. List the ID, name and salary for all Global Fast Foods employees. Display salary with a \$ sign and two decimal places
  - `SELECT employee_id, last_name, '$' || TO_CHAR(salary, '999,999.99') AS salary FROM employees;`

**Ex. No : 10**

**Date:**

**Register No: 221701020**

**Name: Hemalatha R**

### **Sub queries**

#### **Objectives**

After completing this lesson, you should be able to do the following:

- Define subqueries
- Describe the types of problems that subqueries can solve
- List the types of subqueries
- Write single-row and multiple-row subqueries

#### **Using a Subquery to Solve a Problem**

Who has a salary greater than Abel's?

#### **Main query:**

Which employees have salaries greater than Abel's salary?

#### **Subquery:**

What is Abel's salary?

#### **Subquery Syntax**

`SELECT select_list FROM table WHERE expr operator (SELECT select_list FROM table);`

- The subquery (inner query) executes once before the main query (outer query).
- The result of the subquery is used by the main query.

A subquery is a SELECT statement that is embedded in a clause of another SELECT statement.

You can build powerful statements out of simple ones by using subqueries. They can be very useful when you need to select rows from a table with a condition that depends on the data in the table itself.

You can place the subquery in a number of SQL clauses, including the following:

- WHERE clause
- HAVING clause
- FROM clause

#### **In the syntax:**

*operator* includes a comparison condition such as  $>$ ,  $=$ , or IN

**Note:** Comparison conditions fall into two classes: single-row operators

( $>$ ,  $=$ ,  $\geq$ ,  $<$ ,  $\neq$ ,  $\leq$ ) and multiple-row operators (IN, ANY, ALL). statement. The subquery generally executes first, and its output is used to complete the query condition for the main (or outer) query

#### **Using a Subquery**

```
SELECT last_name FROM employees WHERE salary > (SELECT salary FROM employees  
WHERE last_name = 'Abel');
```

The inner query determines the salary of employee Abel. The outer query takes the result of the inner query and uses this result to display all the employees who earn more than this amount.

#### **Guidelines for Using Subqueries**

- Enclose subqueries in parentheses.
- Place subqueries on the right side of the comparison condition.

- The ORDER BY clause in the subquery is not needed unless you are performing Top-N analysis.
- Use single-row operators with single-row subqueries, and use multiple-row operators with multiple-row subqueries.

## **Types of Subqueries**

- Single-row subqueries: Queries that return only one row from the inner SELECT statement.
- Multiple-row subqueries: Queries that return more than one row from the inner SELECT statement.

### **Single-Row Subqueries**

- Return only one row
- Use single-row comparison operators

#### **Example**

Display the employees whose job ID is the same as that of employee 141:

```
SELECT last_name, job_id FROM employees WHERE job_id = (SELECT job_id FROM
employees
WHERE employee_id = 141);
```

Displays employees whose job ID is the same as that of employee 141 and whose salary is greater than that of employee 143.

```
SELECT last_name, job_id, salary FROM employees WHERE job_id = (SELECT job_id FROM employees WHERE employee_id = 141) AND salary > (SELECT salary FROM employees WHERE employee_id = 143);
```

### **Using Group Functions in a Subquery**

Displays the employee last name, job ID, and salary of all employees whose salary is equal to the minimum salary. The MIN group function returns a single value (2500) to the outer query.

```
SELECT last_name, job_id, salary FROM employees WHERE salary = (SELECT MIN(salary) FROM employees);
```

### **The HAVING Clause with Subqueries**

- The Oracle server executes subqueries first.
- The Oracle server returns results into the HAVING clause of the main query.

Displays all the departments that have a minimum salary greater than that of department 50.

```
SELECT department_id, MIN(salary)  
FROM employees  
GROUP BY department_id  
HAVING MIN(salary) >  
(SELECT MIN(salary)  
FROM employees  
WHERE department_id = 50);
```

### **Example**

**Find the job with the lowest average salary.**

```
SELECT job_id, AVG(salary)
FROM employees
GROUP BY job_id
HAVING AVG(salary) = (SELECT MIN(AVG(salary))
FROM employees
GROUP BY job_id);
```

### **What Is Wrong in this Statements?**

```
SELECT employee_id, last_name
FROM employees
WHERE salary =(SELECT MIN(salary) FROM employees GROUP BY department_id);
Will This Statement Return Rows?
SELECT last_name, job_id
FROM employees
WHERE job_id =(SELECT job_id FROM employees WHERE last_name = 'Haas');
```

### **Multiple-Row Subqueries**

- Return more than one row
- Use multiple-row comparison operators

### **Example**

Find the employees who earn the same salary as the minimum salary for each department.

```
SELECT last_name, salary, department_id FROM employees WHERE salary IN (SELECT
MIN(salary)
FROM employees GROUP BY department_id);
```

Using the ANY Operator in Multiple-Row Subqueries

```
SELECT employee_id, last_name, job_id, salary FROM employees WHERE salary < ANY  
(SELECT salary FROM employees WHERE job_id = 'IT_PROG') AND job_id <> 'IT_PROG';
```

Displays employees who are not IT programmers and whose salary is less than that of any IT programmer. The maximum salary that a programmer earns is \$9,000.

< ANY means less than the maximum. >ANY means more than the minimum. =ANY is equivalent to IN.

### Using the ALL Operator in Multiple-Row Subqueries

```
SELECT employee_id, last_name, job_id, salary  
FROM employees  
WHERE salary < ALL (SELECT salary FROM employees WHERE job_id = 'IT_PROG')  
AND job_id <> 'IT_PROG';
```

Displays employees whose salary is less than the salary of all employees with a job ID of IT\_PROG and whose job is not IT\_PROG.

- ALL means more than the maximum, and <ALL means less than the minimum.

The NOT operator can be used with IN, ANY, and ALL operators.

### Null Values in a Subquery

```
SELECT emp.last_name FROM employees emp  
WHERE emp.employee_id NOT IN (SELECT mgr.manager_id FROM employees mgr);
```

Notice that the null value as part of the results set of a subquery is not a problem if you use the IN operator. The IN operator is equivalent to =ANY. For example, to display the employees who have subordinates, use the following SQL statement:

```
SELECT emp.last_name
```

```
FROM employees emp  
WHERE emp.employee_id IN (SELECT mgr.manager_id FROM employees mgr);
```

Display all employees who do not have any subordinates:

```
SELECT last_name FROM employees  
WHERE employee_id NOT IN (SELECT manager_id FROM employees WHERE manager_id IS  
NOT NULL);
```

**Find the Solution for the following:**

1. The HR department needs a query that prompts the user for an employee last name. The query then displays the last name and hire date of any employee in the same department as the employee whose name they supply (excluding that employee). For example, if the user enters Zlotkey, find all employees who work with Zlotkey (excluding Zlotkey).

- `SELECT e.last_name, e.hire_date FROM employees e JOIN employees emp ON e.department_id = emp.department_id WHERE emp.last_name = :last_name AND e.last_name != emp.last_name;`

2. Create a report that displays the employee number, last name, and salary of all employees who earn more than the average salary. Sort the results in order of ascending salary.

- `SELECT employee_id, last_name, salary FROM employees WHERE salary > (SELECT AVG(salary) FROM employees) ORDER BY salary ASC;`

3. Write a query that displays the employee number and last name of all employees who work in a department with any employee whose last name contains a *u*.

- a. `SELECT DISTINCT e.employee_id, e.last_name FROM employees e WHERE e.department_id IN ( SELECT department_id FROM employees WHERE last_name LIKE '%u%');`

4. The HR department needs a report that displays the last name, department number, and job ID of all employees whose department location ID is 1700.

- ```
SELECT last_name, department_id, job_id FROM employees WHERE department_id
IN (
    SELECT department_id FROM departments WHERE location_id = 1700 );
```

5. Create a report for HR that displays the last name and salary of every employee who reports to King.

- ```
SELECT last_name, salary FROM employees WHERE manager_id = (SELECT
employee_id FROM employees WHERE last_name = 'King');
```

6. Create a report for HR that displays the department number, last name, and job ID for every employee in the Executive department.

- ```
SELECT department_id, last_name, job_id FROM employees WHERE department_id
=
(SELECT department_id FROM departments WHERE department_name =
'Executive');
```

7. Modify the query 3 to display the employee number, last name, and salary of all employees who earn more than the average salary and who work in a department with any employee whose last name contains a *u*.

- ```
SELECT e.employee_id, e.last_name, e.salary FROM employees e WHERE e.salary >
(SELECT AVG(salary) FROM employees) AND e.department_id IN ( SELECT
department_id FROM employees WHERE last_name LIKE '%u%' );
```

## **Practice Questions**

1. Ellen Abel is an employee who has received a \$2,000 raise. Display her first name and last name, her current salary, and her new salary. Display both salaries with a \$ and two decimal places. Label her new salary column AS New Salary.

- ```
SELECT first_name, last_name, '$' || TO_CHAR(salary, '999,999.99') AS current_salary,
'$' || TO_CHAR(salary + 2000, '999,999.99') AS "New Salary" FROM employees WHERE
first_name = 'Ellen' AND last_name = 'Abel';
```

2. On what day of the week and date did Global Fast Foods' promotional code 110 Valentine's Special begin?

- ```
SELECT first_name, last_name, '$' || TO_CHAR(salary, '999,999.99') AS current_salary, '$' ||
TO_CHAR(salary + 2000, '999,999.99') AS "New Salary" FROM employees WHERE
first_name = 'Ellen' AND last_name = 'Abel';
```

3. Create one query that will convert 25-Dec-2004 into each of the following (you will have to convert 25-Dec-2004 to a date and then to character data):

December 25th, 2004

DECEMBER 25TH, 2004

25th december, 2004

- ```
SELECT TO_CHAR(TO_DATE('25-Dec-2004', 'DD-Mon-YYYY'), 'FMMonth DDth,
YYYY')
AS "December 25th, 2004", TO_CHAR(TO_DATE('25-Dec-2004', 'DD-Mon-YYYY'),
'UPPER(FMMonth DDth, YYYY)') AS "DECEMBER 25TH, 2004",
TO_CHAR(TO_DATE('25-Dec-2004', 'DD-Mon-YYYY'), 'FMDDth Month, YYYY') AS
"25th december, 2004" FROM dual;
```

4. Create a query that will format the DJs on Demand d\_packages columns, low-range and high- range package costs, in the format \$2500.00.

- ```
SELECT '$' || TO_CHAR(low_range, '999,999.00') AS "Low-Range Cost", '$' ||
TO_CHAR(high_range, '999,999.00') AS "High-Range Cost" FROM d_packages;
```

5. Convert JUNE192004 to a date using the fx format model.

- ```
SELECT TO_DATE('JUNE192004', 'MONDDYYYY') AS converted_date FROM dual;
```

6. What is the distinction between implicit and explicit datatype conversion? Give an example of each.

- **Implicit Data Type Conversion:** This occurs automatically when Oracle converts data from one type to another, such as when performing arithmetic operations between numbers and dates. Eg: 

```
SELECT 'The amount is ' || 100 FROM dual;
```
- **Explicit Data Type Conversion:** This requires the user to explicitly convert the data type using functions like TO\_NUMBER, TO\_DATE, etc. Eg: 

```
SELECT TO_CHAR(salary) FROM employees;
```

7. Why is it important from a business perspective to have datatype conversions?

- Data type conversions are important in business because different data sources and systems often store and process data in various formats. Being able to convert data types ensures data consistency, accurate reporting, and the ability to integrate data from different systems.

For example, converting a date stored as a string into an actual date format allows businesses to perform date-based calculations, such as tracking financial periods or employee tenure.

**Ex. No: 11**

**Date:**

**Register No: 221701020**

**Name: Hemalatha R**

## **USING THE SET OPERATORS**

### **Objectives**

After the completion this exercise, the students should be able to do the following:

- Describe set operators
- Use a set operator to combine multiple queries into a single query
- Control the order of rows returned

The set operators combine the results of two or more component queries into one result.

Queries containing set operators are called *compound queries*.

| Operator  | Returns                                                                                                           |
|-----------|-------------------------------------------------------------------------------------------------------------------|
| UNION     | All distinct rows selected by either query                                                                        |
| UNION ALL | All rows selected by either query, including all duplicates                                                       |
| INTERSECT | All distinct rows selected by both queries                                                                        |
| MINUS     | All distinct rows that are selected by the first SELECT statement and not selected in the second SELECT statement |

### **The tables used in this lesson are:**

- EMPLOYEES: Provides details regarding all current employees
- JOB\_HISTORY: Records the details of the start date and end date of the former job, and the job identification number and department when an employee switches jobs

### **UNION Operator**

## Guidelines

- The number of columns and the data types of the columns being selected must be identical in all the SELECT statements used in the query. The names of the columns need not be identical.
- UNION operates over all of the columns being selected.
- NULL values are not ignored during duplicate checking.
- The IN operator has a higher precedence than the UNION operator.
- By default, the output is sorted in ascending order of the first column of the SELECT clause.

## Example:

Display the current and previous job details of all employees. Display each employee only once.

```
SELECT employee_id, job_id FROM employees UNION SELECT employee_id, job_id  
FROM job_history;
```

## Example:

```
SELECT employee_id, job_id, department_id  
FROM employees  
UNION  
SELECT employee_id, job_id, department_id  
FROM job_history;
```

## UNION ALL Operator

## Guidelines

The guidelines for UNION and UNION ALL are the same, with the following two exceptions that pertain to UNION ALL:

- Unlike UNION, duplicate rows are not eliminated and the output is not sorted by default.
- The DISTINCT keyword cannot be used.

**Example:**

Display the current and previous departments of all employees.

```
SELECT employee_id, job_id, department_id  
FROM employees  
UNION ALL  
SELECT employee_id, job_id, department_id  
FROM job_history  
ORDER BY employee_id;
```

**INTERSECT Operator**

**Guidelines**

- The number of columns and the data types of the columns being selected by the SELECT statements in the queries must be identical in all the SELECT statements used in the query. The names of the columns need not be identical.
- Reversing the order of the intersected tables does not alter the result.
- INTERSECT does not ignore NULL values.

**Example:**

Display the employee IDs and job IDs of those employees who currently have a job title that is the same as their job title when they were initially hired (that is, they changed jobs but have now gone back to doing their original job).

```
SELECT employee_id, job_id FROM employees
```

INTERSECT

```
SELECT employee_id, job_id  
FROM job_history;
```

**Example**

```
SELECT employee_id, job_id, department_id  
FROM employees  
INTERSECT  
SELECT employee_id, job_id, department_id  
FROM job_history;
```

**MINUS Operator**

**Guidelines**

- The number of columns and the data types of the columns being selected by the SELECT statements in the queries must be identical in all the SELECT statements used in the query. The names of the columns need not be identical.
- All of the columns in the WHERE clause must be in the SELECT clause for the MINUS operator to work.

**Example:**

Display the employee IDs of those employees who have not changed their jobs even once.

```
SELECT employee_id, job_id  
FROM employees  
MINUS  
SELECT employee_id, job_id  
FROM job_history;
```

**Find the Solution for the following:**

1. The HR department needs a list of department IDs for departments that do not contain the job ID ST\_CLERK. Use set operators to create this report.

- SELECT department\_id FROM departments WHERE department\_id NOT IN (SELECT department\_id FROM employees WHERE job\_id = 'ST\_CLERK' );

2. The HR department needs a list of countries that have no departments located in them.

Display the country ID and the name of the countries. Use set operators to create this report.

```
SELECT country_id, country_name FROM countries WHERE country_id NOT IN ( SELECT DISTINCT location_id FROM departments );
```

3. Produce a list of jobs for departments 10, 50, and 20, in that order. Display job ID and department ID using set operators.

- SELECT job\_id, department\_id FROM employees WHERE department\_id IN (10, 50, 20) ORDER BY department\_id;

4. Create a report that lists the employee IDs and job IDs of those employees who currently have a job title that is the same as their job title when they were initially hired by the company (that is, they changed jobs but have now gone back to doing their original job).

- SELECT employee\_id, job\_id FROM employees WHERE job\_id = ( SELECT job\_id FROM employees WHERE employee\_id = employees.employee\_id AND hire\_date = (SELECT MIN(hire\_date) FROM employees WHERE employee\_id = employees.employee\_id) );

5. The HR department needs a report with the following specifications:

- Last name and department ID of all the employees from the EMPLOYEES table, regardless of whether or not they belong to a department.

- Department ID and department name of all the departments from the DEPARTMENTS table, regardless of whether or not they have employees working in them Write a compound query to accomplish this.

- SELECT last\_name, department\_id FROM employees;

- Department ID and department name of all the departments from the DEPARTMENTS table, regardless of whether or not they have employees working in them Write a compound query to accomplish this.

- SELECT department\_id, department\_name FROM departments;

## **NULL Functions**

1. Create a report that shows the Global Fast Foods promotional name, start date, and end date from the f\_promotional\_menus table. If there is an end date, temporarily replace it with “end in two weeks”. If there is no end date, replace it with today’s date.

- ```
SELECT promo_name, start_date, CASE WHEN end_date IS NOT NULL THEN 'end in two weeks' WHEN end_date IS NULL THEN TO_CHAR(SYSDATE, 'MM-DD-YYYY') END AS end_date FROM f_promotional_menus;
```

2. Not all Global Fast Foods staff members receive overtime pay. Instead of displaying a null value for these employees, replace null with zero. Include the employee’s last name and overtime rate in the output. Label the overtime rate as “Overtime Status”.

- ```
SELECT last_name, NVL(overtime_rate, 0) AS "Overtime Status" FROM employees;
```

3. The manager of Global Fast Foods has decided to give all staff who currently do not earn overtime an overtime rate of \$5.00. Construct a query that displays the last names and the overtime rate for each staff member, substituting \$5.00 for each null overtime value.

- ```
SELECT last_name, NVL(overtime_rate, 5.00) AS overtime_rate FROM employees;
```

4. Not all Global Fast Foods staff members have a manager. Create a query that displays the employee last name and 9999 in the manager ID column for these employees.

```
SELECT last_name, NVL(manager_id, 9999) AS manager_id FROM employees;
```

5. Which statement(s) below will return null if the value of v\_sal is 50?
- a. SELECT nvl(v\_sal, 50) FROM emp;
  - b. SELECT nvl2(v\_sal, 50) FROM emp;
  - c. SELECT nullif(v\_sal, 50) FROM emp;
  - d. SELECT coalesce (v\_sal, Null, 50) FROM emp;
- c. SELECT nullif(v\_sal, 50) FROM emp;

6. What does this query on the Global Fast Foods table return?

```
SELECT COALESCE(last_name, to_char(manager_id)) as NAME  
FROM f_staffs;
```

- This query will return the **first name** if last\_name is null, otherwise it will return the **last\_name**. If last\_name is null, it converts the manager\_id to a character string using to\_char() and returns it.

- 7a. Create a report listing the first and last names and month of hire for all employees in the EMPLOYEES table (use TO\_CHAR to convert hire\_date to display the month).

- SELECT first\_name, last\_name, TO\_CHAR(hire\_date, 'Month') AS month\_of\_hire FROM employees;

- b. Modify the report to display null if the month of hire is September. Use the NULLIF function.

```
SELECT first_name, last_name, NULLIF(TO_CHAR(hire_date, 'Month'), 'September') AS month_of_hire  
FROM employees;
```

8. For all null values in the specialty column in the DJs on Demand d\_partners table, substitute “No Specialty.” Show the first name and specialty columns only.

- `SELECT first_name, NVL(specialty, 'No Specialty') AS specialty FROM d_partners;`

## Conditional Expressions

1. From the DJs on Demand d\_songs table, create a query that replaces the 2-minute songs with “shortest” and the 10-minute songs with “longest”. Label the output column “Play Times”.

- `SELECT CASE WHEN play_time = 2 THEN 'shortest' WHEN play_time = 10 THEN 'longest' ELSE TO_CHAR(play_time) END AS "Play Times" FROM d_songs;`

2. Use the Oracle database employees table and CASE expression to decode the department id. Display the department id, last name, salary and a column called “New Salary” whose value is based on the following conditions:

If the department id is 10 then  $1.25 * \text{salary}$   
If the department id is 90 then  $1.5 * \text{salary}$

If the department id is 130 then  $1.75 * \text{salary}$

Otherwise, display the old salary.

- `SELECT department_id, last_name, salary, CASE WHEN department_id = 10 THEN salary * 1.25 WHEN department_id = 90 THEN salary * 1.5 WHEN department_id = 130 THEN salary * 1.75 ELSE salary END AS "New Salary" FROM employees;`

3. Display the first name, last name, manager ID, and commission percentage of all employees in departments 80 and 90. In a 5<sup>th</sup> column called “Review”, again display the manager ID. If they don’t have a manager, display the commission percentage. If they don’t have a commission, display 99999.

- ```
SELECT first_name, last_name, manager_id, commission_pct, CASE WHEN manager_id IS NULL THEN CASE WHEN commission_pct IS NULL THEN 99999 ELSE commission_pct END ELSE manager_id END AS "Review" FROM employees WHERE department_id IN (80, 90);
```

## Cross Joins and Natural Joins

Use the Oracle database for problems 1-4.

1. Create a cross-join that displays the last name and department name from the employees and departments tables.

- ```
SELECT e.last_name, d.department_name FROM employees e CROSS JOIN departments d;
```

2. Create a query that uses a natural join to join the departments table and the locations table. Display the department id, department name, location id, and city.

- ```
SELECT d.department_id, d.department_name, l.location_id, l.city FROM departments d NATURAL JOIN locations l;
```

3. Create a query that uses a natural join to join the departments table and the locations table. Restrict the output to only department IDs of 20 and 50. Display the department id, department name, location id, and city.

- ```
SELECT d.department_id, d.department_name, l.location_id, l.city FROM departments d NATURAL JOIN locations l WHERE d.department_id IN (20, 50);
```

221701020

**Ex. No: 13**

**Date:**

**Register No: 221701020**

**Name: Hemalatha R**

---

## **CREATING VIEWS**

After the completion of this exercise, students will be able to do the following:

- Describe a view
- Create, alter the definition of, and drop a view
- Retrieve data through a view
- Insert, update, and delete data through a view
- Create and use an inline view

### **View**

A view is a logical table based on a table or another view. A view contains no data but is like a window through which data from tables can be viewed or changed. The tables on which a view is based are called base tables.

### **Advantages of Views**

- To restrict data access
- To make complex queries easy
- To provide data independence
- To present different views of the same data

### **Classification of views**

1. Simple view
2. Complex view

Feature	Simple	Complex
No. of tables	One	One or more
Contains functions	No	Yes
Contains groups of data	No	Yes
DML operations thr' view	Yes	Not always

### Creating a view

#### Syntax

CREATE OR REPLACE FORCE/NOFORCE VIEW view\_name AS Subquery WITH CHECK  
OPTION CONSTRAINT constraint WITH READ ONLY CONSTRAINT constraint;

**FORCE** - Creates the view regardless of whether or not the base tables exist.

**NOFORCE** - Creates the view only if the base table exist.

WITH CHECK OPTION CONSTRAINT-specifies that only rows accessible to the view can be inserted or updated.

WITH READ ONLY CONSTRAINT-ensures that no DML operations can be performed on the view.

#### Example: 1 (Without using Column aliases)

Create a view EMPVU80 that contains details of employees in department80.

#### Example 2:

CREATE VIEW empvu80 AS SELECT employee\_id, last\_name, salary FROM employees  
WHERE department\_id=80;

### **Example:1 (Using column aliases)**

```
CREATE VIEW salvu50
AS SELECT employee_id,id_number, last_name NAME, salary *12 ANN_SALARY
FROM employees
WHERE department_id=50;
```

### **Retrieving data from a view**

#### **Example:**

```
SELECT * from salvu50;
```

### **Modifying a view**

A view can be altered without dropping, re-creating.

#### **Example: (Simple view)**

Modify the EMPVU80 view by using CREATE OR REPLACE.

```
CREATE OR REPLACE VIEW empvu80 (id_number, name, sal, department_id)
AS SELECT employee_id,first_name, last_name, salary, department_id
FROM employees
WHERE department_id=80;
```

#### **Example: (complex view)**

```
CREATE VIEW dept_sum_vu (name, minsal, maxsal,avgsal)
AS SELECT d.department_name, MIN(e.salary), MAX(e.salary), AVG(e.salary)
FROM employees e, department d
WHERE e.department_id=d.department_id
GROUP BY d.department_name;
```

### **Rules for performing DML operations on view**

- Can perform operations on simple views
- Cannot remove a row if the view contains the following:
  - Group functions
  - Group By clause
  - Distinct keyword
- Cannot modify data in a view if it contains
  - Group functions
  - Group By clause
  - Distinct keyword
  - Columns contain by expressions
  -
- Cannot add data thr' a view if it contains
  - Group functions
  - Group By clause
  - Distinct keyword
  - Columns contain by expressions
  - NOT NULL columns in the base table that are not selected by the view

### **Example: (Using the WITH CHECK OPTION clause)**

```
CREATE OR REPLACE VIEW empvu20
AS    SELECT *
FROM employees
WHERE department_id=20
WITH CHECK OPTION CONSTRAINT empvu20_ck;
```

**Note:** Any attempt to change the department number for any row in the view fails because it violates the WITH CHECK OPTION constraint.

**Example** – (Execute this and note the error)

```
UPDATE empvu20 SET department_id=10 WHERE employee_id=201;
```

### **Denying DML operations**

Use of WITH READ ONLY option.

Any attempt to perform a DML on any row in the view results in an oracle server error.

### **Try this code:**

```
CREATE OR REPLACE VIEW empvu10(employee_number, employee_name, job_title)
AS SELECT employee_id, last_name, job_id
FROM employees
WHERE department_id=10
WITH READ ONLY;
```

### **Find the Solution for the following:**

1. Create a view called EMPLOYEE\_VU based on the employee numbers, employee names and department numbers from the EMPLOYEES table. Change the heading for the employee name to EMPLOYEE.

```
CREATE VIEW EMPLOYEE_VU AS SELECT employee_id, first_name || ' ' || last_name AS
employee, department_id FROM employees;
```

2. Display the contents of the EMPLOYEES\_VU view.
  - SELECT \* FROM EMPLOYEE\_VU;

3. Select the view name and text from the USER\_VIEWS data dictionary views.
- `SELECT view_name, text FROM user_views;`
4. Using your EMPLOYEES\_VU view, enter a query to display all employees names and department.
- `SELECT employee, department_id FROM EMPLOYEE_VU;`
5. Create a view named DEPT50 that contains the employee number, employee last names and department numbers for all employees in department 50. Label the view columns EMPNO, EMPLOYEE and DEPTNO. Do not allow an employee to be reassigned to another department through the view.
- `CREATE VIEW DEPT50 AS SELECT employee_id AS EMPNO, last_name AS EMPLOYEE, department_id AS DEPTNO FROM employees WHERE department_id = 50; -- Make the view read-only to prevent reassignment ALTER VIEW DEPT50 READ ONLY;`
6. Display the structure and contents of the DEPT50 view.
- `DESCRIBE DEPT50;`
  - `SELECT * FROM DEPT50;`
7. Attempt to reassign Matos to department 80.
- `UPDATE DEPT50 SET department_id = 80 WHERE employee_id = (SELECT employee_id FROM employees WHERE last_name = 'Matos');`

8. Create a view called SALARY\_VU based on the employee last names, department names, salaries, and salary grades for all employees. Use the Employees, DEPARTMENTS and JOB\_GRADE tables. Label the column Employee, Department, salary, and Grade respectively.

- ```
CREATE VIEW SALARY_VU AS SELECT e.last_name AS Employee,
d.department_name AS Department, e.salary AS Salary, j.grade_level AS Grade
FROM employees e JOIN departments d ON e.department_id = d.department_id JOIN
job_grades j
ON e.salary BETWEEN j.low_salary AND j.high_salary;
```

221701020

**Ex. No: P-6**

**Date:**

**Register No: 221701020**

**Name: Hemalatha R**

---

## **Join Clauses**

Use the Oracle database for problems 1-6.

1. Join the Oracle database locations and departments table using the location\_id column. Limit the results to location 1400 only.
  - `SELECT l.location_id, d.department_id, d.department_name FROM locations l JOIN departments d ON l.location_id = d.location_id WHERE l.location_id = 1400;`
2. Join DJs on Demand d\_play\_list\_items, d\_track\_listings, and d\_cds tables with the JOIN USING syntax. Include the song ID, CD number, title, and comments in the output.
  - `SELECT p.song_id, c.cd_number, t.title, p.comments FROM d_play_list_items p JOIN d_track_listings t USING (song_id) JOIN d_cds c USING (cd_number);`
3. Display the city, department name, location ID, and department ID for departments 10, 20, and 30 for the city of Seattle.
  - `SELECT l.city, d.department_name, d.location_id, d.department_id FROM locations l JOIN departments d ON l.location_id = d.location_id WHERE d.department_id IN (10, 20, 30) AND l.city = 'Seattle';`

4. Display country name, region ID, and region name for Americas.
- ```
SELECT c.country_name, c.region_id, r.region_name FROM countries c JOIN regions r ON c.region_id = r.region_id WHERE r.region_name = 'Americas';
```
5. Write a statement joining the employees and jobs tables. Display the first and last names, hire date, job id, job title, and maximum salary. Limit the query to those employees who are in jobs that can earn more than \$12,000.
- 6.
- ```
SELECT e.first_name, e.last_name, e.hire_date, e.job_id, j.job_title, j.max_salary FROM employees e JOIN jobs j ON e.job_id = j.job_id WHERE j.max_salary > 12000;
```

## Inner versus Outer Joins

Use the Oracle database for problems 1-7.

1. Return the first name, last name, and department name for all employees including those employees not assigned to a department.
- ```
SELECT e.first_name, e.last_name, d.department_name FROM employees e LEFT JOIN departments d ON e.department_id = d.department_id;
```
2. Return the first name, last name, and department name for all employees including those departments that do not have an employee assigned to them.
- ```
SELECT e.first_name, e.last_name, d.department_name FROM employees e RIGHT JOIN departments d ON e.department_id = d.department_id;
```

3. Return the first name, last name, and department name for all employees including those departments that do not have an employee assigned to them and those employees not assigned to a department.

- `SELECT e.first_name, e.last_name, d.department_name FROM employees e FULL OUTER JOIN departments d ON e.department_id = d.department_id;`

4. Create a query of the DJs on Demand database to return the first name, last name, event date, and description of the event the client held. Include all the clients even if they have not had an event scheduled.

- `SELECT e.first_name, e.last_name, d.department_name FROM employees e FULL OUTER JOIN departments d ON e.department_id = d.department_id;`

5. Using the Global Fast Foods database, show the shift description and shift assignment date even if there is no date assigned for each shift description.

- `SELECT s.shift_description, s.shift_assignment_date FROM shifts s LEFT JOIN shift_assignments sa ON s.shift_id = sa.shift_id;`

## Self Joins and Hierarchical Queries

For each problem, use the Oracle database.

1. Display the employee's last name and employee number along with the manager's last name and manager number. Label the columns: Employee, Emp#, Manager, and Mgr#, respectively.

- `SELECT e.last_name AS Employee, e.employee_id AS "Emp#", m.last_name AS Manager,`

2. Modify question 1 to display all employees and their managers, even if the employee does not have a manager. Order the list alphabetically by the last name of the employee.

- `SELECT e.last_name AS Employee, e.employee_id AS "Emp#", m.last_name AS Manager,  
m.employee_id AS "Mgr#" FROM employees e LEFT JOIN employees m ON e.manager_id  
=  
m.employee_id ORDER BY e.last_name;`

3. Display the names and hire dates for all employees who were hired before their managers, along with their managers' names and hire dates. Label the columns Employee, Emp Hired, Manager, and Mgr Hired, respectively.

- `SELECT e.last_name AS Employee, e.hire_date AS "Emp Hired", m.last_name AS Manager,  
m.hire_date AS "Mgr Hired" FROM employees e JOIN employees m ON e.manager_id =  
m.employee_id WHERE e.hire_date < m.hire_date;`

4. Write a report that shows the hierarchy for Lex De Haans department. Include last name, salary, and department id in the report.

- `SELECT e.last_name, e.salary, e.department_id FROM employees e START WITH e.last_name = 'De Haan' CONNECT BY PRIOR e.employee_id = e.manager_id;`

5. What is wrong in the following statement:

```
SELECT last_name, department_id, salary  
FROM employees  
START WITH last_name = 'King'  
CONNECT BY PRIOR manager_id = employee_id;
```

- The error in the statement is the START WITH clause specifying `last_name = 'King'`, which is not unique. You should use a unique identifier (e.g., `employee_id`) instead.

6. Create a report that shows the organization chart for the entire employee table. Write the report so that each level will indent each employee 2 spaces. Since Oracle Application Express cannot display the spaces in front of the column, use - (minus) instead.

- `SELECT LPAD(' ', LEVEL * 2, '-') || e.last_name AS "Employee", e.salary, e.department_id FROM employees e START WITH e.manager_id IS NULL CONNECT BY PRIOR e.employee_id = e.manager_id;`

7. Re-write the report from 6 to exclude De Haan and all the people working for him.

- `SELECT LPAD(' ', LEVEL * 2, '-') || e.last_name AS "Employee", e.salary, e.department_id FROM employees e START WITH e.manager_id IS NULL CONNECT BY PRIOR e.employee_id = e.manager_id AND e.last_name != 'De Haan';`

## Oracle Equijoin and Cartesian Product

1. Create a Cartesian product that displays the columns in the d\_play\_list\_items and the d\_track\_listings in the DJs on Demand database.
  - `SELECT * FROM d_play_list_items, d_track_listings;`
2. Correct the Cartesian product produced in question 1 by creating an equijoin using a common column.
  - `SELECT * FROM d_play_list_items p JOIN d_track_listings t ON p.track_id = t.track_id;`
3. Write a query to display the title, type, description, and artist from the DJs on Demand database.

`SELECT title, type, description, artist FROM d_track_listings;`

4. Rewrite the query in question 3 to select only those titles with an ID of 47 or 48.

`SELECT title, type, description, artist FROM d_track_listings WHERE track_id IN (47, 48);`

5. Write a query that extracts information from three tables in the DJs on Demand database, the d\_clients table, the d\_events table, and the d\_job\_assignments table.

- `SELECT c.client_name, e.event_date, ja.job_title FROM d_clients c JOIN d_events e ON c.client_id = e.client_id JOIN d_job_assignments ja ON e.event_id = ja.event_id;`

## Group Functions

1. Define and give an example of the seven group functions: AVG, COUNT, MAX, MIN, STDDEV, SUM, and VARIANCE.

**AVG:** Calculates the average of a numerical column.

- Example: `SELECT AVG(salary) FROM employees;`

**COUNT:** Counts the number of rows or non-NULL values in a column.

- Example: `SELECT COUNT(employee_id) FROM employees;`

**MAX:** Returns the maximum value in a column.

- Example: `SELECT MAX(salary) FROM employees;`

Returns the minimum value in a column.

- Example: `SELECT MIN(salary) FROM employees;`

**STDDEV:** Calculates the standard deviation of a numerical column.

- Example: `SELECT STDDEV(salary) FROM employees;`

**SUM:** Calculates the total sum of a numerical column.

- Example: `SELECT SUM(salary) FROM employees;`

**VARIANCE:** Returns the variance of a numerical column.

Example: `SELECT VARIANCE(salary) FROM employees;`

2. Create a query that will show the average cost of the DJs on Demand events. Round to two decimal places.

- `SELECT ROUND(AVG(event_cost), 2) AS average_event_cost FROM d_events;`

3. Find the average salary for Global Fast Foods staff members whose manager ID is 19.

- `SELECT AVG(salary) AS average_salary FROM employees WHERE manager_id = 19;`

4. Find the sum of the salaries for Global Fast Foods staff members whose IDs are 12 and 9.

- `SELECT SUM(salary) AS total_salary FROM employees WHERE employee_id IN (12, 9);`

Using the Oracle database, select the lowest salary, the most recent hire date, the last name of the person who is at the top of an alphabetical list of employees, and the last name of the person who is at the bottom of an alphabetical list of employees. Select only employees who are in departments 50 or 60

5. Your new Internet business has had a good year financially. You have had 1,289 orders this year. Your customer order table has a column named total\_sales. If you submit the following query, how many rows will be returned?

```
SELECT sum(total_sales) fFROM orders;
```

- The query uses the SUM() function, which aggregates values across all rows and returns a **single row** as the result. So, **1 row** will be returned, containing the sum of the total\_sales column.

6. You were asked to create a report of the average salaries for all employees in each division of the company. Some employees in your company are paid hourly instead of by salary. When you ran the report, it seemed as though the averages were not what you expected—they were much higher than you thought! What could have been the cause?

- The cause could be that hourly employees have lower wage values in the salary column, which skews the average. To fix this, filter out hourly employees or handle them differently using a case statement.

7. Employees of Global Fast Foods have birth dates of July 1, 1980, March 19, 1979, and March 30, 1969. If you select MIN(birthdate), which date will be returned?

- The `MIN()` function returns the **earliest** date in the column. Given the dates July 1, 1980, March 19, 1979, and March 30, 1969, the **earliest date is March 30, 1969**.

8. Create a query that will return the average order total for all Global Fast Foods orders from January 1, 2002, to December 21, 2002.

- `SELECT AVG(total_sales) AS average_order_total FROM orders WHERE order_date BETWEEN TO_DATE('2002-01-01', 'YYYY-MM-DD') AND TO_DATE('2002-12-21', 'YYYY-MM-DD');`

9. What was the hire date of the last Oracle employee hired?

- `SELECT MAX(hire_date) AS last_hire_date FROM employees;`

10. Your new Internet business has had a good year financially. You have had 1,289 orders this year. Your customer order table has a column named total\_sales. If you submit the following query, how many rows will be returned?

```
SELECT sum(total_sales)  
FROM orders;
```

- This query calculates the total sum of the total\_sales column across all rows, but it will return **1 row** (since SUM() is an aggregate function that returns a single result for the entire table).

**Ex. No: P-7**

**Date:**

**Register No: 221701020**

**Name: Hemalatha R**

---

## **COUNT, DISTINCT, NVL**

1. How many songs are listed in the DJs on Demand D\_SONGS table?
  - SELECT COUNT(\*) FROM d\_songs;
  
2. In how many different location types has DJs on Demand had venues?
  - SELECT COUNT(DISTINCT location\_type) FROM d\_venues;
  
3. The d\_track\_listings table in the DJs on Demand database has a song\_id column and a cd\_number column. How many song IDs are in the table and how many different CD numbers are in the table?
  - SELECT COUNT(song\_id), COUNT(DISTINCT cd\_number) FROM d\_track\_listings;
  
4. How many of the DJs on Demand customers have email addresses?
  - SELECT COUNT(\*) FROM d\_customers WHERE email IS NOT NULL;
  
5. Some of the partners in DJs on Demand do not have authorized expense amounts (auth\_expense\_amt). How many partners do have this privilege?
  - SELECT COUNT(\*) FROM d\_partners WHERE auth\_expense\_amt IS NOT NULL;

6. What values will be returned when the statement below is issued?

| ID  | type    | shoe_color |
|-----|---------|------------|
| 456 | oxford  | brown      |
| 463 | sandal  | tan        |
| 262 | heel    | black      |
| 433 | slipper | tan        |

```
SELECT COUNT(shoe_color),
COUNT(DISTINCT shoe_color)
FROM shoes;
```

- **COUNT(shoe\_color)** will return 4 (total number of rows with shoe color).
- **COUNT(DISTINCT shoe\_color)** will return 3 (unique shoe colors: brown, tan, black).

7. Create a query that will convert any null values in the auth\_expense\_amt column on the DJs on Demand D\_PARTNERS table to 100000 and find the average of the values in this column. Round the result to two decimal places.

- `SELECT ROUND(AVG(NVL(auth_expense_amt, 100000)), 2) FROM d_partners;`

8. Which of the following statements is/are TRUE about the following query?

```
SELECT AVG(NVL(selling_bonus, 0.10))
FROM bonuses;
```

- \_\_\_\_\_ a. The datatypes of the values in the NVL clause can be any datatype except date data.
- \_\_\_\_\_ b. If the selling\_bonus column has a null value, 0.10 will be substituted.
- \_\_\_\_\_ c. There will be no null values in the selling\_bonus column when the average is calculated.
- \_\_\_\_\_ d. This statement will cause an error. There cannot be two functions in the SELECT statement.

True True False True

9. Which of the following statements is/are TRUE about the following query?

SELECT DISTINCT colors, sizes

FROM items;

- a. Each color will appear only once in the results set.
- b. Each size will appear only once in the results set.
- c. Unique combinations of color and size will appear only once in the results set.
- d. Each color and size combination will appear more than once in the results set.

- False
- False
- True
- False

## Using GROUP BY and HAVING Clauses

1. In the SQL query shown below, which of the following are true about this query?
  - a. Kimberly Grant would not appear in the results set.
  - b. The GROUP BY clause has an error because the manager\_id is not listed in the SELECT clause.
  - c. Only salaries greater than 16001 will be in the result set.
  - d. Names beginning with Ki will appear after names beginning with Ko.
  - e. Last names such as King and Kochhar will be returned even if they don't have salaries > 16000.

```
SELECT last_name, MAX(salary)  
FROM employees  
WHERE last_name LIKE 'K%'  
GROUP BY manager_id, last_name  
HAVING MAX(salary) > 16000  
ORDER BY last_name DESC ;
```

- False
- True
- False
- True
- False

2. Each of the following SQL queries has an error. Find the error and correct it. Use Oracle Application Express to verify that your corrections produce the desired results.

```
a. SELECT manager_id  
FROM employees  
WHERE AVG(salary) < 16000  
GROUP BY manager_id;
```

- AVG(salary) is an aggregate function and should be used in the SELECT clause. The WHERE clause cannot directly filter on an aggregate function. The HAVING clause should be used to filter the results after aggregation.

b. 

```
SELECT cd_number, COUNT(title)
FROM d_cds
WHERE cd_number < 93;
```

- Aggregate functions like COUNT should be used in conjunction with GROUP BY unless you are selecting over the entire table. Add a GROUP BY clause

c. 

```
SELECT ID, MAX(ID), artist AS Artist FROM d_songs
WHERE duration IN('3 min', '6 min', '10 min')
HAVING ID < 50
GROUP by ID;
```

- You cannot use MAX(ID) without grouping by other columns, and HAVING is used incorrectly. The GROUP BY should be adjusted to include all selected non-aggregated columns.

d. 

```
SELECT loc_type, rental_fee AS Fee
FROM d_venues
WHERE id <100
GROUP BY "Fee"
ORDER BY 2;
```

- GROUP BY "Fee" is invalid because Fee is a column alias and cannot be used in GROUP BY. The correct column name should be used in the GROUP BY clause

3. Rewrite the following query to accomplish the same result:

```
SELECT DISTINCT MAX(song_id)
FROM d_track_listings
WHERE track IN ( 1, 2, 3);
```

- ```
SELECT MAX(song_id) FROM d_track_listings WHERE track IN (1, 2, 3) GROUP BY track;
```

4. Indicate True or False

- a. If you include a group function and any other individual columns in a SELECT clause, then each individual column must also appear in the GROUP BY clause.
  - b. You can use a column alias in the GROUP BY clause.
  - c. The GROUP BY clause always includes a group function.
- True
  - False
  - False

5. Write a query that will return both the maximum and minimum average salary grouped by department from the employees table.

- `SELECT department_id, MAX(AVG(salary)) AS max_avg_salary, MIN(AVG(salary)) AS min_avg_salary FROM employees GROUP BY department_id;`

6. Write a query that will return the average of the maximum salaries in each department for the employees table.

- `SELECT AVG(max_salary) FROM ( SELECT MAX(salary) AS max_salary FROM employees GROUP BY department_id );`

## Using Set Operators

1. Name the different Set operators?

- **UNION:** Combines the results of two queries and removes duplicates.
- **UNION ALL:** Combines the results of two queries and includes all rows, even duplicates.
- **INTERSECT:** Returns only the rows that are common to both queries.
- **MINUS (or EXCEPT in some databases):** Returns the rows from the first query that are not in the second query.

2. Write one query to return the employee\_id, job\_id, hire\_date, and department\_id of all employees and a second query listing employee\_id, job\_id, start\_date, and department\_id from the job\_history table and combine the results as one single output. Make sure you suppress duplicates in the output.

- `SELECT employee_id, job_id, hire_date, department_id FROM employees UNION  
SELECT employee_id, job_id, start_date AS hire_date, department_id FROM job_history;`

3. Amend the previous statement to not suppress duplicates and examine the output. How many extra rows did you get returned and which were they? Sort the output by employee\_id to make it easier to spot.

- `SELECT employee_id, job_id, hire_date, department_id FROM employees UNION ALL  
SELECT employee_id, job_id, start_date AS hire_date, department_id FROM job_history  
ORDER BY employee_id;`

4. List all employees who have not changed jobs even once. (Such employees are not found in the job\_history table)

`SELECT e.employee_id, e.job_id, e.hire_date, e.department_id FROM employees e LEFT JOIN job_history jh ON e.employee_id = jh.employee_id WHERE jh.employee_id IS NULL; There is one extra row on employee 176 with a job_id of SA_REP.`

5. List the employees that HAVE changed their jobs at least once.
- ```
SELECT DISTINCT e.employee_id, e.job_id, e.hire_date, e.department_id FROM employees e JOIN job_history jh ON e.employee_id = jh.employee_id;
```
6. Using the UNION operator, write a query that displays the employee\_id, job\_id, and salary of ALL present and past employees. If a salary is not found, then just display a 0 (zero) in its place.
- ```
SELECT employee_id, job_id, COALESCE(salary, 0) AS salary FROM employees UNION SELECT employee_id, job_id, COALESCE(salary, 0) AS salary FROM job_history;
```

221701020

221701020

## **Fundamentals of Subqueries**

1. What is the purpose of using a subquery?

- A subquery is used to perform operations that are dependent on the result of another query. It helps in breaking down complex queries, allowing you to retrieve data that can be used in the outer query's filter, calculations, or other clauses

2. What is a subquery?

- A subquery is a query embedded within another query, usually enclosed in parentheses. It provides intermediate results that are used by the outer query. It can be used in various clauses like WHERE, FROM, or SELECT.

3. What DJs on Demand d\_play\_list\_items song\_id's have the same event\_id as song\_id 45?

- `SELECT song_id FROM d_play_list_items WHERE event_id = (SELECT event_id FROM d_play_list_items WHERE song_id = 45);`

4. Which events in the DJs on Demand database cost more than event\_id = 100?

- `SELECT event_id, event_cost FROM d_events WHERE event_cost > (SELECT event_cost FROM d_events WHERE event_id = 100);`

5. Find the track number of the song that has the same CD number as "Party Music for All Occasions."

`SELECT track_number FROM d_track_listings WHERE cd_number = (SELECT cd_number FROM d_cds WHERE title = 'Party Music for All Occasions');`

6. List the DJs on Demand events whose theme code is the same as the code for “Tropical.”
- ```
SELECT event_id, theme_code FROM d_events WHERE theme_code = (SELECT theme_code
FROM d_events WHERE theme = 'Tropical');
```
7. What are the names of the Global Fast Foods staff members whose salaries are greater than the staff member whose ID is 12?
- ```
SELECT first_name, last_name FROM staff WHERE salary > (SELECT salary FROM staff
WHERE staff_id = 12);
```
8. What are the names of the Global Fast Foods staff members whose staff types are not the same as Bob Miller’s?
- ```
SELECT first_name, last_name FROM staff WHERE staff_type != (SELECT staff_type FROM
staff WHERE first_name = 'Bob' AND last_name = 'Miller');
```
9. Which Oracle employees have the same department ID as the IT department?
- ```
SELECT first_name, last_name FROM employees WHERE department_id = (SELECT
department_id FROM departments WHERE department_name = 'IT');
```
10. What are the department names of the Oracle departments that have the same location ID as Seattle?
- ```
SELECT department_name FROM departments WHERE location_id = (SELECT
location_id FROM locations WHERE city = 'Seattle');
```
11. Which statement(s) regarding subqueries is/are true?
- a. It is good programming practice to place a subquery on the right side of the comparison operator.  
False
  - b. A subquery can reference a table that is not included in the outer query’s FROM clause.  
True
  - c. Single-row subqueries can return multiple values to the outer query.  
False

## Single-Row Subqueries

1. Write a query to return all those employees who have a salary greater than that of Lorentz and are in the same department as Abel.

- ```
SELECT employee_id, first_name, last_name, salary, department_id FROM employees
WHERE salary > (SELECT salary FROM employees WHERE last_name = 'Lorentz') AND
department_id = (SELECT department_id FROM employees WHERE last_name = 'Abel');
```

2. Write a query to return all those employees who have the same job id as Rajs and were hired after Davies.

- ```
SELECT employee_id, first_name, last_name, job_id, hire_date FROM employees
WHERE job_id = (SELECT job_id FROM employees WHERE last_name = 'Rajs')
AND hire_date > (SELECT hire_date FROM employees WHERE last_name = 'Davies');
```

3. What DJs on Demand events have the same theme code as event ID = 100?

- ```
SELECT event_id, theme_code FROM d_events WHERE theme_code = (SELECT
theme_code FROM d_events WHERE event_id = 100);
```

4. What is the staff type for those Global Fast Foods jobs that have a salary less than those of any Cook staff-type jobs?

- ```
SELECT staff_type FROM staff WHERE salary < ALL (SELECT salary FROM staff
WHERE staff_type = 'Cook');
```

5. Write a query to return a list of department id's and average salaries where the department's average salary is greater than Ernst's salary.

- ```
SELECT department_id, AVG(salary) FROM employees GROUP BY department_id
HAVING
AVG(salary) > (SELECT salary FROM employees WHERE last_name = 'Ernst');
```

6. Return the department ID and minimum salary of all employees, grouped by department ID, having a minimum salary greater than the minimum salary of those employees whose department ID is not equal to 50.

- ```
SELECT department_id, MIN(salary) FROM employees GROUP BY department_id
HAVING MIN(salary) > (SELECT MIN(salary) FROM employees WHERE department_id
!= 50);
```

## Multiple-Row Subqueries

1. What will be returned by a query if it has a subquery that returns a null?
  - a. If a subquery returns NULL, the outer query will not return any rows (unless the outer query handles it using IS NULL or similar).
2. Write a query that returns jazz and pop songs. Write a multi-row subquery and use the d\_songs and d\_types tables. Include the id, title, duration, and the artist name.
  - a. 

```
SELECT id, title, duration, artist FROM d_songs WHERE type_id IN (SELECT id FROM d_types
WHERE type IN ('jazz', 'pop'));
```
3. Find the last names of all employees whose salaries are the same as the minimum salary for any department.
  - a. 

```
SELECT last_name FROM employees WHERE salary = (SELECT MIN(salary) FROM employees
GROUP BY department_id);
```
4. Which Global Fast Foods employee earns the lowest salary? Hint: You can use either a single- row or a multiple-row subquery.
  - a. 

```
SELECT first_name, last_name FROM staff WHERE salary = (SELECT MIN(salary) FROM staff);
```

5. Place the correct multiple-row comparison operators in the outer query WHERE clause of each of the following:

a. Which CDs in our d\_cds collection were produced before “Carpe Diem” was produced?

WHERE year \_\_\_\_\_(SELECT year ...

- WHERE year < (SELECT year FROM d\_cds WHERE title = 'Carpe Diem')

b. Which employees have salaries lower than any one of the programmers in the IT department?

WHERE salary \_\_\_\_\_(SELECT salary ...

WHERE salary < ALL (SELECT salary FROM employees WHERE department\_id = (SELECT department\_id FROM departments WHERE department\_name = 'IT') AND job\_id = 'Programmer')

c. What CD titles were produced in the same year as “Party Music for All Occasions” or “Carpe Diem”?

WHERE year \_\_\_\_\_(SELECT year ...

d. What song title has a duration longer than every type code 77 title?

WHERE duration \_\_\_\_\_(SELECT duration ...

- WHERE year IN (SELECT year FROM d\_cds WHERE title IN ('Party Music for All Occasions', 'Carpe Diem'))

6. If each WHERE clause is from the outer query, which of the following are true?

a. WHERE size > ANY -- If the inner query returns sizes ranging from 8 to 12, the value 9 could be returned in the outer query.

- b. WHERE book\_number IN -- If the inner query returns books numbered 102, 105, 437, and 225 then 325 could be returned in the outer query.
- c. WHERE score <= ALL -- If the inner query returns the scores 89, 98, 65, and 72, then 82 could be returned in the outer query.
- d. WHERE color NOT IN -- If the inner query returns red, green, blue, black, and then the outer query could return white.
- e. WHERE game\_date = ANY -- If the inner query returns 05-Jun-1997, 10-Dec-2002, and 2-Jan-2004, then the outer query could return 10-Sep-2002.

- True
- False
- True
- True
- True

7. The goal of the following query is to display the minimum salary for each department whose minimum salary is less than the lowest salary of the employees in department 50. However, the subquery does not execute because it has five errors. Find them, correct them, and run the query.

```
SELECT department_id  
FROM employees WHERE  
MIN(salary) HAVING  
MIN(salary) > GROUP BY  
department_id SELECT  
MIN(salary)  
WHERE department_id < 50;
```

- SELECT department\_id, MIN(salary) FROM employees WHERE department\_id < 50  
GROUP BY department\_id HAVING MIN(salary) > (SELECT MIN(salary) FROM  
employees WHERE department\_id = 50);

No data was returned from this query.

8. Which statements are true about the subquery below?

```
SELECT employee_id, last_name  
FROM employees  
WHERE salary =  
(SELECT MIN(salary)  
FROM employees  
GROUP BY department_id);
```

- a. The inner query could be eliminated simply by changing the WHERE clause to WHERE MIN(salary).
- b. The query wants the names of employees who make the same salary as the smallest salary in any department.
- c. The query first selects the employee ID and last name, and then compares that to the salaries in every department.
- d. This query will not execute.

- False
- True
- False
- False

9. Write a pair-wise subquery listing the last\_name, first\_name, department\_id, and manager\_id for all employees that have the same department\_id and manager\_id as employee 141. Exclude employee 141 from the result set.

- ```
SELECT last_name, first_name, department_id, manager_id FROM employees WHERE  
(department_id, manager_id) = (SELECT department_id, manager_id FROM employees  
WHERE employee_id = 141) AND employee_id != 141;
```

10. Write a non-pair-wise subquery listing the last\_name, first\_name, department\_id, and manager\_id for all employees that have the same department\_id and manager\_id as employee 141.

- `SELECT last_name, first_name, department_id, manager_id FROM employees WHERE department_id = (SELECT department_id FROM employees WHERE employee_id = 141) AND manager_id = (SELECT manager_id FROM employees WHERE employee_id = 141);`

## Correlated Subqueries

1. Explain the main difference between correlated and non-correlated subqueries?

### Correlated Subquery:

- Executes once for each row in the outer query.
- Refers to a column in the outer query, making it dependent on the outer query

### Non-Correlated Subquery:

- Executes independently of the outer query.
- Can run by itself and is typically executed once, with the result used in the outer query.

2. Write a query that lists the highest earners for each department. Include the last\_name, department\_id, and the salary for each employee.

- `SELECT last_name, department_id, salary FROM employees e1 WHERE salary = ( SELECT MAX(salary) FROM employees e2 WHERE e2.department_id = e1.department_id );`

3. Examine the following select statement and finish it so that it will return the last\_name, department\_id, and salary of employees who have at least one person reporting to them. So we are effectively looking for managers only. In the partially written SELECT statement, the WHERE clause will work as it is. It is simply testing for the existence of a row in the subquery.

- `SELECT last_name, department_id, salary FROM employees outer WHERE 'x' IN ( SELECT 'x' FROM employees inner WHERE inner.manager_id = outer.employee_id ) ORDER BY department_id;`

SELECT (enter columns here)  
FROM (enter table name here) outer  
WHERE 'x' IN (SELECT 'x'  
FROM (enter table name here) inner  
WHERE inner(enter column name here) = inner(enter column name here) Finish  
off the statement by sorting the rows on the department\_id column.

4. Using a WITH clause, write a SELECT statement to list the job\_title of those jobs whose maximum salary is more than half the maximum salary of the entire company. Name your subquery MAX\_CALC\_SAL. Name the columns in the result JOB\_TITLE and JOB\_TOTAL, and sort the result on JOB\_TOTAL in descending order.

Hint: Examine the jobs table. You will need to join JOBS and EMPLOYEES to display the job\_title.

- WITH MAX\_CALC\_SAL AS ( SELECT job\_id, MAX(salary) AS max\_salary FROM employees GROUP BY job\_id ) SELECT j.job\_title AS JOB\_TITLE, m.max\_salary AS JOB\_TOTAL FROM jobs j JOIN MAX\_CALC\_SAL m ON j.job\_id = m.job\_id WHERE m.max\_salary > (SELECT MAX(salary) / 2 FROM employees) ORDER BY JOB\_TOTAL DESC;

# Summarizing Queries for practice

## INSERT Statements

**Students should execute DESC tablename before doing INSERT to view the data types for each column. VARCHAR2 data-type entries need single quotation marks in the VALUES statement.**

1. Give two examples of why it is important to be able to alter the data in a database.
  - Keeping Data Current: As business information (like addresses, prices, or employee positions) changes, altering data ensures records stay accurate, preventing outdated or incorrect information from leading to mistakes in decision-making or customer interaction.
  - Correcting Errors: Mistakes in data entry can lead to inconsistencies. Having the ability to update data allows for corrections that maintain data integrity and reliability across the database.
2. DJs on Demand just purchased four new CDs. Use an explicit INSERT statement to add each CD to the copy\_d\_cds table. After completing the entries, execute a SELECT \* statement to verify your work.

CD_NUMBER	TITLE	PRODUCER	YEAR
97	Celebrate the Day	R&B Inc.	2003
98	Holiday Tunes for All Ages	Tunes are Us	2004
99	Party Music	Old Town Records	2004
100	Best of Rock and Roll	Old Town Records	2004

- INSERT INTO copy\_d\_cds (cd\_id, title, artist, genre, release\_date)  
VALUES (101, 'Greatest Hits', 'Artist A', 'Pop', '2024-10-01');
- INSERT INTO copy\_d\_cds (cd\_id, title, artist, genre, release\_date)

- VALUES (102, 'Rock Legends', 'Artist B', 'Rock', '2024-09-15');
- INSERT INTO copy\_d\_cds (cd\_id, title, artist, genre, release\_date) VALUES (103, 'Classical Essentials', 'Artist C', 'Classical', '2024-08-25');
- INSERT INTO copy\_d\_cds (cd\_id, title, artist, genre, release\_date) VALUES (104, 'Jazz Nights', 'Artist D', 'Jazz', '2024-11-10');
- SELECT \* FROM copy\_d\_cds;

3. DJs on Demand has two new events coming up. One event is a fall football party and the other event is a sixties theme party. The DJs on Demand clients requested the songs shown in the table for their events. Add these songs to the copy\_d\_songs table using an implicit INSERT statement.

- INSERT INTO copy\_d\_songs SELECT song\_id, song\_title, artist, genre, duration FROM song\_library WHERE song\_title IN ('Football Anthem', 'Retro Sixties', 'Autumn Ballad', 'Party Classics');

ID	TITLE	DURATION	TYPE_CODE
52	Surfing Summer	Not known	12
53	Victory Victory	5 min	12

4. Add the two new clients to the copy\_d\_clients table. Use either an implicit or an explicit INSERT.

CLIENT_NUMBER	FIRST_NAME	LAST_NAME	PHONE	EMAIL
6655	Ayako	Dahish	3608859030	dahisha@harbor.net
6689	Nick	Neuville	9048953049	nnicky@charter.net

- INSERT INTO copy\_d\_clients SELECT client\_id, client\_name, contact\_number FROM existing\_clients\_table WHERE client\_name IN ('Fall Football Club', 'Sixties Theme Group');

5. Add the new client's events to the copy\_d\_events table. The cost of each event has not been determined at this date.

ID	NAME	EVENT_DATE	DESCRIPTION	COST	VENUE_ID	PACKAGE_CODE	THEME_CODE	CLIENT_NUMBER
110	Ayako Anniversary	07-Jul-2004	Party for 50, sixties dress, decorations		245	79	240	6655
115	Neuville Sports Banquet	09-Sep-2004	Barbecue at residence, college alumni, 100 people		315	87	340	6689

- `INSERT INTO copy_d_events (event_id, client_id, event_name, event_date, event_cost) VALUES (301, 201, 'Fall Football Party', '2024-11-20', NULL);` `INSERT INTO copy_d_events (event_id, client_id, event_name, event_date, event_cost) VALUES (302, 202, 'Sixties Theme Party', '2024-12-05', NULL);`

Create a table called rep\_email using the following statement:

```
CREATE TABLE rep_email ( id NUMBER(3) CONSTRAINT rel_id_pk PRIMARY KEY, first_name
VARCHAR2(10), last_name VARCHAR2(10), email_address VARCHAR2(10))
```

Populate this table by running a query on the employees table that includes only those employees who are REP's.

- `INSERT INTO rep_email (id, first_name, last_name, email_address) SELECT employee_id, first_name, last_name, email FROM employees WHERE job_title LIKE '%REP%';`

221701020

## Updating Column Values and Deleting Rows

**NOTE: Copy tables in this section do not yet exist; students must create them.**

If any change is not possible, give an explanation as to why it is not possible.

1. Monique Tuttle, the manager of Global Fast Foods, sent a memo requesting an immediate change in prices. The price for a strawberry shake will be raised from \$3.59 to \$3.75, and the price for fries will increase to \$1.20. Make these changes to the copy\_f\_food\_items table.

- UPDATE copy\_f\_food\_items SET price = 3.75 WHERE item\_name = 'Strawberry Shake';
- UPDATE copy\_f\_food\_items SET price = 1.20 WHERE item\_name = 'Fries';

2. Bob Miller and Sue Doe have been outstanding employees at Global Fast Foods. Management has decided to reward them by increasing their overtime pay. Bob Miller will receive an additional \$0.75 per hour and Sue Doe will receive an additional \$0.85 per hour. Update the copy\_f\_staffs table to show these new values. (Note: Bob Miller currently doesn't get overtime pay. What function do you need to use to convert a null value to 0?)

- UPDATE copy\_f\_staffs SET overtime\_pay = NVL(overtime\_pay, 0) + 0.75 WHERE first\_name = 'Bob' AND last\_name = 'Miller';
- UPDATE copy\_f\_staffs SET overtime\_pay = NVL(overtime\_pay, 0) + 0.85 WHERE first\_name = 'Sue' AND last\_name = 'Doe';

3. Add the orders shown to the Global Fast Foods copy\_f\_orders table:

ORDER_NUMB ER	ORDER_DAT E	ORDER_TOT AL	CUST_ID	STAFF_ID
5680	June 12, 2004	159.78	145	9
5691	09-23-2004	145.98	225	12
5701	July 4, 2004	229.31	230	12

- `INSERT INTO copy_f_orders (order_number, order_date, order_total, cust_id, staff_id)  
VALUES (5680, TO_DATE('12-JUN-2004', 'DD-MON-YYYY'), 159.78, 145, 9);`
- `INSERT INTO copy_f_orders (order_number, order_date, order_total, cust_id, staff_id)  
VALUES (5691, TO_DATE('23-SEP-2004', 'DD-MON-YYYY'), 145.98, 225, 12);`

4. Add the new customers shown below to the copy\_f\_customers table. You may already have added Katie Hernandez. Will you be able to add all these records successfully?

ID	FIRS T_ NAM E	LAST_ NAME	ADDRES S	CITY	STAT E	ZIP	PHONE_NUMB ER
145	Katie	Hernandez	92 Chico Way	Los Angeles	CA	98008	8586667641
225	Daniel	Spode	1923 Silverado	Denver	CO	80219	7193343523
230	Adam	Zurn	5 Admiral Way	Seattle	WA		4258879009

- ```
INSERT INTO copy_f_orders (order_number, order_date, order_total, cust_id, staff_id)
VALUES
(5701, TO_DATE('04-JUL-2004', 'DD-MON-YYYY'), 229.31, 230, 12);
```

5. Sue Doe has been an outstanding Global Foods staff member and has been given a salary raise. She will now be paid the same as Bob Miller. Update her record in copy\_f\_staffs.

- ```
UPDATE copy_f_staffs SET salary = (SELECT salary FROM copy_f_staffs WHERE
first_name =
'Bob' AND last_name = 'Miller') WHERE first_name = 'Sue' AND last_name = 'Doe';
```

6. Global Fast Foods is expanding their staff. The manager, Monique Tuttle, has hired Kai Kim. Not all information is available at this time, but add the information shown at right.

ID	FIRST_NA ME	LAST_NA ME	BIRTHDAT E	SALARY	STAFF TYPE
25	Kai	Kim	3-Nov-1988	6.75	Order Taker

- ```
INSERT INTO copy_f_staffs (id, first_name, last_name, birthdate, salary, staff_type)
VALUES
(25, 'Kai', 'Kim', TO_DATE('03-NOV-1988', 'DD-MON-YYYY'), 6.75, 'Order Taker');
```

7. Now that all the information is available for Kai Kim, update his Global Fast Foods record to include the following: Kai will have the same manager as Sue Doe. He does not qualify for overtime. Leave the values for training, manager budget, and manager target as null.

```
UPDATE copy_f_staffs SET manager_id = (SELECT
manager_id FROM copy_f_staffs WHERE
first_name = 'Sue' AND last_name = 'Doe'),
overtime_pay = 0 WHERE first_name = 'Kai' AND
last_name = 'Kim';
```

8. Execute the following SQL statement. Record your results.

DELETE from departments

WHERE department\_id = 60;

- The record with department\_id = 60 will be deleted from the departments table if it exists.

9. Kim Kai has decided to go back to college and does not have the time to work and go to school.

Delete him from the Global Fast Foods staff. Verify that the change was made.

- DELETE FROM copy\_f\_staffs WHERE first\_name = 'Kai' AND last\_name = 'Kim';
- SELECT \* FROM copy\_f\_staffs WHERE first\_name = 'Kai' AND last\_name = 'Kim';

10. Create a copy of the employees table and call it lesson7\_emp;

Once this table exists, write a correlated delete statement that will delete any employees from the lesson7\_employees table that also exist in the job\_history table.

- CREATE TABLE lesson7\_emp AS SELECT \* FROM employees;
- DELETE FROM lesson7\_emp WHERE employee\_id IN (SELECT employee\_id FROM job\_history);

## DEFAULT Values, MERGE, and Multi-Table Inserts

- When would you want a DEFAULT value?

To auto-populate fields with current date/time (e.g., SYSDATE) for columns like creation\_date, allowing entries to record when they were added automatically.

- Currently, the Global Foods F\_PROMOTIONAL\_MENU table START\_DATE column does not have SYSDATE set as DEFAULT. Your manager has decided she would like to be able to set the starting date of promotions to the current day for some entries. This will require three steps:

- In your schema, Make a copy of the Global Foods F\_PROMOTIONAL\_MENU table using the following SQL statement:

- CREATE TABLE copy\_f\_promotional\_menus AS SELECT \* FROM f\_promotional\_menus;

- Alter the current START\_DATE column attributes using:

```
ALTER TABLE copy_f_promotional_menus MODIFY (start_date DATE DEFAULT SYSDATE);
```

- INSERT the new information and check to verify the results.

- INSERT INTO copy\_f\_promotional\_menus (promotion\_code, name, start\_date, end\_date, giveaway) VALUES (120, 'New Customer', DEFAULT, TO\_DATE('01-JUN-2005', 'DD-MON-YYYY'), '10% discount coupon');

INSERT a new row into the copy\_f\_promotional\_menus table for the manager's new promotion. The promotion code is 120. The name of the promotion is 'New Customer.' Enter DEFAULT for the start date and '01-Jun-2005' for the ending date. The giveaway is a 10% discount coupon. What was the correct syntax used?

3. Allison Plumb, the event planning manager for DJs on Demand, has just given you the following list of CDs she acquired from a company going out of business. She wants a new updated list of CDs in inventory in an hour, but she doesn't want the original D\_CDS table changed. Prepare an updated inventory list just for her.

a. Assign new cd\_numbers to each new CD acquired.

b. Create a copy of the D\_CDS table called manager\_copy\_d\_cds. What was the correct syntax used?

c. INSERT into the manager\_copy\_d\_cds table each new CD title using an INSERT statement. Make up one example or use this data:

- `INSERT INTO manager_copy_d_cds (cd_number, title, label, year) VALUES (20, 'Hello World Here I Am', 'Middle Earth Records', 1998);`

d. Use a merge statement to add to the manager\_copy\_d\_cds table, the CDs from the original table. If there is a match, update the title and year. If not, insert the data from the original table. What was the correct syntax used?

- `MERGE INTO manager_copy_d_cds tgt USING d_cds src ON (tgt.cd_number = src.cd_number)  
WHEN MATCHED THEN UPDATE SET tgt.title = src.title, tgt.year = src.year WHEN NOT  
MATCHED THEN INSERT (cd_number, title, label, year) VALUES (src.cd_number, src.title,  
src.label, src.year);`

4. Run the following 3 statements to create 3 new tables for use in a Multi-table insert statement. All 3 tables should be empty on creation, hence the WHERE 1=2 condition in the WHERE clause.

```
CREATE TABLE sal_history (employee_id, hire_date, salary) AS  
SELECT employee_id, hire_date, salary  
FROM employees  
WHERE 1=2;  
CREATE TABLE mgr_history (employee_id, manager_id, salary)  
AS SELECT employee_id, manager_id, salary  
FROM employees  
WHERE 1=2;  
CREATE TABLE special_sal (employee_id, salary)  
AS SELECT employee_id, salary  
FROM employees  
WHERE 1=2;
```

Once the tables exist in your account, write a Multi-Table insert statement to first select the employee\_id, hire\_date, salary, and manager\_id of all employees. If the salary is more than 20000 insert the employee\_id and salary into the special\_sal table. Insert the details of employee\_id, hire\_date, and salary into the sal\_history table. Insert the employee\_id, manager\_id, and salary into the mgr\_history table.

You should get a message back saying 39 rows were inserted. Verify you get this message and verify you have the following number of rows in each table:

Sal\_history: 19 rows  
Mgr\_history: 19 rows  
Special\_sal: 1

## Creating Tables

1. Complete the GRADUATE CANDIDATE table instance chart. Credits is a foreign-key column referencing the requirements table.
  - CREATE TABLE grad\_candidates ( candidate\_id NUMBER PRIMARY KEY, first\_name VARCHAR2(50), last\_name VARCHAR2(50), credits NUMBER, FOREIGN KEY (credits) REFERENCES requirements(credit\_id) );
2. Confirm creation of the table using DESCRIBE.
  - DESCRIBE grad\_candidates;
3. Create a new table using a subquery. Name the new table your last name – e.g., smith\_table. Using a subquery, copy grad\_candidates into smith\_table.
  - CREATE TABLE lastname\_table AS SELECT \* FROM grad\_candidates;
4. Insert your personal data into the table created in question 4.
  - INSERT INTO lastname\_table (candidate\_id, first\_name, last\_name, credits) VALUES (1, 'YourFirstName', 'YourLastName', <credits\_value>);

## Modifying a Table

Before beginning the practice exercises, execute a DESCRIBE for each of the following tables: o\_employees and o\_jobs. These tables will be used in the exercises. You will need to know which columns do not allow null values.

**NOTE: If students have not already created the o\_employees, o\_departments, and o\_jobs tables they should create them using the four steps outlined in the practice.**

1. Create the three o\_tables – jobs, employees, and departments – using the syntax:

- CREATE TABLE o\_jobs ( job\_id NUMBER PRIMARY KEY, job\_title VARCHAR2(50) NOT NULL, min\_salary NUMBER, max\_salary NUMBER );
- CREATE TABLE o\_employees ( employee\_id NUMBER PRIMARY KEY, first\_name VARCHAR2(50), last\_name VARCHAR2(50) NOT NULL, job\_id NUMBER REFERENCES o\_jobs(job\_id), salary NUMBER NOT NULL, department\_id NUMBER );
- CREATE TABLE o\_departments ( department\_id NUMBER PRIMARY KEY, department\_name VARCHAR2(50) NOT NULL, manager\_id NUMBER );

2. Add the Human Resources job to the jobs table:

- INSERT INTO o\_jobs (job\_id, job\_title, min\_salary, max\_salary) VALUES (10, 'Human Resources', 40000, 70000);

3. Add the three new employees to the employees table:

- INSERT INTO o\_employees (employee\_id, first\_name, last\_name, job\_id, salary, department\_id) VALUES (101, 'John', 'Doe', 10, 45000, 1);
- INSERT INTO o\_employees (employee\_id, first\_name, last\_name, job\_id, salary, department\_id) VALUES (102, 'Jane', 'Smith', 10, 50000, 1);

4. Add Human Resources to the departments table:

- `INSERT INTO o_employees (employee_id, first_name, last_name, job_id, salary, department_id) VALUES (103, 'Alex', 'Johnson', 10, 55000, 2);`

5. Why is it important to be able to modify a table?

- `INSERT INTO o_departments (department_id, department_name, manager_id) VALUES (1, 'Human Resources', 101);`

1. CREATE a table called Artists.

a. Add the following to the table:

artist ID, first name, last name, band name, email, hourly rate, song ID from d\_songs table

- `CREATE TABLE Artists ( artist_id NUMBER PRIMARY KEY, first_name VARCHAR2(50), last_name VARCHAR2(50), band_name VARCHAR2(100), email VARCHAR2(100), hourly_rate NUMBER, song_id NUMBER REFERENCES d_songs(song_id) );`

b. INSERT one artist from the d\_songs table.

- `INSERT INTO Artists (artist_id, first_name, last_name, band_name, email, hourly_rate, song_id) VALUES (1, 'Sam', 'Hill', 'The Hills', 'sam.hill@example.com', 50, 101);`

c. INSERT one artist of your own choosing; leave song\_id blank.

- `INSERT INTO Artists (artist_id, first_name, last_name, band_name, email, hourly_rate) VALUES (2, 'Jamie', 'Lynn', 'Solo', 'jamie.lynn@example.com', 45);`

d. Give an example how each of the following may be used on the table that you have created:

1) ALTER TABLE

- `ALTER TABLE Artists ADD performance_date DATE;`

`DROP TABLE`

- `DROP TABLE Artists;`

3) RENAME TABLE

- `ALTER TABLE Artists RENAME TO Music_Artists;`

4) TRUNCATE

- `TRUNCATE TABLE Artists;`

5) COMMENT ON TABLE

- COMMENT ON TABLE Artists IS 'This table holds artist details and performance rates.';

a. Explain to students how you want the DJs on Demand artist's table assignment to be completed.

Students should be able to list the term followed by the SQL statement they used. For example:

1. In your o\_employees table, enter a new column called "Termination." The datatype for the new column should be VARCHAR2. Set the DEFAULT for this column as SYSDATE to appear as character data in the format: February 20th, 2003.

- ALTER TABLE o\_employees ADD termination VARCHAR2(30) DEFAULT TO\_CHAR(SYSDATE, 'Month DDth, YYYY');

2. Create a new column in the o\_employees table called start\_date. Use the TIMESTAMP WITH LOCAL TIME ZONE as the datatype.

- ALTER TABLE o\_employees ADD start\_date TIMESTAMP WITH LOCAL TIME ZONE;

3. Truncate the o\_jobs table. Then do a SELECT \* statement. Are the columns still there? Is the data still there?

- TRUNCATE TABLE o\_jobs;
- SELECT \* FROM o\_jobs;

4. What is the distinction between TRUNCATE, DELETE, and DROP for tables?

- a. **TRUNCATE:** Removes all rows without logging individual row deletions; table structure remains.
- b. **DELETE:** Removes specific rows or all rows while logging individual deletions; table structure remains.
- c. **DROP:** Deletes the entire table including its structure.

5. List the changes that can and cannot be made to a column.

- 

6. Add the following comment to the o\_jobs table:

"New job description added"

View the data dictionary to view your comments.

- COMMENT ON TABLE o\_jobs IS 'New job description added';

7. Add the following comment to the o\_jobs table: "New job description added"

View the data dictionary to view your comments.

- ALTER TABLE o\_jobs RENAME TO o\_job\_description;

#### 8.F\_staffs table exercises:

A. Create a copy of the f\_staffs table called copy\_f\_staffs and use this copy table for the remaining labs in this lesson.

- CREATE TABLE copy\_f\_staffs AS SELECT \* FROM f\_staffs

B. Describe the new table to make sure it exists.

- DESCRIBE copy\_f\_staffs;

C. Drop the table.

- DROP TABLE copy\_f\_staffs;

D. Try to select from the table.

- SELECT \* FROM copy\_f\_staffs;

E. Investigate your recyclebin to see where the table went.

- SELECT OBJECT\_NAME FROM recyclebin WHERE ORIGINAL\_NAME = 'COPY\_F\_STAFFS';

a. Try to select from the dropped table by using the value stored in the OBJECT\_NAME column.

You will need to copy and paste the name as it is exactly, and enclose the new name in “ “ (double quotes). So if the dropped name returned to you is BIN\$Q+x1nJdcUnngQESYELViIdQ==\$0, you need to write a query that refers to “BIN\$Q+x1nJdcUnngQESYELViIdQ==\$0”.

- SELECT \* FROM "BIN\$Q+x1nJdcUnngQESYELViIdQ==\$0";

b. Undrop the table.

- FLASHBACK TABLE copy\_f\_staffs TO BEFORE DROP;

c. Describe the table.

- DESCRIBE copy\_f\_staffs;

11. Still working with the copy\_f\_staffs table, perform an update on the table.

- UPDATE copy\_f\_staffs SET salary = 12 WHERE last\_name = 'Doe' AND first\_name = 'Sue'; COMMIT;

a. Issue a select statement to see all rows and all columns from the copy\_f\_staffs table; •

- SELECT \* FROM copy\_f\_staffs;

- b. Change the salary for Sue Doe to 12 and commit the change.
- `UPDATE copy_f_staffs SET salary = 2 WHERE last_name = 'Doe' AND first_name = 'Sue'; COMMIT;`
- c. For Sue Doe, update the salary to 2 and commit the change.
- `UPDATE copy_f_staffs SET salary = <original_salary> WHERE last_name = 'Doe' AND first_name = 'Sue'; COMMIT;`
- d. Issue a select statement to see all rows and all columns from the `copy_f_staffs` table;
- `SELECT * FROM copy_f_staffs;`
- e. Now, issue a FLASHBACK QUERY statement against the `copy_f_staffs` table, so you can see all the changes made.
- `SELECT * FROM copy_f_staffs VERSIONS BETWEEN TIMESTAMP MINVALUE AND MAXVALUE WHERE last_name = 'Doe' AND first_name = 'Sue';`
- f. Investigate the result of f), and find the original salary and update the `copy_f_staffs` table salary column for Sue Doe back to her original salary.
- `UPDATE copy_f_staffs SET salary = <original_salary> WHERE last_name = 'Doe' AND first_name = 'Sue';`

**Ex. No: 14**

**Date:**

**Register No: 221701020**

**Name: Hemalatha R**

## **Intro to Constraints; NOT NULL and UNIQUE Constraints**

Global Fast Foods has been very successful this past year and has opened several new stores. They need to add a table to their database to store information about each of their store's locations. The owners want to make sure that all entries have an identification number, date opened, address, and city and that no other entry in the table can have the same email address. Based on this information, answer the following questions about the global\_locations table. Use the table for your answers.

| <b>Global Fast Foods global_locations Table</b> |             |               |                       |              |                      |                     |
|-------------------------------------------------|-------------|---------------|-----------------------|--------------|----------------------|---------------------|
| <b>NAME</b>                                     | <b>TYPE</b> | <b>LENGTH</b> | <b>PRECISIO<br/>N</b> | <b>SCALE</b> | <b>NULLABL<br/>E</b> | <b>DEFAUL<br/>T</b> |
| Id                                              |             |               |                       |              |                      |                     |
| name                                            |             |               |                       |              |                      |                     |
| date_opened                                     |             |               |                       |              |                      |                     |
| address                                         |             |               |                       |              |                      |                     |
| city                                            |             |               |                       |              |                      |                     |
| zip/postal code                                 |             |               |                       |              |                      |                     |
| phone                                           |             |               |                       |              |                      |                     |
| email                                           |             |               |                       |              |                      |                     |
| manager_id                                      |             |               |                       |              |                      |                     |
| Emergency                                       |             |               |                       |              |                      |                     |

|         |  |  |  |  |  |  |
|---------|--|--|--|--|--|--|
| contact |  |  |  |  |  |  |
|---------|--|--|--|--|--|--|

1. What is a “constraint” as it relates to data integrity?
  - A constraint is a rule applied to a database table column to ensure the accuracy and reliability of the data within the table. Constraints enforce data integrity by restricting the type of data that can be stored in a column, such as requiring unique values, forbidding null values, or enforcing valid relationships between tables.
  
2. What are the limitations of constraints that may be applied at the column level and at the table level?

#### **Column Level Constraints:**

- They can only be applied to single columns directly within the column definition.
- They are limited to constraints that are specific to individual column values, such as NOT NULL, DEFAULT, CHECK, UNIQUE, and PRIMARY KEY on single columns.

#### **Table Level Constraints:**

- These can apply to one or multiple columns within a table, making them more flexible for complex constraints, such as composite keys or multi-column checks.
  - However, they may not offer the same direct syntax as column-level constraints for simpler constraints like NOT NULL.
- 
3. Why is it important to give meaningful names to constraints?
    - Using meaningful names for constraints makes it easier to understand their purpose when reviewing database schemas or logs. Clear names improve readability, maintainability, and troubleshooting because they provide insight into each constraint’s role, making the database structure easier to manage.
  
  4. Based on the information provided by the owners, choose a datatype for each column. Indicate the length, precision, and scale for each NUMBER datatype.
    - NUMBER(6, 0): Integer numbers up to 6 digits.
    - NUMBER(7, 2): Numbers up to 7 digits with 2 decimal places.
  
  5. Use “(nullable)” to indicate those columns that can have null values.
    - location\_description VARCHAR2(255) (nullable)

6. Write the CREATE TABLE statement for the Global Fast Foods locations table to define the constraints at the column level.

- CREATE TABLE Global\_Fast\_Foods\_Locations ( location\_id NUMBER(5) CONSTRAINT loc\_id\_pk PRIMARY KEY, location\_name VARCHAR2(50) NOT NULL, address VARCHAR2(100) NOT NULL, city VARCHAR2(50), state CHAR(2), zip\_code VARCHAR2(10), phone\_number VARCHAR2(15), manager\_id NUMBER(5) CONSTRAINT loc\_mgr\_fk REFERENCES employees(employee\_id), UNIQUE (location\_name) );

7. Execute the CREATE TABLE statement in Oracle Application Express.

- Run the CREATE TABLE command in Oracle Application Express (or similar SQL execution environment) to create the table as defined.

8. Execute a DESCRIBE command to view the Table Summary information.

- DESCRIBE Global\_Fast\_Foods\_Locations;

9.

Rewrite the CREATE TABLE statement for the Global Fast Foods locations table to define the UNIQUE constraints at the table level. Do not execute this statement.

| NAME       | TYPE     | LENGTH | PRECISION | SCALE | NULLABLE | DEFAULT |
|------------|----------|--------|-----------|-------|----------|---------|
| id         | number   | 4      |           |       |          |         |
| loc_name   | varchar2 | 20     |           |       | X        |         |
|            | date     |        |           |       |          |         |
| address    | varchar2 | 30     |           |       |          |         |
| city       | varchar2 | 20     |           |       |          |         |
| zip_postal | varchar2 | 20     |           |       | X        |         |
| phone      | varchar2 | 15     |           |       | X        |         |
| email      | varchar2 | 80     |           |       | X        |         |
| manager_id | number   | 4      |           |       | X        |         |
| contact    | varchar2 | 40     |           |       | X        |         |

- CREATE TABLE Global\_Fast\_Foods\_Locations (id NUMBER(5) CONSTRAINT loc\_id\_pk PRIMARY KEY, location\_name VARCHAR2(50) NOT NULL, address VARCHAR2(100) NOT NULL, city VARCHAR2(50), state CHAR(2), zip\_code VARCHAR2(10), phone\_number VARCHAR2(15), manager\_id NUMBER(5) CONSTRAINT loc\_mgr\_fk REFERENCES employees(employee\_id), CONSTRAINT loc\_name\_uk UNIQUE (location\_name) );

221701020

# **PRIMARY KEY, FOREIGN KEY, and CHECK Constraints**

1. What is the purpose of a
  - I. PRIMARY KEY
  - II. FOREIGN KEY
  - III. CHECK CONSTRAINT
  - **PRIMARY KEY:** Uniquely identifies each record in a table, ensuring uniqueness and prohibiting null values. Essential for establishing relationships.
  - **FOREIGN KEY:** Links two tables by referencing the primary key of another table, ensuring only valid references are allowed for referential integrity.
  - **CHECK CONSTRAINT:** Restricts values in a column to meet specific conditions, enforcing valid data entry according to defined rules.

2. Using the column information for the animals table below, name constraints where applicable at the table level, otherwise name them at the column level. Define the primary key (animal\_id). The license\_tag\_number must be unique. The admit\_date and vaccination\_date columns cannot contain null values.

```
animal_id NUMBER(6)
name VARCHAR2(25)
license_tag_number
NUMBER(10) admit_date
DATE adoption_id
NUMBER(5),
vaccination_date DATE
```

- CREATE TABLE animals ( animal\_id NUMBER(6) CONSTRAINT animal\_id\_pk PRIMARY KEY, name VARCHAR2(25), license\_tag\_number NUMBER(10) CONSTRAINT license\_tag\_number\_uk UNIQUE, admit\_date DATE NOT NULL, adoption\_id NUMBER(5), vaccination\_date DATE NOT NULL );

3. Create the animals table. Write the syntax you will use to create the table.

- CREATE TABLE animals ( animal\_id NUMBER(6) CONSTRAINT animal\_id\_pk PRIMARY KEY, name VARCHAR2(25), license\_tag\_number NUMBER(10) CONSTRAINT license\_tag\_number\_uk UNIQUE, admit\_date DATE NOT NULL, adoption\_id NUMBER(5), vaccination\_date DATE NOT NULL );

4. Enter one row into the table. Execute a SELECT \* statement to verify your input. Refer to the graphic below for input.

| ANIMAL_ID | NAME | LICENSE_TAG_NUM<br>BER | ADMIT_DATE  | ADOPTION_ID | VACCINATION_DATE |
|-----------|------|------------------------|-------------|-------------|------------------|
| 101       | Spot | 35540                  | 10-Oct-2004 | 205         | 12-Oct-2004      |

- INSERT INTO animals (animal\_id, name, license\_tag\_number, admit\_date, adoption\_id, vaccination\_date) VALUES (101, 'Spot', 35540, TO\_DATE('10-Oct-2004', 'DD-Mon-YYYY'), 205, TO\_DATE('12-Oct-2004', 'DD-Mon-YYYY'));
- SELECT \* FROM animals;

5. Write the syntax to create a foreign key (adoption\_id) in the animals table that has a corresponding primary-key reference in the adoptions table. Show both the column-level and table-level syntax. Note that because you have not actually created an adoptions table, no adoption\_id primary key exists, so the foreign key cannot be added to the animals table.

- adoption\_id NUMBER(5) CONSTRAINT animals\_adoption\_fk REFERENCES adoptions(adoption\_id)
- CREATE TABLE animals ( animal\_id NUMBER(6) CONSTRAINT animal\_id\_pk PRIMARY KEY, name VARCHAR2(25), license\_tag\_number NUMBER(10) CONSTRAINT license\_tag\_number\_uk UNIQUE, admit\_date DATE NOT NULL,

```
adoption_id NUMBER(5), vaccination_date DATE NOT NULL, CONSTRAINT  
animals_adoption_fk FOREIGN KEY (adoption_id) REFERENCES adoptions(adoption_id)  
);
```

6. What is the effect of setting the foreign key in the ANIMAL table as:
  - a. ON DELETE CASCADE
  - b. ON DELETE SET NULL
  - If a row in the adoptions table (referenced table) is deleted, all rows in the animals table (referencing table) that reference it will also be automatically deleted. This maintains referential integrity by removing dependent records.
  - If a row in the adoptions table is deleted, the adoption\_id in the animals table for that row is set to NULL rather than deleting the row. This keeps the referencing rows intact but removes the relationship.
  
7. What are the restrictions on defining a CHECK constraint?
  - A CHECK constraint must contain a logical expression that returns a Boolean value.
  - It cannot reference columns in other tables; it must only apply to the column(s) within the same row.

## PRACTICE PROBLEM

### Managing Constraints

Using Oracle Application Express, click the SQL Workshop tab in the menu bar. Click the Object Browser and verify that you have a table named copy\_d\_clients and a table named copy\_d\_events. If you don't have these tables in your schema, create them before completing the exercises below. Here is how the original tables are related. The d\_clients table has a primary key client\_number. This has a primary-key constraint and it is referenced in the foreign-key constraint on the d\_events table.

**NOTE: The practice exercises use the d\_clients and d\_events tables in the DJs on Demand database. Students will work with copies of these two tables named copy\_d\_clients and copy\_d\_events. Make sure they have new copies of the tables (without changes made from previous exercises). Remember, tables copied using a subquery do not have the integrity constraints as established in the original tables. When using the SELECT**

## statement to view the constraint name, the tablenames must be all capital letters

1. What are four functions that an ALTER statement can perform on constraints?
  - **ADD:** Adds a new constraint to a table.
  - **DROP:** Removes an existing constraint from a table.
  - **MODIFY:** Modifies an existing constraint (e.g., changing the conditions of a CHECK constraint).
  - **RENAME:** Changes the name of an existing constraint.
2. Since the tables are copies of the original tables, the integrity rules are not passed onto the new tables; only the column datatype definitions remain. You will need to add a PRIMARY KEY constraint to the copy\_d\_clients table. Name the primary key copy\_d\_clients\_pk . What is the syntax you used to create the PRIMARY KEY constraint to the copy\_d\_clients.table?
  - `ALTER TABLE copy_d_clients ADD CONSTRAINT copy_d_clients_pk PRIMARY KEY (client_number);`
3. Create a FOREIGN KEY constraint in the copy\_d\_events table. Name the foreign key copy\_d\_events\_fk. This key references the copy\_d\_clients table client\_number column. What is the syntax you used to create the FOREIGN KEY constraint in the copy\_d\_events table?
  - `ALTER TABLE copy_d_events ADD CONSTRAINT copy_d_events_fk FOREIGN KEY (client_number) REFERENCES copy_d_clients(client_number);`
4. Use a SELECT statement to verify the constraint names for each of the tables. Note that the tablenames must be capitalized.
  - `SELECT constraint_name FROM user_constraints WHERE table_name = 'COPY_D_CLIENTS';`
  - a. The constraint name for the primary key in the copy\_d\_clients table is \_\_\_\_\_.
    - The constraint name for the primary key in the copy\_d\_clients table is COPY\_D\_CLIENTS\_PK.

5. Drop the PRIMARY KEY constraint on the copy\_d\_clients table. Explain your results.

- `ALTER TABLE copy_d_clients DROP CONSTRAINT copy_d_clients_pk;`

6. Add the following event to the copy\_d\_events table. Explain your results.

| ID  | NAME              | EVENT_DATE  | DESCRIPTION                    | COST | VENUE_ID | PACKAGE_CODE | THEME_CODE | CLIENT_NUMBER |
|-----|-------------------|-------------|--------------------------------|------|----------|--------------|------------|---------------|
| 140 | Cline Bas Mitzvah | 15-Jul-2004 | Church and Private Home formal | 4500 | 105      | 87           | 77         | 7125          |

- `INSERT INTO copy_d_events (ID, NAME, EVENT_DATE, DESCRIPTION, COST, VENUE_ID, PACKAGE_CODE, THEME_CODE, CLIENT_NUMBER) VALUES (140, 'Cline Bas Mitzvah', TO_DATE('15-`

`Jul-2004', 'DD-Mon-YYYY'), 'Church and Private Home formal', 4500, 105, 87, 77, 7125);`

7. Create an ALTER TABLE query to disable the primary key in the copy\_d\_clients table. Then add the values from #6 to the copy\_d\_events table. Explain your results.

- `ALTER TABLE copy_d_clients DISABLE CONSTRAINT copy_d_clients_pk;`

8. Repeat question 6: Insert the new values in the copy\_d\_events table. Explain your results.

- 

9. Enable the primary-key constraint in the copy\_d\_clients table. Explain your results.

- `ALTER TABLE copy_d_clients ENABLE CONSTRAINT copy_d_clients_pk;`

10. If you wanted to enable the foreign-key column and reestablish the referential integrity between these two tables, what must be done?

- Ensure that all values in the foreign key column (client\_number in copy\_d\_events) exist in the parent table (copy\_d\_clients).
- Enable the foreign key constraint:

`ALTER TABLE copy_d_events ENABLE CONSTRAINT copy_d_events_fk;`

11. Why might you want to disable and then re-enable a constraint?

- To allow certain operations, like bulk inserts or updates, that would violate the constraints (e.g., inserting duplicate values or temporarily removing a value restriction).
  - To improve performance during operations like mass data loading or maintenance tasks.
  - To allow changes to the table structure (e.g., modifying or dropping columns).
12. Query the data dictionary for some of the constraints that you have created. How does the data dictionary identify each constraint type?
- `SELECT constraint_name, constraint_type FROM user_constraints WHERE table_name = 'COPY_D_CLIENTS'`

221701020

**Ex. No: 15**

**Date:**

**Register No: 221701020**

**Name: Hemalatha R**

---

## **Creating Views**

.What are three uses for a view from a DBA's perspective?

### **Three Uses for a View from a DBA's Perspective:**

1. **Data Security:** Views can be used to restrict access to sensitive data by hiding specific columns or rows. For example, a view can expose only the necessary information to a particular user role, preventing unauthorized access.
2. **Data Simplification:** Views can simplify complex queries by combining data from multiple tables or by filtering and transforming data. This can make it easier for users to access and analyze the data they need.
3. **Data Consistency:** Views can be used to enforce data consistency by ensuring that data is always accessed through a defined and controlled interface. This can help to prevent accidental data corruption and inconsistencies.

2.Create a simple view called view\_d\_songs that contains the ID, title and artist from the DJs on Demand table for each “New Age” type code. In the subquery, use the alias “Song Title” for the title column.

Ans:

```
CREATE VIEW view_d_songs
```

```
AS
```

```
SELECT song_id AS ID,
```

```
title AS  
"Song Title",  
artist  
FROM djs_on_demand  
WHERE type_code = 'New Age';
```

3.SELECT \* FROM view\_d\_songs. What was returned?

221701020

Ans: SELECT \* FROM view\_d\_songs;

221701020

4.REPLACE view\_d\_songs. Add type\_code to the column list. Use aliases for all columns. Or use alias after the CREATE statement as shown.

Ans:

```
CREATE OR REPLACE VIEW view_d_songs
AS
SELECT song_id AS ID,
       title AS
"Song Title",
       artist,
       type_code AS "Song Type"
FROM djs_on_demand
WHERE type_code = 'New Age';
```

5.Tsang, the disk jockey for DJs on Demand, needs a list of the past events and those planned for the coming months so he can make arrangements for each event's equipment setup. As the company manager, you do not want him to have access to the price that clients paid for their events. Create a view for Jason to use that displays the name of the event, the event date, and the theme description. Use aliases for each column name.

Ans:

```
CREATE VIEW jason_event_view
AS
SELECT event_name AS "Event Name",
       event_date AS "Event Date",
       theme_description AS "Theme
Description"
FROM events;
```

6. It is company policy that only upper-level management be allowed access to individual employee salaries. The department managers, however, need to know the minimum, maximum, and average salaries, grouped by department. Use the Oracle database to prepare a view that displays the needed information for department managers.

221701020

Ans:

221701020

```
CREATE VIEW dept_salary_summary  
AS  
SELECT department_id,  
       MIN(salary) AS min_salary,  
       MAX(salary) AS max_salary,  
       AVG(salary) AS avg_salary  
FROM employees  
GROUP BY department_id;
```

## DML Operations and Views

Use the DESCRIBE statement to verify that you have tables named copy\_d\_songs, copy\_d\_events, copy\_d\_cds, and copy\_d\_clients in your schema. If you don't, write a query to create a copy of each.

Ans:

```
DESCRIBE copy_d_songs;  
DESCRIBE copy_d_events;  
DESCRIBE copy_d_cds;  
DESCRIBE copy_d_clients;
```

Use the same syntax but change table\_name of the other tables.

2. Use the CREATE or REPLACE option to create a view of *all* the columns in the copy\_d\_songs table called view\_copy\_d\_songs.

Ans:

```
SELECT TABLE_NAME, COLUMN_NAME, UPDATABLE  
FROM USER_UPDATABLE_COLUMNS  
WHERE TABLE_NAME = 'COPY_D_SONGS';
```

3. Use view\_copy\_d\_songs to INSERT the following data into the underlying copy\_d\_songs table. Execute a SELECT \* from copy\_d\_songs to verify your DML command. See the graphic.

| ID | TITLE       | DURATION | ARTIST   | TYPE_CODE |
|----|-------------|----------|----------|-----------|
| 88 | Mello Jello | 2        | The What | 4         |

Ans:

```
CREATE OR REPLACE VIEW view_copy_d_songs  
AS  
SELECT * FROM copy_d_songs;
```

4. Create a view based on the DJs on Demand COPY\_D\_CDS table. Name the view read\_copy\_d\_cds. Select all columns to be included in the view. Add a WHERE clause to restrict the year to 2000. Add the WITH READ ONLY option.

Ans:

```
INSERT INTO view_copy_d_songs (id, title, duration, artist, type_code)  
VALUES (88, 'Mello Jello', 2, 'The What', 4);
```

5. Using the read\_copy\_d\_cds view, execute a DELETE FROM read\_copy\_d\_cds WHERE cd\_number

= 90;

Ans:

```
CREATE OR REPLACE VIEW read_copy_d_cds  
AS  
SELECT * FROM copy_d_cds  
WHERE year = 2000  
WITH READ ONLY;
```

Use REPLACE to modify read\_copy\_d\_cds. Replace the READ ONLY option with WITH CHECK OPTION CONSTRAINT ck\_read\_copy\_d\_cds. Execute a SELECT \* statement to verify that the view exists.

Ans:

```
DELETE FROM read_copy_d_cds WHERE cd_number = 90;
```

7. Use the read\_copy\_d\_cds view to delete any CD of year 2000 from the underlying copy\_d\_cds.

Ans:

```
CREATE OR REPLACE VIEW read_copy_d_cds  
AS  
SELECT * FROM copy_d_cds  
WHERE year = 2000  
WITH CHECK OPTION CONSTRAINT ck_read_copy_d_cds;
```

8. Use the read\_copy\_d\_cds view to delete cd\_number 90 from the underlying copy\_d\_cds table.

Ans:

DELETE FROM read\_copy\_d\_cds WHERE cd\_number = 90;

9. Use the read\_copy\_d\_cds view to delete year 2001 records.

Ans:

DELETE FROM read\_copy\_d\_cds WHERE year = 2001;

10. Execute a SELECT \* statement for the base table copy\_d\_cds. What rows were deleted?

Ans:

SELECT \* FROM copy\_d\_cds;

11. What are the restrictions on modifying data through a view?

Ans:

#### **Restrictions on Modifying Data Through a View:**

- **Read-Only Views:** Cannot be used for INSERT, UPDATE, or DELETE operations.
- **Updatable Views:** Can be used for DML operations, but there are limitations. The view must be based on a single base table, and the underlying table must allow modifications.

12. What is Moore's Law? Do you consider that it will continue to apply indefinitely? Support your opinion with research from the internet.

Ans:

Moore's Law states that the number of transistors in a dense integrated circuit doubles approximately every two years. While it has held true for decades, its continued validity is a subject of debate. Factors like physical limitations and diminishing returns may slow down the pace of technological advancement.

13. What is the “singularity” in terms of computing?

Ans:

The singularity refers to a hypothetical future point in time at which technological growth becomes uncontrollable and irreversible, resulting in unforeseeable changes to human civilization. This concept is often associated with the development of artificial general intelligence, which could surpass human intelligence and potentially lead to significant societal and ethical implications.

221701020

## Managing Views

1. Create a view from the copy\_d\_songs table called view\_copy\_d\_songs that includes only the title and artist. Execute a SELECT \* statement to verify that the view exists.

```
CREATE OR REPLACE VIEW view_copy_d_songs
AS
SELECT title, artist
FROM copy_d_songs;
```

2. Issue a DROP view\_copy\_d\_songs. Execute a SELECT \* statement to verify that the view has been deleted.

Ans:

```
DROP VIEW view_copy_d_songs;
```

```
SELECT * FROM view_copy_d_songs;
```

- 3.Create a query that selects the last name and salary from the Oracle database. Rank the salaries from highest to lowest for the top three employees.

Ans:

```
SELECT last_name, salary  
FROM employees  
ORDER BY salary DESC  
FETCH FIRST 3 ROWS ONLY;
```

- 4.Construct an inline view from the Oracle database that lists the last name, salary, department ID, and maximum salary for each department. Hint: One query will need to calculate maximum salary by department ID.

Ans:

```
SELECT last_name, salary, department_id,  
(SELECT MAX(salary)  
FROM employees  
WHERE department_id = e.department_id) AS max_salary  
FROM employees e;
```

5. Create a query that will return the staff members of Global Fast Foods ranked by salary from

lowest to highest.

Ans:

```
SELECT last_name, salary, department_id  
FROM employees  
WHERE department_id = 'Global Fast Foods'  
ORDER BY salary ASC;
```

## Indexes and Synonyms

1. What is an index and what is it used for?

Ans:

An index is a data structure that improves the speed of data retrieval operations on a database table. It works by creating a sorted list of values and their corresponding row locations, similar to an index in a book. When a query is executed, the database can use the index to quickly locate the relevant rows, rather than scanning the entire table.

2. What is a ROWID, and how is it used?

Ans:

A ROWID is a unique identifier assigned to each row in an Oracle database table. It is a physical address that points to the specific location of the row data on disk. ROWIDs are used internally by Oracle to efficiently locate and access rows. They are often used in conjunction with indexes to optimize query performance.

3. When will an index be created automatically?

Ans:

Oracle automatically creates indexes in the following situations:

- **Primary Key Constraints:** When a primary key constraint is defined on a column or a set of columns, Oracle automatically creates a unique index on those columns.
- **Unique Constraints:** When a unique constraint is defined on a column or a set of columns, Oracle automatically creates a unique index on those columns.
- **Foreign Key Constraints:** When a foreign key constraint is defined, Oracle may create an index on the foreign key column to improve join performance.

4. Create a nonunique index (foreign key) for the DJs on Demand column (cd\_number) in the D\_TRACK\_LISTINGS table. Use the Oracle Application Express SQL Workshop Data Browser to confirm that the index was created.

Ans:

```
CREATE INDEX idx_d_track_listings_cd_number  
ON d_track_listings (cd_number);
```

5. Use the join statement to display the indexes and uniqueness that exist in the data dictionary for the DJs on Demand D\_SONGS table.

Ans:

```
SELECT index_name, table_name, uniqueness  
FROM user_indexes  
WHERE table_name = 'D_SONGS';
```

6. Use a SELECT statement to display the index\_name, table\_name, and uniqueness from the data dictionary USER\_INDEXES for the DJs on Demand D\_EVENTS table.

Ans:

```
SELECT index_name, table_name, uniqueness  
FROM user_indexes  
WHERE table_name = 'D_EVENTS';
```

7. Write a query to create a synonym called dj\_tracks for the DJs on Demand d\_track\_listings table.
8. Create a function-based index for the last\_name column in DJs on Demand D\_PARTNERS table that makes it possible not to have to capitalize the table name for searches. Write a SELECT statement that would use this index.

Ans:

```
CREATE INDEX idx_d_partners_upper_last_name  
ON d_partners (UPPER(last_name));
```

```
SELECT * FROM d_partners  
WHERE UPPER(last_name) = 'SMITH';
```

9. Create a synonym for the D\_TRACK\_LISTINGS table. Confirm that it has been created by querying the data dictionary.

Ans:

```
CREATE SYNONYM track_list FOR d_track_listings;
```

10. Drop the synonym that you created in question

Ans:

```
DROP SYNONYM track_list;
```

221701020

**Ex. No: 16**

**Date:**

**Register No.: 221701020**

**Name: Hemalatha R**

---

## **OTHER DATABASE OBJECTS**

### **Objectives**

After the completion of this exercise, the students will be able to do the following:

- Create, maintain, and use sequences
- Create and maintain indexes

### **Database Objects**

Many applications require the use of unique numbers as primary key values. You can either build code into the application to handle this requirement or use a sequence to generate unique numbers. If you want to improve the performance of some queries, you should consider creating an index.

You

can also use indexes to enforce uniqueness on a column or a collection of columns.

You can provide alternative names for objects by using synonyms.

### **What Is a Sequence?**

A sequence:

- Automatically generates unique numbers
- Is a sharable object
- Is typically used to create a primary key value
- Replaces application code
- Speeds up the efficiency of accessing sequence values when cached in memory

## The CREATE SEQUENCE Statement Syntax

Define a sequence to generate sequential numbers automatically:

```
CREATE SEQUENCE sequence
[INCREMENT BY n]
[START WITH n]
[{:MAXVALUE n | NOMAXVALUE}]
[{:MINVALUE n | NOMINVALUE}]
[{:CYCLE | NOCYCLE}]
[{:CACHE n | NOCACHE}];
```

### In the syntax:

*sequence* is the name of the sequence generator

INCREMENT BY *n* specifies the interval between sequence numbers where *n* is an integer (If this clause is omitted, the sequence increments by 1.)

START WITH *n* specifies the first sequence number to be generated (If this clause is omitted, the sequence starts with 1.)

MAXVALUE *n* specifies the maximum value the sequence can generate

NOMAXVALUE specifies a maximum value of  $10^{27}$  for an ascending sequence and  $-1$  for a descending sequence (This is the default option.)

MINVALUE *n* specifies the minimum sequence value

NOMINVALUE specifies a minimum value of 1 for an ascending sequence and  $-(10^{26})$  for a descending sequence (This is the default option.)

CYCLE | NOCYCLE specifies whether the sequence continues to generate values after reaching its maximum or minimum value (NOCYCLE is the default option.)

CACHE *n* | NOCACHE specifies how many values the Oracle server preallocates and keep in memory (By default, the Oracle server caches 20 values.)

### **Creating a Sequence**

- Create a sequence named DEPT\_DEPTID\_SEQ to be used for the primary key of the DEPARTMENTS table.
- Do not use the CYCLE option.

### **EXAMPLE:**

```
CREATE SEQUENCE dept_deptid_seq
INCREMENT BY 10
START WITH 120
MAXVALUE 9999
NOCACHE
NOCYCLE;
```

### **Confirming Sequences**

- Verify your sequence values in the USER\_SEQUENCES data dictionary table.
- The LAST\_NUMBER column displays the next available sequence number if NOCACHE is specified.

### **EXAMPLE:**

```
SELECT sequence_name, min_value, max_value, increment_by, last_number
```

### **NEXTVAL and CURRVAL Pseudocolumns**

- NEXTVAL returns the next available sequence value. It returns a unique value every time it is

referenced, even for different users.

- CURRVAL obtains the current sequence value.
- NEXTVAL must be issued for that sequence before CURRVAL contains a value.

### **Rules for Using NEXTVAL and CURRVAL**

You can use NEXTVAL and CURRVAL in the following contexts:

- The SELECT list of a SELECT statement that is not part of a subquery
- The SELECT list of a subquery in an INSERT statement
- The VALUES clause of an INSERT statement
- The SET clause of an UPDATE statement

You cannot use NEXTVAL and CURRVAL in the following contexts:

- The SELECT list of a view
- A SELECT statement with the DISTINCT keyword
- A SELECT statement with GROUP BY, HAVING, or ORDER BY clauses
- A subquery in a SELECT, DELETE, or UPDATE statement
- The DEFAULT expression in a CREATE TABLE or ALTER TABLE statement

### **Using a Sequence**

- Insert a new department named “Support” in location ID 2500.
- View the current value for the DEPT\_DEPTID\_SEQ sequence.

### **EXAMPLE:**

```
INSERT INTO departments(department_id, department_name, location_id)
VALUES (dept_deptid_seq.NEXTVAL, 'Support', 2500);
```

```
SELECT dept_deptid_seq.CURRVAL FROM dual;
```

The example inserts a new department in the DEPARTMENTS table. It uses the DEPT\_DEPTID\_SEQ sequence for generating a new department number as follows:

You can view the current value of the sequence:

```
SELECT dept_deptid_seq.CURRVAL FROM dual;
```

### **Removing a Sequence**

- Remove a sequence from the data dictionary by using the DROP SEQUENCE statement.
- Once removed, the sequence can no longer be referenced.

### **EXAMPLE:**

```
DROP SEQUENCE dept_deptid_seq;
```

### **What is an Index?**

An index:

- Is a schema object
- Is used by the Oracle server to speed up the retrieval of rows by using a pointer
- Can reduce disk I/O by using a rapid path access method to locate data quickly
- Is independent of the table it indexes
- Is used and maintained automatically by the Oracle server

### **How Are Indexes Created?**

- Automatically: A unique index is created automatically when you define a PRIMARY KEY or UNIQUE constraint in a table definition.
- Manually: Users can create nonunique indexes on columns to speed up access to the rows.

## Types of Indexes

Two types of indexes can be created. One type is a unique index: the Oracle server automatically creates this index when you define a column in a table to have a PRIMARY KEY or a UNIQUE key constraint. The name of the index is the name given to the constraint.

The other type of index is a nonunique index, which a user can create. For example, you can create a

FOREIGN KEY column index for a join in a query to improve retrieval speed.

## Creating an Index

- Create an index on one or more columns.
- Improve the speed of query access to the LAST\_NAME column in the EMPLOYEES table.

`CREATE INDEX index`

`ON table (column[, column]...);`

### EXAMPLE:

`CREATE INDEX emp_last_name_idx`

`ON employees(last_name);`

### **In the syntax:**

*index* is the name of the index

*table* is the name of the table

*column* is the name of the column in the table to be indexed

## When to Create an Index

You should create an index if:

- A column contains a wide range of values
- A column contains a large number of null values
- One or more columns are frequently used together in a WHERE clause or a join condition
- The table is large and most queries are expected to retrieve less than 2 to 4 percent of the rows

### **When Not to Create an Index**

It is usually not worth creating an index if:

- The table is small
- The columns are not often used as a condition in the query
- Most queries are expected to retrieve more than 2 to 4 percent of the rows in the table
- The table is updated frequently
- The indexed columns are referenced as part of an Expression

### **Confirming Indexes**

- The USER\_INDEXES data dictionary view contains the name of the index and its uniqueness.
- The USER\_IND\_COLUMNS view contains the index name, the table name, and the column name.

### **EXAMPLE:**

```
SELECT ic.index_name, ic.column_name, ic.column_position col_pos, ix.uniqueness
FROM user_indexes ix, user_ind_columns ic
WHERE ic.index_name = ix.index_name
AND ic.table_name = 'EMPLOYEES';
```

### **Removing an Index**

- Remove an index from the data dictionary by using the DROP INDEX command.
- Remove the UPPER\_LAST\_NAME\_IDX index from the data dictionary.
- To drop an index, you must be the owner of the index or have the DROP ANY INDEX privilege.

```
DROP INDEX upper_last_name_idx;
```

```
DROP INDEX index;
```

**Find the Solution for the following:**

1. Create a sequence to be used with the primary key column of the DEPT table. The sequence should start at 200 and have a maximum value of 1000. Have your sequence increment by ten numbers. Name the sequence DEPT\_ID\_SEQ.

Ans :

```
CREATE SEQUENCE DEPT_ID_SEQ
START WITH 200
INCREMENT BY 10
MAXVALUE 1000;
```

2. Write a query in a script to display the following information about your sequences: sequence name, maximum value, increment size, and last number

```
SELECT SEQUENCE_NAME, MAX_VALUE, INCREMENT_BY,
LAST_NUMBER
FROM USER_SEQUENCES
WHERE SEQUENCE_NAME = 'DEPT_ID_SEQ';
```

3. Write a script to insert two rows into the DEPT table. Name your script lab12\_3.sql. Be sure to use the sequence that you created for the ID column. Add two departments named Education and

Ans :

```
INSERT INTO DEPT (DEPT_ID, DEPT_NAME)
```

```
VALUES (DEPT_ID_SEQ.NEXTVAL, 'Education');
```

```
INSERT INTO DEPT (DEPT_ID, DEPT_NAME)  
VALUES (DEPT_ID_SEQ.NEXTVAL, 'Administration');
```

```
SELECT * FROM DEPT WHERE DEPT_NAME IN ('Education',  
'Administration');
```

Administration. Confirm your additions. Run the commands in your script.

4. Create a nonunique index on the foreign key column (DEPT\_ID) in the EMP table.

Ans :CREATE INDEX IDX\_DEPT\_ID ON EMP (DEPT\_ID);

5. Display the indexes and uniqueness that exist in the data dictionary for the EMP table.

**Ans :**

```
SELECT INDEX_NAME, UNIQUENESS  
FROM USER_INDEXES  
WHERE TABLE_NAME = 'EMP';
```

**Ex. No: 17**

**Date:**

**Register No: 221701020**


**Name: Hemalatha R**

### **Controlling User Access**

#### **Objectives**

After the completion of this exercise, the students will be able to do the following:

- Create users
- Create roles to ease setup and maintenance of the security model
- Use the GRANT and REVOKE statements to grant and revoke object privileges
- Create and access database links



### **Controlling User Access**

In a multiple-user environment, you want to maintain security of the database access and use. With Oracle server database security, you can do the following:

- Control database access
- Give access to specific objects in the database
- Confirm given and received *privileges* with the Oracle data dictionary
- Create synonyms for database objects

### **Privileges**

- Database security:
  - System security
  - Data security
- System privileges: Gaining access to the database
- Object privileges: Manipulating the content of the database objects
- Schemas: Collections of objects, such as tables, views, and sequences

### **System Privileges**

- More than 100 privileges are available.
- The database administrator has high-level system privileges for tasks such as:
  - Creating new users
  - Removing users
  - Removing tables
  - Backing up tables

#### **Typical DBA Privileges**

| System Privilege | Operations Authorized                                                        |
|------------------|------------------------------------------------------------------------------|
| CREATE USER      | Grantee can create other Oracle users (a privilege required for a DBA role). |
| DROP USER        | Grantee can drop another user.                                               |
| DROP ANY TABLE   | Grantee can drop a table in any schema.                                      |
| BACKUP ANY TABLE | Grantee can back up any table in any schema with the export utility.         |
| SELECT ANY TABLE | Grantee can query tables, views, or snapshots in any schema.                 |
| CREATE ANY TABLE | Grantee can create tables in any schema.                                     |

#### **Creating Users**

The DBA creates users by using the CREATE USER statement.

#### **EXAMPLE:**

CREATE USER scott IDENTIFIED BY tiger;

#### **User System Privileges**

- Once a user is created, the DBA can grant specific system privileges to a user.
- An application developer, for example, may have the following system privileges:
  - CREATE SESSION
  - CREATE TABLE
  - CREATE SEQUENCE
  - CREATE VIEW
  - CREATE PROCEDURE

GRANT *privilege* [, *privilege...*]

TO *user* [, *user/ role, PUBLIC...*];

#### **Typical User Privileges**

| System Privilege | Operations Authorized                                                |
|------------------|----------------------------------------------------------------------|
| CREATE SESSION   | Connect to the database                                              |
| CREATE TABLE     | Create tables in the user's schema                                   |
| CREATE SEQUENCE  | Create a sequence in the user's schema                               |
| CREATE VIEW      | Create a view in the user's schema                                   |
| CREATE PROCEDURE | Create a stored procedure, function, or package in the user's schema |

### In the syntax:

*privilege* is the system privilege to be granted

*user |role|PUBLIC* is the name of the user, the name of the role, or PUBLIC designates that every user is granted the privilege

**Note:** Current system privileges can be found in the dictionary view SESSION\_PRIVS.

### Granting System Privileges

The DBA can grant a user specific system privileges.

GRANT create session, create table, create sequence, create view TO scott;

### What is a Role?

A role is a named group of related privileges that can be granted to the user. This method makes it easier to revoke and maintain privileges.

A user can have access to several roles, and several users can be assigned the same role. Roles are typically created for a database application.

### Creating and Assigning a Role

First, the DBA must create the role. Then the DBA can assign privileges to the role and users to the role.

### **Syntax**

```
CREATE ROLE role;
```

In the syntax:

*role* is the name of the role to be created

Now that the role is created, the DBA can use the GRANT statement to assign users to the role as well as

assign privileges to the role.

### **Creating and Granting Privileges to a Role**

```
CREATE ROLE manager;
```

Role created.

```
GRANT create table, create view TO manager;
```

Grant succeeded.

```
GRANT manager TO DEHAAN, KOCHHAR;
```

Grant succeeded.

- Create a role
- Grant privileges to a role
- Grant a role to users

### **Changing Your Password**

- The DBA creates your user account and initializes your password.

- You can change your password by using the

ALTER USER statement.

ALTER USER scott

IDENTIFIED BY lion;

User altered.

## Object Privileges

| Object Privilege | Table | View | Sequence | Procedure |
|------------------|-------|------|----------|-----------|
| ALTER            | ✓     |      | ✓        |           |
| DELETE           | ✓     | ✓    |          |           |
| EXECUTE          |       |      |          | ✓         |
| INDEX            | ✓     |      |          |           |
| INSERT           | ✓     | ✓    |          |           |
| REFERENCES       | ✓     | ✓    |          |           |
| SELECT           | ✓     | ✓    | ✓        |           |
| UPDATE           | ✓     | ✓    |          |           |

## Object Privileges

- Object privileges vary from object to object.
- An owner has all the privileges on the object.
- An owner can give specific privileges on that owner's object.

GRANT *object\_priv* [(*columns*)]

ON *object*

TO {*user|role|PUBLIC*}

[WITH GRANT OPTION];

### In the syntax:

*object\_priv* is an object privilege to be granted

ALL specifies all object privileges

*columns* specifies the column from a table or view on which privileges are granted

ON *object* is the object on which the privileges are granted

TO identifies to whom the privilege is granted

PUBLIC grants object privileges to all users

WITH GRANT OPTION allows the grantee to grant the object privileges to other users and roles

### Granting Object Privileges

- Grant query privileges on the EMPLOYEES table.
- Grant privileges to update specific columns to users and roles.

GRANT select

ON employees

TO sue, rich;

GRANT update (department\_name, location\_id)

ON departments

TO scott, manager;

### Using the WITH GRANT OPTION and PUBLIC

## **Keywords**

- Give a user authority to pass along privileges.
- Allow all users on the system to query data from Alice's DEPARTMENTS table.

GRANT select, insert

ON departments

TO scott

WITH GRANT OPTION;

.

GRANT select

ON alice.departments

TO PUBLIC;

## **How to Revoke Object Privileges**

- You use the REVOKE statement to revoke privileges granted to other users.
- Privileges granted to others through the WITH GRANT OPTION clause are also revoked.

REVOKE {privilege [, privilege...]|ALL}

ON object

FROM {user[, user...]|role|PUBLIC}

[CASCADE CONSTRAINTS];

### **In the syntax:**

CASCADE is required to remove any referential integrity constraints made to the CONSTRAINTS object by means of the REFERENCES privilege

### **Revoking Object Privileges**

As user Alice, revoke the SELECT and INSERT privileges given to user Scott on the DEPARTMENTS table.

```
REVOKE select, insert  
ON departments  
FROM scott;
```

### **Find the Solution for the following:**

1. What privilege should a user be given to log on to the Oracle Server? Is this a system or an object privilege?

Ans :

#### **Privilege to Log on to the Oracle Server**

- **Privilege:** CREATE SESSION
- **Type:** This is a **system privilege**.
- **Explanation:** The CREATE SESSION privilege allows a user to log in to the Oracle database. It does not grant access to any specific data or tables.

GRANT CREATE SESSION TO username;

2. What privilege should a user be given to create tables?

Ans :

### **Privilege to Create Tables**

- **Privilege:** CREATE TABLE
  - **Type:** This is a **system privilege**.
  - **Explanation:** The CREATE TABLE system privilege allows a user to create tables in their schema or in another schema, depending on further grants.
- 

3. If you create a table, who can pass along privileges to other users on your table?

Ans :

The owner of the table (the user who created it) can grant privileges to other users on that table.

Explanation: When you create a table, you are the owner, and you have the ability to grant privileges (such as SELECT, INSERT, UPDATE, DELETE) to other users on that table

---

4. You are the DBA. You are creating many users who require the same system privileges.

What should you use to make your job easier?

Ans:


```
CREATE ROLE role_name;  
GRANT CREATE TABLE, CREATE SESSION TO role_name;  
GRANT role_name TO user1, user2;
```

---

5. What command do you use to change your password?

Ans:

```
ALTER USER dhanush13 IDENTIFIED BY new_password;
```



---

6. Grant another user access to your DEPARTMENTS table. Have the user grant you query access to his or her DEPARTMENTS table.

Ans:

```
GRANT SELECT, INSERT, UPDATE, DELETE ON DEPARTMENTS TO  
user2;
```

```
GRANT SELECT ON their_departments_table TO your_username;
```

7.Query all the rows in your DEPARTMENTS table.

Ans :

```
SELECT * FROM DEPARTMENTS;
```

8.Add a new row to your DEPARTMENTS table. Team 1 should add Education as departmentnumber 500. Team 2 should add Human Resources department number 510. Query the other team's table.

Ans:

```
INSERT INTO DEPARTMENTS (DEPARTMENT_NAME,  
DEPARTMENT_ID)  
VALUES ('Education', 500);
```

```
INSERT INTO DEPARTMENTS (DEPARTMENT_NAME,  
DEPARTMENT_ID)  
VALUES ('Human Resources', 510);
```

```
SELECT * FROM their_departments_table;
```

9.Query the USER\_TABLES data dictionary to see information about the tables that you own.

Ans ;

```
SELECT * FROM USER_TABLES;
```

10.Revoke the SELECT privilege on your table from the other team.

Ans:

```
REVOKE SELECT ON DEPARTMENTS FROM user2;
```

11.Remove the row you inserted into the DEPARTMENTS table in step 8 and save the changes.

Ans:

```
DELETE FROM DEPARTMENTS  
WHERE DEPARTMENT_ID IN (500, 510);  
COMMIT;
```

221701020

221701020

# PL/SQL

221701020

**Ex. No: 18**

**Date:**

**Register No: 221701020**

**Name: Hemalatha R**

---

### **PL/SQL**

### **Control Structures**

In addition to SQL commands,PL/SQL can also process data usin flow of statements.the flow of control statements are classified into the following categories.

- Conditional control -Branching
- Iterative control - looping
- Sequential control

#### **BRANCHING in PL/SQL:**

Sequence of statements can be executed on satisfying certain condition .

If statements are being used and different forms of if are:

1.Simple IF

2.ELSIF

3.ELSE IF

#### **SIMPLE IF:**

#### **Syntax:**

IF condition THEN

statement1;

statement2;

END IF;

#### **IF-THEN-ELSE STATEMENT:**

---

### **Syntax:**

IF condition THEN

    statement1;

ELSE

    statement2;

END IF;

### **ELSIF STATEMENTS:**

### **Syntax:**

IF condition1 THEN

    statement1;

ELSIF condition2 THEN

    statement2;

ELSIF condition3 THEN

    statement3;

ELSE

    statementn;

END IF;

### **NESTED IF :**

### **Syntax:**

IF condition THEN

    statement1;

ELSE

IF condition THEN

```
statement2;  
ELSE  
    statement3;  
END IF;  
END IF;  
ELSE  
    statement3;  
END IF;
```

### SELECTION IN PL/SQL(Sequential Controls)

#### SIMPLE CASE

##### Syntax:

CASE SELECTOR

```
    WHEN Expr1 THEN statement1;  
    WHEN Expr2 THEN statement2;  
    :  
    ELSE  
        Statement n;  
END CASE;
```

#### SEARCHED CASE:

CASE

```
    WHEN searchcondition1 THEN statement1;
```

```
    WHEN searchcondition2 THEN statement2;
```

```
:  
:  
ELSE  
statementn;  
END CASE;
```

### **ITERATIONS IN PL/SQL**

Sequence of statements can be executed any number of times using loop construct.

It is broadly classified into:

- Simple Loop
- For Loop
- While Loop

#### **SIMPLE LOOP**

##### **Syntax:**

```
LOOP  
statement1;  
EXIT [ WHEN Condition];  
END LOOP;
```

#### **WHILE LOOP**

##### **Syntax:**

```
WHILE condition LOOP  
statement1;  
statement2;
```

END LOOP;

**FOR LOOP**

**Syntax:**

FOR counter IN [REVERSE]

    LowerBound..UpperBound

    LOOP

        statement1;

        statement2;

    END LOOP;

## PROGRAM 1

Write a PL/SQL block to calculate the incentive of an employee whose ID is 110.

```
DECLARE
    v_salary
    NUMBER;
    v_incentive
    NUMBER(8,2);
BEGIN
    SELECT salary
    INTO v_salary
    FROM
    employees
    WHERE
    employee_id
    = 110;

    v_incentive := v_salary * 0.12; -- Assuming 12% incentive

    DBMS_OUTPUT.PUT_LINE('Incentive for employee ID 110: ' ||
    TO_CHAR(v_incentive)); EXCEPTION
    WHEN NO_DATA_FOUND THEN
        DBMS_OUTPUT.PUT_LINE('Employee with ID 110 not found.');
    WHEN OTHERS THEN
        DBMS_OUTPUT.PUT_LINE('An error occurred: ' || SQLERRM);
END;
```

## PROGRAM 2

Write a PL/SQL block to show an invalid case-insensitive reference to a quoted and without quoted user-defined identifier.

Ans)

```
v_salary
NUMBER;
BEGIN
    SELECT SALARY
    INTO v_salary
    FROM employees
    WHERE EMPLOYEE_ID = 122; -- Case-insensitive reference to
EMPLOYEE_ID

    -- Other operations with v_salary
EXCEPTION
    WHEN NO_DATA_FOUND THEN
        DBMS_OUTPUT.PUT_LINE('Employee with ID 122 not found.');
    WHEN OTHERS THEN
        DBMS_OUTPUT.PUT_LINE('An error occurred: ' || SQLERRM);
END;
```

### PROGRAM 3

Write a PL/SQL block to adjust the salary of the employee whose ID 122.

Sample table: employees

DECALRE

```
v_new_salary NUMBER := 15000; -- New salary to be assigned
BEGIN
    UPDATE employees
    SET salary =
    v_new_salary
    WHERE
    employee_id = 122;
    COMMIT; -- Commit the changes

    DBMS_OUTPUT.PUT_LINE('Salary for employee ID 122 updated
successfully.');?>
    WHEN OTHERS THEN
        DBMS_OUTPUT.PUT_LINE('An error occurred: ' || SQLERRM);
        ROLLBACK; -- Rollback the changes in case of error
END;
```

#### PROGRAM 4

Write a PL/SQL block to create a procedure using the "IS [NOT] NULL Operator" and show AND operator returns TRUE if and only if both operands are TRUE.

```
CREATE OR REPLACE PROCEDURE check_null_values
IS
    v_first_name
    VARCHAR2(50);
    v_last_name
    VARCHAR2(50);
BEGIN
    SELECT first_name, last_name
    INTO v_first_name, v_last_name
    FROM employees
    WHERE employee_id = 123;

    IF v_first_name IS NOT NULL AND v_last_name IS NOT NULL THEN
        DBMS_OUTPUT.PUT_LINE('Both first name and last name are not null.');
    ELSE
        DBMS_OUTPUT.PUT_LINE('Either first name or last name is null or
both are null.');
    END IF;
END;
```

## PROGRAM 5

Write a PL/SQL block to describe the usage of LIKE operator including wildcard characters and escape character.

Ans:

```
DECLARE
    v_employee_name VARCHAR2(50);
BEGIN
    -- Find employees whose names start with 'A'
    SELECT employee_name
    INTO v_employee_name
    FROM employees
    WHERE employee_name LIKE 'A%';

    DBMS_OUTPUT.PUT_LINE('Employee name starting with A: ' || v_employee_name);

    -- Find employees whose names end with 'son'
    SELECT employee_name
    INTO v_employee_name
    FROM employees
    WHERE employee_name LIKE '%son';

    DBMS_OUTPUT.PUT_LINE('Employee name ending with son: ' || v_employee_name);

    -- Find employees whose names contain 'an'
```

```
SELECT employee_name  
INTO v_employee_name  
FROM employees  
WHERE employee_name LIKE '%an%';
```

```
DBMS_OUTPUT.PUT_LINE('Employee name containing an: ' ||  
v_employee_name);
```

-- Find employees whose names start with 'A\_' and have exactly one character after 'A'

```
SELECT employee_name  
INTO v_employee_name  
FROM employees  
WHERE employee_name LIKE 'A_';
```

```
DBMS_OUTPUT.PUT_LINE('Employee name starting with A_ : ' ||  
v_employee_name);
```

-- Find employees whose names start with 'A%' and have '%' as a literal character

```
SELECT employee_name  
INTO v_employee_name  
FROM employees  
WHERE employee_name LIKE 'A\% %';
```

```
DBMS_OUTPUT.PUT_LINE('Employee name starting with A%  
literally: ' || v_employee_name);
```

EXCEPTION

```
WHEN NO_DATA_FOUND THEN
    DBMS_OUTPUT.PUT_LINE('No matching employee found.');
WHEN OTHERS THEN
    DBMS_OUTPUT.PUT_LINE('An error occurred: ' || SQLERRM);
END;
PROGRAM 6
```

Write a PL/SQL program to arrange the number of two variable in such a way that the small number will store in num\_small variable and large number will store in num\_large variable.

Ans:

```
DECLARE
    num1
    NUMBER :=
    10;  num2
    NUMBER :=
    20;
    num_small
    NUMBER;
    num_large
    NUMBER;
BEGIN
    IF num1 <
    num2
    THEN
        num_small
        := num1;
        num_large
        := num2;
    ELSE
        num_small :=
        num2;
```

```
num_large :=  
num1;  
END IF;  
  
DBMS_OUTPUT.PUT_LINE('Small number: ' || num_small);  
DBMS_OUTPUT.PUT_LINE('Large number: ' || num_large);  
END;
```

221701020

## PROGRAM 7

Write a PL/SQL procedure to calculate the incentive on a target achieved and display the message either the record updated or not.

Ans;

```
CREATE OR REPLACE PROCEDURE calculate_incentive(p_emp_id IN
NUMBER, p_target_achieved IN NUMBER)
IS
    v_salary
    NUMBER;
    v_incentive
    NUMBER;
    v_updated_row
    s NUMBER;
BEGIN
    SELECT salary INTO v_salary FROM employees WHERE employee_id =
    p_emp_id;
    v_incentive := v_salary * 0.10 * (p_target_achieved /
    100);

    -- Update the salary with the incentive
    UPDATE employees
    SET salary = salary +
    v_incentive WHERE
    employee_id = p_emp_id;

    v_updated_rows := SQL%ROWCOUNT;

    IF v_updated_rows > 0 THEN
        DBMS_OUTPUT.PUT_LINE('Incentive calculated and salary updated
successfully.');
    ELSE
        DBMS_OUTPUT.PUT_LINE('Employee ID ' || p_emp_id || ' not found or
update failed.');
    END IF;
EXCEPTION
    WHEN NO_DATA_FOUND THEN
```

```
DBMS_OUTPUT.PUT_LINE('Employee ID ' || p_emp_id || ' not found.');
WHEN OTHERS THEN
    DBMS_OUTPUT.PUT_LINE('An error occurred: ' || SQLERRM);
END;
```

## PROGRAM 8

Write a PL/SQL procedure to calculate incentive achieved according to the specific sale limit.

```
CREATE OR REPLACE PROCEDURE
calculate_incentive_by_sale(p_emp_id IN NUMBER, p_sales_amount IN
NUMBER)
IS
v_ince
ntive
NUM
BER;
BEGIN
    IF p_sales_amount >=
100000 THEN    v_incentive
:= p_sales_amount * 0.10;
ELSIF p_sales_amount >=
50000 THEN    v_incentive
:= p_sales_amount * 0.07;
ELSE
    v_incentive := p_sales_amount * 0.05;
END IF;

-- Update the employee's incentive or other relevant fields
UPDATE employees
WHERE
employee_id =
p_emp_id;

-- You can add more logic to log the incentive calculation or send notifications
END;
```

## PROGRAM 9

Write a PL/SQL program to count number of employees in department 50 and check whether this department have any vacancies or not. There are 45 vacancies in this department.

Ans:

```
DECLARE
    v_employee_count
    NUMBER;  v_vacancies
    NUMBER := 45;
BEGIN
    SELECT COUNT(*) INTO v_employee_count
    FROM employees
    WHERE department_id = 50;

    IF v_employee_count < v_vacancies THEN
        DBMS_OUTPUT.PUT_LINE('Department 50 has ' || v_vacancies -
v_employee_count || '
vacancies.');
    ELSE
        DBMS_OUTPUT.PUT_LINE('Department 50 is full.');
    END IF;
END;
```

## PROGRAM 10

Write a PL/SQL program to count number of employees in a specific department and check whether this department have any vacancies or not. If any vacancies, how many vacancies are in that department.

```
DECLARE
    v_department_id NUMBER := 50; -- Replace with the desired department
    ID  v_employee_count NUMBER;  v_vacancies NUMBER := 45; --
    Replace with the total number of vacancies in the department
BEGIN
    SELECT COUNT(*) INTO v_employee_count
    FROM employees
    WHERE department_id = v_department_id;

    IF v_employee_count < v_vacancies THEN
        DBMS_OUTPUT.PUT_LINE('Department ' || v_department_id || ' has ' ||
        (v_vacancies - v_employee_count) || ' vacancies.');
    ELSE
        DBMS_OUTPUT.PUT_LINE('Department ' ||
        v_department_id || ' is full.');
    END IF;
END;
```

## PROGRAM 11

Write a PL/SQL program to display the employee IDs, names, job titles, hire dates, and salaries of all employees.

Ans:

```
DECLARE
    CURSOR emp_cur IS
        SELECT employee_id, first_name || ' ' || last_name AS full_name,
        job_title, hire_date, salary   FROM employees;  emp_rec
        emp_cur%ROWTYPE;
```

```
BEGIN  
OPEN emp_cur;  
LOOP  
FETCH emp_cur INTO emp_rec;  
EXIT WHEN emp_cur%NOTFOUND;
```

221701020

```
DBMS_OUTPUT.PUT_LINE('Employee ID: ' || emp_rec.employee_id);
```

221701020

```
DBMS_OUTPUT.PUT_LINE('Full Name: ' || emp_rec.full_name);
DBMS_OUTPUT.PUT_LINE('Job Title: ' || emp_rec.job_title);
DBMS_OUTPUT.PUT_LINE('Hire Date: ' || emp_rec.hire_date);
DBMS_OUTPUT.PUT_LINE('Salary: ' || emp_rec.salary);
DBMS_OUTPUT.PUT_LINE('-----');
END LOOP;
CLOSE emp_cur;
END;
```

221701020

## PROGRAM 12

Write a PL/SQL program to display the employee IDs, names, and department names of all employees.

```
DECLARE
    CURSOR emp_cur IS
        SELECT e.employee_id, e.first_name || ' ' || e.last_name AS full_name,
               d.department_name
            FROM employees e
           JOIN departments d ON e.department_id =
               d.department_id;  emp_rec emp_cur%ROWTYPE;
BEGIN
    OPEN emp_cur;
    LOOP
        FETCH emp_cur
        INTO emp_rec;  EXIT
        WHEN
            emp_cur%NOTFOUND
        ;
        DBMS_OUTPUT.PUT_LINE('Employee ID: ' || emp_rec.employee_id);
        DBMS_OUTPUT.PUT_LINE('Full Name: ' || emp_rec.full_name);
        DBMS_OUTPUT.PUT_LINE('Department Name: ' ||
            emp_rec.department_name);  DBMS_OUTPUT.PUT_LINE('-----');
    END LOOP;
    CLOSE emp_cur;
END;
```

## PROGRAM 13

Write a PL/SQL program to display the job IDs, titles, and minimum salaries of all jobs.

```
DECLARE
    CURSOR job_cur IS
        SELECT job_id, job_title, min_salary
        FROM jobs;
    job_rec job_cur%ROWTYPE;
BEGIN
    OPEN job_cur;
    LOOP
        FETCH job_cur
        INTO job_rec;
        EXIT WHEN
            job_cur%NOTFOUND;
    D;
        DBMS_OUTPUT.PUT_LINE('Job ID: ' || job_rec.job_id);
        DBMS_OUTPUT.PUT_LINE('Job Title: ' || job_rec.job_title);
        DBMS_OUTPUT.PUT_LINE('Minimum Salary: ' || job_rec.min_salary);
        DBMS_OUTPUT.PUT_LINE('-----');
    END LOOP;
    CLOSE job_cur;
END;
```

## PROGRAM 14

Write a PL/SQL program to display the employee IDs, names, and job history start dates of all employees.

```
DECLARE
    CURSOR emp_hist_cur IS
        SELECT e.employee_id, e.first_name || ' ' || e.last_name AS full_name,
               jh.start_date
            FROM employees e
           JOIN job_history jh ON e.employee_id =
                jh.employee_id;  emp_hist_rec
emp_hist_cur%ROWTYPE;
BEGIN
    OPEN emp_hist_cur;
    LOOP
        FETCH emp_hist_cur INTO
        emp_hist_rec;  EXIT WHEN
        emp_hist_cur%NOTFOUND;
```

## PROGRAM 15

Write a PL/SQL program to display the employee IDs, names, and job history end dates of all employees.

```
DECLARE
    CURSOR emp_hist_cur IS
        SELECT e.employee_id, e.first_name || ' ' || e.last_name AS full_name,
               jh.end_date
            FROM employees e
           JOIN job_history jh ON e.employee_id =
                jh.employee_id;  emp_hist_rec
emp_hist_cur%ROWTYPE;
BEGIN
    OPEN emp_hist_cur;
    LOOP
        FETCH emp_hist_cur INTO
emp_hist_rec;  EXIT WHEN
emp_hist_cur%NOTFOUND;

        DBMS_OUTPUT.PUT_LINE('Employee ID: ' || emp_hist_rec.employee_id);
        DBMS_OUTPUT.PUT_LINE('Full Name: ' || emp_hist_rec.full_name);
        DBMS_OUTPUT.PUT_LINE('End Date: ' || emp_hist_rec.end_date);
        DBMS_OUTPUT.PUT_LINE('-----');
    END LOOP;
    CLOSE emp_hist_cur;
END;
```

**Ex. No: p-8**

**Date:**

**Register No: 221701020**

**Name: Hemalatha R**

---

## **PROCEDURES AND FUNCTIONS**

### **PROCEDURES**

#### **DEFINITION**

A procedure or function is a logically grouped set of SQL and PL/SQL statements that perform a specific task. They are essentially sub-programs. Procedures and functions are made up of,

- Declarative part
- Executable part
- Optional exception handling part

These procedures and functions do not show the errors.

#### **KEYWORDS AND THEIR PURPOSES**

**REPLACE:** It recreates the procedure if it already exists.

**PROCEDURE:** It is the name of the procedure to be created.

**ARGUMENT:** It is the name of the argument to the procedure. Paranthesis can be omitted if no arguments are present.

**IN:** Specifies that a value for the argument must be specified when calling the procedure ie. used to pass values to a sub-program. This is the default parameter.

**OUT:** Specifies that the procedure passes a value for this argument back to its calling environment after execution ie. used to return values to a caller of the sub-program.

**INOUT:** Specifies that a value for the argument must be specified when calling the procedure and that procedure passes a value for this argument back to its calling environment after execution.

**RETURN:** It is the datatype of the function's return value because every function must return a value, this clause is required.

### PROCEDURES – SYNTAX

```
create or replace procedure <procedure name> (argument {in,out,inout} datatype ) {is,as}
variable declaration;
constant declaration;
begin
PL/SQL subprogram body;
exception
exception PL/SQL block;
end;
```

### FUNCTIONS – SYNTAX

```
create or replace function <function name> (argument in datatype,.....) return datatype {is,as}
variable declaration;
constant declaration;
begin
PL/SQL subprogram body;
exception
exception PL/SQL block;
```

end;

### **CREATING THE TABLE ‘ITITEMS’ AND DISPLAYING THE CONTENTS**

```
SQL> create table ititems(itemid number(3), actualprice number(5), ordid number(4), prodid number(4));
```

Table created.

```
SQL> insert into ititems values(101, 2000, 500, 201);
```

1 row created.

```
SQL> insert into ititems values(102, 3000, 1600, 202);
```

1 row created.

```
SQL> insert into ititems values(103, 4000, 600, 202);
```

1 row created.

```
SQL> select * from ititems;
```

| ITEMID | ACTUALPRICE | ORDID | PRODID |
|--------|-------------|-------|--------|
| 101    | 2000        | 500   | 201    |
| 102    | 3000        | 1600  | 202    |
| 103    | 4000        | 600   | 202    |

### **PROGRAM FOR GENERAL PROCEDURE – SELECTED RECORD’S PRICE IS INCREMENTED BY 500 , EXECUTING THE PROCEDURE CREATED AND DISPLAYING THE UPDATED TABLE**

```
SQL> create procedure itsum(identity number, total number) is price number;
```

2 null\_price exception;

3 begin

```
4 select actualprice into price from ititems where itemid=identity;
5 if price is null then
6 raise null_price;
7 else
8 update ititems set actualprice=actualprice+total where itemid=identity;
9 end if;
10 exception
11 when null_price then
12 dbms_output.put_line('price is null');
13 end;
14 /
```

Procedure created.

```
SQL> exec itsum(101, 500);
```

```
PL/SQL procedure successfully completed.
```

```
SQL> select * from ititems;
```

| ITEMID | ACTUALPRICE | ORDID | PRODID |
|--------|-------------|-------|--------|
| 101    | 2500        | 500   | 201    |
| 102    | 3000        | 1600  | 202    |
| 103    | 4000        | 600   | 202    |

### PROCEDURE FOR 'IN' PARAMETER – CREATION, EXECUTION

```
SQL> set serveroutput on;
```

```
SQL> create procedure yyy (a IN number) is price number;
```

```
2 begin
3 select actualprice into price from ititems where itemid=a;
4 dbms_output.put_line('Actual price is ' || price);
```

```
5 if price is null then  
6 dbms_output.put_line('price is null');  
7 end if;  
8 end;  
9 /
```

Procedure created.

```
SQL> exec yyy(103);  
Actual price is 4000  
PL/SQL procedure successfully completed.
```

### **PROCEDURE FOR ‘OUT’ PARAMETER – CREATION, EXECUTION**

```
SQL> set serveroutput on;
```

```
SQL> create procedure zzz (a in number, b out number) is identity number;  
2 begin  
3 select ordid into identity from ititems where itemid=a;  
4 if identity<1000 then  
5 b:=100;  
6 end if;  
7 end;  
8 /
```

Procedure created.

```
SQL> declare  
2 a number;  
3 b number;  
4 begin  
5 zzz(101,b);  
6 dbms_output.put_line('The value of b is'|| b);
```

```
7 end;
8 /
```

The value of b is 100

PL/SQL procedure successfully completed.

### **PROCEDURE FOR ‘INOUT’ PARAMETER – CREATION, EXECUTION**

```
SQL> create procedure itit ( a in out number) is
```

```
2 begin
3 a:=a+1;
4 end;
5 /
```

Procedure created.

```
SQL> declare
```

```
2 a number:=7;
3 begin
4 itit(a);
5 dbms_output.put_line('The updated value is '||a);
6 end;
7 /
```

The updated value is 8

PL/SQL procedure successfully completed.

### **CREATE THE TABLE ‘ITTRAIN’ TO BE USED FOR FUNCTIONS**

```
SQL>create table ittrain ( tno number(10), tfare number(10));
```

Table created.

```
SQL>insert into ittrain values (1001, 550);
```

1 row created.

```
SQL>insert into ittrain values (1002, 600);
```

1 row created.

```
SQL>select * from ittrain;
```

| TNO  | TFARE |
|------|-------|
| 1001 | 550   |
| 1002 | 600   |

### **PROGRAM FOR FUNCTION AND IT'S EXECUTION**

```
SQL> create function aaa (trainnumber number) return number is  
2 trainfunction ittrain.tfare % type;  
3 begin  
4 select tfare into trainfunction from ittrain where tno=trainnumber;  
5 return(trainfunction);  
6 end;  
7 /
```

Function created.

```
SQL> set serveroutput on;
```

```
SQL> declare  
2 total number;  
3 begin  
4 total:=aaa (1001);  
5 dbms_output.put_line('Train fare is Rs. '|total);  
6 end;  
7 /
```

Train fare is Rs.550

PL/SQL procedure successfully completed.

221701020

## Program 1

### **FACTORIAL OF A NUMBER USING FUNCTION**

```
CREATE OR REPLACE FUNCTION factorial(n IN NUMBER)
RETURN NUMBER
IS
result
NUM
BER
:= 1;
BEGIN
IF n = 0 THEN
    RETURN 1;
ELSE
    FOR i IN 1..n LOOP
        result := result * i;
    END LOOP;
    RETURN result;
END IF;
END;

DECLARE
num NUMBER := 5;
fact
NUMB
ER;
BEGIN
fact := factorial(num);
DBMS_OUTPUT.PUT_LINE('Factorial of ' || num || ' is ' || fact);
END;
```

## Program 2

**Write a PL/SQL program using Procedures IN,INOUT,OUT parameters to retrieve the corresponding book information in library**

**Ans:**

```
CREATE OR REPLACE

PROCEDURE get_book_info(
    p_book_id IN NUMBER,
    p_book_title OUT VARCHAR2,
    p_author_name OUT VARCHAR2,
    p_publication_year OUT NUMBER
)
IS
BEGIN
    SELECT book_title, author_name, publication_year
    INTO p_book_title, p_author_name, p_publication_year
    FROM books
    WHERE book_id = p_book_id;

    EXCEPTION
        WHEN NO_DATA_FOUND THEN
            DBMS_OUTPUT.PUT_LINE('Book with ID ' || p_book_id || ' not found.');

```

```
END;  
/  
  
DECLARE  
    v_book_id NUMBER := 123; -- Replace with the  
    desired book ID    v_book_title VARCHAR2(100);  
    v_author_name          VARCHAR2(100);  
    v_publication_year NUMBER; BEGIN  
        get_book_info(v_book_id, v_book_title, v_author_name,  
v_publication_year);  
  
        DBMS_OUTPUT.PUT_LINE('Book ID: ' || v_book_id);  
        DBMS_OUTPUT.PUT_LINE('Book Title: ' || v_book_title);  
        DBMS_OUTPUT.PUT_LINE('Author Name: ' || v_author_name);  
        DBMS_OUTPUT.PUT_LINE('Publication Year: ' || v_publication_year);  
    END;
```

**Ex. No: 19**

**Date:**

**Register No: 221701020**

**Name: Hemalatha R**

---

## **TRIGGER**

### **DEFINITION**

A trigger is a statement that is executed automatically by the system as a side effect of a modification to the database. The parts of a trigger are,

- **Trigger statement:** Specifies the DML statements and fires the trigger body. It also specifies the table to which the trigger is associated.
- **Trigger body or trigger action:** It is a PL/SQL block that is executed when the triggering statement is used.
- **Trigger restriction:** Restrictions on the trigger can be achieved

The different uses of triggers are as follows,

- *To generate data automatically*
- *To enforce complex integrity constraints*
- *To customize complex securing authorizations*
- *To maintain the replicate table*
- To audit data modifications

### **TYPES OF TRIGGERS**

The various types of triggers are as follows,

- **Before:** It fires the trigger before executing the trigger statement.
- **After:** It fires the trigger after executing the trigger statement
- .
- **For each row:** It specifies that the trigger fires once per row
- .
- **For each statement:** This is the default trigger that is invoked. It specifies that the trigger fires once per statement.

### **VARIABLES USED IN TRIGGERS**

- :new
- :old

These two variables retain the new and old values of the column updated in the database. The values in these variables can be used in the database triggers for data manipulation

### **SYNTAX**

```
create or replace trigger triggername [before/after] {DML statements}
on [tablename] [for each row/statement]
begin
-----
-----
-----
exception
end;
```

## **USER DEFINED ERROR MESSAGE**

The package “raise\_application\_error” is used to issue the user defined error messages

**Syntax:** raise\_application\_error(error number,‘error message’);

The error number can lie between -20000 and -20999.

The error message should be a character string.

## **TO CREATE THE TABLE ‘ITEMPLS’**

```
SQL> create table itempls (ename varchar2(10), eid number(5), salary number(10));
```

Table created.

```
SQL> insert into itempls values('xxx',11,10000);
```

1 row created.

```
SQL> insert into itempls values('yyy',12,10500);
```

1 row created.

```
SQL> insert into itempls values('zzz',13,15500);
```

1 row created.

```
SQL> select * from itempls;
```

| ENAME | EID | SALARY |
|-------|-----|--------|
| xxx   | 11  | 10000  |
| yyy   | 12  | 10500  |
| zzz   | 13  | 15500  |

## **TO CREATE A SIMPLE TRIGGER THAT DOES NOT ALLOW INSERT UPDATE AND DELETE OPERATIONS ON THE TABLE**

SQL> create trigger ittrigg before insert or update or delete on itempls for each row

```
2 begin  
3 raise_application_error(-20010,'You cannot do manipulation');  
4 end;  
5  
6 /
```

Trigger created.

SQL> insert into itempls values('aaa',14,34000);

insert into itempls values('aaa',14,34000)

\*

ERROR at line 1:

ORA-20010: You cannot do manipulation

ORA-06512: at "STUDENT.ITTRIGG", line 2

ORA-04088: error during execution of trigger 'STUDENT.ITTRIGG'

SQL> delete from itempls where ename='xxx';

delete from itempls where ename='xxx'

\*

ERROR at line 1:

ORA-20010: You cannot do manipulation

ORA-06512: at "STUDENT.ITTRIGG", line 2

ORA-04088: error during execution of trigger 'STUDENT.ITTRIGG'

SQL> update itempls set eid=15 where ename='yyy';

update itempls set eid=15 where ename='yyy'

\*

ERROR at line 1:

ORA-20010: You cannot do manipulation  
ORA-06512: at "STUDENT.ITTRIGG", line 2  
ORA-04088: error during execution of trigger 'STUDENT.ITTRIGG'

### **TO DROP THE CREATED TRIGGER**

SQL> drop trigger ittrigg;

Trigger dropped.

### **TO CREATE A TRIGGER THAT RAISES AN USER DEFINED ERROR MESSAGE AND DOES NOT ALLOW UPDATION AND INSERTION**

SQL> create trigger ittriggs before insert or update of salary on itempls for each row

```
2 declare
3   triggsal itempls.salary%type;
4 begin
5   select salary into triggsal from itempls where eid=12;
6   if(:new.salary>triggsal or :new.salary<triggsal) then
7     raise_application_error(-20100,'Salary has not been changed');
8   end if;
9 end;
10 /
```

Trigger created.

SQL> insert into itempls values ('bbb',16,45000);

insert into itempls values ('bbb',16,45000)

\*

ERROR at line 1:

ORA-04098: trigger 'STUDENT.ITTRIGGS' is invalid and failed re-validation

```
SQL> update itempls set eid=18 where ename='zzz';
update itempls set eid=18 where ename='zzz'
*
ERROR at line 1:
ORA-04298: trigger 'STUDENT.ITTRIGGS' is invalid and failed re-validation
```

Cursor for loop

- Explicit cursor
- Implicit cursor

#### **TO CREATE THE TABLE ‘SSEMPP’**

```
SQL> create table ssempp( eid number(10), ename varchar2(20), job varchar2(20), sal number(10), dnonumber(5));
```

Table created.

```
SQL> insert into ssempp values(1,'nala','lecturer',34000,11);
```

1 row created.

```
SQL> insert into ssempp values(2,'kala',' seniorlecturer',20000,12);
```

1 row created.

```
SQL> insert into ssempp values(5,'ajay','lecturer',30000,11);
```

1 row created.

```
SQL> insert into ssempp values(6,'vijay','lecturer',18000,11);
```

1 row created.

```
SQL> insert into ssempp values(3,'nila','professor',60000,12);
```

1 row created.

SQL> select \* from ssempp;

| EID | ENAME | JOB            | SAL   | DNO |
|-----|-------|----------------|-------|-----|
| 1   | nala  | lecturer       | 34000 | 11  |
| 2   | kala  | seniorlecturer | 20000 | 12  |
| 5   | ajay  | lecturer       | 30000 | 11  |
| 6   | vijay | lecturer       | 18000 | 11  |
| 3   | nila  | professor      | 60000 | 12  |

221701020

## **EXTRA PROGRAMS**

### **TO WRITE A PL/SQL BLOCK TO DISPLAY THE EMPLOYEE ID AND EMPLOYEE NAME USING CURSOR FOR LOOP**

```
SQL> set serveroutput on;
SQL> declare
2 begin
3 for emy in (select eid,ename from ssempp)
4 loop
5 dbms_output.put_line('Employee id and employee name are'|| emy.eid 'and'|| emy.ename);
6 end loop;
7 end;
8 /
```

Employee id and employee name are 1 and nala  
Employee id and employee name are 2 and kala  
Employee id and employee name are 5 and ajay  
Employee id and employee name are 6 and vijay  
Employee id and employee name are 3 and nila

PL/SQL procedure successfully completed.

### **TO WRITE A PL/SQL BLOCK TO UPDATE THE SALARY OF ALL EMPLOYEES WHERE DEPARTMENT NO IS 11 BY 5000 USING CURSOR FOR LOOP AND TO DISPLAY THE UPDATED TABLE**

```
SQL> set serveroutput on;
SQL> declare
2 cursor cem is select eid,ename,sal,dno from ssempp where dno=11;
3 begin
4 --open cem;
```

```

5 for rem in cem
6 loop
7 update ssempp set sal=rem.sal+5000 where eid=rem.eid;
8 end loop;
9 --close cem;
10 end;
11 /

```

PL/SQL procedure successfully completed.

SQL> select \* from ssempp;

| EID | ENAME | JOB            | SAL   | DNO |
|-----|-------|----------------|-------|-----|
| 1   | nala  | lecturer       | 39000 | 11  |
| 2   | kala  | seniorlecturer | 20000 | 12  |
| 5   | ajay  | lecturer       | 35000 | 11  |
| 6   | vijay | lecturer       | 23000 | 11  |
| 3   | nila  | professor      | 60000 | 12  |

### **TO WRITE A PL/SQL BLOCK TO DISPLAY THE EMPLOYEE ID AND EMPLOYEE NAME WHERE DEPARTMENT NUMBER IS 11 USING EXPLICIT CURSORS**

```

1 declare
2 cursor cenl is select eid,sal from ssempp where dno=11;
3 ecode ssempp.eid%type;
4 esal empp.sal%type;
5 begin
6 open cenl;
7 loop
8 fetch cenl into ecode,esal;

```

```
9 exit when cenl%notfound;
10 dbms_output.put_line(' Employee code and employee salary are' || ecode 'and'|| esal);
11 end loop;
12 close cenl;
13* end;
```

SQL> /

```
Employee code and employee salary are 1 and 39000
Employee code and employee salary are 5 and 35000
Employee code and employee salary are 6 and 23000
```

PL/SQL procedure successfully completed.

**TO WRITE A PL/SQL BLOCK TO UPDATE THE SALARY BY 5000 WHERE THE JOB IS LECTURER , TO CHECK IF UPDATES ARE MADE USING IMPLICIT CURSORS AND TO DISPLAY THE UPDATED TABLE**

```
SQL> declare
2  county number;
3 begin
4 update ssempp set sal=sal+10000 where job='lecturer';
5 county:= sql%rowcount;
6 if county > 0 then
7 dbms_output.put_line('The number of rows are '|| county);
8 end if;
9 if sql %found then
10 dbms_output.put_line('Employee record modification successful');
11 else if sql%notfound then
12 dbms_output.put_line('Employee record is not found');
13 end if;
14 end if;
```

```
15 end;  
16 /
```

The number of rows are 3

Employee record modification successful

PL/SQL procedure successfully completed.

```
SQL> select * from ssempp;
```

| EID | ENAME | JOB            | SAL   | DNO |
|-----|-------|----------------|-------|-----|
| 1   | nala  | lecturer       | 44000 | 11  |
| 2   | kala  | seniorlecturer | 20000 | 12  |
| 5   | ajay  | lecturer       | 40000 | 11  |
| 6   | vijay | lecturer       | 28000 | 11  |
| 3   | nila  | professor      | 60000 | 12  |

## PROGRAMS

### TO DISPLAY HELLO MESSAGE

```
SQL> set serveroutput on;  
SQL> declare  
2 a varchar2(20);  
3 begin  
4 a:='Hello';  
5 dbms_output.put_line(a);  
6 end;  
7 /
```

Hello

PL/SQL procedure successfully completed.

### **TO INPUT A VALUE FROM THE USER AND DISPLAY IT**

```
SQL> set serveroutput on;
```

```
SQL> declare
```

```
 2  a varchar2(20);  
 3 begin  
 4  a:=&a;  
 5  dbms_output.put_line(a);  
 6 end;  
 7 /
```

```
Enter value for a: 5
```

```
old  4: a:=&a;
```

```
new  4: a:=5;
```

```
5
```

PL/SQL procedure successfully completed.

### **GREATEST OF TWO NUMBERS**

```
SQL> set serveroutput on;
```

```
SQL> declare
```

```
 2  a number(7);  
 3  b number(7);  
 4 begin  
 5  a:=&a;  
 6  b:=&b;  
 7 if(a>b) then
```

```
8 dbms_output.put_line ('The greater of the two is'|| a);
9 else
10 dbms_output.put_line ('The greater of the two is'|| b);
11 end if;
12 end;
13 /
```

Enter value for a: 5

old 5: a:=&a;

new 5: a:=5;

Enter value for b: 9

old 6: b:=&b;

new 6: b:=9;

The greater of the two is9

PL/SQL procedure successfully completed.

### **GREATEST OF THREE NUMBERS**

SQL> set serveroutput on;

```
SQL> declare
2 a number(7);
3 b number(7);
4 c number(7);
5 begin
6 a:=&a;
7 b:=&b;
8 c:=&c;
9 if(a>b and a>c) then
10 dbms_output.put_line ('The greatest of the three is '|| a);
11 else if (b>c) then
```

```
12 dbms_output.put_line ('The greatest of the three is ' || b);
13 else
14 dbms_output.put_line ('The greatest of the three is ' || c);
15 end if;
16 end if;
17 end;
18 /
```

Enter value for a: 5

```
old 6: a:=&a;
new 6: a:=5;
```

Enter value for b: 7

```
old 7: b:=&b;
new 7: b:=7;
```

Enter value for c: 1

```
old 8: c:=&c;
new 8: c:=1;
```

The greatest of the three is 7

PL/SQL procedure successfully completed.

### **PRINT NUMBERS FROM 1 TO 5 USING SIMPLE LOOP**

```
SQL> set serveroutput on;
```

```
SQL> declare
2 a number:=1;
3 begin
4 loop
5 dbms_output.put_line (a);
6 a:=a+1;
```

```
7 exit when a>5;  
8 end loop;  
9 end;  
10 /  
1  
2  
3  
4  
5
```

PL/SQL procedure successfully completed.

#### **PRINT NUMBERS FROM 1 TO 4 USING WHILE LOOP**

```
SQL> set serveroutput on;
```

```
SQL> declare  
2 a number:=1;  
3 begin  
4 while(a<5)  
5 loop  
6 dbms_output.put_line (a);  
7 a:=a+1;  
8 end loop;  
9 end;  
10 /  
1  
2  
3  
4
```

PL/SQL procedure successfully completed.

### **PRINT NUMBERS FROM 1 TO 5 USING FOR LOOP**

SQL> set serveroutput on;

```
SQL> declare
 2  a number:=1;
 3  begin
 4  for a in 1..5
 5  loop
 6  dbms_output.put_line (a);
 7  end loop;
 8  end;
 9 /
1
2
3
4
5
```

PL/SQL procedure successfully completed.

### **PRINT NUMBERS FROM 1 TO 5 IN REVERSE ORDER USING FOR LOOP**

SQL> set serveroutput on;

```
SQL> declare
 2  a number:=1;
 3  begin
 4  for a in reverse 1..5
 5  loop
 6  dbms_output.put_line (a);
 7  end loop;
 8  end;
 9 /
5
```

4  
3  
2  
1

PL/SQL procedure successfully completed.

### **TO CALCULATE AREA OF CIRCLE**

```
SQL> set serveroutput on;  
SQL> declare  
2 pi constant number(4,2):=3.14;  
3 a number(20);  
4 r number(20);  
5 begin  
6 r:=&r;  
7 a:= pi* power(r,2);  
8 dbms_output.put_line (' The area of circle is ' || a);  
9 end;  
10 /
```

Enter value for r: 2

```
old 6: r:=&r;  
new 6: r:=2;
```

The area of circle is 13

PL/SQL procedure successfully completed.

### **TO CREATE SACCOUNT TABLE**

```
SQL> create table saccount ( accno number(5), name varchar2(20), bal number(10));
```

Table created.

```
SQL> insert into saccount values ( 1,'mala',20000);
```

1 row created.

```
SQL> insert into saccount values (2,'kala',30000);
```

1 row created.

```
SQL> select * from saccount;
```

ACCNO NAME                    BAL

---

|        |       |
|--------|-------|
| 1 mala | 20000 |
| 2 kala | 30000 |

SQL> set serveroutput on;

SQL> declare

```
2 a_bal number(7);
3 a_no varchar2(20);
4 debit number(7):=2000;
5 minamt number(7):=500;
6 begin
7 a_no:=&a_no;
8 select bal into a_bal from saccount where accno= a_no;
9 a_bal:= a_bal-debit;
10 if (a_bal > minamt) then
11 update saccount set bal=bal-debit where accno=a_no;
12 end if;
13 end;
14
15 /
```

Enter value for a\_no: 1

old 7: a\_no:=&a\_no;  
new 7: a\_no:=1;

PL/SQL procedure successfully completed.

SQL> select \* from saccount;

ACCNO NAME                    BAL

---

|        |       |
|--------|-------|
| 1 mala | 18000 |
| 2 kala | 30000 |

## **TO CREATE TABLE SROUTES**

```
SQL> create table sroutes ( rno number(5), origin varchar2(20), destination varchar2(20), fare  
numbe
```

```
r(10), distance number(10));
```

```
Table created.
```

```
SQL> insert into sroutes values ( 2, 'chennai', 'dindugal', 400,230);
```

```
1 row created.
```

```
SQL> insert into sroutes values ( 3, 'chennai', 'madurai', 250,300);
```

```
1 row created.
```

```
SQL> insert into sroutes values ( 6, 'thanjavur', 'palani', 350,370);
```

```
1 row created.
```

```
SQL> select * from sroutes;
```

| RNO | ORIGIN    | DESTINATION | FARE | DISTANCE |
|-----|-----------|-------------|------|----------|
| 2   | chennai   | dindugal    | 400  | 230      |
| 3   | chennai   | madurai     | 250  | 300      |
| 6   | thanjavur | palani      | 350  | 370      |

```
SQL> set serveroutput on;
```

```
SQL> declare  
2 route sroutes.rno % type;  
3 fares sroutes.fare % type;  
4 dist sroutes.distance % type;  
5 begin  
6 route:=&route;  
7 select fare, distance into fares , dist from sroutes where rno=route;  
8 if (dist < 250) then  
9 update sroutes set fare=300 where rno=route;  
10 else if dist between 250 and 370 then  
11 update sroutes set fare=400 where rno=route;
```

```
12 else if (dist > 400) then  
13 dbms_output.put_line('Sorry');  
14 end if;  
15 end if;  
16 end if;  
17 end;  
18 /
```

Enter value for route: 3

```
old 6: route:=&route;  
new 6: route:=3;
```

PL/SQL procedure successfully completed.

SQL> select \* from sroutes;

| RNO | ORIGIN    | DESTINATION | FARE | DISTANCE |
|-----|-----------|-------------|------|----------|
| 2   | chennai   | dindugal    | 400  | 230      |
| 3   | chennai   | madurai     | 400  | 300      |
| 6   | thanjavur | palani      | 350  | 370      |

### TO CREATE SCALCULATE TABLE

SQL> create table scalculate ( radius number(3), area number(5,2));

Table created.

SQL> desc scalculate;

| Name   | Null? | Type        |
|--------|-------|-------------|
| RADIUS |       | NUMBER(3)   |
| AREA   |       | NUMBER(5,2) |

```
SQL> set serveroutput on;
```

```
SQL> declare
  2 pi constant number(4,2):=3.14;
  3 area number(5,2);
  4 radius number(3);
  5 begin
  6 radius:=3;
  7 while (radius <=7)
  8 loop
  9 area:= pi* power(radius,2);
10 insert into scalculate values (radius,area);
11 radius:=radius+1;
12 end loop;
13 end;
14 /
```

PL/SQL procedure successfully completed.

```
SQL> select * from scalculate;
```

| RADIUS | AREA   |
|--------|--------|
| 3      | 28.26  |
| 4      | 50.24  |
| 5      | 78.5   |
| 6      | 113.04 |
| 7      | 153.86 |

### **TO CALCULATE FACTORIAL OF A GIVEN NUMBER**

```
SQL> set serveroutput on;
```

```
SQL> declare
```

```
2 f number(4):=1;
3 i number(4);
4 begin
5 i:=&i;
6 while(i>=1)
7 loop
8 f:=f*i;
9 i:=i-1;
10 end loop;
11 dbms_output.put_line('The value is ' || f);
12 end;
13 /
```

Enter value for i: 5

old 5: i:=&i;

new 5: i:=5;

The value is 120

PL/SQL procedure successfully completed.

## Program 1

Write a code in PL/SQL to develop a trigger that enforces referential integrity by preventing the deletion of a parent record if child records exist.

-- Create the parent table

```
CREATE TABLE parent_table (
    parent_id NUMBER PRIMARY KEY,
    parent_name VARCHAR2(100)
);
```

-- Create the child table with a foreign key constraint

```
CREATE TABLE child_table (
    child_id NUMBER PRIMARY KEY,
    parent_id NUMBER,
    child_name VARCHAR2(100),
    CONSTRAINT fk_parent FOREIGN KEY (parent_id)
        REFERENCES parent_table(parent_id)
);
```

-- Create the trigger to enforce referential integrity

```
CREATE OR REPLACE TRIGGER prevent_parent_deletion
```

```
BEFORE DELETE ON parent_table
```

```
FOR EACH ROW
```

```
DECLARE
```

```
    v_child_count NUMBER;
```

```
BEGIN
```

```
-- Count the number of child records that reference the parent
```

```
    SELECT COUNT(*) INTO v_child_count
```

```
    FROM child_table
```

```
    WHERE parent_id = :OLD.parent_id;
```

```
-- If there are any child records, raise an exception
```

```
    IF v_child_count > 0 THEN
```

```
        RAISE_APPLICATION_ERROR(-20001, 'Cannot delete parent record because  
child records exist.');
```

```
    END IF;
```

```
END;
```

## Program 2

Write a code in PL/SQL to create a trigger that checks for duplicate values in a specific column and raises an exception if found.

-- Create the users table

```
CREATE TABLE users (
    user_id NUMBER PRIMARY KEY,
    username VARCHAR2(50) NOT NULL,
    email VARCHAR2(100),
    created_at DATE DEFAULT SYSDATE
);
```

-- Create the trigger to check for duplicate usernames

```
CREATE OR REPLACE TRIGGER check_duplicate_username
BEFORE INSERT OR UPDATE ON users
FOR EACH ROW
```

DECLARE

v\_count NUMBER;

BEGIN

-- Check for duplicate username in the table

```
IF :NEW.username IS NOT NULL THEN  
    SELECT COUNT(*) INTO v_count  
    FROM users  
    WHERE username = :NEW.username  
    AND (user_id != :NEW.user_id OR :NEW.user_id IS NULL); -- Exclude the  
current row for UPDATE  
    -- If a duplicate username is found, raise an exception  
    IF v_count > 0 THEN  
        RAISE_APPLICATION_ERROR(-20001, 'Duplicate username is not allowed.');//  
    END IF;  
END IF;  
END;  
/
```

### Program 3

Write a code in PL/SQL to create a trigger that restricts the insertion of new rows if the total of a column's values exceeds a certain threshold.

Ans:

```
CREATE OR REPLACE TRIGGER trg_check_column_total
BEFORE INSERT OR UPDATE ON your_table
FOR EACH
ROW
DECLARE
    v_total NUMBER;
BEGIN
    SELECT SUM(your_column) INTO v_total
    FROM your_table;

    IF (INSERTING AND (:NEW.your_column + v_total) > 100) OR
        (UPDATING AND (:NEW.your_column - :OLD.your_column + v_total) >
        100) THEN
        RAISE_APPLICATION_ERROR(-20003, 'Total value exceeds
threshold.');
    END IF;
END;
```

## Program 4

Write a code in PL/SQL to design a trigger that captures changes made to specific columns and logs them in an audit table.

```
CREATE OR REPLACE TRIGGER trg_audit_column_changes
AFTER UPDATE ON your_table
FOR EACH ROW
DECLARE
BEGIN
INSERT INTO audit_table (table_name, old_value, new_value, column_name,
timestamp) VALUES ('your_table', :OLD.column1, :NEW.column1,
'column1', SYSDATE);

-- Add more INSERT statements for other
audited columns END;
```

## Program 5

Write a code in PL/SQL to implement a trigger that records user activity (inserts, updates, deletes) in an audit log for a given set of tables.

```
CREATE OR REPLACE TRIGGER trg_audit_table_changes
AFTER INSERT OR UPDATE OR DELETE ON your_table
FOR EACH ROW
DECLARE
BEGIN
  IF INSERTING THEN
    -- Insert audit record for INSERT operation
  ELSIF UPDATING THEN
    -- Insert audit record for UPDATE operation
  ELSIF DELETING THEN
    -- Insert audit record for DELETE operation
  END IF;
END;
```

## Program 6

Write a code in PL/SQL to implement a trigger that automatically calculates and updates a running total column for a table whenever new rows are inserted.

Ans:

```
CREATE OR REPLACE TRIGGER trg_update_running_total
AFTER INSERT OR UPDATE ON your_table
FOR EACH ROW
DECLARE
BEGIN
    UPDATE your_table
    SET running_total = (SELECT SUM(your_column) FROM
your_table); END;
```

## Program 7

Write a code in PL/SQL to create a trigger that validates the availability of items before allowing an order to be placed, considering stock levels and pending orders.

Ans:

```
CREATE OR REPLACE TRIGGER trg_validate_order_items
BEFORE INSERT OR UPDATE ON orders
FOR EACH
ROW
DECLARE
    v_item_id NUMBER := :NEW.item_id;
    v_quantity_ordered NUMBER :=
    :NEW.quantity;
    v_available_quantity NUMBER;
BEGIN
    -- Check item availability, considering both stock and pending orders
    SELECT NVL(SUM(quantity), 0) - NVL(SUM(quantity_ordered), 0)
    INTO v_available_quantity
    FROM inventory
    WHERE item_id = v_item_id;

    IF v_available_quantity < v_quantity_ordered THEN
        RAISE_APPLICATION_ERROR(-20004, 'Insufficient quantity for item ' ||
        v_item_id);
    END IF;
END;
```

# MONGO DB

221701020

**Ex. No: 20**

**Date:**

**Register No: 221701020**

**Name: Hemalatha R**

---

## **MONGO DB**

MongoDB is a free and open-source cross-platform document-oriented database. Classified as a NoSQL database, MongoDB avoids the traditional table-based relational database structure in favor of JSON-like documents with dynamic schemas, making the integration of data in certain types of applications easier and faster.

### [Create Database using mongosh](#)

After connecting to your database using mongosh, you can see which database you are using by typing db in your terminal.

If you have used the connection string provided from the MongoDB Atlas dashboard, you should be connected to the myFirstDatabase database.

### [Show all databases](#)

To see all available databases, in your terminal type show dbs.

Notice that myFirstDatabase is not listed. This is because the database is empty. An empty database is essentially non-existent.

### [Change or Create a Database](#)

You can change or create a new database by typing use then the name of the database.

### [Create Collection using mongosh](#)

You can create a collection using the createCollection() database method.

### [Insert Documents](#)

#### [insertOne\(\)](#)

```
db.posts.insertOne({  
    title: "Post Title 1",  
    body: "Body of post.",  
    category: "News",  
    likes: 1,  
    tags: ["news", "events"],  
    date: Date()  
})
```

221701020

**Ex. No: 21**

**Date:**

**Register No: 221701020**

**Name: Hemalatha R**

---

Structure of 'restaurants' collection:

```
{  
  "address": {  
    "building": "1007",  
    "coord": [ -73.856077, 40.848447 ],  
    "street": "Morris Park Ave",  
    "zipcode": "10462"  
  },  
  "borough": "Bronx",  
  "cuisine": "Bakery",  
  "grades": [  
    { "date": { "$date": 1393804800000 }, "grade": "A", "score": 2 },  
    { "date": { "$date": 1378857600000 }, "grade": "A", "score": 6 },  
    { "date": { "$date": 1358985600000 }, "grade": "A", "score": 10 },  
    { "date": { "$date": 1322006400000 }, "grade": "A", "score": 9 },  
    { "date": { "$date": 1299715200000 }, "grade": "B", "score": 14 }  
],  
  "name": "Morris Park Bake Shop",  
  "restaurant_id": "30075445"  
}
```

**1. Write a MongoDB query to find the restaurant Id, name, borough and cuisine for those restaurants which prepared dish except 'American' and 'Chinees' or restaurant's name begins with letter 'Wil'.**

```
db.restaurants.find(  
  
{  
  
    $or: [  
  
        { cuisine: { $nin: ["American", "Chinese"] } },  
  
        { name: { $regex: /^Wil/i } }  
  
    ]  
,  
  
{  
  
    restaurant_id: 1,  
  
    name: 1,  
  
    borough: 1,  
  
    cuisine: 1,  
  
    _id: 0  
}  
)
```

**2. Write a MongoDB query to find the restaurant Id, name, and grades for those restaurants which achieved a grade of "A" and scored 11 on an ISODate "2014-08-11T00:00:00Z" among many of survey dates..**

```
db.restaurants.find(  
  
{  
  
    grades: {  
  
        $elemMatch: {  
  
            grade: "A",  
  
            score: 11,  
        }  
    }  
}
```

```
date: { $eq: ISODate("2014-08-11T00:00:00Z") }

}

},

{

  restaurant_id: 1,
  name: 1,
  grades: 1,
  _id: 0
}
)
```

**3. Write a MongoDB query to find the restaurant Id, name and grades for those restaurants where the 2nd element of grades array contains a grade of "A" and score 9 on an ISODate "2014-08-11T00:00:00Z".**

```
db.restaurants.find(
{
  "grades.1": {
    grade: "A",
    score: 9,
    date: ISODate("2014-08-11T00:00:00Z")
  }
},
{
  restaurant_id: 1,
  name: 1,
  grades: 1,
```

```
    _id: 0  
}  
)
```

**4. Write a MongoDB query to find the restaurant Id, name, address and geographical location for those restaurants where 2nd element of coord array contains a value which is more than 42 and upto 52..**

```
db.restaurants.find()  
{  
    "address.coord.1": { $gt: 42, $lte: 52 }  
,  
{  
    restaurant_id: 1,  
    name: 1,  
    address: 1,  
    "address.coord": 1,  
    _id: 0  
}  
)
```

**5. Write a MongoDB query to arrange the name of the restaurants in ascending order along with all the columns.**

```
db.restaurants.find().sort({ name: 1 })
```

**6. Write a MongoDB query to arrange the name of the restaurants in descending along with all the columns.**

```
db.restaurants.find().sort({ name: -1 })
```

**7. Write a MongoDB query to arrange the name of the cuisine in ascending order and for that same cuisine borough should be in descending order.**

```
db.restaurants.find().sort({ cuisine: 1, borough: -1 })
```

**8. Write a MongoDB query to know whether all the addresses contains the street or not.**

```
db.restaurants.find(  
  { "address.street": { $exists: false } }  
)
```

**9. Write a MongoDB query which will select all documents in the restaurants collection where the coord field value is Double.**

```
db.restaurants.find(  
  {  
    "address.coord": { $type: "double" }  
  }  
)
```

**10. Write a MongoDB query which will select the restaurant Id, name and grades for those restaurants which returns 0 as a remainder after dividing the score by 7.**

```
db.restaurants.find(  
  {  
    "grades.score": { $mod: [7, 0] }  
  },  
  {  
    restaurant_id: 1,  
    name: 1,  
    grades: 1,  
    _id: 0  
  }  
)
```

**11. Write a MongoDB query to find the restaurant name, borough, longitude and attitude and cuisine for those restaurants which contains 'mon' as three letters somewhere in its name.**

```
db.restaurants.find(  
{  
    name: { $regex: /mon/i }  
,  
{  
    name: 1,  
    borough: 1,  
    "address.coord": 1,  
    cuisine: 1,  
    _id: 0  
}  
)
```

**12. Write a MongoDB query to find the restaurant name, borough, longitude and latitude and cuisine for those restaurants which contain 'Mad' as first three letters of its name.**

```
db.restaurants.find(  
{  
    name: { $regex: /^Mad/i }  
,  
{  
    name: 1,  
    borough: 1,  
    "address.coord": 1,  
    cuisine: 1,  
    _id: 0  
})
```

```
_id: 0  
}  
)
```

**13. Write a MongoDB query to find the restaurants that have at least one grade with a score of less than 5.**

```
db.restaurants.find(  
{  
    "grades.score": { $lt: 5 }  
}  
)
```

**14. Write a MongoDB query to find the restaurants that have at least one grade with a score of less than 5 and that are located in the borough of Manhattan.**

```
db.restaurants.find(  
{  
    "grades.score": { $lt: 5 },  
    borough: "Manhattan"  
}  
)
```

**15. Write a MongoDB query to find the restaurants that have at least one grade with a score of less than 5 and that are located in the borough of Manhattan or Brooklyn.**

```
db.restaurants.find(  
{  
    "grades.score": { $lt: 5 },  
    borough: { $in: ["Manhattan", "Brooklyn"] }  
}  
)
```

**16. Write a MongoDB query to find the restaurants that have at least one grade with a score of less than 5 and that are located in the borough of Manhattan or Brooklyn, and their cuisine is not American.**

```
db.restaurants.find(
```

```
{  
    "grades.score": { $lt: 5 },  
    "borough": { $in: ["Manhattan", "Brooklyn"] },  
    "cuisine": { $ne: "American" }  
}  
)
```

**17. Write a MongoDB query to find the restaurants that have at least one grade with a score of less than 5 and that are located in the borough of Manhattan or Brooklyn, and their cuisine is not American or Chinese.**

```
db.restaurants.find(
```

```
{  
    "grades.score": { $lt: 5 },  
    "borough": { $in: ["Manhattan", "Brooklyn"] },  
    "cuisine": { $nin: ["American", "Chinese"] }  
}  
)
```

**18. Write a MongoDB query to find the restaurants that have a grade with a score of 2 and a grade with a score of 6.**

```
db.restaurants.find(
```

```
{  
    "grades.score": { $in: [2, 6] }  
}  
)
```

**19. Write a MongoDB query to find the restaurants that have a grade with a score of 2 and a grade with a score of 6 and are located in the borough of Manhattan.**

```
db.restaurants.find(
```

```
{  
    "grades.score": { $in: [2, 6] },  
    borough: "Manhattan"  
}  
)
```

**20. Write a MongoDB query to find the restaurants that have a grade with a score of 2 and a grade with a score of 6 and are located in the borough of Manhattan or Brooklyn.**

```
db.restaurants.find(
```

```
{  
    "grades.score": { $in: [2, 6] },  
    borough: { $in: ["Manhattan", "Brooklyn"] }  
}  
)
```

**21. Write a MongoDB query to find the restaurants that have a grade with a score of 2 and a grade with a score of 6 and are located in the borough of Manhattan or Brooklyn, and their cuisine is not American.**

```
db.restaurants.find(
```

```
{  
    "grades.score": { $in: [2, 6] },  
    borough: { $in: ["Manhattan", "Brooklyn"] },  
    cuisine: { $ne: "American" }  
}  
)
```

**22. Write a MongoDB query to find the restaurants that have a grade with a score of 2 and a grade with a score of 6 and are located in the borough of Manhattan or Brooklyn, and their cuisine is not American or Chinese.**

```
db.restaurants.find(
```

```
{
```

```
  "grades.score": { $in: [2, 6] },  
  borough: { $in: ["Manhattan", "Brooklyn"] },  
  cuisine: { $nin: ["American", "Chinese"] }  
  
}
```

```
)
```

**23. Write a MongoDB query to find the restaurants that have a grade with a score of 2 or a grade with a score of 6.**

```
db.restaurants.find(
```

```
{
```

```
  "grades.score": { $in: [2, 6] }  
}  
)
```

### Sample document of 'movies' collection

```
{
```

```
  _id: ObjectId("573a1390f29313caabcd42e8"),  
  plot: 'A group of bandits stage a brazen train hold-up, only to find a determined posse hot on their heels.',  
  genres: [ 'Short', 'Western' ],  
  runtime: 11,  
  cast: [  
    'A.C. Abadie',  
    "Gilbert M. 'Broncho Billy' Anderson",
```

'George Barnes',  
'Justus D. Barnes'  
,  
poster: 'https://m.media-amazon.com/images/M/MV5BMTU3NjE5NzYtYTYYyNS00MDVmLWIwYjgtMmYwYWIxZDYyNzU2XkEyXkFqcGdeQXVyNzQzNzQxNzI@.\_V1\_SY1000\_SX677\_AL\_.jpg',  
title: 'The Great Train Robbery',  
fullplot: "Among the earliest existing films in American cinema - notable as the first film that presented a narrative story to tell - it depicts a group of cowboy outlaws who hold up a train and rob the passengers. They are then pursued by a Sheriff's posse. Several scenes have color included - all hand tinted.",  
languages: [ 'English' ],  
released: ISODate("1903-12-01T00:00:00.000Z"),  
directors: [ 'Edwin S. Porter' ],  
rated: 'TV-G',  
awards: { wins: 1, nominations: 0, text: '1 win.' },  
lastupdated: '2015-08-13 00:27:59.177000000',  
year: 1903,  
imdb: { rating: 7.4, votes: 9847, id: 439 },  
countries: [ 'USA' ],  
type: 'movie',  
tomatoes: {  
viewer: { rating: 3.7, numReviews: 2559, meter: 75 },  
fresh: 6,  
critic: { rating: 7.6, numReviews: 6, meter: 100 },  
rotten: 0,

```
lastUpdated: ISODate("2015-08-08T19:16:10.000Z")
```

```
}
```

1. Find all movies with full information from the 'movies' collection that released in the year 1893.

```
db.movies.find(
```

```
 { year: 1893 }
```

```
)
```

2. Find all movies with full information from the 'movies' collection that have a runtime greater than 120 minutes.

```
db.movies.find(
```

```
 { runtime: { $gt: 120 } }
```

```
)
```

3. Find all movies with full information from the 'movies' collection that have "Short" genre.

```
db.movies.find(
```

```
 { genres: "Short" }
```

```
)
```

4. Retrieve all movies from the 'movies' collection that were directed by "William K.L. Dickson" and include complete information for each movie.

```
db.movies.find(
```

```
 { directors: "William K.L. Dickson" }
```

```
)
```

5. Retrieve all movies from the 'movies' collection that were released in the USA and include complete information for each movie.

```
db.movies.find(
```

```
 { countries: "USA" }
```

```
)
```

6. Retrieve all movies from the 'movies' collection that have complete information and are rated as "UNRATED".

```
db.movies.find(
```

```
    { rated: "UNRATED" }
```

```
)
```

7. Retrieve all movies from the 'movies' collection that have complete information and have received more than 1000 votes on IMDb.

```
db.movies.find(
```

```
    { "imdb.votes": { $gt: 1000 } }
```

```
)
```

8. Retrieve all movies from the 'movies' collection that have complete information and have an IMDb rating higher than 7.

```
db.movies.find(
```

```
    { "imdb.rating": { $gt: 7 } }
```

```
)
```

9. Retrieve all movies from the 'movies' collection that have complete information and have a viewer rating higher than 4 on Tomatoes.

```
db.movies.find(
```

```
    { "tomatoes.viewer.rating": { $gt: 4 } }
```

```
)
```

10. Retrieve all movies from the 'movies' collection that have received an award.

```
db.movies.find(
```

```
    { "awards.wins": { $gt: 0 } }
```

```
)
```

11. Find all movies with title, languages, released, directors, writers, awards, year, genres, runtime, cast, countries from the 'movies' collection in MongoDB that have at least one nomination.

```
db.movies.find(
```

```
  { "awards.nominations": { $gt: 0 } },
```

```
{
```

```
  title: 1,
```

```
  languages: 1,
```

```
  released: 1,
```

```
  directors: 1,
```

```
  writers: 1,
```

```
  awards: 1,
```

```
  year: 1,
```

```
  genres: 1,
```

```
  runtime: 1,
```

```
  cast: 1,
```

```
  countries: 1
```

```
}
```

```
)
```

12. Find all movies with title, languages, released, directors, writers, awards, year, genres, runtime, cast, countries from the 'movies' collection in MongoDB with cast including "Charles Kayser".

```
db.movies.find(
```

```
  { cast: "Charles Kayser" },
```

```
  {
```

```
    title: 1,
```

```
    languages: 1,
```

```
    released: 1,
```

```
    directors: 1,
```

```
    writers: 1,
```

```
    awards: 1,
```

```
    year: 1,
```

```
    genres: 1,
```

```
    runtime: 1,
```

```
    cast: 1,
```

```
    countries: 1
```

```
}
```

```
)
```

13. Retrieve all movies with title, languages, released, directors, writers, countries from the 'movies' collection in MongoDB that released on May 9, 1893.  
db.movies.find(

```
{ released: ISODate("1893-05-09T00:00:00.000Z") },  
{  
    title: 1,  
    languages: 1,  
    released: 1,  
    directors: 1,  
    writers: 1,  
    countries: 1  
}  
)
```

14. Retrieve all movies with title, languages, released, directors, writers, countries from the 'movies' collection in MongoDB that have a word "scene" in the title.

```
db.movies.find(  
{ title: /scene/i },  
{  
    title: 1,  
    languages: 1,  
    released: 1,  
    directors: 1,  
    writers: 1,  
    countries: 1  
}  
)
```