

Elements of HTML

HTML code is divided into elements, each holding a specific type of content. An HTML page can be compared to a suitcase, with separate sections for clothes, toiletries, and travel documents. These sub-elements make it easier to find things and arrange the suitcase in just the way a user wants.

Tags

< > </ >

HTML is primarily written with tags that have angular brackets. Every opening tag must have a matching closing tag, with the content between them. Common HTML tags include paragraphs (<p>), tables (<table>), and links (<a>). The “opening tag + content + closing tag” combo is collectively called an element.

IN DEPTH

Markup languages

HTML is considered a markup language, which means it's more limited than a regular programming language, and can't be used to write a 3D game or a mobile app. Instead, markup languages are used to help process and format text. They specify things such as font, spacing, and colour. They're also used to annotate the text, making it easier for other languages to manipulate sections. Examples of markup languages include XML, XHTML, and LaTeX.

```
<html>
  <head>
  </head>
  <body>
    <header>
      <title>Welcome!</title>
    </header>
    <div id="main">
      <h1>Welcome!</h1>
      <p class="centered_text">Welcome again...</p>
      </img>
    </div>
    <footer>
      example.email@example.com
    </footer>
  </body>
</html>
```

Semantics

HTML tags are semantic, which is a fancy way of saying that the type of tag indicates the type of content it contains. A “header” tag, for instance, stores content displayed at the top of the page, while a “footer” tag is displayed at the bottom. Having different types of tag makes it easier for the rendering engine to build the final webpage. It's also easier for programmers to read the code.



Attributes

< = " " >

An image tag might have a “size” attribute and a “source” attribute, while a font tag could have a “colour” attribute. Attributes are used to pass details to the rendering engine. The value of an attribute is called a modifier. “Id” and “class” are special attributes that help the rendering engine quickly locate the elements it needs on a webpage. They're particularly important for CSS code, which uses id and class to distinguish between styles.

△ Nested tags

Well-organized HTML is a series of tags within tags, each more specific than the last.