

THE EXTERIOR

Concorde had to withstand huge variations in temperature as well as the stresses imposed on it by supersonic flight. Most of the airframe was made from an aluminum alloy developed for engine parts in the 1920s. The engines were secured inside their nacelles, which flexed with the movements of the wing.

1. Passenger door 2. Latch for outward-opening plug-type passenger door 3. Port side navigation light 4. Port wing root fillet 5. Nosewheel landing lights 6. Instrumentation access panel 7. Main undercarriage retraction jacks 8. Specially designed multi-ply tires, inflated to 187lb per square inch (13 kg per sq cm) 9. Variable-geometry engine air intake 10. Ram-air turbine 11. Vent on underside of fuselage 12. Detailed riveting toward tail of plane 13. Engine thrust-reverse buckets (closed) 14. Tail wheel (in case of over-rotation during takeoff)



THE INTERIOR

The cabin of Concorde set very specific challenges of its own to the designers, the interior having to provide a feeling of comfort and luxury while at the same time adhering to the extremely precise technical demands of a highly advanced supersonic airliner. Although the windows were small in comparison with those in a standard airliner, a great deal of attention was paid to the cabin furnishings, which were updated periodically during the type's long service career.

22. Inside of passenger door 23. Concorde logo on galley unit 24. Oven controls in Galley No 1 25. One of Concorde's three toilets 26. Passenger cabin 27. Overhead lockers 28. Passenger overhead panel 29. Passenger seating in fabric used 1996–2000 30. Passenger seat armrest controls 31. Storage for front row of passenger seats set into wall 32. Cabin window

