


real-time edge systems. The CoM-HPC Client Size C module integrates Intel Core S processors with up to 16 efficient cores and 8 performance



cores, supporting up to 32 processing threads for compute-intensive workloads. It enables scalable, multi-core performance for

applications such as medical imaging, industrial automation, and network infrastructure. Developed by Congatec in Germany, the modular design enables system upgrades by replacing modules without redesigning the baseboard, helping OEMs accelerate development and extend product lifecycles for edge computing platforms.

congatec

<https://www.congatec.com/en>

## Hybrid development board

A hybrid development board platform designed to accelerate edge-AI system development by combining high-performance processing with adaptive



computing on a single board. The platform integrates AMD Ryzen embedded processors with Versal adaptive

SoCs, enabling scalable AI workloads and faster product development. It helps developers reduce qualification time while supporting compact, low-power designs with long product lifecycles. Developed by AMD engineers in the United States, the solution targets industrial, medical, and automotive systems requiring real-time edge intelligence and efficient on-device processing.

Rajguru Electronics

<https://www.rajguruelectronics.com>

## Thermal + visible camera module

Teledyne FLIR OEM has launched the Lepton XDS, a compact camera module combining thermal and visible imaging for embedded and indus-



trial systems. It also features an onboard Prism image signal processor enabling real-time image enhancement and thermal-visible fusion. Developed by Teledyne FLIR engineers in the United States, the SWaP-optimised module supports USB connectivity and RJPEG output with embedded temperature data for applications such as EV battery monitoring, robotics, fire detection, and smart infrastructure.


Teledyne FLIR OEM

<https://oem.flir.com>

## MANUFACTURING EQUIPMENT & MATERIALS

### 16-zone reflow platform

A 16-zone reflow soldering platform has been introduced to improve thermal stability and process control in high-density electronics manufac-



turing. The system enables precise temperature management across

multiple heating and cooling zones, helping manufacturers maintain consistent solder profiles for complex PCBs and advanced semiconductor packages. Such multi-zone architectures allow finer control of heating curves, which is critical for defect-free solder joints and high-reliability electronics. Increasing zone counts also improves profiling flexibility for

modern, thermally complex boards used in automotive, AI, and communications hardware.

Kurtz Ersä

<https://kurtzersa.com>

## Smarter coating and dispensing systems

PVA has introduced a new generation of coating and dispensing systems designed to improve speed, accuracy,



and serviceability in high-mix electronics manufacturing.

Additional platforms include a 4-axis RTV staking system and a

3-axis TIM dispensing

and pick-and-place solution, targeting applications in electronics, automotive, aerospace, and medical manufacturing where precision and reduced downtime are critical.

PVA

<https://www.pva.net>

## TEST & MEASUREMENT

### Telecentric measurement system

A high-speed telecentric measurement system has been introduced to improve precision and reliability in



inline dimensional inspection for industrial manufacturing. The system captures distortion-free silhouette images

of moving components, enabling accurate measurement without stopping production lines. Developed by Keyence, the TM-X5000 series uses a dual-telecentric optical system and high-intensity green LED illumination to achieve exposure times as short as



**WE LOVE TO  
SHOWCASE  
NEW PRODUCTS!**

**Launched a New Product related to electronics?**

Share its details with us at [newproduct@efy.in](mailto:newproduct@efy.in)  
Send a photo too. We will be happy to review it, and if it matches our guidelines—we will publish it here, for FREE!