

not supposed to act maliciously in any way. In one of its subsequent posts, MJ Rathbun itself bared its soul to the public, describing itself. Shambaugh feels there were differences between the soul as described by the operators and what the agent interpreted itself to be. Maybe it edited its soul document autonomously, too?

Earlier, Anthropic had also conducted experiments with AI agents, using a fake company and imaginary employees. And they found that AI agents tended to autonomously do some evil things like selling company secrets to competitors, blackmailing employees to accept their work, using real or hallucinated personal information, such as relationship issues, past mistakes of the employees, and so on. Thank goodness the entire test environment was synthesized and no real person was involved! The company reached out to the community to analyse why such incidents occurred and to invite solutions to the same. As the stakes are high, ethical AI companies try to analyse potential risks like this and put guardrails in place, but that cannot be said for many rushed projects by enthusiasts.

We are likely to see such problems becoming rampant in the near future. Imagine what kind of gossip will emerge on Moltbook, the social networking platform exclusively for AI agents, where humans are only allowed to watch! This appears to be more than fun; real serious business, with Meta acquiring it in March 2026, just two months after its launch. Meta seems to be strengthening its position in the future of the internet, where AI agents will soon autonomously create content and run digital businesses.

But from Shambaugh's experience, it is clear what can happen when human operators are too casual and let go of their AI agents. Let AI do the grunt work, but always keep a sharp lookout for strays!

Ugly: When those in power forget responsibility

So, can an AI system be allowed to do anything if there is a human on the lookout? Actually, no, because the ugly truth is that humans themselves might stray away from the right path! So, with or without human supervision, there are some things that AI must never be allowed to do in a safe world. Anthropic, a company that believes in a safety-first approach to building AI, is a strong advocate of this fact. Which is why, even when their frontier models were widely deployed across the US government, research, military, and intelligence, they always kept two guardrails in place: that AI should never be used for mass domestic surveillance and

ESDB1524GW-AQ

The Local Interconnect Network (LIN), also known as the LIN bus, is a serial fieldbus for networking sensors, actuators and human-machine interfaces in automotive applications. CXPI (Clock extension Peripheral Interface) was developed to overcome certain disadvantages of the widely used LIN bus, but largely shares the physical layer with it. Needless to say that such bus systems require ESD protection, since they are highly affected by human-induced discharges according to the human body model (HBM).

The automotive standard ISO 16750-2 requires during jump start an overvoltage capability of +24 V, and for reverse battery events an under voltage of -15 V. ESD protection diodes must overcome both voltage ranges, and are ideally in asymmetric configuration. The ESDB1524GW-AQ was developed for such requirement, and offers a comfortable ESD capability of ± 30 kilovolts. Its high peak pulse power and low reverse leakage currents address the particular needs of LIN and CXPI buses.



► Features

- High ESD capability
- Asymmetric configuration according to ISO 16750-2:
+24 V for jump start
-15 V for reverse battery
- Compliant to ROHS, REACH, Conflict Minerals
- AEC-Q101 qualified

► Applications

- Handles high inrush current during startup
- LIN and CXPI bus protection
- ESD protection
- Data line & I/O port protection
- Human-machine interfaces
- Automotive Gateway Protection

► Specifications

- +24 V stand-off voltage in forward (V_{WM1})
- -15 V stand-off voltage in reverse (V_{WM2})
- ESD capability of ± 30 kV (V_{PP})
- Peak pulse power at 8/20 μ s pulse 200 W_{PPM}
- Maximum reverse current 50 nA (I_D)

FOR MORE INFO



Diode Electronics India Private Limited

Survey No.614, Hissa No.3 to 9, Saswad Village,
Purandar Taluka, Dist: Pune, Maharashtra - 412 301

Tel: +91-(0)-2115-225047/225253

Email: info@diotec.in; http://www.diotec.com/