

Key Selection Criteria For BGA Rework Station For Electronics Manufacturing

SELECTION CRITERIA	WHY IT MATTERS IN EMS	WHAT TO EVALUATE	RECOMMENDED BENCH-MARK FOR EMS
Thermal Profile Accuracy	Incorrect heating damages PCB, pads, and components	Closed-loop PID control, multiple thermocouples, and profile repeatability	±1-2°C thermal accuracy
Hybrid Heating Technology	Prevents PCB warpage in multilayer boards	IR bottom heater + hot air top heater	Hybrid heating preferred
Lead-Free Rework Capability	Most EMS production is RoHS compliant	Ability to handle SAC305 and high-temp profiles	Mandatory
Optical Alignment Precision	Critical for fine-pitch BGAs and CSPs	Split-vision camera, alignment resolution	≤20µm alignment accuracy
PCB Size Handling Capacity	EMS companies handle large telecom/server boards	Maximum PCB dimensions supported	Minimum 450mm×500mm
Component Size Capability	Needed for CPUs, FPGAs, GPUs, and large BGAs	Maximum package size supported	Up to 80mm×80mm or higher
Automation Level	Reduces operator dependency and improves repeatability	Manual, semi-auto, or fully automatic operation	Semi-auto minimum for EMS
Repeatability and Yield	Consistent rework quality reduces scrap and failures	First-pass success rate, process stability	>95% repeatability
Multi-Zone Heating	Important for complex HDI and multilayer PCBs	Number of independent heating zones	3-6 zones preferred
Thermal Profiling Software	Ensures process standardisation	Profile storage, graphing, export capability	Advanced profile management
Industry 4.0/MES Connectivity	Required for traceability and audits	Ethernet, SPC logging, and MES integration	Preferred for large EMS
X-Ray Compatibility	Hidden solder joints require inspection	Workflow compatibility with AXI/X-ray systems	Important for automotive/aerospace
Ease of Profile Creation	Faster setup reduces engineering time	Auto profile generation, and guided setup	Strongly preferred
Bottom Heater Power	Large boards need uniform preheating	Wattage and heating area coverage	High-power IR preheater
Airflow Control Precision	Excess airflow can disturb adjacent components	Adjustable airflow and nozzle optimisation	Fine digital airflow control
Nozzle Availability	Different BGA sizes require multiple nozzles	Nozzle range and replacement availability	Wide nozzle library
Service and Technical Support	Downtime directly affects production	Local service presence, and response time	Local support essential
Spare Parts Availability	Heater or camera failure can stop production	Spare lead time and inventory	<1-2 week availability
Calibration Support	Accuracy drifts over time	Annual calibration process and certification	OEM-certified calibration
Operator Skill Dependency	EMS environments need process consistency	Automation and guided workflows	Low dependency preferred
Traceability and Logging	Required for quality audits and customers	Process history, operator logs, thermal logs	Mandatory in automotive EMS
Rework Cycle Time	Impacts throughput and productivity	Average time per BGA rework	Faster automated cycle preferred
Compatibility with Advanced Packages	New electronics use complex packages	FC-BGA, PoP, CSP, and µBGA support	Future-ready capability
Reliability and MTBF	Production lines need high uptime	Machine robustness and failure history	Industrial-grade systems
Safety Features	Protects operator and PCB	ESD protection, and overheat shutdown	Mandatory
Total Cost of Ownership (TCO)	Purchase cost alone is misleading	Maintenance	

KYORITSU ELECTRIC INDIA PVT LTD

Website: www.kyoritsuelectric.com
 Email-ID: sales@kyoritsuelectric.com
 Contact: 020-24668247
 Address: Plot No.10(P), Survey No.234, 235 & 245, India Land Global Industrial Park, Rajiv Gandhi Infotech Park, Phase 1, Hinjewadi, Pune, Maharashtra, India - 411057
Brand(s) Supplied: Den-ON

LEAPTECH CORPORATION

Website: www.leaptech.in
 Email-ID: info@leaptech.in
 Contact: 022-49730589
 Address: Unit No.240, Raheja Tesla Industrial, TTC Industrial Area, MIDC Juinagar, Mumbai, Maharashtra, India - 400705

Brand(s) Supplied: Fonton

MAXIM SMT TECHNOLOGIES PVT LTD

Website: www.maximsmt.com
 Email-ID: sales@maximsmt.com
 Contact: 9540870431
 Address: Plot No.78 A, Sector-5, IMT Manesar, Gurugram, Haryana, India - 122050
Brand(s) Supplied: Seamark

MECTRONICS MARKETING SERVICES

Website: www.mectronics.in
 Email-ID: manish@mectronics.in
 Contact: 011-43041581
 Address: 313, 2nd Floor, Patparganj Industrial Area, Functional Industrial Estate New Delhi, Delhi, India - 110092
Brand(s) Supplied: Seamark

Seamark ZM R5860

Supplied by:
DAIICHI
JITSUGYO
INDIA PVT LTD

