

mission-critical sectors with platforms like its Intel-based eRoC-XT board built for extreme environments. Such rugged compute blocks support industrial automation, transportation, defence command & control and real-time analytics at the edge, bringing robust processing closer to sensors and reducing dependency on cloud links.

ELDAAS Technologies Pvt Ltd
<https://eldaas.com>

Universal AFE

A new two-channel 'Universal AFE' analogue front end from Triad Semiconductor aims to simplify audio input stages by handling both mic-level and line-level signals on the same input without external pads or separate circuits. Its current-conveyor architecture delivers ~156dB dynamic range and >90dB common-mode rejection, enabling it to interface directly with audio ADCs. This suits professional mixers, field recorders, and pro/consumer audio gear where space, noise, and flexibility matter.

Triad Semiconductor
<https://triadsemi.com>

Compact SBC

A new 8.89cm (3.5-inch) compact single-board computer (SBC) from IBASE Technology packs 13th-gen Intel Core CPUs, DDR5 with ECC, dual 2.5GbE and triple M.2 expansion into a rugged, space-saving form factor for industrial edge systems. It supports flexible I/O and wide-temperature operation, enabling machine vision preprocessing, edge gateways, real-time control

and intelligent inspection in automation, transportation, and distributed industrial infrastructure without large enclosures.

IBASE Technology
www.ibase.com.tw

Industrial-grade compute module

A new industrial-grade compute module now lets systems run AI locally without relying on the cloud, addressing limits that often block on-device intelligence in transport, automation, and robotics. The latest COM Express Type 6 compact module delivers up to ~59 TOPS of on-board AI performance with integrated NPU, GPU, and CPU cores, enabling real-time vision, control, and data analysis at the edge, reducing latency and cutting connectivity dependency in rugged applications.

congatec
<https://www.congatec.com/en>

Embedded platform

A new embedded platform with certified mixed-criticality support expands the TQMa8x ecosystem by integrating SYSGO's PikeOS hypervisor-based RTOS on NXP i.MX8 multicore hardware that lets safety-critical and non-critical workloads coexist in a single module with strict isolation. It targets industrial automation, automotive and regulated AI systems, simplifying compliance with functional safety and cybersecurity standards while supporting Linux, real-time tasks, and safety-certifiable HMI/AI functions.

TQ Systems
<https://www.tq-group.com/en>

Low-power embedded module

Variscite's VAR-SMARC-MX8M-PLUS low-power embedded module packs a quad-core ARM CPU with a real-time




core, AI/ML acceleration, vision processing, and integrated security

into a compact SMARC form factor, tackling the classic trade-off between performance and energy draw. It targets industrial IoT, edge AI vision, medical systems, and mobile devices, offering rich I/O, dual Ethernet, and TPM-based security while keeping power budgets tight.

Variscite
<https://variscite.com>

GaN DC-DC platform

Navitas Semiconductor has unveiled a GaN-based 10kW DC-DC power platform that delivers up to 98.5% peak efficiency and operates near



1MHz switching to support the power-conversion demands of next-generation

AI data centres adopting high-voltage DC distribution. The full-brick module supports 800V→50V and ±400V→50V architectures, delivering high power density (~2.1kW/in³) and enabling compact, efficient step-down conversion for racks and HVDC systems driving intense AI workloads.

Navitas Semiconductor
<https://navitassemi.com>

MANUFACTURING EQUIPMENT & MATERIALS

Scalable surface mounter

A new scalable surface mounter (NeoDen N10P) is positioned to help



**WE LOVE TO
SHOWCASE
NEW PRODUCTS!**

Launched a New Product related to electronics?

Share its details with us at newproduct@efy.in
 Send a photo too. We will be happy to review it, and if it matches our guidelines—we will publish it here, for FREE!