



Dry Cabinets

Control MSL floor life - without the hidden cost of high-temperature baking



MSL

1-6

floor-life classes

MSL is a floor-life clock.

Once components leave the moisture barrier bag, exposure time matters. Track it, control it and reset it safely.



WHAT MSL ACTUALLY MEANS

MSL defines how long a component may remain exposed before reflow or dry storage.

$\leq 5\%$ RH

dry storage for exposed parts

40-60°C

mild-temperature
fast drying

WHEN FAST DRYING BECOMES EXPENSIVE DRYING

Traditional oven baking has long been the default when components need to be dried or have their floor life reset. At temperatures of 100°C and above, components and PCBs can experience accelerated oxidation, intermetallic growth and stress on plastic packaging materials.

Totech XSD(B) fast-drying cabinets take a different approach: ultra-low humidity below 0.5% RH combined with mild temperatures of 40-60°C. For most devices, drying can outpace oven baking while avoiding the oxidation and intermetallic damage introduced by high temperatures.

FLOOR LIFE MATTERS

The MSL value sets the exposure time under typical factory conditions ($\leq 30^\circ\text{C}$ / 60% RH). Once that floor life is exceeded, absorbed moisture can vaporise during reflow - causing popcorning, delamination and pad cratering.

Three pillars of MSD handling:
• Know the MSL • Track floor life •
Store exposed parts at $\leq 5\%$ RH

Know the MSL. Track floor life. Store parts dry.

Review your MSL & reset process

Use the QR code to get in contact with Totech Europe.



Scan
and get
in **contact**

Member of the ASYS Group

Totech Europe B.V Head Office The Netherlands | info@totech.eu

Scan and get in contact
with **RMG** sales team



$< 0.5\%$ RH

XSD(B) ultra-low humidity

