


Electric Vehicle Plug & Cables



IEC 62196 Part2 For 4-Wheeler Charger (Plug) With Tethered Cable



Type	Available in 4 models with tethered cable
RC 1P 230 16	Single Phase, 16A, 230V AC RMS, 3.7 KW; 3.5 M/ 5.0 M Length
RC 1P 230 32	Single Phase, 32A, 230V AC RMS, 7.3 KW; 3.5 M/ 5.0 M Length
RC 3P 415 16	Three Phase, 16A, 415V AC RMS, 11 KW; 3.5 M/ 5.0 M Length
RC 3P 415 32	Three Phase, 32A, 415V AC RMS, 22 KW; 3.5 M/ 5.0 M Length




4 Core Charging Cable

230V, 16A, 3 Core x 2.50 sq mm (Power Cores) + 1 Core x 0.75 sq mm (Control Cores)

Power Cores

Yellow-Green, Blue, Brown
Control Core - Red




4 Core Charging Cable

230V, 32A, 3 Core x 6.00 sq mm (Power Cores) + 1 Core x 0.75 sq mm (Control Cores)

Power Cores

Yellow-Green, Blue, Brown
Control Core - Red




6 Core Charging Cable

415V, 16A, 5 Core x 2.50 sq mm (Power Cores) + 1 Core x 0.75 sq mm (Control Cores)

Power Cores

Yellow-Green, Blue, Brown, Red, Black
Control Core - Red



6 Core Charging Cable

415V, 32A, 5 Core x 6.00 sq mm (Power Cores) + 1 Core x 0.75 sq mm (Control Cores)

Power Cores

Yellow-Green, Blue, Brown, Red, Black
Control Core - Red



Approvals



RAYCORE

An ISO 9001:2015 CERTIFIED

Raycor Electromech

KH. No 1100-1101, Salempur Rajputan, Industrial Estate,
Roorkee-247667, District-Haridwar [Uttarakhand].

Web : www.raycore.co.in

Mail Box: info@raycore.co.in; sales@raycore.co.in

Contact

Mr. Awadhesh Yadav : +91 7060540200

Mr. Abdul Rauf : +91 9758050904