

DC TO 86 GHz


Filter Technologies

For Every Application

LEARN MORE




CAVITY



- Passbands to 43.5 GHz
- Stopbands to 57 GHz
- Bandwidths as narrow as 1%
- 100+ dB rejection

CERAMIC RESONATOR




- Fractional bandwidths from 0.5 to 40%
- Excellent power handling, up to 20W
- High Q in miniature SMT package

LUMPED L-C




- Wide catalog selection
- Several package options including aqueous washable
- Variety of filter topologies

LTCC




- Tiny size, as small as 0202
- Industry's widest selection of mmWave LTCC filters
- Proprietary designs with stopband rejection up to 100 dB

MICROSTRIP



- Connectorized designs with 4 to 40% fractional bandwidth
- Power handling up to 10W
- Flat group delay

MMIC REFLECTIONLESS



- Patented topology absorbs and internally terminates stopband signals
- Perfect for pairing with amplifiers, mixers, multipliers, ADC/DACs & more

RECTANGULAR WAVEGUIDE



- WR-12, WR-15 and WR-28 interfaces
- Passbands up to 87 GHz
- High stopband rejection, 40 dB

SUSPENDED SUBSTRATE



- Ultra-wide passbands up to 26 GHz
- Wide stopbands up to 40 GHz
- High Q

THIN FILM ON ALUMINA



- Passbands from DC to 40 GHz
- High rejection with wide passband
- Miniature SMT package