

SiC device portfolio

Navitas has rolled out a new 3300V and 2300V ultra-high-voltage SiC device portfolio built on a trench-assisted planar MOSFET platform, delivering higher voltage-blocking capability, switching

efficiency, and reliability for demanding power systems. The range includes power modules, discrete parts, and known-good dies with enhanced thermal-cycling and shock-resilience. Designers can use them in solid-state transformers, utility storage, renewables, megawatt EV fast chargers, and grid-class converters where efficiency and uptime are critical.

Navitas Semiconductor
<https://navitassemi.com>

24-bit stereo DAC

Nuvoton's NAU8421YG is a compact 24-bit stereo DAC designed for clear, low-noise audio conversion, with



128dB SNR and -99dB THD + N, offering 8Vpp differential output

and strong channel separation to minimise crosstalk. It integrates easily via I²C or standalone control and runs on separate digital/analogue supplies. Key use cases include computers and streamers, audio interfaces and mixers, studio monitors and precision measurement systems where clean analogue output is critical.

Nuvoton Technology Corporation
<https://www.nuvoton.com>

Mass-airflow sensors

Posifa Technologies' PMF82000 mass-airflow sensor series delivers accurate, low-flow measurement with both



analogue (0.5V-4.5V) and digital (I²C) outputs, and minimal airflow resistance, making

it easy to integrate into small systems without heavy computation or power draw. The sensors handle flows up to

~ 10 SLM, respond quickly to changes, and tolerate over-pressure and a wide temperature range, targeting medical breathing/oxygen devices, respiratory equipment, and other compact air-flow-critical products where precision and energy efficiency matter most.

Posifa Technologies
<https://posifatech.com>

Ultra-slim SiC MOSFETs

ROHM's new ultra-slim SiC MOSFETs in low-profile TO-leadless (TOLL) packages cut device height to about 2.3mm



and shrink PCB footprint by ~26%, while boosting thermal performance. Designed

for AI-server supplies, data-centre converters, compact PV inverters, and ESS power stages, they help designers meet tight size, heat, and power-density targets in next-gen systems.

Rohm Semiconductor
<https://www.rohm.com>

DALI sensor

Signify's mains-powered interact motion and daylight DALI sensor helps industrial facilities cut lighting energy



waste by switching lights based on occupancy and ambient light levels, giving real-time activity and daylight data for smarter zone

control and schedule adjustments. It fits existing DALI systems across ceiling heights of 2-16m and supports multiple luminaire families, making it useful for manufacturing floors, warehouses, logistics hubs, and indoor parking.

Signify
<https://www.signify.com/global>

LTCC chip antennas

Taoglas has expanded its high-performance compact LTCC chip antenna range to help wireless connectivity in space-constrained electronics, addressing integration challenges in dense, multi-radio designs. The lineup includes ultra-small antennas for Wi-Fi 6/7, UWB, and ISM bands, delivering

high radiation efficiency, a stable frequency response, and compatibility



with automated SMT assembly. These antennas suit wearables, portable IoT modules, consumer


gadgets, and industrial wireless devices that require reliable RF links in minimal board space.

Taoglas
<https://www.taoglas.com>

EMBEDDED

Computers on modules

Toradex's new OSM Computer on Module family brings edge AI and industrial reliability into tiny devices with compact, solderable modules



built on NXP i.MX 93/91 processors for con-

trollers, gateways, smart sensors, and handhelds in industrial IoT systems. i.MX 93 variants include a 0.5 TOPS NPU for running basic machine-learning tasks, such as sensing and analytics, on-device. Designed for automated production and rugged use from -40°C to +85°C, they support long-term software, OTA updates and secure management for scalable volume deployment.

Toradex
<https://www.toradex.com>

Edge AI vision box

A new edge AI vision box from E-consys-tems, designed for autonomous deployments, combines high-performance AI compute with multi-camera and sensor



fusion to enable real-time perception. Designed for autonomous mobile robots,

it enables navigation, obstacle detection, and fleet scalability. In intelligent transportation systems, it supports traffic monitoring and analytics using synchronised multi-camera inputs. For delivery and service robots, the platform enables reliable vision processing in rugged, field-ready environments.

E-consystems
www.e-consystems.com