

LTpower Analyzer System



The LTpowerAnalyzer System—powered by ADI's high-performance technologies—delivers professional power lab features and performance at fraction of the cost and size. Analyze signals from wide range of sources in a form factor small enough to sit on top of your bench.

A Power Lab on Your Benchtop

Power supply frequency and time domain measurements often require expensive and large lab equipment to get accurate results. The Power Analyzer was developed with the goal of putting a small, portable, and inexpensive instrument that can measure Bode plots, impedances, power supply rejection, and transient load response into the hands of every engineer designing power supplies.



EVAL-LTPA-KIT

The Power Analyzer kit

Get the Power Analyzer kit and start measuring in no time. It works with the ADALM2000 portable oscilloscope, providing a comprehensive solution for your power testing needs.

What's in the box

- ▶ Power Analyzer Board (LB3031A)
- ▶ 4x Current Probes (LB3058A): 1 A, 10 A, 50 A, and 100 A
- ▶ Optional ADALM2000 (M2K) Active Learning Module

Included Accessories

LT8642 DUT, 8" and 2" Ribbon Cables, 1x Interface Board A, and 5x Interface Board B.



LTpowerAnalyzer



Advanced Active Learning Module

Features and Benefits

- Two-channel USB digital oscilloscope and arbitrary function generator
- 16-channel digital logic analyzer (3.3V CMOS and 1.8V or 5V tolerant, 100MS/s)
- 16-channel pattern generator (3.3V CMOS, 100MS/s) and virtual digital I/O
- Two input/output digital trigger signals for linking multiple instruments (3.3V CMOS)
- Network analyzer – Bode, Nyquist, Nichols transfer diagrams of a circuit.
Range: 1Hz to 10MHz
- Spectrum Analyzer – power spectrum and spectral measurements (noise floor, SFDR, SNR, THD, etc.)
- Digital Bus Analyzers (SPI, I²C, UART, Parallel)
- Two programmable power supplies (0...+5V, 0...-5V)



ADALM2000

For more information, please reach out to Cic.asia@analog.com