

LED OBSTRUCTION LIGHTING for




Industrial
chimneys and
smokestacks



Transmission,
microwave and
cellular towers



Radio, TV
and similar
structural towers



High-rise
buildings and
structures



Airports
and airfields

**DESIGNED,
DEVELOPED,
AND
MANUFACTURED
IN INDIA**



*Medium Intensity
20,000 candela
(Flashing White LEDs)*



*High Intensity
200,000 candela
(Flashing White LEDs)*



*Medium Intensity
2,000 candela
(Flashing Red
OR Fixed Red LEDs)*



All BINAY Aviation Lights are based on Non-switching passive type circuitry (NO SMPS)

The circuitry incorporated inside the LED Aviation Obstruction Lights is passive electronic (solid-state) in nature, and does not use internal SMPS driver switching units to control the light unit. Internal LED current control is by non-switching electronic means only. No electrolytic capacitors are used inside the Aviation Obstruction Light unit.

The above is necessary to ensure reliability of the LED Aviation Obstruction Light. This system design effectively eliminates any active components and circuits inside the aviation light itself, and enhances the solid-state passive reliability of the LEDs (mounted in relatively inaccessible locations at the height of tall structures). This drastically reduces the possibility of component failure - and hence possibility of any maintenance requirement - in the LED Aviation Obstruction Lights themselves (which are mounted at extreme heights in the system).

THE BINAY LED OBSTRUCTION LIGHT IS UNDER ACCEPTED PATENT, AND AS SUCH IS A PROPRIETARY PRODUCT



Binay Opto Electronics Pvt. Ltd.

(An ISO 9001:2015 Certified Company)

27, Panditia Terrace, Calcutta 700 029, India

Ph.: +91 (33) 4006 9875, 2475 0062

Email: info@binayLED.com

Website: www.binayled.com

SCAN
QR Code



PROVIDING LED POWERED TECHNOLOGIES SINCE 1983