



Key Selection Criteria For Selective Solder

Section	Key Parameter	Why It Matters	Buyer Tip
Throughput and Handling	Throughput requirement	Defines production mode—batch or inline	Study the PCBA cycle time before deciding
	Max. PCBA size	Determines machine capability	Match with your largest board (e.g., 610×610 mm)
	Clearance (top and bottom)	Ability to process tall components	Ensure enough clearance on both sides
	Max. pallet weight	Affects conveyor durability	Use heavy-duty conveyors for >8kg boards
Fluxing System	Type of fluxer	Impacts solder joint quality through precise fluxing	Drop Jet
	Flux amount control	Offers process flexibility	Look for control of the Flux volume for each joint
	Usage of different types of fluxes	Usage of different fluxes for different products	Dual tanks are recommended for multiple flux types
	Spray speed	Controls deposition	A decent range of fluxer speed
Preheating	Bottom preheat type	Uniform heating, energy saving by segmented control	Shortwave IR with segmented control
	Top preheat type	Aids solder flow in multilayer boards	Go for convection top heaters
Soldering System	Movement type	Affects flexibility and accuracy	Choose a moving pot for large PCBs
	Solder pot capacity	Defines solder volume	Optimum 13-15kg
	Nozzle type	Determines quality and ability to move in any orientation	Wettable nozzles
	Pump type	Better Process control, maintenance-free	Electromagnetic pump
	Auto wire feed and dual pots	Boosts throughput and reduces errors	Ideal for volume or mixed-model production
Other Features	Process camera	Enables live quality monitoring	Choose with built-in camera
	Nitrogen purity	Reduces dross, improves finish	Closed-pot nitrogen preferred
	Traceability	Critical for regulated industries	Ensure ZEV/ITAC/IPC-CFX compatibility
	Offline programming	Cuts setup time	Useful for high-mix production

PIONEER SMT TECHNOLOGIES PVT LTD

Website: www.pioneersmt.com
 Address: Plot No. 78A, 2nd Floor, Sec-5
 IMT Manesar, Gurugram - 122050 Haryana
 Email: sales@pioneersmt.com
 Contact: 9958076012
 Inline Brands Supplied: Nordson

SUMITRON

Website: sumitron.com
 Address: No. F19/1, Sector 8, Rohini,
 Land Mark: Near M2K Cinema Hall,
 Delhi - 110085
 Email: contact@sumitron.com
 Contact: 011-43824444
 Inline Brands Supplied: Koki Tec

Pillar House Synchrodex Pro



AST SEL 31/32

TRANSTECHNOLOGY INDIA PVT LTD

Website: www.trans-tec.com
 Address: 601A, 6th Floor, Tower-2,
 DLF Corporate Greens, Sector-74A,
 Gurugram, Haryana -122004
 Email: trans-tec.india@trans-tec.com
 Contact: 9845485937
 Inline Brands Supplied: Pillar House

HOW
TO GET
FEATURED
HERE?



To help electronics manufacturers make informed decisions while purchasing manufacturing equipment, the *Electronics For You* team has taken on the challenge of publishing a directory of leading suppliers in India and the brands they offer. The next few lists planned include: **Automated Storage Units for Components** and **Solder Paste Inspection (SPI)**. To enquire about being featured here, please write to efy-edit-team@efy.in.