

```

27.
28.     # Clean up the dice string:
29.     diceStr = diceStr.lower().replace(' ', '')
30.
31.     # Find the "d" in the dice string input:
32.     dIndex = diceStr.find('d')
33.     if dIndex == -1:
34.         raise Exception('Missing the "d" character.')
35.
36.     # Get the number of dice. (The "3" in "3d6+1"):
37.     numberOfDice = diceStr[dIndex]
38.     if not numberOfDice.isdecimal():
39.         raise Exception('Missing the number of dice.')
40.     numberOfDice = int(numberOfDice)
41.
42.     # Find if there is a plus or minus sign for a modifier:
43.     modIndex = diceStr.find('+')
44.     if modIndex == -1:
45.         modIndex = diceStr.find('-')
46.
47.     # Find the number of sides. (The "6" in "3d6+1"):
48.     if modIndex == -1:
49.         numberOfSides = diceStr[dIndex + 1 :]
50.     else:
51.         numberOfSides = diceStr[dIndex + 1 : modIndex]
52.     if not numberOfSides.isdecimal():
53.         raise Exception('Missing the number of sides.')
54.     numberOfSides = int(numberOfSides)
55.
56.     # Find the modifier amount. (The "1" in "3d6+1"):
57.     if modIndex == -1:
58.         modAmount = 0
59.     else:
60.         modAmount = int(diceStr[modIndex + 1 :])
61.         if diceStr[modIndex] == '-':
62.             # Change the modification amount to negative:
63.             modAmount = -modAmount
64.
65.     # Simulate the dice rolls:
66.     rolls = []
67.     for i in range(numberOfDice):
68.         rollResult = random.randint(1, numberOfSides)
69.         rolls.append(rollResult)
70.
71.     # Display the total:
72.     print('Total:', sum(rolls) + modAmount, '(Each die:', end='')
73.
74.     # Display the individual rolls:
75.     for i, roll in enumerate(rolls):
76.         rolls[i] = str(roll)
77.     print(', '.join(rolls), end='')
78.
79.     # Display the modifier amount:
80.     if modAmount != 0:
81.         modSign = diceStr[modIndex]

```