

The Program in Action

When you run *gullible.py*, the output will look like this:

```
Gullible, by Al Sweigart al@inventwithpython.com
Do you want to know how to keep a gullible person busy for hours? Y/N
> y
Do you want to know how to keep a gullible person busy for hours? Y/N
> y
Do you want to know how to keep a gullible person busy for hours? Y/N
> yes
Do you want to know how to keep a gullible person busy for hours? Y/N
> YES
Do you want to know how to keep a gullible person busy for hours? Y/N
> TELL ME HOW TO KEEP A GULLIBLE PERSON BUSY FOR HOURS
"TELL ME HOW TO KEEP A GULLIBLE PERSON BUSY FOR HOURS" is not a valid yes/no
response.
Do you want to know how to keep a gullible person busy for hours? Y/N
> y
Do you want to know how to keep a gullible person busy for hours? Y/N
> y
Do you want to know how to keep a gullible person busy for hours? Y/N
> n
Thank you. Have a nice day!
```

How It Works

To be more user friendly, your programs should attempt to interpret a range of possible inputs from the user. For example, this program asks the user a yes/no question, but it would be simpler for the player to simply enter “y” or “n” instead of enter the full word. The program can also understand the player’s intent if their CAPS LOCK key is activated, because it calls the `lower()` string method on the string the player entered. This way, 'y', 'yes', 'Y', 'Yes', and 'YES', are all interpreted the same by the program. The same goes for a negative response from the player.

```
1. """Gullible, by Al Sweigart al@inventwithpython.com
2. How to keep a gullible person busy for hours. (This is a joke program.)
3. View this code at https://nostarch.com/big-book-small-python-projects
4. Tags: tiny, beginner, humor"""
5.
6. print('Gullible, by Al Sweigart al@inventwithpython.com')
7.
8. while True: # Main program loop.
9.     print('Do you want to know how to keep a gullible person busy for
10.         hours? Y/N')
11.     response = input('> ') # Get the user's response.
12.     if response.lower() == 'no' or response.lower() == 'n':
13.         break # If "no", break out of this loop.
14.     if response.lower() == 'yes' or response.lower() == 'y':
15.         continue # If "yes", continue to the start of this loop.
```