

```

4. Tags: extra-large, game, humor, puzzle""
5.
6. # Play the original Flash game at:
7. # https://homestarrunner.com/videlectrix/wheresanegg.html
8. # More info at: http://www.hrwiki.org/wiki/Where's_an_Egg%3F
9.
10. import time, random, sys
11.
12. # Set up the constants:
13. SUSPECTS = ['DUKE HAUTDOG', 'MAXIMUM POWERS', 'BILL MONOPOLIS', 'SENATOR SCHMEAR',
    'MRS. FEATHERTOSS', 'DR. JEAN SPLICER', 'RAFFLES THE CLOWN', 'ESPRESSA TOFFEEPOT',
    'CECIL EDGAR VANDERTON']
14. ITEMS = ['FLASHLIGHT', 'CANDLESTICK', 'RAINBOW FLAG', 'HAMSTER WHEEL', 'ANIME VHS TAPE',
    'JAR OF PICKLES', 'ONE COWBOY BOOT', 'CLEAN UNDERPANTS', '5 DOLLAR GIFT CARD']
15. PLACES = ['ZOO', 'OLD BARN', 'DUCK POND', 'CITY HALL', 'HIPSTER CAFE', 'BOWLING ALLEY',
    'VIDEO GAME MUSEUM', 'UNIVERSITY LIBRARY', 'ALBINO ALLIGATOR PIT']
16. TIME_TO_SOLVE = 300 # 300 seconds (5 minutes) to solve the game.
17.
18. # First letters and longest length of places are needed for menu display:
19. PLACE_FIRST_LETTERS = {}
20. LONGEST_PLACE_NAME_LENGTH = 0
21. for place in PLACES:
22.     PLACE_FIRST_LETTERS[place[0]] = place
23.     if len(place) > LONGEST_PLACE_NAME_LENGTH:
24.         LONGEST_PLACE_NAME_LENGTH = len(place)
25.
26. # Basic sanity checks of the constants:
27. assert len(SUSPECTS) == 9
28. assert len(ITEMS) == 9
29. assert len(PLACES) == 9
30. # First letters must be unique:
31. assert len(PLACE_FIRST_LETTERS.keys()) == len(PLACES)
32.
33.
34. knownSuspectsAndItems = []
35. # visitedPlaces: Keys=places, values=strings of the suspect & item there.
36. visitedPlaces = {}
37. currentLocation = 'TAXI' # Start the game at the taxi.
38. accusedSuspects = [] # Accused suspects won't offer clues.
39. liars = random.sample(SUSPECTS, random.randint(3, 4))
40. accusationsLeft = 3 # You can accuse up to 3 people.
41. culprit = random.choice(SUSPECTS)
42.
43. # Common indexes link these; e.g. SUSPECTS[0] and ITEMS[0] are at PLACES[0].
44. random.shuffle(SUSPECTS)
45. random.shuffle(ITEMS)
46. random.shuffle(PLACES)
47.
48. # Create data structures for clues the truth-tellers give about each
49. # item and suspect.
50. # clues: Keys=suspects being asked for a clue, value="clue dictionary".
51. clues = {}
52. for i, interviewee in enumerate(SUSPECTS):
53.     if interviewee in liars:
54.         continue # Skip the liars for now.

```