

```

55.
56.     # This "clue dictionary" has keys=items & suspects,
57.     # value=the clue given.
58.     clues[interviewee] = {}
59.     clues[interviewee]['debug_liar'] = False # Useful for debugging.
60.     for item in ITEMS: # Select clue about each item.
61.         if random.randint(0, 1) == 0: # Tells where the item is:
62.             clues[interviewee][item] = PLACES[ITEMS.index(item)]
63.         else: # Tells who has the item:
64.             clues[interviewee][item] = SUSPECTS[ITEMS.index(item)]
65.     for suspect in SUSPECTS: # Select clue about each suspect.
66.         if random.randint(0, 1) == 0: # Tells where the suspect is:
67.             clues[interviewee][suspect] = PLACES[SUSPECTS.index(suspect)]
68.         else: # Tells what item the suspect has:
69.             clues[interviewee][suspect] = ITEMS[SUSPECTS.index(suspect)]
70.
71. # Create data structures for clues the liars give about each item
72. # and suspect:
73. for i, interviewee in enumerate(SUSPECTS):
74.     if interviewee not in liars:
75.         continue # We've already handled the truth-tellers.
76.
77.     # This "clue dictionary" has keys=items & suspects,
78.     # value=the clue given:
79.     clues[interviewee] = {}
80.     clues[interviewee]['debug_liar'] = True # Useful for debugging.
81.
82.     # This interviewee is a liar and gives wrong clues:
83.     for item in ITEMS:
84.         if random.randint(0, 1) == 0:
85.             while True: # Select a random (wrong) place clue.
86.                 # lies about where the item is.
87.                 clues[interviewee][item] = random.choice(PLACES)
88.                 if clues[interviewee][item] != PLACES[ITEMS.index(item)]:
89.                     # Break out of the loop when wrong clue is selected.
90.                     break
91.         else:
92.             while True: # Select a random (wrong) suspect clue.
93.                 clues[interviewee][item] = random.choice(SUSPECTS)
94.                 if clues[interviewee][item] != SUSPECTS[ITEMS.index(item)]:
95.                     # Break out of the loop when wrong clue is selected.
96.                     break
97.     for suspect in SUSPECTS:
98.         if random.randint(0, 1) == 0:
99.             while True: # Select a random (wrong) place clue.
100.                 clues[interviewee][suspect] = random.choice(PLACES)
101.                 if clues[interviewee][suspect] != PLACES[ITEMS.index(item)]:
102.                     # Break out of the loop when wrong clue is selected.
103.                     break
104.         else:
105.             while True: # Select a random (wrong) item clue.
106.                 clues[interviewee][suspect] = random.choice(ITEMS)
107.                 if clues[interviewee][suspect] != ITEMS[SUSPECTS.index(suspect)]:
108.                     # Break out of the loop when wrong clue is selected.
109.                     break

```