

```

59.
60.     # Display the results:
61.     print('The %sed message is:' % (myMode))
62.     print(translated)
63.
64.     try:
65.         pyperclip.copy(translated)
66.         print('Full %sed text copied to clipboard.' % (myMode))
67.     except:
68.         pass # Do nothing if pyperclip wasn't installed.
69.
70.
71. def checkKey(key):
72.     """Return True if key is valid. Otherwise return False."""
73.     keyList = list(key)
74.     lettersList = list(LETTERS)
75.     keyList.sort()
76.     lettersList.sort()
77.     if keyList != lettersList:
78.         print('There is an error in the key or symbol set.')
79.         return False
80.     return True
81.
82.
83. def encryptMessage(message, key):
84.     """Encrypt the message using the key."""
85.     return translateMessage(message, key, 'encrypt')
86.
87.
88. def decryptMessage(message, key):
89.     """Decrypt the message using the key."""
90.     return translateMessage(message, key, 'decrypt')
91.
92.
93. def translateMessage(message, key, mode):
94.     """Encrypt or decrypt the message using the key."""
95.     translated = ''
96.     charsA = LETTERS
97.     charsB = key
98.     if mode == 'decrypt':
99.         # For decrypting, we can use the same code as encrypting. We
100.        # just need to swap where the key and LETTERS strings are used.
101.        charsA, charsB = charsB, charsA
102.
103.        # Loop through each symbol in the message:
104.        for symbol in message:
105.            if symbol.upper() in charsA:
106.                # Encrypt/decrypt the symbol:
107.                symIndex = charsA.find(symbol.upper())
108.                if symbol.isupper():
109.                    translated += charsB[symIndex].upper()
110.                else:
111.                    translated += charsB[symIndex].lower()
112.            else:
113.                # The symbol is not in LETTERS, just add it unchanged.

```