

```

154.     card if showDealerHand is False."""
155.     print()
156.     if showDealerHand:
157.         print('DEALER:', getHandValue(dealerHand))
158.         displayCards(dealerHand)
159.     else:
160.         print('DEALER: ???')
161.         # Hide the dealer's first card:
162.         displayCards([BACKSIDE] + dealerHand[1:])
163.
164.     # Show the player's cards:
165.     print('PLAYER:', getHandValue(playerHand))
166.     displayCards(playerHand)
167.
168.
169. def getHandValue(cards):
170.     """Returns the value of the cards. Face cards are worth 10, aces are
171.     worth 11 or 1 (this function picks the most suitable ace value)."""
172.     value = 0
173.     numberOfAces = 0
174.
175.     # Add the value for the non-ace cards:
176.     for card in cards:
177.         rank = card[0] # card is a tuple like (rank, suit)
178.         if rank == 'A':
179.             numberOfAces += 1
180.         elif rank in ('K', 'Q', 'J'): # Face cards are worth 10 points.
181.             value += 10
182.         else:
183.             value += int(rank) # Numbered cards are worth their number.
184.
185.     # Add the value for the aces:
186.     value += numberOfAces # Add 1 per ace.
187.     for i in range(numberOfAces):
188.         # If another 10 can be added with busting, do so:
189.         if value + 10 <= 21:
190.             value += 10
191.
192.     return value
193.
194.
195. def displayCards(cards):
196.     """Display all the cards in the cards list."""
197.     rows = [' ', ' ', ' ', ' ', ' '] # The text to display on each row.
198.
199.     for i, card in enumerate(cards):
200.         rows[0] += ' ____ ' # Print the top line of the card.
201.         if card == BACKSIDE:
202.             # Print a card's back:
203.             rows[1] += '|##| '
204.             rows[2] += '|###| '
205.             rows[3] += '|_##| '
206.         else:
207.             # Print the card's front:
208.             rank, suit = card # The card is a tuple data structure.

```