

```

209.         rows[1] += '|{}|'.format(rank.ljust(2))
210.         rows[2] += '| {}|'.format(suit)
211.         rows[3] += '|_{}|'.format(rank.rjust(2, '_'))
212.
213.     # Print each row on the screen:
214.     for row in rows:
215.         print(row)
216.
217.
218. def getMove(playerHand, money):
219.     """Asks the player for their move, and returns 'H' for hit, 'S' for
220.     stand, and 'D' for double down."""
221.     while True: # Keep looping until the player enters a correct move.
222.         # Determine what moves the player can make:
223.         moves = ['(H)it', '(S)tand']
224.
225.         # The player can double down on their first move, which we can
226.         # tell because they'll have exactly two cards:
227.         if len(playerHand) == 2 and money > 0:
228.             moves.append('(D)ouble down')
229.
230.         # Get the player's move:
231.         movePrompt = ', '.join(moves) + '> '
232.         move = input(movePrompt).upper()
233.         if move in ('H', 'S'):
234.             return move # Player has entered a valid move.
235.         if move == 'D' and '(D)ouble down' in moves:
236.             return move # Player has entered a valid move.
237.
238.
239. # If the program is run (instead of imported), run the game:
240. if __name__ == '__main__':
241.     main()

```

After entering the source code and running it a few times, try making experimental changes to it. Blackjack has several custom rules that you could implement. For example, if the first two cards have the same value, a player can split them into two hands and wager on them separately. Also, if the player receives a “blackjack” (the ace of spades and a black jack) for their first two cards, the player wins a ten-to-one payout. You can find out more about the game from <https://en.wikipedia.org/wiki/Blackjack>.

Exploring the Program

Try to find the answers to the following questions. Experiment with some modifications to the code and rerun the program to see what effect the changes have.

1. How can you make the player start with a different amount of money?
2. How does the program prevent the player from betting more money than they have?