

```

67.
68.         # Handle the wrap-around if num is larger than the length of
69.         # SYMBOLS or less than 0:
70.         if num >= len(SYMBOLS):
71.             num = num - len(SYMBOLS)
72.         elif num < 0:
73.             num = num + len(SYMBOLS)
74.
75.         # Add encrypted/decrypted number's symbol to translated:
76.         translated = translated + SYMBOLS[num]
77.     else:
78.         # Just add the symbol without encrypting/decrypting:
79.         translated = translated + symbol
80.
81. # Display the encrypted/decrypted string to the screen:
82. print(translated)
83.
84. try:
85.     pyperclip.copy(translated)
86.     print('Full {}ed text copied to clipboard.'.format(mode))
87. except:
88.     pass # Do nothing if pyperclip wasn't installed.

```

After entering the source code and running it a few times, try making experimental changes to it. The comments marked with (!) have suggestions for small changes you can make. You can expand the encryptable symbols by adding characters to the SYMBOLS string.

Exploring the Program

Try to find the answers to the following questions. Experiment with some modifications to the code and rerun the program to see what effect the changes have.

1. What happens if you change `SYMBOLS = 'ABCDEFGHIJKLMNOPQRSTUVWXYZ'` on line 16 to `SYMBOLS = 'ABC'`?
2. What happens when you encrypt a message with key 0?
3. What error message do you get if you delete or comment out `translated = ''` on line 56?
4. What error message do you get if you delete or comment out `key = int(response)` on line 45?
5. What happens if you change `translated = translated + SYMBOLS[num]` on line 76 to `translated = translated + symbol`?