

```
{% for course in object_list %}
<div class="card m-1 d-inline-flex" style="width: 18rem;
height:10rem;">
<div class="card-body">
<h5 class="card-title h-50">{{ course.title|upper }}</h5>
<p class="card-text">{{ course.get_level_display }}</p>
<a href="{% url 'course_detail' course.pk%}" class="btn btn-
primary p-0 d-block w-50 mx-auto" style="height:1.2rem; font-
size:0.8rem">Go Detail</a>
</div>
</div>
{% endfor %}

</div>

{% endblock %}
```

Here are some explanations of Bootstrap utilities.

- **text-center**: Text utility to move content or nested elements to the center horizontally
- **m-#**: Spacing utility to adjust margin. You can specify numbers between 0 and 5.
- **d-inline-flex**: Display or Flex utility to change the element to flex inline box.
- **h-#**: Sizing utility to adjust the height of the element relative to the parent element. 50 means 50% of the parent element's height.
- **p-#**: Spacing utility to adjust padding. You can specify numbers between 0 and 5. 0 means zero padding.
- **d-block**: Display utility to change the element to a block element.
- **w-#**: Sizing utility to adjust the width of the element relative to the parent element. 50 means 50% of the parent element's width.
- **mx-auto**: Spacing utility to horizontally center fixed-width block-level content

We are also using the **container** class to wrap all elements, which sets a **max-width** at each responsive breakpoint and allows appropriate margins on the right and left edges.

Now, you can see that the layout and sizes are nicely set.