

First, you need to import `environ`, and add initial settings to read the `.env` file.

config/settings/production.py

```
from .base import *
import environ

env = environ.Env()
env.read_env('.env')
```

Then, bring the settings for production from the `base.py` file.

And replace confidential data with `env('ENVIRONMENT_VARIABLE')`. If there is a list of parameters, use `env.list('ENVIRONMENT_VARIABLE')`.

Here is an example of `production.py` for our Django app. We don't include email settings and `STATIC_ROOT` here yet. We'll explain them later.

config/settings/production.py

```
from .base import *
import environ

env = environ.Env()
env.read_env('.env')

SECRET_KEY = env('SECRET_KEY')

DEBUG = False

ALLOWED_HOSTS = env.list('ALLOWED_HOSTS')

DATABASES = {
    'default': {
        'ENGINE': env('DB_ENGINE'),
        'NAME': env('DB_NAME'),
        'USER': env('DB_USER'),
        'PASSWORD': env('DB_PASSWORD'),
        'HOST': env('DB_HOST'),
        'PORT': env('DB_PORT'),
    }
}
```

And this is the example of the `.env` file. Make sure that the `.env` file is created directly under the project directory.

.env

```
SECRET_KEY=django-insecure-a6e%75-^!....
ALLOWED_HOSTS=localhost,xx.xx.xx.xx
```