

1. To run *Gunicorn* using *systemd*, you need to create two **unit files**. Unit files are used to set rules to manage units (processes) by *systemd*.
2. Enable the **unit files** and start the units
3. Check if the **units** are running

Create unit files

To run Gunicorn, you need to create a **service unit file** and a **socket unit file**.

Create a service unit file

A service unit file is used to create a service to run the application itself. The file should be stored under */etc/systemd/system*. You can set any name but usually use a project name like *project_d.service*. To create and edit the file, use the *vim* command.

Command Line - INPUT

```
ubuntu@ip-xx:~$ | sudo vim /etc/systemd/system/project_d.service
```

Edit the file like in the example below.

/etc/systemd/system/project_d.service

```
[Unit]
Description=gunicorn daemon
Requires=project_d.socket
After=network.target

[Service]
User=ubuntu
Group=www-data
WorkingDirectory=/home/ubuntu/project_d
ExecStart=/home/ubuntu/project_d/d_env/bin/gunicorn \
  --access-logfile - \
  --workers 3 \
  --bind unix:/home/ubuntu/project_d/project_d.sock \
  config.wsgi:application

[Install]
WantedBy=multi-user.target
```

You need to carefully type file paths, as the file paths are also used in other files. For example, *home/ubuntu/project_d/project_d.sock* is the actual file that will be created under the project directory when the