

```
ubuntu@ip-xx:~$ | sudo mkdir /usr/share/nginx/html/static
ubuntu@ip-xx:~$ | sudo chown -R ubuntu
/usr/share/nginx/html/static
ubuntu@ip-xx:~$ | cd ~/project_d
ubuntu@ip-xx:~$ | source d_env/bin/activate
```

Command Line - INPUT

```
(d_env) ubuntu@ip-xx:~/project_d$ | python manage.py
collectstatic
```

You'll see that the static files are successfully copied to the new directory.

Command Line - RESPONSE

```
138 static files copied to '/usr/share/nginx/html/static'
```

As the old static file directory is not needed anymore, delete it.

Command Line - INPUT

```
(d_env) ubuntu@ip-xx:~/project_d$ | p rm -r collectstatic_path
```

Firewall settings

This process is optional as AWS Lightsail has its firewall. On Ubuntu OS, you can use UFW (Uncomplicated Firewall) to manage *iptables*.

To enable UFW, run the command below.

Command Line - INPUT

```
ubuntu@ip-xx:~$ | sudo ufw enable
```

You'll see the message below. This explains the importance of opening an SSH port to keep the SSH connection.

Command Line - INTERACTIVE

```
Command may disrupt existing ssh connections. Proceed with
operation (y|n)? y
Firewall is active and enabled on system startup
```

Open the SSH port and ports for Nginx by running the following commands.