

```

from .base import *
import environ

env = environ.Env()
env.read_env('.env')

SECRET_KEY = env('SECRET_KEY')

DEBUG = True

ALLOWED_HOSTS = env.list('ALLOWED_HOSTS')

DATABASES = {
    'default': {
        'ENGINE': 'django.db.backends.sqlite3',
        'NAME': BASE_DIR / 'db.sqlite3',
    }
}

# Console email
#EMAIL_BACKEND = 'django.core.mail.backends.console.EmailBackend'

# Gmail
EMAIL_BACKEND = 'django.core.mail.backends.smtp.EmailBackend'
EMAIL_HOST = 'smtp.gmail.com'
EMAIL_HOST_USER = env('EMAIL_HOST_USER')
EMAIL_HOST_PASSWORD = env('EMAIL_HOST_PASSWORD')
EMAIL_PORT = 465
EMAIL_USE_TLS = False
EMAIL_USE_SSL = True
DEFAULT_FROM_EMAIL = env('DEFAULT_FROM_EMAIL')

```

`SECRET_KEY` is the same for both development and production, but we put it in each requirement file to create a consistent structure.

For `EMAIL_BACKEND`, keep two options – console and Gmail, but one setting should be commented out.

Here is an example of an `.env` file for development. `ALLOWED_HOSTS` can be directly written in the `development.py` file. This is the case when you are using your **private IP address** for a mobile UI design, which is explained on this topic page [Check Developing App UI on Mobile Device](#).

.env(for development)

```

SECRET_KEY=your_secret_key
ALLOWED_HOSTS=localhost,your_private_IP_address

# Gmail
EMAIL_HOST_USER = 'your_account@gmail.com'
EMAIL_HOST_PASSWORD = 'App Password'
DEFAULT_FROM_EMAIL = 'your_account@gmail.com'

```