

production.py

Here is the final version of the *productino.py* example. Put confidential information in the *.env* file, just like you did for *development.py*.

settings/production.py

```
from .base import *
import environ

env = environ.Env()
env.read_env('.env')
SECRET_KEY = env('SECRET_KEY')

DEBUG = False

ALLOWED_HOSTS = env.list('ALLOWED_HOSTS')

DATABASES = {
    'default': {
        'ENGINE': env('DB_ENGINE'),
        'NAME': env('DB_NAME'),
        'USER': env('DB_USER'),
        'PASSWORD': env('DB_PASSWORD'),
        'HOST': env('DB_HOST'),
        'PORT': env('DB_PORT'),
    }
}

STATIC_ROOT = '/usr/share/nginx/html/static'

# SendGrid
EMAIL_BACKEND = 'sendgrid_backend.SendgridBackend'
SENDGRID_API_KEY = env('SENDGRID_API_KEY')
DEFAULT_FROM_EMAIL = env('DEFAULT_FROM_EMAIL')
SENDGRID_SANDBOX_MODE_IN_DEBUG = False
SENDGRID_TRACK_CLICKS_PLAIN = False
```

In the *.env* file, we defined the following settings:

- SECRET_KEY
- ALLOWED_HOSTS
- DB settings
- SENDGRID settings

.env(for production)

```
SECRET_KEY=your_secret_key

ALLOWED_HOSTS=your_public_IP_address,your_site_domain
```