

urlpatterns inside `RiffMates/RiffMates/urls.py`—I usually keep mine next to the admin route:

```
path('accounts/', include('django.contrib.auth.urls')),
```

The URL/view mappings defined in that module include a view for a login page, now registered under `/accounts/login/`. This view has all the login page logic, but it expects a template called `registration/login.html`. The view uses a Django Form that the user fills providing their username and password. Chapter 7 shows you how to write your own forms; for now, you need to know two things: first, an object called `form` has a method called `.as_p()` that renders the `<input>` tags of the login page, and second, there is a bit of “black magic” called a `{% csrf_token %}` tag used for security. The black magic bits will be explained in Chapter 7. Create a directory called *registration* under `RiffMates/templates`, and add the contents from the following listing to a file named `login.html`.

Listing 6.5 Login template for the built-in view

```
<!-- RiffMates/templates/registration/login.html -->
{% extends "base.html" %}

{% block content %}
<h1>Login</h1>

<form method="post">
  {% csrf_token %}
  {{form.as_p}}
  <button class="btn btn-dark" type="submit">Login</button>
</form>

{% endblock content %}
```

Your login view is registered, and you have written the corresponding template. You’re all set to try it out. Revisit `http://localhost:8000/bands/restricted_page/`. Unfortunately, logging out is not a simple matter. You’ll learn how to create a logout button shortly, but in the meantime, you have to visit the Django Admin and use their logout link. If you’re playing around with accounts and you’re logged in as *nicky* (or any other non-staff account), you’ll have to log in with your admin account to log out altogether.

6.4 Authorization in views

The `@login_required` decorator quickly gives you the ability to restrict a view to only authenticated users. Often, though, you want finer-grained control than this. Your view can contain logic for authorization. For example, let’s create a view that is limited to a musician and their bandmates: `musician_restricted`.

This view still uses `@login_required`, as you want to ensure users got authenticated first. The `request` object passed to a view includes information on the authentication state, including who the authenticated user is. The `musician_restricted` view takes a