

```
</p>

{% endblock content %}
```

While it shows the user this message, Django simultaneously determines whether there is a `User` object with the submitted email address. If so, an email gets sent to the address. If there is no match, Django does nothing. Configuring your system to send email correctly is a book in its own right. Django provides a variety of *email backends*, depending on how you communicate with your email server.

The most common email backend uses SMTP to communicate with an email server. There are many third-party providers for such a service, or if you're brave, you can run your own. Appendix B has more details on how to configure the `smtp.EmailBackend` for use in a production environment.

Thankfully, you don't need to setup SMPT if you're still developing or if you only want to test. My favorite email backend prints the email to the console instead of sending it; you see the results inline with the other output from the development server. To use the console backend, add the following to `settings.py`:

```
EMAIL_BACKEND = 'django.core.mail.backends.console.EmailBackend'
```

The email sent to the user is based on a template: `password_reset_email.html`. The message can say anything you want, as long as it includes the reset link. This link is accessible through the `{% url %}` tag, using `password_reset_confirm` as the argument. The view for this link takes two arguments that must be provided to the `{% url %}` tag: `uidb64=uid` and `token=token`. These values make up the one-time token in the reset link. A sample email message including the reset link is shown in the following listing. Add a new file called `RiffMates/templates/registration/password_reset_email.html` with the contents from the listing.

Listing 6.11 Template for the reset email sent to the user

```
{% autoescape off %}
    Turn off HTML escaping
    throughout the template.

You're receiving this email because you requested a password reset
for your user account at Alexandria.

Please go to the following page and choose a new password:

{% block reset_link %}
    {{ protocol }}://{{ domain }}{% url 'password_reset_confirm'
    uidb64=uid token=token %}
    A fully qualified reset link
    with a one-time token
{% endblock %}

Your username, in case you've forgotten: {{ user.get_username }}

Thanks for using our site!

{% endautoescape %}
```