

If you aren't seeing the bands grouping or the musicians command, double-check that you created the bands/management/commands structure correctly and remembered each of the required `__init__.py` scripts. If the command is there, then run it:

```
(venv) RiffMates$ python manage.py musicians
Bonham, John
Cousin, Nicky
Hendrix, Jimi
Lennon, John
Star, Ringo
Vai, Steve
```

You should see each of the `Musician` objects in your database output to the screen. I mentioned that Django automatically provides a help interface:

```
(venv) RiffMates$ python manage.py musicians --help
usage: manage.py musicians [-h] [--version] [-v {0,1,2,3}]
                        [--settings SETTINGS]
                        [--pythonpath PYTHONPATH] [--traceback]
                        [--no-color] [--force-color] [--skip-checks]
```

Lists registered musicians

← The help string from
your command class

```
options:
  -h, --help            show this help message and exit
  --version             Show program's version number and exit.
  -v {0,1,2,3}, --verbosity {0,1,2,3}
                        Verbosity level; 0=minimal output,
                        1=normal output, 2=verbose output,
                        3=very verbose output
  --settings SETTINGS  The Python path to a settings module, e.g.
                        "myproject.settings.main". If this isn't
                        provided, the DJANGO_SETTINGS_MODULE environment
                        variable will be used.
  --pythonpath PYTHONPATH
                        A directory to add to the Python path, e.g.
                        "/home/djangoprojects/myproject".
  --traceback          Raise on CommandError exceptions.
  --no-color           Don't colorize the command output.
  --force-color        Force colorization of the command output.
  --skip-checks        Skip system checks.
```

There is a lot buried in there. For now, just note that your help string is showing up. The rest of the options get covered in the next section when command-line arguments get discussed.

9.3 *Handling arguments*

When you write a program, you often need to pass in some configuration information or data that changes the behavior of the script. Consider the `musicians` management command; it would be great to be able to filter the musicians based on name or date of birth, especially if you have a lot in your database. The kinds of arguments you pass to a command-line script are divided into two categories: positional arguments