

```

        hx-trigger="load">
        <i> Loading promoters... </i>
    </div>
{% endblock content %}

```

Placeholder text visible until the lazy load completes

hx-trigger specifies when the GET occurs—in this case, on page load.

The `hx-get` tag fires when the page loads and calls the associated URL. The following listing contains the view this GET invokes.

Listing 12.3 An HTMX-invoked promoters listing view

```

# RiffMates/promoters/views.py
from time import sleep
...
def partial_promoters(request):
    sleep(2)
    data = {
        "promoters": Promoter.objects.all(),
    }
    return render(request, "partials/promoters.html",
                  data)

```

A two-second delay to simulate lazy loading taking a while

HTMX results get rendered the same as any other template, but the contents are only a partial page.

The following listing contains the partial HTML segment, rendered by the `partial_promoters()` view. I keep all my partials together in a subdirectory, created under `templates`. This first partial is named `RiffMates/templates/partials/promoters.html`.

Listing 12.4 A snippet of HTML that gets rendered in response to an HTMX GET call

```

<!-- RiffMates/templates/partials/promoters.html -->
<ul>
    {% for promoter in promoters %}
        <li>
            {{promoter.full_name}}
            {% if promoter.birth %}
                (
                    {{promoter.birth}} -
                    {% if promoter.death %}
                        {{promoter.death}}
                    {% endif %}
                )
            {% endif %}
        </li>
    {% empty %}
        <li> <i>No promoters in the database</i> </li>
    {% endfor %}
</ul>

```

Render each promoter as a list item.

Loop through all promoters.

An alternate message if there are no promoters

To test all this out, you need to add a `urls.py` file to the `promoters` app, register the two new views, and include the URL routes in the main `RiffMates/urls.py` file. You'll also need some promoters if you haven't created them already. You can do this with the