

consistent approach, though; having a habit of “if it is for editing, it should be secure” is a good one.

Your code is now complete. Make sure to register the views as routes you haven’t done so far, and revisit http://localhost:8000/bands/room_editor/1/ to play with the CBGB venue’s rooms.

A true room editor would also allow you to create and delete rooms. These features can be added using the same techniques you’ve used so far. An Add link on the page could dynamically render the Edit form with empty data. Your room editing view would need to handle the `ID = 0` case, or you could write a separate view for adding, if you prefer. Delete is just another link, like Edit. You can use `hx-delete` in the view if you like, but `hx-get` works equally well. The only trick with deletion is to remove the display tag afterwards, so the partial returned from the view needs to be empty. HTMX even has an `hx-confirm` tag, which presents an *Are You Sure?* dialog that you can use in the delete case. See <https://htmx.org/docs/#confirming> for more information.

HTMX may not be as powerful as full SPA frameworks, but it does allow you to inject a large degree of interactivity into your project with very little change in your code. For most CRUD-based websites, HTMX is more than enough, and the overhead is far smaller than a full SPA framework. The HTMX website includes a couple of case studies in which companies converted React-based projects to HTMX. The conversion significantly shrank the size of their code base; reduced the load time of their pages; and, due to the smaller memory footprint, actually enabled the application to handle more data on the screen at a time. See the Essays section of the HTMX website for more information: <https://htmx.org/essays/>.

12.6 Exercises

- 1 Add search functionality for your ad content, similar to the musicians search page. Implement both search-as-you-type and infinite scrolling.
- 2 Create a page that has two tabs: one for musicians and one for venues. You’ll need a new view for the page, but the existing listing views for musicians and venues can be used to populate the tabs. An example covering how to write tabs is provided on the HTMX site: <https://htmx.org/examples/tabs-hateoas/>

Summary

- Django is constructed using a Web 1.0 architecture and requires integration with JavaScript libraries to make pages more interactive.
- HTMX enables replacing part of a page using similar techniques to clicking a link in the Web 1.0 world.
- HTMX adds a series of HTTP method attributes that can be assigned to tags in your HTML. Interacting with such a tag causes a GET, POST, or other method to be invoked on the server.
- All HTMX attributes begin with `hx-`.
- HTMX has attributes that control when the HTTP method gets invoked, such as when clicking a tag, when a page gets loaded, when a tag becomes visible, or when an event like a keypress occurs.