

Table C.1 Built-in Django template tags

Tag	Description
<code>{% csrf_token %}</code>	This tag is part of Django's cross-site request forgery (CSRF) protection and should be included in any forms.
<code>{% cycle "red" "blue" %}</code>	Each time this tag is called, it produces its next listed argument. When the list is exhausted, it resumes from the start. It is typically used inside a <code>{% for %}</code> tag, changing its value on each iteration. One common use is creating a zebra-stripe effect by changing the style of an <code></code> element or the class of a <code><tr></code> .
<code>{% debug %}</code>	This outputs a large amount of debug information, including text component parts of the page, user information, and every loaded module. It only works if you have <code>DEBUG=True</code> in <code>settings.py</code> .
<code>{% extends "base.html" %}</code>	Part of the template inheritance mechanism, <code>{% extends %}</code> is used at the top of a file to indicate a template is a child of the named template, <code>"base.html"</code> in the example. Any <code>{% block %}</code> tags in this instance will override <code>{% block %}</code> tags of the same name in the parent.
<code>{% filter force_escape lower %}</code> This content will have the named filters applied before rendering <code>{% endfilter %}</code>	This allows the use of one or more filters on the body of the tag. Filters to be applied are named as arguments; multiple filters can be applied through the use of the pipe (<code> </code>).
<code>{% firstof is_leapyear is_winter is_week day "default" %}</code>	This outputs the value of the first value in its list that is not false-y, where <i>not false-y</i> means <i>it exists, is not empty, is not False, and is greater than zero if numeric</i> . A final string value can be provided to force a default result (all nonempty strings are <code>True</code>).
<code>{% for person in people %}</code> <code>{{ person.name }}</code> <code>{% empty %}</code> <i><i> No people </i> <code>{% endfor %}</code></i>	This is the template equivalent of a Python <code>for</code> statement, and it loops over an iterable (<code>people</code>) and places the current instance in a value (<code>person</code>). The optional <code>{% empty %}</code> clause is run if the iterable is empty.
<code>{{ forloop.counter }}</code> <code>{{ forloop.counter0 }}</code> <code>{{ forloop.revcounter }}</code> <code>{{ forloop.revcounter0 }}</code> <code>{{ forloop.first }}</code> <code>{{ forloop.last }}</code> <code>{{ forloop.parentloop }}</code>	These values are defined within the context of a <code>{% for %}</code> block, giving information on the current state of the loop. They correspond to the current count (1-based), current count (0-based), number of iterations from the end (1-based), number of iterations from the end (0-based), <code>True</code> if the first iteration, <code>True</code> if the last iteration, and the context value of a parent loop in the case of nested <code>{% for %}</code> tags. For a nested <code>{% for %}</code> tag, <code>{{ forloop.parentloop.counter }}</code> contains the counter of the parent loop.