

Table C.1 Built-in Django template tags (continued)

Tag	Description
<pre>{% if count > 50 %} It is big {% elif count > 20 %} It is medium {% else %} It is small {% endif %}</pre>	This is the template equivalent of a Python <code>if</code> statement. The Boolean condition supports <code>and</code>, <code>or</code>, <code>not</code>, <code>==</code>, <code>!=</code>, <code><</code>, <code>></code>, <code>>=</code>, <code>in</code>, <code>not in</code>, <code>is</code>, and <code>is not</code> operators. Values in the condition support the use of filters through the pipe (<code> </code>) operator and can be grouped with parentheses.
<pre>{% ifchanged minute %} More than a minute went by {% else %} Less than a minute went by {% endifchanged %}</pre>	This checks whether a value has changed since the last time the same tag was executed. It is used within a <code>{% for %}</code> tag to determine if a value is different on a subsequent iteration. The <code>{% else %}</code> tag is optional.
<pre>{% include "subtemplate.html" %} or {% include "subtemplate.html" with name="Connor" %}</pre>	This loads and renders a subtemplate. Using with sets values within the subtemplate's context.
<pre>{% load taglibrary %}</pre>	This loads a custom tag/filter library for use. It is equivalent to a Python <code>import</code> statement.
<pre>{% lorem 10 w %}</pre>	This outputs placeholder text, using the traditional "lorem ipsum" text. Arguments are optional, specifying the amount of content, the type of content (<code>w</code> for words, <code>p</code> for HTML paragraphs, and <code>b</code> for plain-text paragraph blocks), and the word <code>random</code> to generate random text instead of lorem ipsum.
<pre>{% now "Y/m/d" %}</pre>	This outputs the current date, using the specified format. This example outputs the date in ISO 8601 format, such as "1999/12/25". Date string specifiers can be found here: https://docs.djangoproject.com/en/dev/ref/templates/builtins/#std-templatefilter-date
<pre>{% regroup value by key as result %}</pre>	This takes a list of dictionaries (<code>value</code>) and creates a new list, where items with the same key are grouped together. For example, if <code>value</code> contained a list of dictionaries with city information, where each city had a key named <code>country</code>, <code>regrouping on country</code> creates a new list, containing a nested list for each unique country found.
<pre>{% resetcycle %}</pre>	This resets a previous cycle tag so that it begins at the start of its argument list again. It is typically used in nested <code>{% for %}</code> tags, so the inner <code>{% for %}</code> starts at the beginning of a cycle rather than the state from the previous iteration.
<pre>{% spaceless %} <p> This is some content </p> {% endspaceless %}</pre>	This removes whitespace (including newlines) between HTML tags. Note that it does not remove spaces <i>within</i> HTML tags. The example renders as <code><p>This is some content</p></code>.