

Table C.2 Loadable Django tags (*continued*)

Tag	Module	Description
<pre>{% blocktranslate %} A translated string with a {{ value }}. {% endblocktranslate %}</pre>	i18n	This returns the translated text equivalent looked up within the translation files. It supports bound variables for look-up within the translation system.
<pre>{% get_available_languages %}</pre>	i18n	This returns a list of available languages from the translation system. The list contains tuples pairing the language code with the name of the language.
<pre>{% get_current_language %}</pre>	i18n	This returns the current language as a language code based on the user's preferred value.
<pre>{% get_current_language_bidi %}</pre>	i18n	This returns the current language's rendering direction—True for right-to-left languages.
<pre>{% get_language_info for "en-ca" as lang %}</pre>	i18n	This puts language information for the named code ("en-ca") in the value (lang). Language information is an object with attributes for the language code (lang.code), language name (lang.name_local), language name in English (lang.name), language bi-direction (lang.bidi), and name in the active language (lang.name_translated).
<pre>{% get_language_info_list for available_langs as langs %}</pre>	i18n	This creates a list (langs) of language info data structures for each language code in the available_langs iterable.
<pre>{% localize on %} {{ value }} {% endlocalize %}</pre>	l10n	This activates (on) or deactivates (off) localization within the block contents.
<pre>{% localtime on %} {{ value }} {% endlocaltime %}</pre>	tz	This activates (on) or deactivates (off) conversion of aware datetime objects contained within the block to the current time zone.
<pre>{% timezone "America/Toronto" %} {{ value }} {% endlocaltime %}</pre>	tz	This converts any datetime objects contained within the block to the named time zone.
<pre>{% get_current_timezone as my_zone %}</pre>	tz	This puts the name of the current time zone in the named argument (my_zone).