

C.2 Filters

Table C.3 Built-in Django template filters

Filter	Description
<code>{{ value add:"2" }}</code>	This adds the argument (2) to the contents being filtered. It supports variables as an argument. If both the filtered value and the argument are lists, the lists will be concatenated (their values aren't added).
<code>{{ value addslashes }}</code>	This adds backslashes before quote characters in a string. It is used to write content that is escaped, so the user can copy it to the clipboard.
<code>{{ value capfirst }}</code>	This capitalizes the first character.
<code>{{ value center:"15" }}</code>	This adds whitespace to center the contents for the given width. Note: this is only visible in HTML inside certain tags, as HTML normally ignores whitespace.
<code>{{ value cut:" " }}</code>	This removes characters in the argument from the value. The example removes all spaces in the value.
<code>{{ value date:"Y/m/d" }}</code>	This formats the value as a date using the given date specifier string. Specifiers can be found in the docs: https://docs.djangoproject.com/en/dev/ref/templates/builtins/#date .
<code>{{ value default:"nothing" }}</code>	If value evaluates to <code>False</code> , it renders the contents of the filter's arguments instead.
<code>{{ value default_if_none:"nothing" }}</code>	If value is <code>None</code> , it renders the contents of the filter's arguments instead.
<code>{{ value dictsort:"name" }}</code>	This sorts a list of dictionaries, using the argument's key. In the example, a list of dictionaries in value would be sorted by the "name" key.
<code>{{ value dictsortreversed:"name" }}</code>	This sorts a list of dictionaries in reverse order, using the argument's key.
<code>{{ value divisibleby:"3" }}</code>	This returns <code>True</code> if value is divisible by the argument.
<code>{{ value escape }}</code>	This performs HTML character escaping on value. If escaping has already been done on value it does not double-escape.
<code>{{ value escapejs }}</code>	This performs JavaScript character escaping on value. It does not make the content safe for use as HTML.
<code>{{ value filesizeformat }}</code>	This renders numbers using file size suffixes. For example, 123456789 is rendered as 117.7 MB.
<code>{{ value first }}</code>	This renders the first item in a list.