

Table C.3 Built-in Django template filters (continued)

Filter	Description
<pre>{{ value floatformat }}</pre> or <pre>{{ value floatformat:3 }}</pre> or <pre>{{ value floatformat:"-3" }}</pre> or <pre>{{ value floatformat:"3g" }}</pre> or <pre>{{ value floatformat:"3u" }}</pre>	This formats float values. With no argument, it displays a single decimal place. Integer arguments specify the number of decimal places. String arguments are converted to integers. Negative arguments specify the number of decimal places but show an integer if the number is precise (e.g., 7.1 becomes 7.100, while 7.0 becomes 7). A <code>g</code> suffix adds a thousandths separator. A <code>u</code> suffix turns localization off.
<pre>{{ value force_escape }}</pre>	This performs HTML escaping on <code>value</code> , even if it has already been escaped.
<pre>{{ value get_digit:"2" }}</pre>	This returns the <code>nth</code> digit of an integer from the right.
<pre>{{ value iriencode }}</pre>	This converts an Internationalized Resource Identifier (IRI) to a string that can be included in a URL.
<pre>{{ value join:", " }}</pre>	This returns a string composed of all the elements in a list, putting the argument between each item. It is equivalent to Python's <code>str.join()</code> .
<pre>{{ value json_script:"my-id" }}</pre>	This converts a Python object to JSON wrapped in a <code><script></code> tag. The tag will have an <code>id</code> attribute corresponding to the argument.
<pre>{{ value last }}</pre>	This returns the last item in a list.
<pre>{{ value length }}</pre>	This returns the length of a string or list.
<pre>{{ value linebreaks }}</pre>	This converts plain text into a paragraph, wrapping the content with <code><p></code> and <code></p></code> tags. A single newline within the content is converted to a <code>
</code> , while double newlines are converted into a second set of paragraph tags.
<pre>{{ value linebreaksbr }}</pre>	This replaces newlines in a string with HTML <code>
</code> tags.
<pre>{{ value linenumbers }}</pre>	This prefixes each line in <code>value</code> with a line number.
<pre>{{ value ljust:"15" }}</pre>	This adds whitespace to left justify the contents for the given width. Note: this is only visible in HTML inside certain tags, as HTML normally ignores whitespace.
<pre>{{ value lower }}</pre>	This converts all characters to lowercase.
<pre>{{ value make_list }}</pre>	This converts <code>value</code> into a list. For strings, the characters become items in the list; for integers, the digits become their character equivalents in the list.
<pre>{{ value phone2numeric }}</pre>	This converts a phone number containing letters to its numeric equivalent. It does not validate the format of the phone number.