

D.2 Field types

Table D.2 contains the fields that ship with the Django ORM. All fields support common field arguments described in D.1. Field-specific arguments are highlighted in the field's description in the table.

Some fields, like `EmailField` and `URLField`, automatically use a field validator. For a complete list of validators, see <https://docs.djangoproject.com/en/dev/ref/validators/>.

Table D.2 ORM field types

Field	Description
<code>AutoField(**options)</code>	An <code>IntegerField</code> that automatically increments. This is not typically used explicitly, as Django includes an ID field using this option automatically.
<code>BigAutoField(**options)</code>	This is a 64-bit version of <code>AutoField</code> ; newer versions of Django use this as the ID field by default.
<code>BinaryField(max_length=None, **options)</code>	This stores raw binary data. An optional <code>max_length</code> argument specifies storage size in the database.
<code>CharField(max_length=None, **options)</code>	A string field, the <code>max_length</code> option maps to the <code>VARCHAR</code> column size in some databases and may be required. It uses a <code>TextInput</code> widget in forms by default (rendered as <code><input></code>).
<code>DateTimeField(auto_now=False, auto_now_add=False, **options)</code>	This stores a Python <code>datetime.date</code> instance. If <code>auto_now</code> is <code>True</code> , the field is set to the current date each time a <code>Model</code> is saved. If <code>auto_now_add</code> is <code>True</code> , the field is set to the date the <code>Model</code> is created.
<code>DurationField(auto_now=False, auto_now_add=False, **options)</code>	This is similar to <code>DateField</code> , but it stores a Python <code>datetime.datetime</code> object.
<code>DecimalField(max_digits=None, decimal_places=None, **options)</code>	This stores a fixed precision decimal number represented by a Python <code>Decimal</code> object. Both <code>max_digits</code> and <code>decimal_places</code> are required arguments, with the first representing the number of digits in the number (including the decimal points) and the second representing the number of decimal digits.
<code>DurationField(**options)</code>	This stores a Python <code>timedelta</code> object to capture periods of time.
<code>EmailField(max_length=254, **options)</code>	This is a <code>CharField</code> instance that validates the contents against an <code>EmailValidator</code> .