

Table D.2 ORM field types

Field	Description
<code>IntegerField(**options)</code>	This stores an integer in the range of -2,147,483,648 to 2,147,483,647.
<code>JSONField(encoder=None, decoder=None, **options)</code>	This stores JSON-encoded data while allowing access to the field as if it were its Python equivalent. This field may not be supported by all databases or may require a plugin for the database. The <code>encoder</code> and <code>decoder</code> arguments can be used to specify a custom encoder or decoded class, according to the <code>json</code> module in the standard library.
<code>PositiveBigIntegerField(**options)</code>	This stores an integer in the range of 0 to 9,223,372,036,854,775,807.
<code>PositiveIntegerField(**options)</code>	This stores an integer in the range of 0 to 2,147,483,647.
<code>PositiveSmallIntegerField(**options)</code>	This stores an integer in the range of 0 to 32,767.
<code>SlugField(max_length=50, allow_unicode=False, **options)</code>	A slug is a short label used in newspaper articles and is often used as part of a URL. The <code>allow_unicode</code> option indicates Unicode values can be accepted—the default <code>False</code> restricts slugs to ASCII.
<code>SmallAutoField(**options)</code>	This is an <code>AutoField</code> restricted to values between 1 and 32,767.
<code>SmallIntegerField(**options)</code>	This stores an integer in the range of -32,768 to 32,767.
<code>TextField(**options)</code>	This is a large text storage field. The underlying column type may or may not be different from a <code>CharField</code> , depending on the database. It uses a <code>Textarea</code> widget in forms by default (rendered as <code><textarea></code>).
<code>TimeField(auto_now=False, auto_now_add=False, **options)</code>	This is similar to <code>DateField</code> but stores a Python <code>datetime.time</code> instance.
<code>URLField(max_length=200, **options)</code>	This <code>CharField</code> validates its contents using a <code>URLValidator</code> .
<code>UUIDField(**options)</code>	This stores universally unique identifiers from Python's <code>UUID</code> class.

D.3 Relationship field types

This section contains the fields that specify inter-Model relationships. All fields support the common arguments described in table D.1. Field-specific arguments are highlighted in the description that follows.