

```

        "version": "0.0.1",
    }

    return JsonResponse(data)

```

The `JsonResponse` object takes data to be serialized and sets the correct MIME type for JSON content.

As with all views, Version Info must be registered against a URL. This is shown in the following listing.

Listing E.4 Register the Version Info view as a route

```

# RiffMates/RiffMates/urls.py
...
from home import views as home_views

urlpatterns = [
    # ...
    path("version/", home_views.version),
    # ...
]

```

E.2 Chapter 3

In chapter 3 you learned about Django's template engine, including how to use tags and filters, as well as how Django escapes content to make it safe to render in HTML.

Exercise 1

Create a new base HTML file, using your favorite web-style framework, such as Bootstrap or Tailwind. Once you have something pretty, test it out by changing `news2.html` to extend from it.

Django's template engine allows you to compose templates together to promote re-use of HTML or any other text content. One of these re-use mechanisms is inheritance. As HTML is quite verbose, writing a good base file to inherit from once means your individual pages can be quite small.

The following listing contains the top part of the content from a base HTML page that uses the Bootstrap 5 framework.

Listing E.5 Declaration and head part of a base HTML file

```

<!-- RiffMates/templates/base_bootstrap.html -->
<!doctype html>
<html lang="en" class="h-100">
<head>
    <meta charset="utf-8">
    <meta name="viewport" content="width=device-width, initial-scale=1">
    <meta name="description" content="">
    <title>
        {% block title %}

```

Putting the page's title in a block allows it to be overridden by child pages.