

```

    RiffMates {% if title %}&mdash; {{ title }} {% endif %}
  {% endblock %}
</title>

<link
  href="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-alpha1/dist/
  ↳ css/bootstrap.min.css"
  rel="stylesheet"
  integrity="sha384-GLhl1TQ8iRABdZL16O3oVMWSktQOp6b7In1Zl3/
  ↳ Jr59b6EGGoI1aFkw7cmDA6j6gD"
  crossorigin="anonymous">
  ↳ Link to the Bootstrap 5 stylesheet

<style>
  main > .container {
    padding: 60px 15px 0;
  }
  ↳ A little extra style definition
  ↳ to leave space at the top of
  ↳ the page for the navbar
</style>

</head>
<body class="d-flex flex-column h-100">
  ↳ These class declarations
  ↳ change how the layout
  ↳ of the page is handled.

```

RiffMates has a navigation bar, so the next piece of content in the base file (shown in the following listing) uses Bootstrap's `<nav>` tag.

Listing E.6 Bootstrap navbar for the base file

```

<header>
  {% block navbar %}
    <!-- Fixed navbar -->
    <nav class="navbar navbar-expand-md navbar-dark fixed-top bg-dark">
      <div class="container-fluid">
        <a class="navbar-brand" href="#">RiffMates</a>
        <button class="navbar-toggler" type="button" data-bs-toggle=
        ↳ "collapse" data-bs-target="#navbarCollapse" aria-controls=
        ↳ "navbarCollapse" aria-expanded=
        ↳ "false" aria-label="Toggle navigation">
          <span class="navbar-toggler-icon"></span>
        </button>
        <div class="collapse navbar-collapse" id="navbarCollapse">
          <ul class="navbar-nav me-auto mb-2 mb-md-0">
            <li class="nav-item">
              <a class="nav-link active" aria-current="page"
              href="{% url 'news' %}">News</a>
            </li>
            <li class="nav-item">
              <a class="nav-link active" aria-current="page"
              href="{% url 'credits' %}">Credits</a>
            </li>
          </ul>
        </div>
      </div>
    </nav>
  {% endblock navbar %}
</header>

```

Putting the content in a block allows it to be overridden or added to by inheriting pages.