

The last portion of the new base file contains a block for page content, a footer, and the JavaScript expected by the Bootstrap framework. Combine the following listing with the other three parts to create your new base file.

Listing E.7 The section where main content gets rendered

```
<!-- Begin page content -->
<main class="flex-shrink-0">
  <div class="container">
    {% block content %}
    {% endblock content %}
  </div>
</main>
```

← This empty block is where page content goes in inheriting files.

```
<footer class="footer mt-auto py-3 bg-light">
  <div class="container">
    {% block footer %}
    <span class="text-muted">RiffMates: by musicians for musicians</span>
    {% endblock footer %}
  </div>
</footer>
```

← Putting the footer in its own block allows the content to be overridden or added to in child pages.

```
<script src="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-alpha1/dist/js/
  bootstrap.bundle.min.js" integrity="sha384-w76AqPfDkMBDXo30jS1Sgez6pr
  3x5MlQ1ZAGC+nuZB+EYdgRZgiwxBTbkF7CXvN" crossorigin="anonymous">
</script>

</body>
</html>
```

With the new `base_bootstrap.html` file in place, you can take advantage of the sexier look by inheriting from it. To try it out, modify the `news2.html` file, changing the `extends` statement to use your new base file. The result is shown in the following listing.

Listing E.8 Modified `news2.html` file using the Bootstrap base template

```
<!-- RiffMates/templates/news2.html -->
{% extends "base_bootstrap.html" %}

{% block title %}
  {{block.super}}: News
{% endblock %}

{% block content %}
  <h1>RiffMates News (2)</h1>

  <ul>
    {% for item in news %}
      <li>{{ item }}</li>
    {% endfor %}
  </ul>

{% endblock content %}
```

← Changing the `extends` tag is all that is required to change where this template is inherited from.